

# CE100 Algorithms and Programming II

## Week-6 (Matrix Chain Order / LCS)

Spring Semester, 2021-2022

Download [DOC](#), [SLIDE](#), [PPTX](#)

`<iframe width=700, height=500 frameBorder=0 src="../../ce100-week-6-lcs.md_slide.html"> </iframe>`

# Matrix Chain Order / Longest Common Subsequence

## Outline

- Elements of Dynamic Programming
  - Optimal Substructure
  - Overlapping Subproblems

- Recursive Matrix Chain Order Memoization
  - Top-Down Approach
  - RMC
  - MemoizedMatrixChain
    - LookupC
  - Dynamic Programming vs Memoization Summary

- Dynamic Programming
  - Problem-2 : Longest Common Subsequence
    - Definitions
    - LCS Problem
    - Notations
    - Optimal Substructure of LCS
      - Proof Case-1
      - Proof Case-2
      - Proof Case-3

- A recursive solution to subproblems (inefficient)
- Computing the length of and LCS
  - LCS Data Structure for DP
  - Bottom-Up Computation
- Constructing and LCS
  - PRINT-LCS
  - Back-pointer space optimization for LCS length

- Most Common Dynamic Programming Interview Questions

# Elements of Dynamic Programming

- When should we look for a DP solution to an optimization problem?
- Two key ingredients for the problem
  - Optimal substructure
  - Overlapping subproblems

## DP Hallmark #1

- **Optimal Substructure**
  - A problem exhibits optimal substructure
    - if an optimal solution to a problem contains within it optimal solutions to subproblems
  - **Example: *matrix-chain-multiplication***
    - Optimal parenthesization of  $A_1 A_2 \dots A_n$  that splits the product between  $A_k$  and  $A_{k+1}$ , contains within it **optimal soln's** to the problems of parenthesizing  $A_1 A_2 \dots A_k$  and  $A_{k+1} A_{k+2} \dots A_n$



# Optimal Substructure

- Finding a suitable space of subproblems
  - Iterate on subproblem instances
  - **Example:** *matrix-chain-multiplication*
    - Iterate and look at the structure of optimal soln's to subproblems, sub-subproblems, and so forth
    - Discover that all subproblems consists of subchains of  $\langle A_1, A_2, \dots, A_n \rangle$
    - Thus, the set of chains of the form  $\langle A_i, A_{i+1}, \dots, A_j \rangle$  for  $1 \leq i \leq j \leq n$
    - Makes a natural and reasonable space of subproblems

## DP Hallmark #2

- **Overlapping Subproblems**
  - Total number of distinct subproblems should be **polynomial** in the input size
  - When a **recursive** algorithm revisits the same problem **over and over again**,
    - We say that the optimization problem has **overlapping subproblems**

## Overlapping Subproblems

- **DP** algorithms typically take advantage of overlapping subproblems
  - by solving each problem once
  - then storing the solutions in a table
    - where it can be looked up when needed
  - using constant time per lookup

# Overlapping Subproblems

- Recursive matrix-chain order

$\text{RMC}(p, i, j)\{$

if  $i = j$  then

return 0

$m[i, j] \leftarrow \infty$

for  $k \leftarrow i$  to  $j - 1$  do

$q \leftarrow \text{RMC}(p, i, k) + \text{RMC}(p, k + 1, j) + p_{i-1}p_kp_j$


if  $q < m[i, j]$  then

$m[i, j] \leftarrow q$

return  $m[i, j]$  }

## Direct Recursion: Inefficient!

- Recursion tree for  $RMC(p, 1, 4)$
- Nodes are labeled with  $i$  and  $j$  values



## Running Time of RMC

$$T(1) \geq 1$$

$$T(n) \geq 1 + \sum_{k=1}^{n-1} (T(k) + T(n-k) + 1) \text{ for } n > 1$$

- For  $i = 1, 2, \dots, n$  each term  $T(i)$  appears twice
  - Once as  $T(k)$ , and once as  $T(n-k)$
- Collect  $n-1$ , 1's in the summation together with the front 1

$$T(n) \geq 2 \sum_{i=1}^{n-1} T(i) + n$$

- Prove that  $T(n) = \Omega(2n)$  using the **substitution method**

## Running Time of RMC: Prove that $T(n) = \Omega(2n)$

- Try to show that  $T(n) \geq 2^{n-1}$  (by substitution)
- Base case:  $T(1) \geq 1 = 2^0 = 2^{1-1}$  for  $n = 1$
- Ind. Hyp.:

$$T(i) \geq 2^{i-1} \text{ for all } i = 1, 2, \dots, n-1 \text{ and } n \geq 2$$

$$\begin{aligned} T(n) &\geq 2 \sum_{i=1}^{n-1} 2^{i-1} + n \\ &= 2 \sum_{i=1}^{n-1} 2^{i-1} + n \\ &= 2(2^{n-1} - 1) + n \\ &= 2^{n-1} + (2^{n-1} - 2 + n) \\ &\Rightarrow T(n) \geq 2^{n-1} \text{ Q.E.D.} \end{aligned}$$

## Running Time of RMC: $T(n) \geq 2^{n-1}$

- Whenever
  - a recursion tree for the natural recursive solution to a problem contains the same subproblem repeatedly
  - the total number of different subproblems is small
    - it is a good idea to see if *DP(Dynamic Programming)* can be applied



## Memoization

- Offers the efficiency of the usual  $DP$  approach while maintaining **top-down** strategy
- Idea is to **memoize** the natural, but inefficient, **recursive algorithm**

## Memoized Recursive Algorithm

- Maintains an **entry** in a **table** for the soln to each subproblem
- Each table entry contains a **special value** to indicate that the entry has yet to be filled in
- When the subproblem is **first encountered** its solution is **computed** and then **stored** in the table
- Each **subsequent** time that the subproblem encountered the value stored in the table is simply **looked up** and **returned**

# Memoized Recursive Matrix-chain Order

- Shaded subtrees are looked-up rather than recomputing

MemoizedMatrixChain(p)

$n \leftarrow \text{length}[p] - 1$

for  $i \leftarrow 1$  to  $n$  do

for  $j \leftarrow 1$  to  $n$  do

$m[i, j] \leftarrow \infty$

return LookupC(p, 1, n)  $\Rightarrow$

$\Rightarrow \text{LookupC}(p, i, j)$

if  $m[i, j] = \infty$  then

if  $i = j$  then

$m[i, j] \leftarrow 0$

else

for  $k \leftarrow i$  to  $j - 1$  do

$q \leftarrow \text{LookupC}(p, i, k) + \text{LookupC}(p, k + 1, j) + p_{i-1}p_kp_j$

if  $q < m[i, j]$  then

$m[i, j] \leftarrow q$

return  $m[i, j]$

## Memoized Recursive Algorithm

- The approach assumes that
  - The set of **all possible subproblem parameters** are known
  - The relation between the **table positions** and **subproblems** is established
- Another approach is to memoize
  - by using **hashing** with subproblem parameters as key

## Dynamic Programming **vs** Memoization Summary (1)

- Matrix-chain multiplication can be solved in  $O(n^3)$  time
  - by either a top-down memoized recursive algorithm
  - or a bottom-up dynamic programming algorithm
- Both methods exploit the **overlapping subproblems** property
  - There are only  $\Theta(n^2)$  different subproblems in total
  - Both methods **compute** the soln to **each problem once**
- **Without memoization** the natural **recursive** algorithm runs in **exponential time** since subproblems are solved repeatedly

## Dynamic Programming **vs** Memoization Summary (2)

- In general practice
  - If all subproblems must be solved at once
    - a bottom-up **DP algorithm** always outperforms a top-down memoized algorithm by a constant factor
  - because, bottom-up **DP** algorithm
    - Has no overhead for recursion
    - Less overhead for maintaining the table
  - **DP: Regular** pattern of **table accesses** can be exploited to reduce the time and/or space requirements even further
  - **Memoized:** If some problems need not be solved at all, it has the advantage of avoiding solutions to those subproblems

## Problem 3: Longest Common Subsequence

### Definitions

- A subsequence of a given sequence is just the **given sequence** with **some elements** (possibly none) **left out**
- Example:
  - $X = \langle A, B, C, B, D, A, B \rangle$
  - $Z = \langle B, C, D, B \rangle$ 
    - $Z$  is a subsequence of  $X$

## Problem 3: Longest Common Subsequence

### Definitions

- **Formal definition:** Given a sequence  $X = \langle x_1, x_2, \dots, x_m \rangle$ , sequence  $Z = \langle z_1, z_2, \dots, z_k \rangle$  is a subsequence of  $X$ 
  - if  $\exists$  a **strictly increasing sequence**  $\langle i_1, i_2, \dots, i_k \rangle$  of indices of  $X$  such that  $x_{i_j} = z_j$  for all  $j = 1, 2, \dots, k$ , where  $1 \leq k \leq m$
- **Example:**  $Z = \langle B, C, D, B \rangle$  is a subsequence of  $X = \langle A, B, C, B, D, A, B \rangle$  with the index sequence  $\langle i_1, i_2, i_3, i_4 \rangle = \langle 2, 3, 5, 7 \rangle$



## Problem 3: Longest Common Subsequence

### Definitions

- If  $Z$  is a subsequence of both  $X$  and  $Y$ , we denote  $Z$  as a **common subsequence** of  $X$  and  $Y$ .
- **Example:**

$$X = \langle A, B^*, C^*, B, D, A^*, B \rangle$$

$$Y = \langle B^*, D, C^*, A^*, B, A \rangle$$

- $Z_1 = \langle B^*, C^*, A^* \rangle$  is a common subsequence (**of length 3**) of  $X$  and  $Y$ .
- **Two longest common subsequence (LCSs) of  $X$  and  $Y$ ?**
  - $Z_2 = \langle B, C, B, A \rangle$  of length 4
  - $Z_3 = \langle B, D, A, B \rangle$  of length 4
    - *The optimal solution value = 4*

# Longest Common Subsequence (LCS) Problem

- **LCS problem:** Given two sequences
  - $X = \langle x_1, x_2, \dots, x_m \rangle$  and
  - $Y = \langle y_1, y_2, \dots, y_n \rangle$ , find the **LCS** of  $X \& Y$
- **Brute force approach:**
  - Enumerate all subsequences of  $X$
  - Check if each subsequence is also a subsequence of  $Y$
  - Keep track of the **LCS**
  - What is the complexity?
  - There are  $2^m$  subsequences of  $X$ 
    - **Exponential runtime**

## Notation

- **Notation:** Let  $X_i$  denote the  $i^{th}$  prefix of  $X$ 
  - i.e.  $X_i = \langle x_1, x_2, \dots, x_i \rangle$
- **Example:**


$$X = \langle A, B, C, B, D, A, B \rangle$$

$$X_4 = \langle A, B, C, B \rangle$$

$$X_0 = \langle \rangle$$

## Optimal Substructure of an LCS


- Let  $X = \langle x_1, x_2, \dots, x_m \rangle$  and  $Y = \langle y_1, y_2, \dots, y_n \rangle$  are given
- Let  $Z = \langle z_1, z_2, \dots, z_k \rangle$  be an **LCS** of  $X$  and  $Y$



- Question 1:** If  $x_m = y_n$ , how to define the optimal substructure?
  - We must have  $z_k = x_m = y_n$  and
  - $Z_{k-1} = \text{LCS}(X_{m-1}, Y_{n-1})$

## Optimal Substructure of an LCS


- Let  $X = \langle x_1, x_2, \dots, x_m \rangle$  and  $Y = \langle y_1, y_2, \dots, y_n \rangle$  are given
- Let  $Z = \langle z_1, z_2, \dots, z_k \rangle$  be an **LCS** of  $X$  and  $Y$



- **Question 2:** If  $x_m \neq y_n$  and  $z_k \neq x_m$ , how to define the optimal substructure?
  - We must have  $Z = \text{LCS}(X_{m-1}, Y)$

## Optimal Substructure of an LCS

- Let  $X = \langle x_1, x_2, \dots, x_m \rangle$  and  $Y = \langle y_1, y_2, \dots, y_n \rangle$  are given
- Let  $Z = \langle z_1, z_2, \dots, z_k \rangle$  be an **LCS** of  $X$  and  $Y$




- **Question 3:** If  $x_m \neq y_n$  and  $z_k \neq y_n$ , how to define the optimal substructure?
  - We must have  $Z = \text{LCS}(X, Y_{n-1})$

## Theorem: Optimal Substructure of an **LCS**

- Let  $X = \langle x_1, x_2, \dots, x_m \rangle$  and  $Y = \langle y_1, y_2, \dots, y_n \rangle$  are given
- Let  $Z = \langle z_1, z_2, \dots, z_k \rangle$  be an **LCS** of  $X$  and  $Y$
- **Theorem:** Optimal substructure of an LCS:
  - If  $x_m = y_n$ 
    - then  $z_k = x_m = y_n$  and  $Z_{k-1}$  is an **LCS** of  $X_{m-1}$  and  $Y_{n-1}$
  - If  $x_m \neq y_n$  and  $z_k \neq x_m$ 
    - then  $Z$  is an **LCS** of  $X_{m-1}$  and  $Y$
  - If  $x_m \neq y_n$  and  $z_k \neq y_n$ 
    - then  $Z$  is an **LCS** of  $X$  and  $Y_{n-1}$

## Optimal Substructure Theorem (case 1)


- If  $x_m = y_n$  then  $z_k = x_m = y_n$  and  $Z_{k-1}$  is an LCS of  $X_{m-1}$  and  $Y_{n-1}$






## Optimal Substructure Theorem (case 2)

- If  $x_m \neq y_n$  and  $z_k \neq x_m$  then  $Z$  is an LCS of  $X_{m-1}$  and  $Y$



## Optimal Substructure Theorem (case 3)

- If  $x_m \neq y_n$  and  $z_k \neq y_n$  then  $Z$  is an LCS of  $X$  and  $Y_{n-1}$



## Proof of Optimal Substructure Theorem (case 1)

- If  $x_m = y_n$  then  $z_k = x_m = y_n$  and  $Z_{k-1}$  is an **LCS** of  $X_{m-1}$  and  $Y_{n-1}$
- **Proof:** If  $z_k \neq x_m = y_n$  then
  - we can append  $x_m = y_n$  to  $Z$  to obtain a common subsequence of length  $k + 1 \implies$  **contradiction**
  - Thus, we must have  $z_k = x_m = y_n$
  - Hence, the prefix  $Z_{k-1}$  is a **length- $(k - 1)$  CS** of  $X_{m-1}$  and  $Y_{n-1}$
- **We have to show that  $Z_{k-1}$  is in fact an **LCS** of  $X_{m-1}$  and  $Y_{n-1}$**
- **Proof by contradiction:**
  - **Assume that  $\exists$  a CS  $W$  of  $X_{m-1}$  and  $Y_{n-1}$  with  $|W| = k$**
  - Then appending  $x_m = y_n$  to  $W$  produces a **CS** of length  $k + 1$

## Proof of Optimal Substructure Theorem (case 2)

- If  $x_m \neq y_n$  and  $z_k \neq x_m$  then  $Z$  is an **LCS** of  $X_{m-1}$  and  $Y$
- **Proof** : If  $z_k \neq x_m$  then  $Z$  is a CS of  $X_{m-1}$  and  $Y_n$ 
  - **We have to show that  $Z$  is in fact an **LCS** of  $X_{m-1}$  and  $Y_n$**
- **(Proof by contradiction)**
  - Assume that  $\exists$  a CS  $W$  of  $X_{m-1}$  and  $Y_n$  with  $|W| > k$
  - Then  $W$  would also be a CS of  $X$  and  $Y$
  - Contradiction to the assumption that
    - $Z$  is an LCS of  $X$  and  $Y$  with  $|Z| = k$
- **Case 3: Dual of the proof for (case 2)**

## A Recursive Solution to Subproblems

- Theorem implies that there are one or two subproblems to examine
- if  $x_m = y_n$  then
  - we must solve the subproblem of finding an **LCS** of  $X_{m-1} \& Y_{n-1}$
  - appending  $x_m = y_n$  to this **LCS** yields an **LCS** of  $X \& Y$
- else
  - we must solve **two subproblems**
    - finding an **LCS** of  $X_{m-1} \& Y$
    - finding an **LCS** of  $X \& Y_{n-1}$
  - longer of these two **LCSs** is an **LCS** of  $X \& Y$
- endif

## Recursive Algorithm (Inefficient)

```

LCS( $X, Y$ ) {
   $m \leftarrow \text{length}[X]$ 
   $n \leftarrow \text{length}[Y]$ 
  if  $x_m = y_n$  then
     $Z \leftarrow \text{LCS}(X_{m-1}, Y_{n-1}) \triangleright$  solve one subproblem
    return  $\langle Z, x_m = y_n \rangle \triangleright$  append  $x_m = y_n$  to  $Z$ 
  else
     $Z' \leftarrow \text{LCS}(X_{m-1}, Y) \triangleright$  solve two subproblems
     $Z'' \leftarrow \text{LCS}(X, Y_{n-1})$ 
    return longer of  $Z'$  and  $Z''$ 
}

```

## A Recursive Solution

- $c[i, j]$  : length of an **LCS** of  $X_i$  and  $Y_j$

$$c[i, j] = \begin{cases} 0 & \text{if } i = 0 \text{ or } j = 0 \\ c[i - 1, j - 1] + 1 & \text{if } i, j > 0 \text{ and } x_i = y_j \\ \max\{c[i, j - 1], c[i - 1, j]\} & \text{if } i, j > 0 \text{ and } x_i \neq y_j \end{cases}$$

## Computing the Length of an LCS

- We can easily write an **exponential-time recursive algorithm** based on the given recurrence.  $\implies$  **Inefficient!**
- How many distinct subproblems to solve?
  - $\Theta(mn)$
- **Overlapping subproblems property:** Many subproblems share the same sub-subproblems.
  - **e.g.** Finding an **LCS** to  $X_{m-1} \& Y$  and an **LCS** to  $X \& Y_{n-1}$
  - has the sub-subproblem of finding an **LCS** to  $X_{m-1} \& Y_{n-1}$
- Therefore, we can use **dynamic programming**.



## Data Structures

- Let:
  - $c[i, j]$  : length of an **LCS** of  $X_i$  and  $Y_j$
  - $b[i, j]$  : direction towards the table entry corresponding to the optimal subproblem solution chosen when computing  $c[i, j]$ .
  - Used to simplify the construction of an optimal solution at the end.
- Maintain the following tables:
  - $c[0 \dots m, 0 \dots n]$
  - $b[1 \dots m, 1 \dots n]$

## Bottom-up Computation

- Reminder:

$$c[i, j] = \begin{cases} 0 & \text{if } i = 0 \text{ or } j = 0 \\ c[i - 1, j - 1] + 1 & \text{if } i, j > 0 \text{ and } x_i = y_j \\ \max\{c[i, j - 1], c[i - 1, j]\} & \text{if } i, j > 0 \text{ and } x_i \neq y_j \end{cases}$$

- How to choose the order in which we process  $c[i, j]$  values?
- The values for  $c[i - 1, j - 1]$ ,  $c[i, j - 1]$ , and  $c[i - 1, j]$  must be computed before computing  $c[i, j]$ .

## Bottom-up Computation

$$c[i, j] = \begin{cases} 0 & \text{if } i = 0 \text{ or } j = 0 \\ c[i - 1, j - 1] + 1 & \text{if } i, j > 0 \text{ and } x_i = y_j \\ \max\{c[i, j - 1], c[i - 1, j]\} & \text{if } i, j > 0 \text{ and } x_i \neq y_j \end{cases}$$

Need to process:


$c[i, j]$

after computing:

$c[i - 1, j - 1]$ ,

$c[i, j - 1]$ ,

$c[i - 1, j]$



## Bottom-up Computation

$$c[i, j] = \begin{cases} 0 & \text{if } i = 0 \text{ or } j = 0 \\ c[i - 1, j - 1] + 1 & \text{if } i, j > 0 \text{ and } x_i = y_j \\ \max\{c[i, j - 1], c[i - 1, j]\} & \text{if } i, j > 0 \text{ and } x_i \neq y_j \end{cases}$$

⇓


for  $i \leftarrow 1$  to  $m$

for  $j \leftarrow 1$  to  $n$

...

...

$c[i, j] = \dots$



# Computing the Length of an LCS

*LCS – LENGTH*( $X, Y$ )

$m \leftarrow \text{length}[X]; n \leftarrow \text{length}[Y]$

for  $i \leftarrow 0$  to  $m$  do  $c[i, 0] \leftarrow 0$

for  $j \leftarrow 0$  to  $n$  do  $c[0, j] \leftarrow 0$

for  $i \leftarrow 1$  to  $m$  do

for  $j \leftarrow 1$  to  $n$  do

if  $x_i = y_j$  then

$c[i, j] \leftarrow c[i - 1, j - 1] + 1$

$b[i, j] \leftarrow “\nwarrow”$

else if  $c[i - 1, j] \geq c[i, j - 1]$

$c[i, j] \leftarrow c[i - 1, j]$

$b[i, j] \leftarrow “\uparrow”$

else

$c[i, j] \leftarrow c[i, j - 1]$

$b[i, j] \leftarrow “\leftarrow”$

Total Runtime =  $\Theta(mn)$   
Total Space =  $\Theta(mn)$

# Computing the Length of an LCS-1

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$	$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0
$1 A$	0					
$2 B$	0					
$3 C$	0					
$4 B$	0					
$5 D$	0					
$6 A$	0					
$7 B$	0					

# Computing the Length of an LCS-2

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$	$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0
<b>1 A</b>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\leftarrow$ 1
2 B	0					
3 C	0					
4 B	0					
5 D	0					
6 A	0					
7 B	0					

# Computing the Length of an LCS-3

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$	$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0
<b>1 A</b>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\swarrow$ 1
<b>2 B</b>	0	$\swarrow$ 1	$\swarrow$ 1	$\swarrow$ 1	$\uparrow$ 1	$\swarrow$ 2
3 C	0					
4 B	0					
5 D	0					
6 A	0					
7 B	0					



# Computing the Length of an LCS-4

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$1 A$	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
$2 B$	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
$3 C$	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
$4 B$	0						
$5 D$	0						
$6 A$	0						
$7 B$	0						

# Computing the Length of an LCS-5

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		<b>1</b> <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
<b>1</b> <i>A</i>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\leftarrow$ 1	$\swarrow$ 1
<b>2</b> <i>B</i>	0	$\swarrow$ 1	$\leftarrow$ 1	$\leftarrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2
<b>3</b> <i>C</i>	0	$\uparrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2	$\uparrow$ 2	$\uparrow$ 2
<b>4</b> <i>B</i>	0	$\swarrow$ 1					
5 <i>D</i>	0						
6 <i>A</i>	0						
7 <i>B</i>	0						

# Computing the Length of an LCS-6

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		<b><math>\overset{1}{B}</math></b>	<b><math>\overset{2}{D}</math></b>	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
<b><math>\overset{1}{A}</math></b>	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
<b><math>\overset{2}{B}</math></b>	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
<b><math>\overset{3}{C}</math></b>	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
<b><math>\overset{4}{B}</math></b>	0	$\swarrow_1$	$\uparrow_1$				
$\overset{5}{D}$	0						
$\overset{6}{A}$	0						
$\overset{7}{B}$	0						

# Computing the Length of an LCS-7

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$\overset{1}{A}$	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
$\overset{2}{B}$	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
$\overset{3}{C}$	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
$\overset{4}{B}$	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$			
$\overset{5}{D}$	0						
$\overset{6}{A}$	0						
$\overset{7}{B}$	0						

# Computing the Length of an LCS-8

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$\overset{1}{A}$	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
$\overset{2}{B}$	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
$\overset{3}{C}$	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
$\overset{4}{B}$	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$		
$\overset{5}{D}$	0						
$\overset{6}{A}$	0						
$\overset{7}{B}$	0						

# Computing the Length of an LCS-9

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$\overset{1}{A}$	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
$\overset{2}{B}$	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
$\overset{3}{C}$	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
$\overset{4}{B}$	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$	
$\overset{5}{D}$	0						
$\overset{6}{A}$	0						
$\overset{7}{B}$	0						

# Computing the Length of an LCS-10

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$1 A$	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
$2 B$	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
$3 C$	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
$4 B$	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$	$\leftarrow_3$
$5 D$	0						
$6 A$	0						
$7 B$	0						

# Computing the Length of an LCS-11

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$1 A$	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\leftarrow_1$	$\swarrow_1$
$2 B$	0	$\swarrow_1$	$\leftarrow_1$	$\leftarrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$
$3 C$	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\leftarrow_2$	$\uparrow_2$	$\uparrow_2$
$4 B$	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$	$\leftarrow_3$
$5 D$	0	$\uparrow_1$	$\swarrow_2$	$\uparrow_2$	$\uparrow_2$	$\uparrow_3$	$\uparrow_3$
$6 A$	0						
$7 B$	0						



# Computing the Length of an LCS-12

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
1 A	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\leftarrow$ 1	$\swarrow$ 1
2 B	0	$\swarrow$ 1	$\leftarrow$ 1	$\leftarrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2
3 C	0	$\uparrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2	$\uparrow$ 2	$\uparrow$ 2
4 B	0	$\swarrow$ 1	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\leftarrow$ 3
5 D	0	$\uparrow$ 1	$\swarrow$ 2	$\uparrow$ 2	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3
6 A	0	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\uparrow$ 3	$\swarrow$ 4
7 B	0						

## Computing the Length of an LCS-13

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

- Running-time =  $O(mn)$   
since each table entry takes  $O(1)$  time to compute

$\downarrow i/j \rightarrow 0y_j$	$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0
<b>1 A</b>	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\swarrow_1$
<b>2 B</b>	0	$\swarrow_1$	$\swarrow_1$	$\swarrow_1$	$\uparrow_1$	$\swarrow_2$
<b>3 C</b>	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\swarrow_2$	$\uparrow_2$
<b>4 B</b>	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$
<b>5 D</b>	0	$\uparrow_1$	$\swarrow_2$	$\uparrow_2$	$\uparrow_2$	$\uparrow_3$
<b>6 A</b>	0	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$	$\uparrow_3$
<b>7 B</b>	0	$\swarrow_1$	$\uparrow_2$	$\uparrow_3$	$\uparrow_3$	$\swarrow_4$

## Computing the Length of an LCS-14

Operation of LCS-LENGTH on the sequences

$$X = \langle \overset{1}{A}, \overset{2}{B}, \overset{3}{C}, \overset{4}{B}, \overset{5}{D}, \overset{6}{A}, \overset{7}{B} \rangle$$

$$Y = \langle \overset{1}{B}, \overset{2}{D}, \overset{3}{C}, \overset{4}{A}, \overset{5}{B}, \overset{6}{A} \rangle$$

- Running-time =  $O(mn)$   
since each table entry takes  $O(1)$  time to compute
- LCS of  $X \& Y = \langle B, C, B, A \rangle$

$\downarrow i/j \rightarrow 0y_j$		$\overset{1}{B}$	$\overset{2}{D}$	$\overset{3}{C}$	$\overset{4}{A}$	$\overset{5}{B}$	$\overset{6}{A}$
$0x_i$	0	0	0	0	0	0	0
$1 A$	0	$\uparrow 0$	$\uparrow 0$	$\uparrow 0$	$\swarrow 1$	$\leftarrow 1$	$\swarrow 1$
$2 B$	0	$\swarrow 1$	$\leftarrow 1$	$\leftarrow 1$	$\uparrow 1$	$\swarrow 2$	$\leftarrow 2$
$3 C$	0	$\uparrow 1$	$\uparrow 1$	$\swarrow 2$	$\leftarrow 2$	$\uparrow 2$	$\uparrow 2$
$4 B$	0	$\swarrow 1$	$\uparrow 1$	$\uparrow 2$	$\uparrow 2$	$\swarrow 3$	$\leftarrow 3$
$5 D$	0	$\uparrow 1$	$\swarrow 2$	$\uparrow 2$	$\uparrow 2$	$\uparrow 3$	$\uparrow 3$
$6 A$	0	$\uparrow 1$	$\uparrow 2$	$\uparrow 2$	$\swarrow 3$	$\uparrow 3$	$\swarrow 4$
$7 B$	0	$\swarrow 1$	$\uparrow 2$	$\uparrow 3$	$\uparrow 3$	$\swarrow 4$	$\uparrow 4$

## Constructing an LCS

- The  $b$  table returned by **LCS-LENGTH** can be used to quickly construct an **LCS** of  $X \& Y$
- Begin at  $b[m, n]$  and trace through the table following arrows
- Whenever you encounter a " $\nwarrow$ " in entry  $b[i, j]$  it implies that  $x_i = y_j$  is an element of **LCS**
- The elements of **LCS** are encountered in **reverse order**

## Constructing an LCS

- The recursive procedure PRINT-LCS prints out LCS in proper order
- This procedure takes  $O(m + n)$  time since at least one of  $i$  and  $j$  is decremented in each stage of the recursion

```

PRINT-LCS( $b, X, i, j$ )
  if  $i = 0$  or  $j = 0$  then
    return
  if  $b[i, j] = \nwarrow$  then
    PRINT-LCS( $b, X, i - 1, j - 1$ )
    print  $x_i$ 
  else if  $b[i, j] = \uparrow$  then
    PRINT-LCS( $b, X, i - 1, j$ )
  else
    PRINT-LCS( $b, X, i, j - 1$ )
  
```

- The initial invocation: PRINT-LCS( $b, X, \text{length}[X], \text{length}[Y]$ )

# Do we really need the b table (back-pointers)?

- **Question:** From which neighbor did we expand to the highlighted cell?
- **Answer:** Upper-left neighbor, because  $X[i] = Y[j]$ .

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
1 <i>A</i>	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2 <i>B</i>	0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3 <i>C</i>	0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4 <i>B</i>	0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5 <i>D</i>	0	↑ 1	↖ 2	↑ 2	↑ 2	↑ 3	↑ 3
6 <i>A</i>	0	↑ 1	↑ 2	↑ 2	↖ 3	↑ 3	↖ 4
7 <i>B</i>	0	↖ 1	↑ 2	↑ 3	↑ 3	↖ 4	↑ 4

## Do we really need the b table (back-pointers)?

- **Question:** From which neighbor did we expand to the highlighted cell?
- **Answer:** Left neighbor, because  $X[i] \neq Y[j]$  and  $LCS[i, j - 1] > LCS[i - 1, j]$ .

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
1 <i>A</i>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\leftarrow$ 1	$\swarrow$ 1
2 <i>B</i>	0	$\swarrow$ 1	$\leftarrow$ 1	$\leftarrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2
3 <i>C</i>	0	$\uparrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2	$\uparrow$ 2	$\uparrow$ 2
4 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\leftarrow$ 3
5 <i>D</i>	0	$\uparrow$ 1	$\swarrow$ 2	$\uparrow$ 2	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3
6 <i>A</i>	0	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\uparrow$ 3	$\swarrow$ 4
7 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3	$\swarrow$ 4	$\uparrow$ 4

# Do we really need the b table (back-pointers)?

- **Question:** From which neighbor did we expand to the highlighted cell?
- **Answer:** Upper neighbor, because  $X[i] \neq Y[j]$  and  $LCS[i, j - 1] = LCS[i - 1, j]$ .  
(See pseudo-code to see how ties are handled.)

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x</i> <sub>i</sub>	0	0	0	0	0	0	0
1 <i>A</i>	0	$\uparrow_0$	$\uparrow_0$	$\uparrow_0$	$\swarrow_1$	$\nwarrow_1$	$\nwarrow_1$
2 <i>B</i>	0	$\swarrow_1$	$\nwarrow_1$	$\nwarrow_1$	$\uparrow_1$	$\swarrow_2$	$\nwarrow_2$
3 <i>C</i>	0	$\uparrow_1$	$\uparrow_1$	$\swarrow_2$	$\nwarrow_2$	$\uparrow_2$	$\uparrow_2$
4 <i>B</i>	0	$\swarrow_1$	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$	$\nwarrow_3$
5 <i>D</i>	0	$\uparrow_1$	$\swarrow_2$	$\uparrow_2$	$\uparrow_2$	$\uparrow_3$	$\uparrow_3$
6 <i>A</i>	0	$\uparrow_1$	$\uparrow_2$	$\uparrow_2$	$\swarrow_3$	$\uparrow_3$	$\swarrow_4$
7 <i>B</i>	0	$\swarrow_1$	$\uparrow_2$	$\uparrow_3$	$\uparrow_3$	$\swarrow_4$	$\uparrow_4$



## Improving the Space Requirements

- We can eliminate the  $b$  table altogether
  - each  $c[i, j]$  entry depends only on 3 other  $c$  table entries:  $c[i - 1, j - 1]$ ,  $c[i - 1, j]$  and  $c[i, j - 1]$
- Given the value of  $c[i, j]$ :
  - We can determine in  $O(1)$  time which of these 3 values was used to compute  $c[i, j]$  without inspecting table  $b$
  - We save  $\Theta(mn)$  space by this method
  - However, space requirement is still  $\Theta(mn)$  since we need  $\Theta(mn)$  space for the  $c$  table anyway

# What if we store the last 2 rows only?

- To compute  $c[i, j]$ , we only need  $c[i - 1, j - 1]$ ,  $c[i - 1, j]$ , and  $c[i - 1, j + 1]$
- So, we can store only the last two rows.

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
1 <i>A</i>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\nwarrow$ 1	$\swarrow$ 1
2 <i>B</i>	0	$\swarrow$ 1	$\nwarrow$ 1	$\nwarrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\nwarrow$ 2
3 <i>C</i>	0	$\uparrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\nwarrow$ 2	$\uparrow$ 2	$\uparrow$ 2
4 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\nwarrow$ 3
5 <i>D</i>	0	$\uparrow$ 1	$\swarrow$ 2	$\uparrow$ 2	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3
6 <i>A</i>	0	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\uparrow$ 3	$\swarrow$ 4
7 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3	$\swarrow$ 4	$\uparrow$ 4

## What if we store the last 2 rows only?

- To compute  $c[i, j]$ , we only need  $c[i - 1, j - 1]$ ,  $c[i - 1, j]$ , and  $c[i - 1, j + 1]$
- So, we can store only the last two rows.

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
1 <i>A</i>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\nwarrow$ 1	$\swarrow$ 1
2 <i>B</i>	0	$\swarrow$ 1	$\nwarrow$ 1	$\nwarrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\nwarrow$ 2
3 <i>C</i>	0	$\uparrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\nwarrow$ 2	$\uparrow$ 2	$\uparrow$ 2
4 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\nwarrow$ 3
5 <i>D</i>	0	$\uparrow$ 1	$\swarrow$ 2	$\uparrow$ 2	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3
6 <i>A</i>	0	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\uparrow$ 3	$\swarrow$ 4
7 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3	$\swarrow$ 4	$\uparrow$ 4

## What if we store the last 2 rows only?

- To compute  $c[i, j]$ , we only need  $c[i - 1, j - 1]$ ,  $c[i - 1, j]$ , and  $c[i - 1, j + 1]$
- So, we can store only the last two rows.
- This reduces space complexity from  $\Theta(mn)$  to  $\Theta(n)$ .
- Is there a problem with this approach?

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
1 <i>A</i>	0	↑ 0	↑ 0	↑ 0	↖ 1	← 1	↖ 1
2 <i>B</i>	0	↖ 1	← 1	← 1	↑ 1	↖ 2	← 2
3 <i>C</i>	0	↑ 1	↑ 1	↖ 2	← 2	↑ 2	↑ 2
4 <i>B</i>	0	↖ 1	↑ 1	↑ 2	↑ 2	↖ 3	← 3
5 <i>D</i>	0	↑ 1	↖ 2	↑ 2	↑ 2	↑ 3	↑ 3
6 <i>A</i>	0	↑ 1	↑ 2	↑ 2	↖ 3	↑ 3	↖ 4
7 <i>B</i>	0	↖ 1	↑ 2	↑ 3	↑ 3	↖ 4	↑ 4

## What if we store the last 2 rows only?

- Is there a problem with this approach?
  - We cannot construct the optimal solution because we cannot backtrace anymore.
  - This approach works if we only need the length of an LCS, not the actual LCS.

$\downarrow i/j \rightarrow 0y_j$		1 <i>B</i>	2 <i>D</i>	3 <i>C</i>	4 <i>A</i>	5 <i>B</i>	6 <i>A</i>
0 <i>x<sub>i</sub></i>	0	0	0	0	0	0	0
1 <i>A</i>	0	$\uparrow$ 0	$\uparrow$ 0	$\uparrow$ 0	$\swarrow$ 1	$\leftarrow$ 1	$\swarrow$ 1
2 <i>B</i>	0	$\swarrow$ 1	$\leftarrow$ 1	$\leftarrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2
3 <i>C</i>	0	$\uparrow$ 1	$\uparrow$ 1	$\swarrow$ 2	$\leftarrow$ 2	$\uparrow$ 2	$\uparrow$ 2
4 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\leftarrow$ 3
5 <i>D</i>	0	$\uparrow$ 1	$\swarrow$ 2	$\uparrow$ 2	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3
6 <i>A</i>	0	$\uparrow$ 1	$\uparrow$ 2	$\uparrow$ 2	$\swarrow$ 3	$\uparrow$ 3	$\swarrow$ 4
7 <i>B</i>	0	$\swarrow$ 1	$\uparrow$ 2	$\uparrow$ 3	$\uparrow$ 3	$\swarrow$ 4	$\uparrow$ 4

## Problem 4 Optimal Binary Search Tree

- Problem-1: Longest Increasing Subsequence
  - <https://www.geeksforgeeks.org/longest-increasing-subsequence-dp-3/>
  - [https://en.wikipedia.org/wiki/Longest\\_increasing\\_subsequence#:~:text=In computer science%2C the longest,not necessarily contiguous%2C or unique.](https://en.wikipedia.org/wiki/Longest_increasing_subsequence#:~:text=In computer science%2C the longest,not necessarily contiguous%2C or unique.)
  - [https://www.youtube.com/watch?v=22s1xxRvy28&ab\\_channel=StableSort](https://www.youtube.com/watch?v=22s1xxRvy28&ab_channel=StableSort)

- Problem-2: Edit Distance

- <https://www.geeksforgeeks.org/edit-distance-dp-5/>
- [https://www.youtube.com/watch?v=tU2f2JwHmfQ&feature=youtu.be&ab\\_channel=PrepForTech](https://www.youtube.com/watch?v=tU2f2JwHmfQ&feature=youtu.be&ab_channel=PrepForTech)
- Recursive
  - [https://www.youtube.com/watch?v=8Q2IEIY2pDU&ab\\_channel=BenLangmead](https://www.youtube.com/watch?v=8Q2IEIY2pDU&ab_channel=BenLangmead)
- DP
  - [https://www.youtube.com/watch?v=0KzWq118UNI&ab\\_channel=BenLangmead](https://www.youtube.com/watch?v=0KzWq118UNI&ab_channel=BenLangmead)
  - [https://www.youtube.com/watch?v=eAVGRWSryGo&ab\\_channel=BenLangmead](https://www.youtube.com/watch?v=eAVGRWSryGo&ab_channel=BenLangmead)



- Problem-3: Partition a set into two subsets such that the difference of subset sums is minimum
  - <https://www.geeksforgeeks.org/partition-a-set-into-two-subsets-such-that-the-difference-of-subset-sums-is-minimum/>
- Problem-4: Count number of ways to cover a distance
  - <https://www.geeksforgeeks.org/count-number-of-ways-to-cover-a-distance/>
- Problem-5: Find the longest path in a matrix with given constraints
  - <https://www.geeksforgeeks.org/find-the-longest-path-in-a-matrix-with-given-constraints/>

- Problem-6: Subset Sum Problem
  - <https://www.geeksforgeeks.org/subset-sum-problem-dp-25/>
- Problem-7: Optimal Strategy for a Game
  - <https://www.geeksforgeeks.org/optimal-strategy-for-a-game-dp-31/>
- Problem-8: 0-1 Knapsack Problem
  - <https://www.geeksforgeeks.org/0-1-knapsack-problem-dp-10/>

- Problem-9: Boolean Parenthesization Problem
  - <https://www.geeksforgeeks.org/boolean-parenthesization-problem-dp-37/>
- Problem-10: Shortest Common Supersequence
  - <https://www.geeksforgeeks.org/shortest-common-supersequence/>
  - [https://en.wikipedia.org/wiki/Shortest\\_common\\_supersequence\\_problem](https://en.wikipedia.org/wiki/Shortest_common_supersequence_problem)
- Problem-11: Partition Problem
  - <https://www.geeksforgeeks.org/partition-problem-dp-18/>
- Problem-12: Cutting a Rod
  - <https://www.geeksforgeeks.org/cutting-a-rod-dp-13/>

- Problem-13: Coin Change
  - <https://www.geeksforgeeks.org/coin-change-dp-7/>
- Problem-14: Word Break Problem
  - <https://www.geeksforgeeks.org/word-break-problem-dp-32/>
- Problem-15: Maximum Product Cutting
  - <https://www.geeksforgeeks.org/maximum-product-cutting-dp-36/>

- Problem-16: Dice Throw
  - <https://www.geeksforgeeks.org/dice-throw-dp-30/>
- Problem-17: Box Stacking Problem
  - <https://www.geeksforgeeks.org/box-stacking-problem-dp-22/>
- Problem-18: Egg Dropping Puzzle
  - <https://www.geeksforgeeks.org/egg-dropping-puzzle-dp-11/>

## References

- [Introduction to Algorithms, Third Edition | The MIT Press](#)
- [Bilkent CS473 Course Notes \(new\)](#)
- [Bilkent CS473 Course Notes \(old\)](#)

*–End – Of – Week – 6 – Course – Module–*