


# CORE JAVA ARCHITECTURE & EXECUTION MECHANICS




A Top-Down Blueprint for C/C++ Developers  
Transitioning to the JVM.




# The Multi-Independence Vision

## The Old Way



## The Java Way



Platform independence is the foundational reason for Java's architecture. A platform is not just hardware; it is the strict combination of an Operating System and underlying Hardware (e.g., Windows 64-bit + Intel).

Beyond hardware, the WORA (Write Once, Run Anywhere) principle extends to Database Independence (JDBC) and Server Independence (Java EE), creating a truly universal ecosystem.



# The Translation Bridge: Byte Code & The JVM

Compile-Time (Platform Independent)


Run-Time (Platform Dependent)



Source Code  
(first.java)




`javac -d ../bin first.java`




Intermediate  
Byte Code  
(first.class)

Binary format strictly  
for a virtual machine,  
not a real one.



Windows JVM



Linux JVM



Mac JVM



Native OS  
Machine Code



Native OS  
Machine Code




Native OS  
Machine Code

JVMs act as  
real-time  
translators.




# Deconstructing the Java Ecosystem





# Smart Class Loading & Package Visibility

```
import java.util.*;
```



## The Assumption

Beginners often assume `.*` forces the JVM to load hundreds of classes into memory.

## The Reality


The `import` statement merely grants the compiler permission to search the package. At runtime, the JVM's Class Loader is lazy and smart—it will only load the specific classes explicitly invoked in your code, keeping the memory footprint minimal.



# Anatomy of the Entry Point


## blueprint note

Maximum visibility. The JVM (an external entity) must be able to see and invoke this method from outside the class.




## blueprint note

The JVM does not expect or accept any return data from the main process.



## blueprint note

The dedicated array for capturing runtime command-line variables.



**public static void main(String[] args)**

The critical keyword.

Allows the JVM to execute HelloWorld.main() without needing to instantiate an object of the HelloWorld class first.



The hardcoded, case-sensitive signature the JVM actively searches for.






# Capturing the Command Line

## The Execution



## The Memory Array



### Key Insight: Context-Sensitive Operators

Because the arguments are captured strictly as Strings, the `+` operator results in concatenation, not arithmetic.


**Code:** `args[0] + args[1]`

**Result:** **1520 (Not 35). Type casting will not work here.**



# The Parsing Engine

```
double num1 = Double.parseDouble(args[0]);
```




## The Mechanical Necessity of Parsing

You cannot cast a String to a primitive. You must parse it. Java provides wrapper classes (`java.lang.Double`, `java.lang.Integer`) with static API methods designed specifically to read string characters and reconstruct them into raw mathematical primitives.



# The System Class Hub






# Output Mechanics: Stream Methods

## print()

### Mechanical Behavior

Prints the literal argument and **leaves the cursor** parked exactly at the end of the data stream.




### Optimal Use Case

Inline console prompts and continuous horizontal appending.

## println()

### Mechanical Behavior

Prints the argument, then actively **injects an OS-specific line separator**, shifting the cursor to a new line.




### Optimal Use Case

Standard terminal logging and sequential vertical outputs.

## printf()

### Mechanical Behavior

Executes formatted printing using C-style specifiers and variable arguments. Arguments are strictly **comma-separated**.



### Optimal Use Case

Complex strings requiring embedded math, precise decimals, or tabular column alignment.



# Precision Formatting with printf

| Specifier   | Translation                                                                                                         |
|-------------|---------------------------------------------------------------------------------------------------------------------|
| <b>%d</b>   | Integer (Decimal)                                                                                                   |
| <b>%f</b>   | Floating-point (Double/Float)                                                                                       |
| <b>%.3f</b> | Precision Floating-point (Truncates and rounds to exactly 3 decimal places)                                         |
| <b>%b</b>   | Boolean (true/false)                                                                                                |
| <b>%s</b>   | String literal                                                                                                      |
| <b>%n</b>   | Platform-independent Line Separator. (Always preferred over <b>\n</b> in format strings to ensure WORA compliance). |

## Code Implementation Blueprint

```
System.out.printf("Result: %.2f%n", (num1 * num2));
```



# Inside the Scanner Class

```
Scanner sc = new Scanner(System.in);
```

## The Instantiation Mechanic

The Scanner class (java.util) is designed to read raw streams and convert them to formatted tokens.

When physically connected to System.in, it inherently spins up an internal ~1 Kilobyte buffer to hold incoming keystrokes.

## Scanner Machine

1K Character Internal Buffer

## The Delimiter Protocol


As the user types, raw character data sits securely in the buffer. The Scanner isolates specific 'tokens' based on a delimiter boundary. By default, this delimiter is strictly any whitespace (space, tab, or newline character).

Keyboard Input Stream



# Blocking, Tokenizing, and Extraction


## 1 Blocking Execution



EMPTY BUFFER


Code hits `sc.nextDouble()`. The internal buffer is completely empty. The JVM actively blocks the thread, effectively freezing the program and waiting until the user hits the Enter key.

## 2 Tokenization



User inputs "12.5 34.2". The Scanner engine identifies the space delimiter. It actively slices the raw input stream into two distinct string tokens, which now sit isolated in the buffer.

## 3 Extraction & Parsing



The pointer grabs the first token ("12.5"), parses it internally, and returns it as a primitive double. The second token ("34.2") remains securely parked in the buffer, waiting for the next scanner method invocation.




# Common Runtime Exceptions Diagnostic

| Exception Signature                   | Trigger Cause                                                                                                                            | Execution Phase | Engineering Fix                                                                                                               |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>ArrayIndexOutOfBoundsException</b> | Running 'java AppName' without supplying command-line arguments, leaving args at size 0, then attempting to forcefully read args[0].     | Runtime         | Always pass arguments at launch (e.g., java AppName 10 20) or validate args.length programmatically before attempting a read. |
| <b>NumberFormatException</b>          | Passing an unparsable string character (e.g., 'A123') into Double.parseDouble() or typing it into a Scanner.nextDouble() console prompt. | Runtime         | Ensure all user input cleanly matches the strictly requested data type format before parsing.                                 |



# Synthesis: The Java Execution Blueprint



**Architectural Takeaway:** Java's strict syntax rules are not arbitrary. Every required keyword, array, and import maps to a highly specific, mechanical function inside the Virtual Machine.