

## Handout: The Big Three: Crafting STL-Like Classes

**Big picture:** By building and analyzing custom classes that mimic STL components like `std::list`, you will internalize key C++ design principles—encapsulation, operator overloading, **dynamic memory management**—while appreciating why STL is robust and reusable.

**Big Three:** Destructor, Copy Constructor, Copy Assignment Operator  
C++ provides default versions of all three functions, but you need to write your own if your class uses dynamic memory.

Complex Class (No Dynamic Memory)

Here's the updated `Complex` class with no dynamic memory from last lecture. The default big three work perfectly fine!

```
C/C++
class Complex {
public:
    Complex(double re = 0.0, double im = 0.0) {
        real = re;
        imag = im;
    }
    double getReal() const { return real; }
    double getImag() const { return imag; }
    void setReal(double re) { real = re; }
    void print() const {
        cout << real << " + "
             << imag << "j" << endl;
    }

private:
    double real;
    double imag;
};
```

## Complex Class (With Dynamic Memory)

Here's the updated **Complex** class with dynamic memory. We'll explore why it needs special handling.

C/C++

```
class Complex {
public:
    Complex(double re = 0.0, double im = 0.0) {
        data = new double[2]; // Dynamic array
        data[0] = re;          // Real part
        data[1] = im;          // Imaginary part
    }
    double getReal() const { return data[0]; }
    double getImag() const { return data[1]; }
    void setReal(double re) { data[0] = re; }
    void print() const {
        cout << data[0] << " + "
              << data[1] << "j" << endl;
    }
    // Big Three methods (live coding)

private:
    double* data; // Pointer to dynamic memory
};
```

## Activity 1: Memory Diagrams with Defaults

**Goal:** Understand how default behavior works (or fails) with both versions of `Complex`. Draw memory diagrams for the stack and heap (if applicable). Use arrows for pointers and boxes for objects/values.

C/C++

```
int foo() {  
    Complex x(3.0, 4.0);  
    Complex y = x; // Default copy constructor  
    y.setReal(5.0);  
    x.print();      // ?  
    y.print();      // ?  
} // Objects destroyed here
```

1. Draw the stack and heap after the first three lines are executed.

2. Will the values printed for x and y differ (as expected)?

A. Yes B. No

3. What happens when `x` and `y` are destroyed after `foo()` returns? Hint: No destructor yet!

- A. No problem occurs
- B. Something goes wrong at **compile time**
- C. Something goes wrong at **run time**  
(Memory Leaks / Crashes / Double deletion/incorrect output)

**Note:** To check for memory leaks, run your executable (a.out) through the tool valgrind. See usage below:

```
Unset  
valgrind --leak-check=full ./a.out
```

(10 mins) Activity 2: Fixing issues in `Complex`

**Goal:** Predict how implementing the Big Three solves the problems. You'll see these implemented live!

1. **Destructor:** Add `~Complex()`. Use `delete[] data;` to free the array. After adding `~Complex()` to free data, does it fix everything?
  - A. Yes, all memory issues are fixed.
  - B. No, copies still share the same data.
  - C. No, it causes a crash immediately.
  - D. Yes, but only for one object.

2. **Copy Constructor:** What does a proper copy constructor, `Complex(const Complex& other)`, need to do to avoid sharing? Draw the stack and heap for `y = x` with a proper deep copy.
- A. Copy the pointer value directly (`data = other.data`)
  - B. Allocate new memory and copy the values

```
data = new double[2];
data[0] = other.data[0];
...
```
  - C. Set `data` to `nullptr`
  - D. Free `other.data` before copying

3. **Copy Assignment Operator:** For `y = x` (where `y` already exists), what must `operator=` do with `y`'s old `data`?

C/C++

```
int foo() {  
    Complex x(3.0, 4.0); // Create x  
    Complex y(1.0, 2.0); // Create y with  
                        // different value  
    y = x; //Calls copy-assignment operator  
    y.setReal(5.0);  
    x.print();        // ?  
    y.print();        // ?  
    return 0;  
} // Objects destroyed here
```

Draw the heap before and after the assignment (`y = x;`). Do you see any issues if the default assignment operator were used?

**Rule of Three** in C++ states that if a class defines one (or more) of the Big three special member functions, it should explicitly define all three to ensure proper resource management.