

# CSE 11

# Accelerated Intro to Programming

## Discussion Section 8

Shihua Lu, Spring 2021

This discussion is being recorded

# Logistics

- PA7 due today at 11:59PM
- PA8 released

# Generic Methods

- Enable us to run the same code for multiple data types
- we use <> to specify parameter types in generic method and class creation
- The type parameter's name is our choice, such as T, U

Example : generic method to print elements in array

```
public class GenericMethodTest {  
    public static < E > void printArray( E[] inputArray ) {  
        for(E element : inputArray) {  
            System.out.println(element);  
        }  
    }  
}
```

*return type* (pointing to < E >)  
*placeholder for the actual type* (pointing to E)

T  
A

*char*

```
public static void main(String args[]) {  
    // Create arrays of Integer, Double and Character  
    Integer[] intArray = { 1, 2, 3, 4, 5 };  
    Double[] doubleArray = { 1.1, 2.2, 3.3, 4.4 };  
    Character[] charArray = { 'H', 'E', 'L', 'L', 'O' };  
    Boolean[] boolArray = { true, false, true };  
    printArray(intArray); // pass an Integer array  
    printArray(doubleArray); // pass a Double array  
    printArray(charArray); // pass a Character array  
}
```

*primitive type X*  
*int[] intArray = { 1, 2, 3 };  
printArray(intArray);* X

# Generic Interfaces and Classes

- write it in front of the name of the interface or class instead

```
interface Checker<T> {  
    boolean check(T t); // We can use T here.  
}
```

- notable difference between generic methods and classes is that when using generic classes/interfaces, Java won't figure out the actual types for us, and we need to provide them manually

```
class LongTweet implements Checker<TextTweet> { // We need to provide the TextTweet type here ...  
    public boolean check(TextTweet t) {  
        return t.content.length() > 20;  
    }  
}
```

# List and ArrayList

↓  
interface

↓  
class that implements List

- ArrayList is an implementation of List interface provided by Java
- we used regular arrays to store lists of data, read them, and modify them. ArrayLists are a generic type in Java that allows us to do all the same things, with slightly different syntax:

arrays

```
int[] numArray = {1, 2, 3};
```

```
int one = numArray[0];
```

```
numArray[1] = one * 2;
```

```
for (int num: numArray) { /* ... */ }
```

↓  
int

check documentation

lists

```
List<Integer> numList = Arrays.asList(1, 2, 3);
```

```
int anotherOne = numList.get(0);
```

```
numList.add(1, anotherOne * 2);
```

```
for (Integer num: numList) { /* ... */ }
```

↓  
Integer

built-in strings, doubles, booleans

index

numList.get(1);

value

# Lists and ArrayLists

- The key distinction between arrays and ArrayLists is that ArrayLists are resizable, so we can add and remove values from them

```
List<String> messages = Arrays.asList("Hello", "CSE11");
```

```
// Appends "on your assignments!" to the end of messages  
messages.add("on your assignments!");
```

```
// Inserts "Good luck" at index 2, shifting "on your assignments!" to the right.  
messages.add(2, "Good luck");
```

*check documentation*

```
// Removes "Hello" from the list, and returns it.
```

```
String hello = messages.remove(0);
```

# Overloading — PA 8

- providing multiple implementations of the same method, differentiated by the parameters they accept

```
int add(int a, int b) { /* ... */ }
```

```
double add(double a, double b) { /* ... */ }
```

- only works if the different methods have a different number of parameters, or parameters of different types, but not if they only have different return types
- A common use for overloading methods is to provide default parameters. For instance, the following method is overloaded to use a default length of 5

```
/*
```

```
    This method returns a new ArrayList containing the Strings in `strs` that  
    are longer than `length`.
```

```
*/
```

```
static ArrayList<String> longStrings(ArrayList<String> strs, int length) {
```

```
    ...
```

```
}
```

```
static ArrayList<String> longStrings(ArrayList<String> strs) {
```

```
    return longStrings(strs, 5);
```

```
}
```

2 parameters

1 parameter

default argument to



# Exceptions

compile error

javac Program.java

run-time java Program

- Java's way of handling errors that can happen when we run our programs
- run into exceptions as a result of incorrect/buggy code as well. Some of these exceptions include: *check documentation*
  - `ArrayOutOfBoundsException`: Happens when we try to get the element at an index of an array that doesn't exist
  - `NullPointerException`: Happens when we try to read a field of, or call a method on a null value.
  - `ArithmeticException`: Happens when we try to run an invalid arithmetic operation (e.g. divide by zero)
- we can provide a custom, more descriptive, error message while throwing exceptions *IOException*

*keyword*

```
static Integer max(ArrayList<Integer> elements) {  
    if (elements.size() == 0) {  
        throw new IllegalArgumentException("max got an empty list");  
    }  
  
    /* ... */  
}
```

*Error message*

*throw SomeException;*

*try {*

*/\* operation \*/*

*}*

*catch (Exception e) {*

*/\* handle exception \*/*

*}*

# PA8

- Start early!

Thanks!