



Raw-Navbar

Attributes:

id, beerclass, beertype, newStyle, libStyle, navBarID, divID, divClass, navBarBrandId

Adding buttons to <beer-navbar> (this could change)

The nav bar uses <beer-buttons> and adding these buttons to the <beer-navbar> is as simple as creating the button you want and then passing the <beer-navbar> and the button the navBarID attribute. There are two ways in which this attribute can be used

```
<beer-button navBarID="bill"></beer-button>
<beer-navbar navBarID="bill" ></beer-navbar>
```

and

```
<beer-button navBarID></beer-button>
<beer-navbar navBarID ></beer-navbar>
```

The first will allow you to specify which <beer-navbar> you want the button to go to. When adding Buttons to the <beer-navbar> they will appear in order.

Adding Style!!

Simply pass in any CSS file you want to the newStyle attribute then use the beerClass attribute to designate which class styles you want to use with the <beer-navbar>.

```
<beer-button navBarID></beer-button>
<beer-navbar navBarID beerClass="navbar navbar-light bg-dark"
```

```
newStyle="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css" >
</beer-navbar>
```

Adding a Brand!!!

adding a brand to <beer-navbar> is as simple as adding a button simply provide the navbarBrandID to both a <beer-navbar> and a <beer-brand>. Just as with <beer-button> you can pass a string to navbarBrandID to get it to link to a specific <beer-navbar> note: if you don't pass ID and inner html attribute to beerBrand then nothing will actually show but you can still right click and check the inspector to see that the <beer-navbar> is actually there

```
<beer-brand navbarBrandID ID="beerbrand">Team11</beer-brand>
<beer-navbar navbarBrandId> </beer-navbar>

<beer-brand navbarBrandID="navNav" ID="beerbrand">Team11</beer-brand>
<beer-navbar navbarBrandId="navNav"> </beer-navbar>
```

Example of fully functioning NavBar

```
<beer-brand
navbarBrandID="bill" id="bob" beerClass="navbar-brand"
brandHref="/navTest1.html" brandImage="../raw-brand/beer_team_logo.png"
brandHeight="30" brandwidth="30" imageClass="d-inline-block align-top"
imageAlt=" "
newStyle="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css">
TEAM BEER!</beer-brand>

<beer-button
navbarID="bill" id="h" beerId="a"
beerClass="btn btn-outline-success"
newStyle="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"
>page 1</beer-button>

<beer-button navbarID="bill" id="heello" beerId="d"
beerClass="btn btn-outline-success"
newStyle="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"
>Page 1</beer-button>

<beer-navbar navbarBrandID="bill" navbarId="bill"
beerClass="navbar navbar-light bg-light"
newStyle="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css">
</beer-navbar>
```