



# CSE 12 Week 7 Discussion

5-14-21

Focus: PA7, BST & File System Filtering



# Reminders

- PA7 is a **closed** assignment - no collaborating!
  - Due Wednesday, May 26th at 11:59 PM
- PA4 Resubmission due today at 11:59 PM
- PA5 Resubmission due Friday, May 21st at 11:59 PM
- PA6 Resubmission due Friday, May 28th at 11:59 PM

# Overview of PA7

- Part I: An Implementation of `DefaultMap`
  - Given the interface `DefaultMap`, implement `BST.java`
  - Descriptions are given in the interface
- Part II: `FileSystem Filter`
  - Similar to PA6, you will create a file system that has specific methods for filtering through the files
- Part III: Gradescope Questions
- Style



# Binary Search Trees (BSTs)

# Binary Search Tree (BST)

## Binary Tree

- Each node has at most 2 children (left child, right child)
  - Node Class
    - Key
    - Value
    - Left child
    - Right child

```
class Node<K,V> {  
    K key;  
    V value;  
    Node<K,V> left, right;  
    public Node(K key, V value,  
                Node<K,V> left, Node<K,V> right) {  
        this.key = key;  
        this.value = value;  
        this.left = left;  
        this.right = right;  
    }  
}
```


## BST

- Nodes belonging to the Left subtree have keys less than the parent node key, and nodes belonging to the right subtree have keys greater than the parent node key


# Helpful Terminology

## Terminology

- **Root:** the top node in the tree
- **Leaf:** a node with no children
- **Depth:** the distance between a node and the root
- **Subtree:** a tree of node T and all of its descendants
- **Edge:** the connection between one node and another
- **Height:** number of edges on the longest path from the root to a leaf




# Example BST



**Binary Search Tree**


# Example BST



**Binary Search Tree**




# Example BST



**Binary Search Tree**

# Example BST



**Binary Search Tree**

## Methods for a BST (we can use the Map interface!)

<code>put(K key, V value)</code>	Adds the key-value pair to the BST
<code>get(K key)</code>	Returns the value corresponding to the given key
<code>remove(K key)</code>	Removes the entry corresponding to the given key
<code>replace(K key, V newValue)</code>	Replace the value that maps to the given key

# BST Visualization

Link to good visualizations where you can create and execute your own examples:

<https://www.cs.usfca.edu/~galles/visualization/BST.html>

# BSTMap: remove

# remove

What cases do we need to consider?

# Remove Cases

Node to remove:

1. Is a leaf (no children)
2. Has 1 child
3. Has 2 children

## Note on the following examples


There are multiple correct solutions for removing an element - any that preserve the rules of a BST would work: for each Node, every Node in its left subtree has a smaller key, and every Node in its right subtree has a larger key.

For this example, we use the following general algorithm:


use binary search to find the node with the key we want to remove, then find the Node with the minimum key in the right subtree, replace our node's fields with the minimum's key and value, then remove this "minimum" Node. This accomplishes "swapping" the Node we want to remove with the Node that has the minimum key of its right subtree.




**Case 1, Leaf: remove(32) ;**




## Case 1, Leaf: remove(32) ;




**Case 2, Has 1 child: remove(35) ;**




**Case 2, Has 1 child: remove(35) ;**




**Case 3, Has 2 Children: `remove(40)` ;**




**Case 3, Has 2 Children: `remove(40)` ;**



## Something to think about



# Recursion handles cases like this elegantly








## Example code & stack trace for remove

@B	Node key = 40 value = 1 left = @C right = @D
@C	Node key = 35 value = 2 left = @E right = @F
@D	Node key = 65 value = 3 left = @G right = @H
@E	Node key = 32 value = 4 left = null right = null
@F	Node key = 37 value = 5 left = null right = null
@G	Node key = 42 value = 6 left = null right = @I
@H	Node key = 68 value = 7 left = null right = null
@I	Node key = 56 value = 8 left = null right = null

@A	BSTMap root = @B size = 6 comparator = String::compare
----	--



# Stack trace of BSTMap remove example


In the interest of readability of the following stack trace, we will only include stack snapshots and Nodes relevant to the example of removing the Node with the key, **65**.

Anything highlighted in **red** represents what is currently “happening” in a particular step

Nodes highlighted in **purple** represent the Node represented by the variable **node** in the current step

**\*\***We suggest zooming in on parts if it is difficult to see, but please let us know if this is not feasible for you such that you can't follow along, so we can address it!

We call `removeRecursively`, passing in the root Node and the key that we wish to remove, 65. We determine the `keyToRemove` is greater than 40 and call the method again on the right child of node, with key, 65.



## Stack

@A.removeRecursively(@B, 65)	
@B.right	
return	
@B	Node key = 40 value = 1 left = @C right = @D
@D	Node key = 65 value = 3 left = @G right = @H
@H	Node key = 68 value = 7 left = null right = null


```

public Node<K, V> removeRecursively(Node<K, V> node, K keyToRemove) throws NoSuchElementException{
    // If tree is empty
    if (node == null) { return null; }

    int compared = this.comparator.compare(node.key, keyToRemove);
    if (compared > 0) {
        System.out.println("Calling remove on left child: <" + node.key + ", " + node.value + ">");
        node.left = removeRecursively(node.left, keyToRemove);
    } else if (compared < 0){
        System.out.println("Calling remove on right child: <" + node.key + ", " + node.value + ">");
        node.right = removeRecursively(node.right, keyToRemove);
    }
    // node has the key we're looking to remove
    else {
        System.out.println("We found the key we're looking for: <" + node.key + ", " + node.value + ">");
        // Case: node with only one child or no children
        if (node.left == null){
            return node.right;
        } else if (node.right == null){
            return node.left;
        }
        // Case: node with two children
        // Get minimum from right subtree, then remove it
        Node<K, V> nextLargest = nodeWithMinimumKey(node.right); //see method in our posted source code
        node.key = nextLargest.key;
        node.value = nextLargest.value;

        // Remove nextLargest node
        node.right = removeRecursively(node.right, node.key);
    }
    return node;
}
  
```

We found the Node with the key, 65. We then find the Node with the minimum key in the right subtree node, which has key 68. We do a deep copy to replace the key and value of node with this minimum Node's fields. We then call removeRecursively on the right child, the other Node with key 68 (which also happens to be the minimum we just found), and the keyToRemove, 68, to remove the now "duplicate" key.



## Stack

@A.removeRecursively(@D, 65)	
@D.key	68
@D.value	7
@D.right	
return	

@A.removeRecursively(@B, 65)	
@B.right	
return	

@B	Node key = 40 value = 1 left = @C right = @D
@D	Node key = 65 68 value = 3 7 left = @G right = @H
@H	Node key = 68 value = 7 left = null right = null

```


public Node<K, V> removeRecursively(Node<K, V> node, K keyToRemove) throws NoSuchElementException{
    // If tree is empty
    if (node == null) { return null; }

    int compared = this.comparator.compare(node.key, keyToRemove);
    if (compared > 0) {
        System.out.println("Calling remove on left child: <" + node.key + ", " + node.value + ">");
        node.left = removeRecursively(node.left, keyToRemove);
    } else if (compared < 0){
        System.out.println("Calling remove on right child: <" + node.key + ", " + node.value + ">");
        node.right = removeRecursively(node.right, keyToRemove);
    }
    // node has the key we're looking to remove
    else {
        System.out.println("We found the key we're looking for: <" + node.key + ", " + node.value + ">");
        // Case: node with only one child or no children
        if (node.left == null){
            return node.right;
        } else if (node.right == null){
            return node.left;
        }

        // Case: node with two children
        // Get minimum from right subtree, then remove it
        Node<K, V> nextLargest = nodeWithMinimumKey(node.right); //see method in our posted source code
        node.key = nextLargest.key;
        node.value = nextLargest.value;

        // Remove nextLargest node
        node.right = removeRecursively(node.right, node.key);
    }
    return node;
}
  
```

We found the Node with key 68. It's left child is null, so we return its right child, which also happens to be null.



## Stack

@A.removeRecursively(@H, 68)

return null

@A.removeRecursively(@D, 65)

@D.key	68
--------	----

@D.value	7
----------	---

@D.right	
----------	--

return

@A.removeRecursively(@B, 65)

@B.right	
----------	--

return

@B

Node

```
key = 40
value = 1
left = @C
right = @D
```

@D

Node

```
key = 68
value = 7
left = @G
right = @H
```

@H

Node

```
key = 68
value = 7
left = null
right = null
```


```
public Node<K, V> removeRecursively(Node<K, V> node, K keyToRemove) throws NoSuchElementException{
    // If tree is empty
    if (node == null) { return null; }

    int compared = this.comparator.compare(node.key, keyToRemove);
    if (compared > 0) {
        System.out.println("Calling remove on left child: <" + node.key + ", " + node.value + ">");
        node.left = removeRecursively(node.left, keyToRemove);
    } else if (compared < 0){
        System.out.println("Calling remove on right child: <" + node.key + ", " + node.value + ">");
        node.right = removeRecursively(node.right, keyToRemove);
    }
    // node has the key we're looking to remove
    else {
        System.out.println("We found the key we're looking for: <" + node.key + ", " + node.value + ">");
        // Case: node with only one child or no children
        if (node.left == null){
            return node.right;
        } else if (node.right == null){
            return node.left;
        }

        // Case: node with two children
        // Get minimum from right subtree, then remove it
        Node<K, V> nextLargest = nodeWithMinimumKey(node.right); //see method in our posted source code
        node.key = nextLargest.key;
        node.value = nextLargest.value;

        // Remove nextLargest node
        node.right = removeRecursively(node.right, node.key);
    }
    return node;
}
```

The null returned is assigned as the right child Node of @D, which “cuts out” @H from our tree. It will be garbage collected upon returning from this call. We return node.



## Stack

@A.removeRecursively(@D, 65)	
@D.key	68
@D.value	7
@D.right	null
return @D	

@A.removeRecursively(@B, 65)	
@B.right	
return	

@B	Node key = 40 value = 1 left = @C right = @D
@D	Node key = 68 value = 7 left = @G right=@H null
@H	Node key = 68 value = 7 left = null right = null

```


public Node<K, V> removeRecursively(Node<K, V> node, K keyToRemove) throws NoSuchElementException{
    // If tree is empty
    if (node == null) { return null; }

    int compared = this.comparator.compare(node.key, keyToRemove);
    if (compared > 0) {
        System.out.println("Calling remove on left child: <" + node.key + ", " + node.value + ">");
        node.left = removeRecursively(node.left, keyToRemove);
    } else if (compared < 0){
        System.out.println("Calling remove on right child: <" + node.key + ", " + node.value + ">");
        node.right = removeRecursively(node.right, keyToRemove);
    }
    // node has the key we're looking to remove
    else {
        System.out.println("We found the key we're looking for: <" + node.key + ", " + node.value + ">");
        // Case: node with only one child or no children
        if (node.left == null){
            return node.right;
        } else if (node.right == null){
            return node.left;
        }
        // Case: node with two children
        // Get minimum from right subtree, then remove it
        Node<K, V> nextLargest = nodeWithMinimumKey(node.right); //see method in our posted source code
        node.key = nextLargest.key;
        node.value = nextLargest.value;

        // Remove nextLargest node
        node.right = removeRecursively(node.right, node.key);
    }
    return node;
}
  
```

The Node returned is assigned as the right child of the Node with key 40. We then return this node. It will be assigned as the root of the map ([see our source code to see the other method that called removeRecursively originally](#)).

## Stack



```

public Node<K, V> removeRecursively(Node<K, V> node, K keyToRemove) throws NoSuchElementException{
    // If tree is empty
    if (node == null) { return null; }

    int compared = this.comparator.compare(node.key, keyToRemove);
    if (compared > 0) {
        System.out.println("Calling remove on left child: <" + node.key + ", " + node.value + ">");
        node.left = removeRecursively(node.left, keyToRemove);
    } else if (compared < 0){
        System.out.println("Calling remove on right child: <" + node.key + ", " + node.value + ">");
        node.right = removeRecursively(node.right, keyToRemove);
    }
    // node has the key we're looking to remove
    else {
        System.out.println("We found the key we're looking for: <" + node.key + ", " + node.value + ">");
        // Case: node with only one child or no children
        if (node.left == null){
            return node.right;
        } else if (node.right == null){
            return node.left;
        }
        // Case: node with two children
        // Get minimum from right subtree, then remove it
        Node<K, V> nextLargest = nodeWithMinimumKey(node.right); //see method in our posted source code
        node.key = nextLargest.key;
        node.value = nextLargest.value;

        // Remove nextLargest node
        node.right = removeRecursively(node.right, node.key);
    }
    return node;
}
  
```

@B	Node key = 40 value = 1 left = @C <b>right = @D</b>
@D	Node key = 68 value = 7 left = @G right = null
@H	Node key = 68 value = 7 left = null right = null

@A.removeRecursively(@B, 65)	
@B.right	@D
return @B	

# File System



# FileData.java

This class represents the file that contains the information for name, directory, and last modified date (**now in yyyy/mm/dd format so we can use compareTo() to compare dates!**).

## *Two Methods*

FileData() - constructor, initializes the instance variables

toString() - returns the string representation of the data in the FileData object

# Comparator: alternative to compareTo()

[Java documentation for Comparator](#)

Example:

```
class Person { String name; int age; }  
// Sometimes we want to order People by age, and we  
// could define a Comparator for this case:  
  
class AgeComparator implements Comparator<Person> {  
    public int compare(Person p1, Person p2) { return p1.age - p2.age; }  
}  
...  
Comparator<Person> c = new AgeComparator();  
if(c.compare(p1, p2) > 0) { // If p1 is older than p2  
    // do something  
}
```

# FileSystem.java

- FileSystem represents the entire structure of the system. This FileSystem though as a focus on filtering through the files to only have files with either a specific date or name.
- Two instance variables:
  - **BST<String, FileData> nameTree;**
    - Note that we only keep ONE file for each name now
    - If we want to add a file with a name that already exists in FileSystem, we only keep the file with the more recent last modified date
  - **BST<String, ArrayList<FileData>> dateTree;**

# Filtering

- `public FileSystem filter(String startDate, String endDate)`
- `public FileSystem filter(String wildCard)`

In order traversal!

# Output the FileSystem

mySample.txt, /home, 02/01/2021

mySample1.txt, /root, 02/01/2021

mySample2.txt, /user, 02/06/2021

outputNameTree

```
["mySample.txt: {Name: mySample.txt,  
Directory: /home, Modified Date: 2021/02/01}",  
"mySample1.txt: {Name: mySample1.txt,  
Directory: /root, Modified Date: 2021/02/01}",  
"mySample2.txt: {Name: mySample2.txt,  
Directory: /user, Modified Date: 2021/02/06}"]
```

outputDateTree

```
["02/06/2021: {Name: mySample2.txt, Directory:  
/user, Modified Date: 2021/02/06}",  
"02/01/2021: {Name: mySample1.txt, Directory:  
/root, Modified Date: 2021/02/01}",  
"02/01/2021: {Name: mySample.txt, Directory:  
/home, Modified Date: 2021/02/01}"]
```