# CSE12 - Lecture 19

Wednesday, May 17, 2023 8:00 AM

PA7 released today → due Tuesday

PA6
PA3 Late/Resubmit → hard deadline today

What order does printAllElement() traverse the tree?

```
void printAllElements(Node<K, N> n) {
  if (n == null ) return;
  System.out.println(n.key);
  printAllElements(n.left);
  printAllElements(n.right);
}

void printAllElement() {
  printAllElements(this.root);
}
```

② ① ③

What's the post, pre, in-order traversal of this tree?




pre ① 8 3 1 6 4 7 10 14 13

post ② 1 4 7 6 3 13 14 10 8

in-order ③ 1 3 4 6 7 8 10 13 14

↳ sorted order

```
class BSTMap<K,V> implements OrderedDefaultMap<K,V>{
  Node<K, V> root;
  int size;
  Comparator<K> comparator;
  ...
  Node<K, V> set(Node<K, V> node, K key, V value) {
    if (node == null) {
      this.size += 1;
      return new Node<K, V>(key, value, null, null);
    }
    int comp = this.comparator.compare(node.key, key);
    if (comp < 0) {
      node.right = this.set(node.right, key, value);
      return node;
    } else if (comp > 0) {
      node.left = this.set(node.left, key, value);
      return node;
    } else {
      node.value = value;
      return node;
    }
  }

  @Override
  public void set(K key, V value) {
    if (key == null) {
      throw new IllegalArgumentException();
    }
    this.root = this.set(this.root, key, value);
  }
}
```

Use the picture on the left and assume the key and value are identical:

set("5", 5);
set("11", 11);
set("15", 15);
set("12", 12);

What is the picture after calling the above set() methods?




Name: _____ PID: _____ Code: _____ 2975

```
public String compare implements Comparator<String> {
    public int compare(String s1, String s2) {
        return
    }
}
```

<0, 0, >0

new BST<String, Student>(new StringCompare())

What is the run-time for a Binary Tree search

set()
Worst Case $\Theta(N)$

What conditions make up the worst case for set()?
sorted or reverse sorted inputs
Best Case: $\Theta(\log_2(N))$

What conditions make up the best case for set()?
root node are median values







get()
Worst Case $\Theta(N)$

What conditions make up the worst case for get()?
sorted → largest element
Best Case: $\Theta(1)$

What conditions make up the best case for get()?
root node has the key we are looking for

average case
complete tree
$\Theta(\log_2(N))$

printAllElements()
Worst Case
Best Case: $\Theta(N)$

What conditions make up the best case for ~~set~~ PAE()?
no best case
prints ALL nodes