

```
import java.util.Arrays;
public class Sort {
    public static void sortA(int[] arr) {
        for(int i = 0; i < arr.length; i += 1) {
            System.out.print(Arrays.toString(arr) + " -> ");
            int minIndex = i;
            for(int j = i; j < arr.length; j += 1) {
                if(arr[minIndex] > arr[j]) { minIndex = j; }
            }
            int temp = arr[i];
            arr[i] = arr[minIndex];
            arr[minIndex] = temp;
            System.out.println(Arrays.toString(arr));
        }
    }

    public static void sortB(int[] arr) {
        for(int i = 0; i < arr.length; i += 1) {
            System.out.print(Arrays.toString(arr) + " -> ");
            for(int j = i; j > 0; j -= 1) {
                if(arr[j] < arr[j-1]) {
                    int temp = arr[j-1];
                    arr[j-1] = arr[j];
                    arr[j] = temp;
                }
            }
            System.out.println(Arrays.toString(arr));
        }
    }
}
```

```
jshell> Sort.sort___(new int[]{ 56, 17, 64, 22, 34, 11 });
[56, 17, 64, 22, 34, 11] -> [11, 17, 64, 22, 34, 56]
[11, 17, 64, 22, 34, 56] -> [11, 17, 64, 22, 34, 56]
[11, 17, 64, 22, 34, 56] -> [11, 17, 22, 64, 34, 56]
[11, 17, 22, 64, 34, 56] -> [11, 17, 22, 34, 64, 56]
[11, 17, 22, 34, 64, 56] -> [11, 17, 22, 34, 56, 64]
[11, 17, 22, 34, 56, 64] -> [11, 17, 22, 34, 56, 64]
```

```
jshell> Sort.sort___(new int[]{ 56, 17, 64, 22, 34, 11 });
[56, 17, 64, 22, 34, 11] -> [56, 17, 64, 22, 34, 11]
[56, 17, 64, 22, 34, 11] ->
```

Which is which?

A: sortA insertion, sortB selection

B: sortA selection, sortB insertion

Selection Sort: Repeatedly find the minimum element and move it to the **end** of a **sorted prefix** of the array.

Worst case complexity?

- A: $O(n)$
- B: $O(n^2)$
- C: $O(n^3)$
- D: $O(n \cdot \log(n))$
- E: Something else

Best case complexity?

- A: $O(n)$
- B: $O(n^2)$
- C: $O(n^3)$
- D: $O(n \cdot \log(n))$
- E: Something else

Insertion Sort: Repeatedly take the next element and insert it into the **correct ordered position within a sorted prefix** of the array.

Worst case complexity?

- A: $O(n)$
- B: $O(n^2)$
- C: $O(n^3)$
- D: $O(n \cdot \log(n))$
- E: Something else

Best case complexity?

- A: $O(n)$
- B: $O(n^2)$
- C: $O(n^3)$
- D: $O(n \cdot \log(n))$
- E: Something else

```
jshell> Sort.sortA(new int[]{ 3, 1, 2 })
```

```
jshell> Sort.sortB(new int[]{ 3, 1, 2 })
```

Selection Sort: What is an **improvement** you can make to the selection sort algorithm on the front page?

Insertion Sort: What is an **improvement** you can make to the insertion sort algorithm on the front page?