CSE 150A-250A AI: Probabilistic Models

Lecture 10

Fall 2026

Trevor Bonjour
Department of Computer Science and Engineering
University of California, San Diego

Slides adapted from previous versions of the course (Prof. Lawrence, Prof. Alvarado, Prof Berg-Kirkpatrick)

Agenda

Review

EM Application

Hidden Markov Models

Review

ML estimation for complete data

- Notation

  Nodes $X_1, X_2, \ldots, X_n$
  Examples $t = 1, 2, \ldots, T$
  Complete data $\{(x_{1t}, x_{2t}, \ldots, x_{nt})\}_{t=1}^{T}$

- ML estimates for CPTs

root nodes

$$P_{\mathrm{ML}}(X_i = x) = \frac{\mathrm{count}(X_i = x)}{T} = \frac{1}{T} \sum_t I(x_{it}, x)$$

nodes with parents

$$P_{\mathrm{ML}}(X_i = x | \mathrm{pa}_i = \pi) = \frac{\mathrm{count}(X_i = x, \mathrm{pa}_i = \pi)}{\mathrm{count}(\mathrm{pa}_i = \pi)} = \frac{\sum_t I(x_{it}, x)\, I(\mathrm{pa}_{it}, \pi)}{\sum_t I(\mathrm{pa}_{it}, \pi)}$$

ML estimation for incomplete data

- **Notation**

  Nodes $X_1, X_2, \ldots, X_n$
  Examples $t = 1, 2, \ldots, T$
  Visible nodes $V_t = v_t$ for t^{th} example

- **EM algorithm**

  Initialize CPTs to nonzero values.
  Repeat until convergence:

  E-step — compute posterior probabilities.
  M-step — update CPTs:

  root nodes

  $$P(X_i = x) \longleftarrow \frac{1}{T} \sum_t P(X_i = x | V_t = v_t)$$

  nodes with parents

  $$P(X_i = x | \mathrm{pa}_i = \pi) \longleftarrow \frac{\sum_t P(X_i = x, \mathrm{pa}_i = \pi | V_t = v_t)}{\sum_t P(\mathrm{pa}_i = \pi | V_t = v_t)}$$

Complete versus incomplete data

- **Complete data**

root nodes

$$P_{\mathrm{ML}}(X_i = x) = \frac{1}{T} \sum_t I(x_{it}, x)$$

nodes with parents

$$P_{\mathrm{ML}}(X_i = x | \mathrm{pa}_i = \pi) = \frac{\sum_t I(x_{it}, x)\, I(\mathrm{pa}_{it}, \pi)}{\sum_t I(\mathrm{pa}_{it}, \pi)}$$

- **Incomplete data**

root nodes

$$P(X_i = x) \longleftarrow \frac{1}{T} \sum_t P(X_i = x | V_t = v_t)$$

nodes with parents

$$P(X_i = x | \mathrm{pa}_i = \pi) \longleftarrow \frac{\sum_{t=1} P(X_i = x, \mathrm{pa}_i = \pi | V_t = v_t)}{\sum_{t=1}^{T} P(\mathrm{pa}_i = \pi | V_t = v_t)}$$

Key properties of EM


- **No learning rate**

  The updates do not require the tuning of a learning rate ($\eta > 0$), as in purely gradient-based methods.

- **Monotonic convergence**

  Changes to CPTs from the EM updates always increase the incomplete-data log-likelihood $\mathcal{L} = \sum_t \log P(V_t = v_t)$.

EM Example



Incomplete data $\{(a_t, c_t)\}_{t=1}^{T}$

A and C are observed.

B is hidden.

- E-step (Inference)

$$P(b|a_t, c_t) = \frac{P(c_t|b)\,P(b|a_t)}{\sum_{b'} P(c_t|b')\,P(b'|a_t)}$$

- M-step (Learning)

$$P(a) = \frac{1}{T}\,\mathrm{count}(A=a)$$

$$P(b|a) \leftarrow \frac{\sum_t I(a, a_t)\,P(b|a_t, c_t)}{\sum_t I(a, a_t)}$$

$$P(c|b) \leftarrow \frac{\sum_t I(c, c_t)\,P(b|a_t, c_t)}{\sum_t P(b|a_t, c_t)}$$

EM Application

Application

- Statistical language modeling

Application

- Statistical language modeling

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

Application

- Statistical language modeling

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- Markov models

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG
unigram	$\prod_\ell P_1(w_\ell)$	$P_1(w) = \frac{\text{count}(w)}{L}$	$\boxed{w_1}$ $\boxed{w_2}$ $\cdots$ $\boxed{w_L}$

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG
unigram	$\prod_\ell P_1(w_\ell)$	$P_1(w) = \frac{\text{count}(w)}{L}$	$\boxed{w_1}$ $\boxed{w_2}$ $\cdots$ $\boxed{w_L}$
bigram	$\prod_\ell P_2(w_\ell \mid w_{\ell-1})$	$P_2(w' \mid w) = \frac{\text{count}(w \to w')}{\text{count}(w)}$	$\boxed{w_1} \to \boxed{w_2} \to \cdots \to \boxed{w_L}$

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG
unigram	$\prod_\ell P_1(w_\ell)$	$P_1(w) = \frac{\text{count}(w)}{L}$	$\boxed{w_1}\ \boxed{w_2}\ \cdots\ \boxed{w_L}$
bigram	$\prod_\ell P_2(w_\ell \mid w_{\ell-1})$	$P_2(w' \mid w) = \frac{\text{count}(w \to w')}{\text{count}(w)}$	$\boxed{w_1} \to \boxed{w_2} \to \cdots \to \boxed{w_L}$
trigram	$\prod_\ell P_3(w_\ell \mid w_{\ell-1}, w_{\ell-2})$	$\vdots$	$\vdots$

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG
unigram	$\prod_\ell P_1(w_\ell)$	$P_1(w) = \frac{\text{count}(w)}{L}$	$\boxed{w_1}\ \boxed{w_2}\ \cdots\ \boxed{w_L}$
bigram	$\prod_\ell P_2(w_\ell \mid w_{\ell-1})$	$P_2(w' \mid w) = \frac{\text{count}(w \to w')}{\text{count}(w)}$	$\boxed{w_1} \to \boxed{w_2} \to \cdots \to \boxed{w_L}$
trigram	$\prod_\ell P_3(w_\ell \mid w_{\ell-1}, w_{\ell-2})$	$\vdots$	$\vdots$

- **Evaluating n-gram models**

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG
unigram	$\prod_\ell P_1(w_\ell)$	$P_1(w) = \frac{\text{count}(w)}{L}$	$\boxed{w_1}\ \boxed{w_2}\ \cdots\ \boxed{w_L}$
bigram	$\prod_\ell P_2(w_\ell \mid w_{\ell-1})$	$P_2(w' \mid w) = \frac{\text{count}(w \to w')}{\text{count}(w)}$	$\boxed{w_1} \to \boxed{w_2} \to \cdots \to \boxed{w_L}$
trigram	$\prod_\ell P_3(w_\ell \mid w_{\ell-1}, w_{\ell-2})$	$\vdots$	$\vdots$

- **Evaluating n-gram models**

  Train on corpus $\mathcal{A} \implies P_1(\mathcal{A}) \leq P_2(\mathcal{A}) \leq P_3(\mathcal{A}) \ldots$

Application

- **Statistical language modeling**

  Let w_ℓ denote the ℓth word in a corpus of text.
  How to model $P(w_1, w_2, \ldots, w_L)$?

- **Markov models**

model	$P(w_1, w_2, \ldots, w_L)$	ML estimate	DAG
unigram	$\prod_\ell P_1(w_\ell)$	$P_1(w) = \frac{\text{count}(w)}{L}$	$\boxed{w_1}\ \boxed{w_2}\ \cdots\ \boxed{w_L}$
bigram	$\prod_\ell P_2(w_\ell \mid w_{\ell-1})$	$P_2(w' \mid w) = \frac{\text{count}(w \to w')}{\text{count}(w)}$	$\boxed{w_1} \to \boxed{w_2} \to \cdots \to \boxed{w_L}$
trigram	$\prod_\ell P_3(w_\ell \mid w_{\ell-1}, w_{\ell-2})$	$\vdots$	$\vdots$

- **Evaluating n-gram models**

  Train on corpus $\mathcal{A}$ $\implies$ $P_1(\mathcal{A}) \leq P_2(\mathcal{A}) \leq P_3(\mathcal{A}) \ldots$
  Test on corpus $\mathcal{B}$ $\implies$ $P_2(\mathcal{B}) = 0$ if $\mathcal{B}$ has unseen bigrams.

Word clustering

Word clustering

- Alternative to bigram model

Word clustering


- **Alternative to bigram model**

  Insert a hidden node $Z \in \{1, 2 \ldots, C\}$ between the previous and next words $W, W' \in \{1, 2, \ldots, V\}$.

Word clustering

- **Alternative to bigram model**


  Insert a hidden node $Z \in \{1, 2 \ldots, C\}$ between the previous and next words $W, W' \in \{1, 2, \ldots, V\}$.



Word clustering

- **Alternative to bigram model**

  Insert a hidden node $Z \in \{1, 2 \ldots, C\}$ between the previous and next words $W, W' \in \{1, 2, \ldots, V\}$.




Words W and W' are observed (as before).
The node Z is a latent variable to detect word clusters.

Word clustering

- **Alternative to bigram model**

  Insert a hidden node $Z \in \{1, 2 \ldots, C\}$ between the previous and next words $W, W' \in \{1, 2, \ldots, V\}$.




  Words W and W' are observed (as before).
  The node Z is a latent variable to detect word clusters.

- **Conditional probability tables**

Word clustering

- **Alternative to bigram model**

  Insert a hidden node $Z \in \{1, 2 \ldots, C\}$ between the previous and next words $W, W' \in \{1, 2, \ldots, V\}$.



  Words W and W' are observed (as before).
  The node Z is a latent variable to detect word clusters.


- **Conditional probability tables**

  $P(z|w)$ is the probability that word w is mapped into cluster z.

Word clustering

- **Alternative to bigram model**

  Insert a hidden node $Z \in \{1, 2 \ldots, C\}$ between the previous and next words $W, W' \in \{1, 2, \ldots, V\}$.




  Words W and W' are observed (as before).
  The node Z is a latent variable to detect word clusters.

- **Conditional probability tables**


  $P(z|w)$ is the probability that word w is mapped into cluster z.
  $P(w'|z)$ is the probability that word w' follows any word in cluster z.

Computing $P(w'|w)$

Computing $P(w'|w)$




Computing $P(w'|w)$



- Inference


Computing $P(w'|w)$



- Inference

$P(w'|w)$


Computing $P(w'|w)$



- Inference

$$P(w'|w) = \sum_z P(w', z|w)$$


Computing $P(w'|w)$



- Inference

$$P(w'|w) = \sum_z P(w', z|w)$$ marginalization

Computing $P(w'|w)$




- Inference

$$P(w'|w) = \sum_z P(w', z|w) \qquad \boxed{\text{marginalization}}$$

$$= \sum_z P(w'|z, w)\, P(z|w)$$

Computing $P(w'|w)$




- Inference

$$P(w'|w) = \sum_z P(w', z|w) \qquad \boxed{\text{marginalization}}$$

$$= \sum_z P(w'|z, w)\, P(z|w) \qquad \boxed{\text{product rule}}$$


Computing $P(w'|w)$



- Inference

$$
\begin{aligned}
P(w'|w) &= \sum_z P(w', z|w) && \boxed{\text{marginalization}} \\
&= \sum_z P(w'|z, w)\, P(z|w) && \boxed{\text{product rule}} \\
&= \sum_z P(w'|z)\, P(z|w)
\end{aligned}
$$

Computing $P(w'|w)$




- Inference

$$P(w'|w) = \sum_z P(w', z|w) \quad \boxed{\text{marginalization}}$$

$$= \sum_z P(w'|z, w)\, P(z|w) \quad \boxed{\text{product rule}}$$

$$= \sum_z P(w'|z)\, P(z|w) \quad \boxed{\text{conditional independence}}$$

Computing $P(w'|w)$




- Inference

$$
\begin{aligned}
P(w'|w) &= \sum_z P(w', z|w) && \text{marginalization} \\
&= \sum_z P(w'|z, w)\, P(z|w) && \text{product rule} \\
&= \sum_z P(w'|z)\, P(z|w) && \text{conditional independence}
\end{aligned}
$$

- Matrix factorization

Computing $P(w'|w)$



- Inference

$$P(w'|w) = \sum_z P(w', z|w) \quad \text{marginalization}$$

$$= \sum_z P(w'|z, w)\, P(z|w) \quad \text{product rule}$$

$$= \sum_z P(w'|z)\, P(z|w) \quad \text{conditional independence}$$

- Matrix factorization

The above expresses the matrix $\overbrace{P(w'|w)}^{V \times V}$ as the product of the two smaller matrices $\underbrace{P(w'|z)}_{V \times C}$ and $\underbrace{P(z|w)}_{C \times V}$.

Model complexity

Model complexity

- Parameter count

Model complexity

- **Parameter count**

size of vocabulary	V

Model complexity

- **Parameter count**

size of vocabulary	V
number of clusters	C

Model complexity

- **Parameter count**

size of vocabulary	V	
number of clusters	C	$C \times V$ $V \times C$
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$

Model complexity

- **Parameter count**

size of vocabulary	V	
number of clusters	C	
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$
parameters in bigram model	V^2	$P(w'\|w)$

Model complexity

- Parameter count

size of vocabulary	V	
number of clusters	C	
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$
parameters in bigram model	V^2	$P(w'\|w)$
parameters in unigram model	V	$P(w)$

Model complexity

- **Parameter count**

size of vocabulary	V	
number of clusters	C	
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$
parameters in bigram model	V^2	$P(w'\|w)$
parameters in unigram model	V	$P(w)$

- **Compact representations of complex worlds**

Model complexity

- **Parameter count**

size of vocabulary	V	
number of clusters	C	
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$
parameters in bigram model	V^2	$P(w'\|w)$
parameters in unigram model	V	$P(w)$

- **Compact representations of complex worlds**

  Setting $C = 1$, we recover the unigram model.

Model complexity

- **Parameter count**

size of vocabulary	V	
number of clusters	C	
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$
parameters in bigram model	V^2	$P(w'\|w)$
parameters in unigram model	V	$P(w)$

- **Compact representations of complex worlds**

  Setting $C = 1$, we recover the unigram model.
  Setting $C = V$, we recover the bigram model.

Model complexity

- **Parameter count**

size of vocabulary	V	
number of clusters	C	
parameters in cluster model	$2CV$	$P(w'\|z), P(z\|w)$
parameters in bigram model	V^2	$P(w'\|w)$
parameters in unigram model	V	$P(w)$

- **Compact representations of complex worlds**

  Setting $C = 1$, we recover the unigram model.
  Setting $C = V$, we recover the bigram model.
  In between, we are exploring a range of different models.

EM algorithm


EM algorithm

The model is the same as our previous example.

EM algorithm


The model is the same as our previous example.

Only the variable names have changed!



EM algorithm


The model is the same as our previous example.
Only the variable names have changed!



- E-step – Inference

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!




- E-step – Inference

$P(z|w_\ell, w_{\ell+1})$

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!




- **E-step – Inference**

$$P(z|w_\ell, w_{\ell+1}) = \frac{P(w_{\ell+1}|z)\,P(z|w_\ell)}{\sum_{z'} P(w_{\ell+1}|z')\,P(z'|w_\ell)}$$

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!




- E-step – Inference

$$P(z|w_\ell, w_{\ell+1}) = \frac{P(w_{\ell+1}|z)\,P(z|w_\ell)}{\sum_{z'} P(w_{\ell+1}|z')\,P(z'|w_\ell)}$$

- M-step – Learning

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!



- **E-step – Inference**


$$P(z|w_\ell, w_{\ell+1}) = \frac{P(w_{\ell+1}|z)\,P(z|w_\ell)}{\sum_{z'} P(w_{\ell+1}|z')\,P(z'|w_\ell)}$$

- **M-step – Learning**

$$P(z|w) \longleftarrow$$

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!



- **E-step – Inference**


$$P(z|w_\ell, w_{\ell+1}) = \frac{P(w_{\ell+1}|z)\,P(z|w_\ell)}{\sum_{z'} P(w_{\ell+1}|z')\,P(z'|w_\ell)}$$

- **M-step – Learning**

$$P(z|w) \longleftarrow \frac{\sum_\ell l(w, w_\ell) P(z|w_\ell, w_{\ell+1})}{\sum_\ell l(w, w_\ell)}$$

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!



- **E-step – Inference**

$$P(z|w_\ell, w_{\ell+1}) = \frac{P(w_{\ell+1}|z)\,P(z|w_\ell)}{\sum_{z'} P(w_{\ell+1}|z')\,P(z'|w_\ell)}$$


- **M-step – Learning**

$$P(z|w) \longleftarrow \frac{\sum_\ell I(w, w_\ell) P(z|w_\ell, w_{\ell+1})}{\sum_\ell I(w, w_\ell)}$$

$$P(w'|z) \longleftarrow$$

EM algorithm

The model is the same as our previous example.
Only the variable names have changed!



- **E-step – Inference**

$$P(z|w_\ell, w_{\ell+1}) = \frac{P(w_{\ell+1}|z)\,P(z|w_\ell)}{\sum_{z'} P(w_{\ell+1}|z')\,P(z'|w_\ell)}$$

- **M-step – Learning**

$$P(z|w) \longleftarrow \frac{\sum_\ell I(w, w_\ell) P(z|w_\ell, w_{\ell+1})}{\sum_\ell I(w, w_\ell)}$$

$$P(w'|z) \longleftarrow \frac{\sum_\ell I(w', w_{\ell+1})\, P(z|w_\ell, w_{\ell+1})}{\sum_\ell P(z|w_\ell, w_{\ell+1})}$$

Experimental results

Experimental results

- Data set

Experimental results

- **Data set**

  60K-word vocabulary

Experimental results

- Data set

  60K-word vocabulary
  80M-word corpus of news articles

Experimental results

- **Data set**


  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \to w')$ is 99% sparse.

Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \to w')$ is 99% sparse.

- **Model**




Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \rightarrow w')$ is 99% sparse.

- **Model**




  The goal is to estimate $P(z|w)$ and $P(w'|z)$.

Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \to w')$ is 99% sparse.

- **Model**




  The goal is to estimate $P(z|w)$ and $P(w'|z)$.
  For $C = 32$ clusters, these CPTs have 3.84M entries.

Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \rightarrow w')$ is 99% sparse.

- **Model**




  The goal is to estimate $P(z|w)$ and $P(w'|z)$.
  For $C = 32$ clusters, these CPTs have 3.84M entries.
  EM converges in 30 iterations.

Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \rightarrow w')$ is 99% sparse.

- **Model**



  The goal is to estimate $P(z|w)$ and $P(w'|z)$.
  For $C = 32$ clusters, these CPTs have 3.84M entries.
  EM converges in 30 iterations.


- **Results**

Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\text{count}(w \to w')$ is 99% sparse.

- **Model**



  The goal is to estimate $P(z|w)$ and $P(w'|z)$.
  For $C = 32$ clusters, these CPTs have 3.84M entries.
  EM converges in 30 iterations.

- **Results**


  The model has no prior knowledge of word meanings.

Experimental results

- **Data set**

  60K-word vocabulary
  80M-word corpus of news articles
  $\mathrm{count}(w \to w')$ is 99% sparse.

- **Model**



  The goal is to estimate $P(z|w)$ and $P(w'|z)$.
  For $C = 32$ clusters, these CPTs have 3.84M entries.
  EM converges in 30 iterations.

- **Results**

  The model has no prior knowledge of word meanings.
  Which words does it cluster? Look at $\mathrm{argmax}_z\, P(z|w)$.

Word clusters

Word clusters

1	as cents made make take
2	ago day earlier Friday Monday month quarter reported said Thursday trading Tuesday Wednesday ⟨. . . ⟩
3	even get to
4	based days down home months up work years ⟨%⟩
5	those ⟨,⟩ ⟨—⟩
6	⟨.⟩ ⟨?⟩
7	eighty fifty forty ninety seventy sixty thirty twenty ⟨(⟩ ⟨·⟩
8	can could may should to will would
9	about at just only or than ⟨&⟩ ⟨;⟩
10	economic high interest much no such tax united well
11	president
12	because do how if most say so then think very what when where
13	according back expected going him plan used way
15	don't I people they we you
16	Bush company court department more officials police retort spokesman
17	former the
18	American big city federal general house military national party political state union York

19	billion hundred million nineteen
20	did ⟨"⟩ ⟨'⟩
21	but called San ⟨:⟩ ⟨start-of-sentence⟩
22	bank board chairman end group members number office out part percent price prices rate sales shares use
23	a an another any dollar each first good her his its my old our their this
24	long Mr. year
25	business California case companies corporation dollars incorporated industry law money thousand time today war week ⟨)⟩ ⟨unknown⟩
26	also government he it market she that there which who
27	A. B. C. D. E. F. G. I. L. M. N. P. R. S. T. U.
28	both foreign international major many new oil other some Soviet stock these west world
29	after all among and before between by during for from in including into like of off on over since through told under until while with
30	eight fifteen five four half last next nine oh one second seven several six ten third three twelve two zero ⟨-⟩
31	are be been being had has have is it's not still was were
32	chief exchange news public service trade

Word clusters


1	as cents made make take
2	ago day earlier Friday Monday month quarter reported said Thursday trading Tuesday Wednesday ⟨. . . ⟩
3	even get to
4	based days down home months up work years ⟨%⟩
5	those ⟨,⟩ ⟨—⟩
6	⟨.⟩ ⟨?⟩
7	eighty fifty forty ninety seventy sixty thirty twenty ⟨(⟩ ⟨·⟩
8	can could may should to will would
9	about at just only or than ⟨&⟩ ⟨;⟩
10	economic high interest much no such tax united well
11	president
12	because do how if most say so then think very what when where
13	according back expected going him plan used way
15	don't I people they we you
16	Bush company court department more officials police retort spokesman
17	former the
18	American big city federal general house military national party political state union York

19	billion hundred million nineteen
20	did ⟨"⟩ ⟨'⟩
21	but called San ⟨:⟩ ⟨start-of-sentence⟩
22	bank board chairman end group members number office out part percent price prices rate sales shares use
23	a an another any dollar each first good her his its my old our their this
24	long Mr. year
25	business California case companies corporation dollars incorporated industry law money thousand time today war week ⟨)⟩ ⟨unknown⟩
26	also government he it market she that there which who
27	A. B. C. D. E. F. G. I. L. M. N. P. R. S. T. U.
28	both foreign international major many new oil other some Soviet stock these west world
29	after all among and before between by during for from in including into like of off on over since through told under until while with
30	eight fifteen five four half last next nine oh one second seven several six ten third three twelve two zero ⟨-⟩
31	are be been being had has have is it's not still was were
32	chief exchange news public service trade


The table shows the most likely cluster assignments $\text{argmax}_z P(z|w)$ for the 300 most common tokens in the corpus.

Example : Noisy-OR

Example : Noisy-OR




Example : Noisy-OR



$x_i \in \{0, 1\}$

Example : Noisy-OR




$x_i \in \{0, 1\}$

$p_i \rightarrow$ parameter

$$P(Y = 1 | x_1, x_2, \ldots, x_n) = 1 - \prod_{i=1}^{n} (1 - p_i)^{x_i}$$

Example : Noisy-OR




$x_i \in \{0, 1\}$

$$P(Y = 1 | x_1, x_2, \ldots, x_n) = 1 - \prod_{i=1}^{n} (1 - p_i)^{x_i}$$

The log (conditional) likelihood is $\sum_t \log P(y_t | x_t)$.

Example : Noisy-OR




$x_i \in \{0, 1\}$

$$P(Y = 1 | x_1, x_2, \ldots, x_n) = 1 - \prod_{i=1}^{n} (1 - p_i)^{x_i}$$

The log (conditional) likelihood is $\sum_t \log P(y_t | x_t)$.

How to estimate parameters $p_i \in [0, 1]$ that maximize this?

Example : Noisy-OR




$x_i \in \{0, 1\}$

$$P(Y = 1 | x_1, x_2, \ldots, x_n) = 1 - \prod_{i=1}^{n} (1 - p_i)^{x_i}$$

The log (conditional) likelihood is $\sum_t \log P(y_t | x_t)$.
How to estimate parameters $p_i \in [0, 1]$ that maximize this?

EM

Example : Noisy-OR



$x_i \in \{0, 1\}$


$$P(Y = 1 | x_1, x_2, \ldots, x_n) = 1 - \prod_{i=1}^{n} (1 - p_i)^{x_i}$$

The log (conditional) likelihood is $\sum_t \log P(y_t | x_t)$.
How to estimate parameters $p_i \in [0, 1]$ that maximize this?


EM — but how? Isn't the data complete?

EM for noisy-OR

EM for noisy-OR




EM for noisy-OR



$x_i \in \{0, 1\}$


EM for noisy-OR



$x_i \in \{0, 1\}$

$z_i \in \{0, 1\}$

EM for noisy-OR




$x_i \in \{0, 1\}$

$z_i \in \{0, 1\}$

$P(Z_i = 1 | x_i) = p_i x_i$

EM for noisy-OR




$x_i \in \{0, 1\}$

$z_i \in \{0, 1\}$

$P(Z_i = 1 | x_i) = p_i x_i$

$P(Y = 1 | Z_1, \ldots, Z_n) = \mathbf{OR}(Z_1, \ldots, Z_n)$

EM for noisy-OR



$x_i \in \{0, 1\}$


$z_i \in \{0, 1\}$

$P(Z_i = 1 | x_i) = p_i x_i$

$$P(Y = 1 | Z_1, \ldots, Z_n) = \textbf{OR}(Z_1, \ldots, Z_n)$$

HW 5

EM for noisy-OR



$x_i \in \{0, 1\}$

$z_i \in \{0, 1\}$


$P(Z_i = 1 | x_i) = p_i x_i$

$$P(Y = 1 | Z_1, \ldots, Z_n) = \textbf{OR}(Z_1, \ldots, Z_n)$$

HW 5

First you will show that this model is equivalent to noisy-OR.

EM for noisy-OR



$x_i \in \{0, 1\}$

$z_i \in \{0, 1\}$

$P(Z_i = 1 | x_i) = p_i x_i$


$P(Y = 1 | Z_1, \ldots, Z_n) = \mathbf{OR}(Z_1, \ldots, Z_n)$

HW 5

First you will show that this model is equivalent to noisy-OR. Then you will derive the EM updates for $p_i \in [0, 1]$.

Hidden Markov Models

Markov Models (Review)




Two simplifying assumptions:


1. Finite Context
2. Position Invariance

Hidden Markov models (HMMs)

Hidden Markov models (HMMs)




Hidden Markov models (HMMs)



- Random variables


Hidden Markov models (HMMs)



- Random variables

  $S_t \in \{1, 2, \ldots, n\}$ hidden state at time t

Hidden Markov models (HMMs)




- Random variables

  $S_t \in \{1, 2, \ldots, n\}$ hidden state at time t

  $O_t \in \{1, 2, \ldots, m\}$ observation at time t

Hidden Markov models (HMMs)




- Random variables

  $S_t \in \{1, 2, \ldots, n\}$ hidden state at time t

  $O_t \in \{1, 2, \ldots, m\}$ observation at time t

- States versus observations

Hidden Markov models (HMMs)



- **Random variables**


  $S_t \in \{1, 2, \ldots, n\}$ hidden state at time t

  $O_t \in \{1, 2, \ldots, m\}$ observation at time t

- **States versus observations**

  Each observation O_t is a noisy, partial reflection of the true underlying (but hidden) state S_t of the world at time t.

Hidden Markov models (HMMs)



- Random variables

  $S_t \in \{1, 2, \ldots, n\}$ hidden state at time t


  $O_t \in \{1, 2, \ldots, m\}$ observation at time t

- States versus observations

  Each observation O_t is a noisy, partial reflection of the true underlying (but hidden) state S_t of the world at time t.

  What makes this model so useful?


Housetraining a puppy



This is Bubbles.

She’s an english spanador.

Housetraining a puppy




This is Bubbles.

She's an english spanador.

O_t

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping},$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating},$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking},$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$


Housetraining a puppy



This is Bubbles.
She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$
S_t

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$

$S_t \in \{\texttt{playful},$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$

$S_t \in \{\texttt{playful}, \texttt{hungry},$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$

$S_t \in \{\texttt{playful}, \texttt{hungry}, \texttt{tired},$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$

$S_t \in \{\texttt{playful}, \texttt{hungry}, \texttt{tired}, \texttt{ready to burst}\}$

Housetraining a puppy




This is Bubbles.

She's an english spanador.

$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$
$S_t \in \{\texttt{playful}, \texttt{hungry}, \texttt{tired}, \texttt{ready to burst}\}$

Does she need to go outside?

Housetraining a puppy



This is Bubbles.

She's an english spanador.


$O_t \in \{\texttt{sleeping}, \texttt{eating}, \texttt{barking}, \texttt{waiting by door}, \texttt{etc.}\}$

$S_t \in \{\texttt{playful}, \texttt{hungry}, \texttt{tired}, \texttt{ready to burst}\}$


Does she need to go outside?

What is $P(s_t|o_1, o_2, \ldots, o_t)$?

Speech recognition




Speech recognition




O_t is the acoustic feature vector for windowed speech at time t.

Speech recognition



O_t is the acoustic feature vector for windowed speech at time t.
S_t is the unit of language (e.g., phoneme) being uttered at time t.


Speech recognition



O_t is the acoustic feature vector for windowed speech at time t.
S_t is the unit of language (e.g., phoneme) being uttered at time t.

What did I just hear?

Speech recognition



O_t is the acoustic feature vector for windowed speech at time t.
S_t is the unit of language (e.g., phoneme) being uttered at time t.

What did I just hear?

What is $\text{argmax}_{s_1,s_2,\ldots,s_T} P(s_1, s_2, \ldots, s_T | o_1, o_2, \ldots, o_T)$**?**

Indoor robot navigation



O_t encodes the sensor readings at time t.

Indoor robot navigation



O_t encodes the sensor readings at time t.

S_t encodes the robot location at time t.

Indoor robot navigation



O_t encodes the sensor readings at time t.

S_t encodes the robot location at time t.

Location in the room:

Indoor robot navigation




O_t encodes the sensor readings at time t.

S_t encodes the robot location at time t.

Location in the room: what is $P(S_t|O_1, O_2, \ldots, O_t)$?

HMMs as belief networks



Q. Which of the following statements are True?

A. $P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$


B. $P(O_t|S_1, S_2, \ldots, S_t) = P(O_t|S_t)$

C. $P(S_t|S_{t-1}) = P(S_t|S_{t-1}, O_t)$

D. A and B


E. A, B and C

HMMs as belief networks



- Conditional independence assumptions


HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1})$$


HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) \quad = \quad P(S_t|S_{t-1})$$

HMMs as belief networks




- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$

$$P(O_t|S_1, S_2, \ldots, S_T)$$


HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

HMMs as belief networks




- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

- CPTs are shared across time

HMMs as belief networks




- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s)$$

HMMs as belief networks




- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$

HMMs as belief networks




- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s)$$

HMMs as belief networks




- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

HMMs as belief networks



- Conditional independence assumptions


$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$

- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P($$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(S_1, \ldots, S_T$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}},$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}}, O_1, \ldots, O_T$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{s}}, \underbrace{O_1, \ldots, O_T}_{\vec{o}}) =$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}}, \underbrace{O_1, \ldots, O_T}_{\vec{O}}) = P(S_1)$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}}, \underbrace{O_1, \ldots, O_T}_{\vec{O}}) = P(S_1)\,P(O_1|S_1)$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}}, \underbrace{O_1, \ldots, O_T}_{\vec{O}}) = P(S_1)\, P(O_1|S_1) \prod_{t=2}^{T}$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}}, \underbrace{O_1, \ldots, O_T}_{\vec{O}}) = P(S_1)\,P(O_1|S_1) \prod_{t=2}^{T} \Big[P(S_t|S_{t-1})$$

HMMs as belief networks



- Conditional independence assumptions

$$P(S_t|S_1, S_2, \ldots, S_{t-1}) = P(S_t|S_{t-1})$$
$$P(O_t|S_1, S_2, \ldots, S_T) = P(O_t|S_t)$$


- CPTs are shared across time

$$P(S_t = s'|S_{t-1} = s) = P(S_{t+1} = s'|S_t = s)$$
$$P(O_t = o|S_t = s) = P(O_{t+1} = o|S_{t+1} = s)$$

- Joint distribution

$$P(\underbrace{S_1, \ldots, S_T}_{\vec{S}}, \underbrace{O_1, \ldots, O_T}_{\vec{O}}) = P(S_1)\, P(O_1|S_1) \prod_{t=2}^{T} \Big[P(S_t|S_{t-1})\, P(O_t|S_t) \Big]$$

Parameters of HMMs



Q. Which of the following is NOT a parameter of the model?

A. $P(S_t|S_{t+1})$


B. $P(S_1)$

C. $P(O_t|O_{t-1})$


D. $P(O_t|S_t)$

E. More than one of these is NOT a parameter of the model.

Parameters of HMMs




Parameters of HMMs




a_{ij}

Parameters of HMMs



$$a_{ij} \quad = \quad P(S_{t+1} = j | S_t = i)$$


Parameters of HMMs



$$a_{ij} = P(S_{t+1} = j | S_t = i)$$

$n \times n$ transition matrix

Parameters of HMMs




$a_{ij} = P(S_{t+1} = j | S_t = i)$

$n \times n$ **transition matrix**

b_{ik}

Parameters of HMMs




$$a_{ij} = P(S_{t+1} = j | S_t = i)$$

$n \times n$ transition matrix

$$b_{ik} = P(O_t = k | S_t = i)$$


Parameters of HMMs



$$a_{ij} = P(S_{t+1} = j | S_t = i)$$ $n \times n$ transition matrix

$$b_{ik} = P(O_t = k | S_t = i)$$ $n \times m$ emission matrix

Parameters of HMMs




n -> no. of states (finite unique)
m -> no. of observations

$a_{ij} = P(S_{t+1} = j | S_t = i)$ — $n \times n$ transition matrix

$b_{ik} = P(O_t = k | S_t = i)$ — $n \times m$ emission matrix

π_i

Parameters of HMMs




$$a_{ij} = P(S_{t+1} = j | S_t = i)$$ $n \times n$ transition matrix

$$b_{ik} = P(O_t = k | S_t = i)$$ $n \times m$ emission matrix

$$\pi_i = P(S_1 = i)$$

Parameters of HMMs




$a_{ij} = P(S_{t+1} = j | S_t = i)$ — $n \times n$ transition matrix

$b_{ik} = P(O_t = k | S_t = i)$ — $n \times m$ emission matrix

$\pi_i = P(S_1 = i)$ — $n \times 1$ initial state distribution

Parameters of HMMs




$$a_{ij} = P(S_{t+1} = j | S_t = i)$$ $n \times n$ transition matrix

$$b_{ik} = P(O_t = k | S_t = i)$$ $n \times m$ emission matrix

$$\pi_i = P(S_1 = i)$$ $n \times 1$ initial state distribution

HMM is a polytree. **True or False?**


Key computations in HMMs[1]



POLYTREE!

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

Key computations in HMMs[1]




POLYTREE!

Inference

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

Key computations in HMMs[1]




POLYTREE!

Inference

1. How to compute the likelihood $P(o_1, o_2, \ldots, o_T)$?

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

Key computations in HMMs[1]




POLYTREE!

Inference

1. How to compute the likelihood $P(o_1, o_2, \ldots, o_T)$?
2. How to compute the most likely state sequence $\textbf{argmax}_{\vec{s}} P(\vec{s}|\vec{o})$?

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

Key computations in HMMs[1]




POLYTREE!

Inference

1. How to compute the likelihood $P(o_1, o_2, \ldots, o_T)$?
2. How to compute the most likely state sequence $\textbf{argmax}_{\vec{s}} P(\vec{s}|\vec{o})$?
3. How to update beliefs by computing $P(s_t|o_1, o_2, \ldots, o_t)$?

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

Key computations in HMMs[1]



POLYTREE!


Inference

1. How to compute the likelihood $P(o_1, o_2, \ldots, o_T)$?
2. How to compute the most likely state sequence $\textbf{argmax}_{\vec{s}} P(\vec{s}|\vec{o})$?
3. How to update beliefs by computing $P(s_t|o_1, o_2, \ldots, o_t)$?

Learning

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

Key computations in HMMs[1]



POLYTREE!

Inference

1. How to compute the likelihood $P(o_1, o_2, \ldots, o_T)$?
2. How to compute the most likely state sequence $\textbf{argmax}_{\vec{s}} P(\vec{s}|\vec{o})$?
3. How to update beliefs by computing $P(s_t|o_1, o_2, \ldots, o_t)$?

Learning

How to estimate parameters $\{\pi_i, a_{ij}, b_{ik}\}$ that maximize the log-likelihood of observed sequences?

[1] Rabiner, L. R. 1989. A tutorial on hidden Markov models and selected applications in speech recognition.

That’s all folks!