

Lecture 2:

Binary and Strings

CSE 29: Systems Programming and Software Tools
Aaron Schulman (Shalev)





Lecture 1 Overview

- How to access strings and arrays in C
- How does binary number representation work
- String functions and how things can go wrong

Course Website / Syllabus



<https://ucsd-cse29.github.io/fa24/>





Demo: Accessing Binary Data in C

□ **Big Lesson:**

- ◆ Programs can interpret and present bits (in arrays) **in many ways:**
 - » They can be **Integers** `printf("%d", arr[i])`
 - » They can be **Characters** `printf("%c",arr[i])`
 - » They can be **Strings** of Characters `printf("%s",arr)`
 - » There are many other ways too!
- ◆ **C gives us direct access to the bit representations of data in memory!**



Why is 'H' or 72 = bin 10010000 ?

$$\begin{aligned} 10010000 &= 1 \times 2^6 + 1 \times 2^4 \\ &= 64 + 8 = 72 \end{aligned}$$

Binary (Base 2) is *similar* to Decimal (Base 10) representation:

$$\begin{aligned} 72 &= 7 \times 10^2 + 2 \times 10^1 \\ &= 70 + 2 = 72 \end{aligned}$$



Converting integers to/from binary arrays

		2 bits		3 bits		
1 bit		<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	=0
<u>0</u> =0		0	1	0	1	=1
<u>1</u> =1		1	0	0	1	=2
2 values: 2^1		1	1	1	0	=3
				1	0	=4
		4 values: 2^2		1	1	=5
				1	1	=6
				1	1	=7
				8 values: 2^3		



What does each index of a bit array mean?

1 byte

128	64	32	16	8	4	2	1
2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0

MSB

LSB



Bit array -> Integer conversions

$$\begin{array}{ccccccc} 1 & 0 & 1 & 0 & = & 1 \times 2^3 & + 0 \times 2^2 & + 1 \times 2^1 & + 0 \times 2^0 \\ & & & & = & 8 & + 0 & + 2 & + 0 & = 10 \end{array}$$

$$\begin{array}{ccccccc} 1 & 1 & 1 & 0 & = & 1 \times 2^3 & + 1 \times 2^2 & + 1 \times 2^1 & + 0 \times 2^0 \\ & & & & = & 8 & + 4 & + 2 & + 0 & = 14 \end{array}$$



Demo: How do strings work in C?

- Big Idea:

- ◆ Strings are just arrays of characters
- ◆ The string is terminated when there is a null character at the end



What is a string, an array of characters!

`char sup[7] = "Hello";`

0	1	2	3	4	5	6
'H'	'e'	'l'	'l'	'o'	' '	'\0'

↓
Special char.
NUL Character
End of string = 0

Demo: What if we forget the NULL Char?



- Big Idea:

- ◆ There are no training wheels anymore in C, this is not Java
- ◆ If you tell the computer to do something, it will do exactly what you say.



What happens if the null is not there?

```
char sup[7] = "Hello";  
char hi[2] = {'H', 'i'};
```

0	1	0	1	2	3	4	5	6
'H'	'i'	'H'	'e'	'l'	'l'	'o'	' '	'\0'

← **hi** → ← **sup** →



Week 1 Announcements

- **Announcements:**

- Lab attendance is **required** and a lot happens there, make sure to go to lab
- Submit the welcome survey before lab on Tuesday of week 1