



UC San Diego


JACOBS SCHOOL OF ENGINEERING
Electrical and Computer Engineering




ZenseTag: An RFID assisted Twin-Tag Single Antenna COTS Sensor Interface

Nagarjun Bhat*, Agrim Gupta, Ishan Bansal, Harine
Govindarajan, Dinesh Bharadia

Ubiquitous sensing - Next wave of IoT




Sensing soil-moisture to automate irrigation



Biochemical sensors¹

Sensors enable continuous data collection for ubiquitous sensing.

Challenges of ubiquitous sensing: Batteries and bulk




➤ Bulky Sensor interfaces with batteries!

- Need batteries/ energy harvesters.
- Rigid PCB with complex electronics to read sensors.

Sensor interfaces are bulky, rigid and need batteries!

Challenges of ubiquitous sensing: Sensor Interface



➤ A zoo of sensors to choose from! But. . .

- Every sensor outputs different voltage/ current!!
- Each sensor needs a unique interface!
- No universal sensor interface!

No universal interface for COTS sensors.
















Challenges of ubiquitous sensing: Radio infrastructure




- So many commercial radio systems available!
 - None of which readily support battery-free sensor interfaces!
 - Passive sensing needs SDRs and custom waveforms.

No passive interface compatible with existing radios.


Current passive interfaces don't meet these needs:

Requirements	Digital Interfaces	Analog Interfaces	ZenseTag
Universal Interface			
Compact / Simple form factor			
Compatible with existing radios			
Reliable despite multipath			
Realtime sensing			


ZenseTag: Contributions




COTS Sensor Interface




Battery-Free/ commercial
RFID Compatible



Robust and Realtime




15x10mm



ZenseTag: Battery-free, reliable sensor interface for
COTS sensors using commercial RFID.

Can RFID tags enable battery-free sensing?




- RFID is a ubiquitous radio platform.
- RFID tags are passive/flexible and inexpensive
- RFID tags simply backscatter their digital ID.
- No inherent sensing capability.

Can we use the digital ID of Tags for sensing?


How to modulate RFID signal with sensor output?

$$Z_{\text{sensor}} = \frac{V_{\text{sensor}}(f)}{I_{\text{sensor}}(f)}$$




$$\Gamma = \frac{Z_{\text{sensor}} - Z_0}{Z_{\text{sensor}} + Z_0}$$

$$Z_0 \rightarrow Z_{\text{TAG}}$$




ZenseTag embeds sensor impedance into the tag digital ID.

ZenseTag: Direct-to-RF Interface of COTS sensors



ZenseTag accurately profiles sensor impedance and tunes its resonance.


ZenseTag: Tuning the resonance of sensors




ZenseTag tunes Sensor Resonance close to RFID band.

ZenseTag: Core Contributions

Measured Phase: $\Delta\phi_{\text{sensor}} + \text{noise}$





Measured Phase: $\Delta\phi_{\text{sensor}}$



ZenseTag uses a single antenna to interface 2 ICs, for robust sensing

Benchmarks: Resonance-enhanced sensitivity


ZenseTag-Soil moisture




Tuning resonance achieves **7x** improvement in phase response of the sensor at RF

Benchmarks: Multipath resilience

CDF For Differential RSSI




CDF For Differential Phase




ZenseTag: >10x accurate phase estimate, +2dB accurate amplitude estimate


Evaluations: Sensing soil moisture



Outdoor measurement setup




Indoor measurement setup




ZenseTag achieves **>93%** classification accuracy for soil moisture


Evaluations: Sensing Light



Measurement setup




Calibration curve




Results

ZenseTag achieves **>85%** classification accuracy for light intensity

Evaluations: Demonstrations



ZenseTag-Luminosity
Sensor




ZenseTag-Contact
Force Sensor




ZenseTag-Soil
Moisture Sensor

ZenseTag enables sensing in real-time using COTS sensors

Future Directions



Improve sensing range



Additional Sensor Interfaces



Compatibility with portable readers

Thank you!

Please read our paper here:

