

Reflective Synthesis Paper

Integrative Industry Synthesis — Clinical Triage and Risk Decision Support Author: Naunihal Singh Sidhu **Capstone integrative artifact (educational only — not for clinical use).**

1. Industry context

Cardiovascular disease (CVD) remains the leading global cause of death, accounting for roughly 17.9 million deaths a year and almost a third of all deaths worldwide (World Health Organization, 2021). A large fraction of these events are downstream of a small set of modifiable risk factors — hypertension, dyslipidaemia, smoking, diabetes, obesity — and a large fraction occur in patients who *did* enter the healthcare system but were not triaged with the urgency their underlying risk warranted (Roth et al., 2020). The bottleneck is not raw clinical knowledge; it is bedside cognitive bandwidth. Clinicians at the front door of a hospital see hundreds of patients a shift, and the cost of mis-prioritising one is asymmetric: a missed acute coronary case is catastrophic, an over-investigated low-risk patient is merely inefficient.

This is the context in which I situated my Integrated AI System capstone. The opportunity here is not to replace clinical judgement (neither legal nor ethical) but to surface a structured, evidence-grounded summary of risk a clinician can accept, reject, or interrogate within seconds. The system is a clinical-triage explainer that takes a single patient's tabular features, returns a calibrated probability, retrieves supporting evidence from a small clinical knowledge base, and produces a citation-bearing English explanation under explicit guardrails.

2. Overview of the integrated solution

The system runs end-to-end as follows:

1. A patient row from the UCI Heart Disease dataset (Janosi et al., 1988) is preprocessed (numeric `log1p + StandardScaler`, categorical one-hot).
2. Two independent classifiers — a scikit-learn `HistGradientBoostingClassifier` and a PyTorch MLP — each return a probability of CVD.
3. An ensemble decision layer averages the two probabilities into a tier (low/moderate/high) and flags `confidence=low` when the two models disagree by more than 0.20.
4. An agent orchestrator implements a plan → retrieve → explain → evaluate → revise loop. It first checks the user request against a refusal substring list, then retrieves the top-k evidence chunks from a ChromaDB vector store of clinician-authored markdown, then asks an OpenAI chat model to draft an explanation grounded *only* in those chunks. A second LLM call acts as evaluator/critic against an explicit rubric; if the draft fails, one bounded revision is permitted.
5. Every event of every run is appended to `outputs/run_log.jsonl`, and a human-readable transcript is persisted to `docs/transcripts/`.

End-to-end behaviour is demonstrated in `notebooks/05_integrated_pipeline.ipynb` and quantitatively evaluated in `notebooks/04_evaluation.ipynb`.

3. Integration of prior projects

The rubric for the Integrated AI System capstone requires integration of at least three prior capstones — concepts and patterns, not copy-pasted code. I rebuilt every component from scratch and used five prior projects as design lineage rather than as code donors.

Prior project	Concept reused	Where it lives in this system
P2 — Data and Statistical Reasoning	Initial Data Analysis discipline; chi-square / Cramer's V; explicit limitations and bias section	<code>notebooks/01_data_exploration.ipynb</code> , the limitations sections of every component
P3 — Machine Learning (RFM clustering)	scikit-learn Pipeline + ColumnTransformer; log1p for skewed numerics; per-slice metric reporting	<code>src/preprocessing.py</code> , <code>src/ml_model.py</code>
P4 — Deep Learning (CNN with dropout)	Fixed-seed PyTorch training loop, dropout regularisation, <i>disaggregated</i> per-slice evaluation rather than headline accuracy	<code>src/dl_model.py</code> , slice tables in <code>src/evaluation.py</code>
P5 — Generative AI (VAE)	Responsible-framing of generative output: under-claim capability, structural mitigations baked into the prompt, mandatory disclaimer as the final line	<code>src/genai_explainer.py</code>
P6 — Agentic AI (research-brief agent)	Plan → retrieve → synthesise → evaluate → revise loop; ChromaDB + OpenAI embeddings; INSUFFICIENT EVIDENCE escape valve; substring refusal list; runtime caps; sha256 ingest manifest; JSONL run log	<code>src/rag/</code> , <code>src/agent_orchestrator.py</code> , <code>src/safeguards.py</code>

Critically, the integration is not stylistic; the same per-sex performance gap that appeared in both ML and DL is acknowledged in the model card retrieved at explanation time, so the disclosure surfaces in the actual explanation a clinician would read.

4. Technical design decisions and tradeoffs

Two models, not one. A single classifier would have been simpler. I deliberately ensembled an HGB and an MLP because the disagreement signal between two architecturally different learners is itself information: when both heads agree, the prediction is structurally more trustworthy than either alone; when they disagree, the system surfaces "human review recommended" instead of pretending the average is meaningful. On the held-out test set the two models tied almost exactly (ROC-AUC 0.960 each), but their per-row probabilities differ enough to make the disagreement flag fire on real borderline patients (demo 2 in notebooks/05_integrated_pipeline.ipynb).

RAG over fine-tuning. Fine-tuning a model on cardiology text would have been more impressive on paper and far less defensible in practice — fine-tuned weights cannot be audited, cannot be revised without retraining, and cannot cite their sources. RAG against a small markdown knowledge base lets clinicians edit a single file and have the change take effect on the next call, with sha256-based idempotent re-ingest (src/rag/manifest.py).

Evaluator-critic, not just a single LLM call. A second LLM call evaluates the draft against an explicit rubric (src/safeguards.py:RUBRIC) and returns structured JSON. In the integrated demo it caught real issues — missing inline citations, low-confidence not surfaced explicitly — and the bounded one-shot revision corrected them (visible in demo 2's transcript). The evaluator is not a guarantee of safety, but it is a measurable second line of defence whose verdict is logged.

Structural refusal before the LLM, not just in the prompt. The substring refusal list (prescribe, dosage, diagnose me, legal advice, ...) short-circuits the pipeline before any expensive call. A prompt-only safety policy can be jailbroken; a hardcoded substring check on the user request cannot. Demo 3 demonstrates this with refused=True and events=[request, refusal] — no model call was made.

Tradeoffs accepted. The substring list will refuse legitimate paraphrases (false-positive rate >0). The evaluator is itself an LLM and can mis-score. The KB is tiny (four markdown files, 29 chunks). The dataset is small (n=303, test n=61). Each of these is an honest engineering tradeoff documented in the model card and limitations sections rather than glossed over.

5. Ethical, governance, and responsible-AI considerations

The system has been built end-to-end with explicit, *structural* mitigations rather than prompt-level pleas. A short audit:

- **Scope refusal at the input layer.** Banned request types never reach the LLM, regardless of phrasing nuance.
- **Citation discipline at the output layer.** The explanation prompt enforces five hard rules including verbatim score quoting and [S?] citations to the retrieved evidence. The Phase J faithfulness check across three live runs found *zero invalid citations* and 36–44% explanation/evidence token overlap.

- **Mandatory disclaimer.** Every non-refusal explanation ends with "Educational artifact only. Not for clinical use. The clinician is the locus of accountability for any decision."
- **Confidence surfacing.** When ML and DL disagree, the explanation explicitly recommends human review.
- **Audit trail.** Every step of every run is persisted to `outputs/run_log.jsonl` and to a human-readable transcript.
- **Disaggregated evaluation, disclosed.** The per-sex AUC gap (sex=0 → 1.00, sex=1 → 0.94 for ML; very similar for DL) is reported in `notebooks/04_evaluation.ipynb` and surfaced in the retrieved model card — a clinician asking the system about a female patient sees the model card text.

These map directly onto the NIST AI Risk Management Framework's "govern / map / measure / manage" function categories (NIST, 2023) and onto the "transparency", "accountability" and "human oversight" requirements that the EU AI Act classifies as load-bearing for high-risk medical use cases (European Parliament, 2024).

6. Limitations and risks

- **Dataset.** UCI Heart Disease is small (303 rows), thirty years old, drawn from four hospitals, and skewed male. Headline metrics on a 61-row test set have wide confidence intervals; I have not bootstrapped them. The system therefore has no claim to clinical validity outside this benchmark.
- **Calibration.** The Brier scores are good (≤ 0.09) but the top failure-case analysis showed both models being most confident exactly when they were wrong on a handful of rows. The ensemble disagreement flag is the only structural mitigation.
- **Generative drift.** The LLM is a closed-weights API; OpenAI can change the underlying weights at any time. The mitigation is the evaluator-critic, not the LLM itself, but the evaluator is also an LLM and shares the failure mode.
- **Adversarial input.** The refusal list is a substring check; an adversarial user can paraphrase past it. The mitigation is that the system is gated behind a clinician — it is not deployed to patients directly — but in a real deployment a stronger classifier-based input filter would be required.
- **Knowledge base.** The KB is intentionally tiny and is not a substitute for an up-to-date guideline corpus (e.g. ACC/AHA, ESC). Replacing the four-file KB with a curated, versioned, regularly refreshed evidence base is a precondition for any non-educational use.

7. Professional and industry relevance

The architectural pattern here — a small, well-evaluated classical model plus a small RAG layer plus a structurally-guarded LLM explainer plus an evaluator-critic loop — is the same pattern currently being adopted across regulated industries beyond healthcare (legal, financial advisory, insurance). The reason is regulatory: regulators are converging on "the model output must be auditable, the evidence must be cite-able, the human must remain the locus of accountability" (NIST, 2023; European Parliament, 2024). A monolithic LLM cannot meet that bar; the multi-stage decomposition built here can. The transferable

lesson: *the architecture is the safety story* — prompt-only safety does not survive contact with regulators or adversarial users.

8. Future extensions

- **Calibration layer** (Platt scaling or isotonic regression) on top of the ensemble probability before tier assignment.
- **Bootstrap confidence intervals** on every reported metric in `notebooks/04_evaluation.ipynb`.
- **Real KB.** Replace the four-file synthetic KB with a versioned snapshot of a real guideline corpus, ingested via the existing sha256 manifest.
- **Multi-arm refusal classifier** to replace the substring list, reducing false positives on legitimate paraphrases.
- **Counterfactual explanation.** Surface the smallest feature change that would move the patient out of the high tier, drawing on the SHAP / DiCE family of methods.
- **Human-in-the-loop feedback capture.** Append clinician accept/reject + free-text feedback to the run log so the evaluator rubric can be refined empirically.

9. Conclusion

The integrated system meets the rubric's letter — five prior projects integrated, RAG + agent loop + ensemble + per-slice evaluation + structural safety — but the more important point is the discipline behind the integration. Every component was rebuilt from scratch under a single set of constraints (auditability, citation, refusal-before-LLM, run logging), and every constraint was demonstrated with a live, persisted transcript. That is the form an industry-pattern AI system has to take when it is deployed inside a regulated workflow: not a single brilliant model, but a set of small, individually-testable components whose composition produces a behaviour a regulator can sign off on.

References

- European Parliament. (2024). *Regulation (EU) 2024/1689 of the European Parliament and of the Council laying down harmonised rules on artificial intelligence (Artificial Intelligence Act)*. Official Journal of the European Union.
- Janosi, A., Steinbrunn, W., Pfisterer, M., & Detrano, R. (1988). *Heart Disease* [Data set]. UCI Machine Learning Repository. <https://doi.org/10.24432/C52P4X>
- National Institute of Standards and Technology. (2023). *Artificial Intelligence Risk Management Framework (AI RMF 1.0)* (NIST AI 100-1). U.S. Department of Commerce.
- Roth, G. A., Mensah, G. A., Johnson, C. O., Addolorato, G., Ammirati, E., Baddour, L. M., ... Fuster, V. (2020). Global burden of cardiovascular diseases and risk factors, 1990–2019: Update from the GBD 2019 study. *Journal of the American College of Cardiology*, 76(25), 2982–3021. <https://doi.org/10.1016/j.jacc.2020.11.010>

- World Health Organization. (2021). *Cardiovascular diseases (CVDs) — fact sheet*.
[https://www.who.int/news-room/fact-sheets/detail/cardiovascular-diseases-\(cvds\)](https://www.who.int/news-room/fact-sheets/detail/cardiovascular-diseases-(cvds))