FLEXI PERSONALIZATION REPORT

<< Start Personalization >>

Application Name: STD - Re Pack Screen

Page Name: STD - Re Pack Screen

Personalization Level : Site

Personalization Value :

New Fields

Field Name	Type	Position
XX_TOTL_LPN_PACK	Text	after textToLPN9
XX_TOTL_QTY_PACK	Text	after XX_TOTL_LPN_PACK
GET_ALLOCATION_WS	Web Service	after btnPreviousscreen
XX_ORDER_NUM	Text	before textFromLPN
GET_ALLOC_WS_NEW	Web Service	after btnPreviousscreen
GET_ORDER_HDR_WS	Web Service	after btnPreviousscreen
GET_ALLO_WS	Web Service	after btnPreviousscreen
XX_ORDER	Text	before textItem
XX_STATUS	Text	before XX_ORDER

Page Level Properties

Property Name	Property Value

Field Level Properties

Field Name: textFromLPN

Property Name	Property Value

_onKeyPress	script:
	if(textFromLPN.getValue().length()>0)
	{
	flexi.putObject("OBLPN_OBJ",textFromLPN.getValue());
	GET_ALLO_WS.callWebService(null);
	if(GET_ALLO_WS.getResponseCode()==200){
	JSONObject json = new
	JSONObject(GET_ALLO_WS.getRawResponse());
	JSONArray arr = json.getJSONArray("results");
	flexi.putObject("ORDER_OBJ_NEW",arr.get(0).get("orderNo"));
	if(arr.length()==1){
	XX_ORDER.setValue(arr.get(0).get("orderNo"));
	}
	}
	}
	
	//To get status of that order from this web service
	GET_ORDER_HDR_WS.callWebService(null);
	if(GET_ORDER_HDR_WS.getResponseCode()==200){
	JSONObject resp = new
	JSONObject(GET_ORDER_HDR_WS.getRawResponse());
	JSONArray arr = resp.getJSONArray("results");
	flexi.putSessionObject("ORDER_STATUS_OBJ",arr.get(0).get("Description"));
	XX_STATUS.setValue(arr.get(0).get("Description"));
	}

_beforeExit	script:
	if(textFromLPN.getValue().length()>0)
	{
	flexi.putObject("OBLPN_OBJ",textFromLPN.getValue());
	GET_ALLO_WS.callWebService(null);
	if(GET_ALLO_WS.getResponseCode()==200){
	JSONObject json = new
	JSONObject(GET_ALLO_WS.getRawResponse());
	JSONArray arr = json.getJSONArray("results");
	flexi.putObject("ORDER_OBJ_NEW",arr.get(0).get("orderNo"));
	if(arr.length()==1){
	XX_ORDER.setValue(arr.get(0).get("orderNo"));
	}
	}
	}
	
	//To get status of that order from this web service
	GET_ORDER_HDR_WS.callWebService(null);
	if(GET_ORDER_HDR_WS.getResponseCode()==200){
	JSONObject resp = new
	JSONObject(GET_ORDER_HDR_WS.getRawResponse());
	JSONArray arr = resp.getJSONArray("results");
	flexi.putSessionObject("ORDER_STATUS_OBJ",arr.get(0).get("Description"));
	XX_STATUS.setValue(arr.get(0).get("Description"));
	}

Field Name: GET_ALLO_WS

Property Name	Property Value
_columnmap	results.orderNo
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation/?to_inventory_id__container_id__container_nbr=${OBLPN_OBJ}&values_list=order_dtl_id__order_id__order_nbr:orderNo
_operationType	GET
_description	To get order number from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: XX_ORDER_NUM

Property Name	Property Value

_onKeyPress	script:
	if(XX_ORDER_NUM.getValue().length()>0)
	{
	flexi.putObject("ORDER_NUM_OBJ",XX_ORDER_NUM.getValue());
	}
	
	//To get status of that order from this web service
	GET_ORDER_HDR_WS.callWebService(null);
	if(GET_ORDER_HDR_WS.getResponseCode()==200){
	JSONObject resp = new
	JSONObject(GET_ORDER_HDR_WS.getRawResponse());
	JSONArray arr = resp.getJSONArray("results");
	flexi.putSessionObject("ORDER_STATUS_OBJ",arr.get(0).get("Descripti
	on"));
	XX_STATUS.setValue(arr.get(0).get("Description"));
	}
	
	//To get packed LPN result count from this web service
	GET_ALLOCATION_WS.callWebService(null);
	if(GET_ALLOCATION_WS.getResponseCode()==200)
	{
	org.json.JSONObject getRes = new
	org.json.JSONObject(GET_ALLOCATION_WS.getRawResponse());
	Integer resultCount = getRes.get("result_count");
	
	flexi.putObject("LPN_COUNT1",String.valueOf(getRes.get("result_count")
	));
	XX_TOTL_LPN_PACK.setValue(flexi.getObject("LPN_COUNT1"));
	//flexi.setStatusMessage("Packed LPN count Object value-----
	>"+flexi.getObject("LPN_COUNT1"));
	}
	
	//To get packed Qty from this web service
	GET_ALLOC_WS_NEW.callWebService(null);
	if(GET_ALLOC_WS_NEW.getResponseCode()==200)
	{
	JSONObject alloc_json =new
	JSONObject(GET_ALLOC_WS_NEW.getRawResponse());
	JSONArray alloc_arr = alloc_json.getJSONArray("results");
	//NEW CODE
	double packQty=0;
	for(int s=0; s<alloc_arr.length(); s++)
	{
	if(!"null".equals(alloc_arr.get(s).get("toInvCurQty").toString()))
	packQty+= alloc_arr.get(s).getInt("toInvCurQty");
	}
	//flexi.setStatusMessage("Packed qty Sum Value------>"+packQty);
	flexi.putObject("PACKED_QTY_OBJ",packQty);
	String cntr=String.valueOf(flexi.getObject("PACKED_QTY_OBJ"));
	XX_TOTL_QTY_PACK.setValue(cntr);
	}

_rendered	false

_beforeExit	script:
	if(XX_ORDER_NUM.getValue().length()>0)
	{
	flexi.putObject("ORDER_NUM_OBJ",XX_ORDER_NUM.getValue());
	}
	
	//To get status of that order from this web service
	GET_ORDER_HDR_WS.callWebService(null);
	if(GET_ORDER_HDR_WS.getResponseCode()==200){
	JSONObject resp = new
	JSONObject(GET_ORDER_HDR_WS.getRawResponse());
	JSONArray arr = resp.getJSONArray("results");
	flexi.putSessionObject("ORDER_STATUS_OBJ",arr.get(0).get("Descripti
	on"));
	XX_STATUS.setValue(arr.get(0).get("Description"));
	}
	
	//To get packed LPN result count from this web service
	GET_ALLOCATION_WS.callWebService(null);
	if(GET_ALLOCATION_WS.getResponseCode()==200)
	{
	org.json.JSONObject getRes = new
	org.json.JSONObject(GET_ALLOCATION_WS.getRawResponse());
	Integer resultCount = getRes.get("result_count");
	
	flexi.putObject("LPN_COUNT1",String.valueOf(getRes.get("result_count")
	));
	XX_TOTL_LPN_PACK.setValue(flexi.getObject("LPN_COUNT1"));
	//flexi.setStatusMessage("Packed LPN count Object value-----
	>"+flexi.getObject("LPN_COUNT1"));
	}
	
	//To get packed Qty from this web service
	GET_ALLOC_WS_NEW.callWebService(null);
	if(GET_ALLOC_WS_NEW.getResponseCode()==200)
	{
	JSONObject alloc_json =new
	JSONObject(GET_ALLOC_WS_NEW.getRawResponse());
	JSONArray alloc_arr = alloc_json.getJSONArray("results");
	//NEW CODE
	double packQty=0;
	for(int s=0; s<alloc_arr.length(); s++)
	{
	if(!"null".equals(alloc_arr.get(s).get("toInvCurQty").toString()))
	packQty+= alloc_arr.get(s).getInt("toInvCurQty");
	}
	//flexi.setStatusMessage("Packed qty Sum Value------>"+packQty);
	flexi.putObject("PACKED_QTY_OBJ",packQty);
	String cntr=String.valueOf(flexi.getObject("PACKED_QTY_OBJ"));
	XX_TOTL_QTY_PACK.setValue(cntr);
	}

label	Order Number

Field Name: XX_ORDER

Property Name	Property Value

_onKeyPress	script:
	if(XX_ORDER.getValue().length()>0)
	{
	flexi.putObject("ORD_OBJ_NEW",XX_ORDER.getValue());
	}
	
	//To get packed LPN result count from this web service
	GET_ALLOCATION_WS.callWebService(null);
	if(GET_ALLOCATION_WS.getResponseCode()==200)
	{
	org.json.JSONObject getRes = new
	org.json.JSONObject(GET_ALLOCATION_WS.getRawResponse());
	Integer resultCount = getRes.get("result_count");
	
	flexi.putObject("LPN_COUNT1",String.valueOf(getRes.get("result_count")
	));
	XX_TOTL_LPN_PACK.setValue(flexi.getObject("LPN_COUNT1"));
	//flexi.setStatusMessage("Packed LPN count Object value-----
	>"+flexi.getObject("LPN_COUNT1"));
	}
	
	//To get packed Qty from this web service
	GET_ALLOC_WS_NEW.callWebService(null);
	if(GET_ALLOC_WS_NEW.getResponseCode()==200)
	{
	JSONObject alloc_json =new
	JSONObject(GET_ALLOC_WS_NEW.getRawResponse());
	JSONArray alloc_arr = alloc_json.getJSONArray("results");
	//NEW CODE
	double packQty=0;
	for(int s=0; s<alloc_arr.length(); s++)
	{
	if(!"null".equals(alloc_arr.get(s).get("toInvCurQty").toString()))
	packQty+= alloc_arr.get(s).getInt("toInvCurQty");
	}
	//flexi.setStatusMessage("Packed qty Sum Value------>"+packQty);
	flexi.putObject("PACKED_QTY_OBJ",packQty);
	String cntr=String.valueOf(flexi.getObject("PACKED_QTY_OBJ"));
	XX_TOTL_QTY_PACK.setValue(cntr);
	}

_lovSourceType	Web Service
_webService	GET_ALLO_WS

_beforeExit	script:
	if(XX_ORDER.getValue().length()>0)
	{
	flexi.putObject("ORD_OBJ_NEW",XX_ORDER.getValue());
	}
	//To get packed LPN result count from this web service
	GET_ALLOCATION_WS.callWebService(null);
	if(GET_ALLOCATION_WS.getResponseCode()==200)
	{
	org.json.JSONObject getRes = new
	org.json.JSONObject(GET_ALLOCATION_WS.getRawResponse());
	Integer resultCount = getRes.get("result_count");
	
	flexi.putObject("LPN_COUNT1",String.valueOf(getRes.get("result_count")
	));
	XX_TOTL_LPN_PACK.setValue(flexi.getObject("LPN_COUNT1"));
	//flexi.setStatusMessage("Packed LPN count Object value-----
	>"+flexi.getObject("LPN_COUNT1"));
	}
	
	//To get packed Qty from this web service
	GET_ALLOC_WS_NEW.callWebService(null);
	if(GET_ALLOC_WS_NEW.getResponseCode()==200)
	{
	JSONObject alloc_json =new
	JSONObject(GET_ALLOC_WS_NEW.getRawResponse());
	JSONArray alloc_arr = alloc_json.getJSONArray("results");
	//NEW CODE
	double packQty=0;
	for(int s=0; s<alloc_arr.length(); s++)
	{
	if(!"null".equals(alloc_arr.get(s).get("toInvCurQty").toString()))
	packQty+= alloc_arr.get(s).getInt("toInvCurQty");
	}
	//flexi.setStatusMessage("Packed qty Sum Value------>"+packQty);
	flexi.putObject("PACKED_QTY_OBJ",packQty);
	String cntr=String.valueOf(flexi.getObject("PACKED_QTY_OBJ"));
	XX_TOTL_QTY_PACK.setValue(cntr);
	}

_columnDisplay	true
_columnPrompt	Order Number
_lovValidation	true
lovEnabled	true
label	Order Number

Field Name: GET_ORDER_HDR_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/oblpn?container_nbr=${OBLPN_OBJ}&values_list=status_id__description:Description&page_size=1250
_operationType	GET
_description	To get status for order number from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: XX_TOTL_LPN_PACK

Property Name	Property Value
label	TOTAL LPN PACKED
_readOnly	true

Field Name: XX_TOTL_QTY_PACK

Property Name	Property Value
label	TOTAL QTY PACKED
_readOnly	true

Field Name: GET_ALLOCATION_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation?order_dtl_id__order_id__order_nbr=${ORD_OBJ_NEW}&to_inventory_id__container_id__status_id__description=Packed&values_list=id,order_dtl_id__order_id__order_nbr:orderNo,order_dtl_id__item_id__description:itemDesc,to_inventory_id__pack_qty:toInvPckQty,to_inventory_id__orig_qty:toInvOrgQty,to_inventory_id__curr_qty:toInvCurQty,from_inventory_id__pack_qty:fromInvPckQty,from_inventory_id__orig_qty:fromInvOrgQty,from_inventory_id__curr_qty:fromInvCurQty,to_inventory_id__id,order_dtl_id__order_id__id,to_inventory_id__container_id__status_id__description
_operationType	GET
_description	To get packed LPN count from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: GET_ALLOC_WS_NEW

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation?order_dtl_id__order_id__order_nbr=${ORD_OBJ_NEW}&&values_list=id,order_dtl_id__order_id__order_nbr:orderNo,order_dtl_id__item_id__description:itemDesc,to_inventory_id__pack_qty:toInvPckQty,to_inventory_id__orig_qty:toInvOrgQty,to_inventory_id__curr_qty:toInvCurQty,from_inventory_id__pack_qty:fromInvPckQty,from_inventory_id__orig_qty:fromInvOrgQty,from_inventory_id__curr_qty:fromInvCurQty,to_inventory_id__id,order_dtl_id__order_id__id,to_inventory_id__container_id__status_id__description
_operationType	GET
_description	To get packed QTY from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: XX_STATUS

Property Name	Property Value
label	Status
_readOnly	true

Barcode Level Properties

<< End Personalization >>