FLEXI PERSONALIZATION REPORT

<< Start Personalization >>

Application Name: STD - Assign Order to Load

Page Name: STD - Assign Order to Load

Personalization Level : Site

Personalization Value :

New Fields

Field Name	Type	Position
XX_ASSIGN_SKU_QTY	Text	after textOrderNbr
XX_ASSIGN_LPN_COUNT	Text	after XX_ASSIGN_SKU_QTY
XX_ASSIGN_PLT_COUNT	Text	after XX_ASSIGN_LPN_COUNT
XX_WEIGHT	Text	after XX_ASSIGN_PLT_COUNT
XX_CAL_AREA	Text	after XX_WEIGHT
XX_CAL_CBM	Text	after XX_CAL_AREA
XX_TOTL_LPN_PACK	Text	after XX_CAL_CBM
XX_TOTL_QTY_PACK	Text	after XX_TOTL_LPN_PACK
GET_OB_STOP_DTL_WS	Web Service	after btnPreviousscreen
GET_ALLOCATION_WS	Web Service	after btnPreviousscreen
GET_INVENTORY_WS	Web Service	after btnPreviousscreen

Page Level Properties

Property Name	Property Value

Field Level Properties

Field Name: XX_CAL_CBM

Property Name	Property Value
_rendered	false
label	Calculate CBM

Field Name: XX_ASSIGN_LPN_COUNT

Property Name	Property Value
label	Assign LPN Count

Field Name: textTotalLPNsonLoad

Property Name	Property Value
label	Total LPN Packed in Pallet

Field Name: textOrderNbr

Property Name	Property Value

_beforeExit	script:
	//To get Inventory Id
	GET_ALLOCATION_WS.callWebService(null);
	if(GET_ALLOCATION_WS.getResponseCode()==200)
	{
	org.json.JSONObject getRes = new
	org.json.JSONObject(GET_ALLOCATION_WS.getRawResponse());
	org.json.JSONArray getArr = getRes.getJSONArray("results");
	flexi.putObject("INV_ID",getArr.get(0).get("to_inventory_id__id"));
	//flexi.setStatusMessage("To inventory id value Object-------->"
	+flexi.getObject("INV_ID"));
	}
	
	/*
	//Call inventory api for result count item
	GET_INVENTORY_WS.callWebService(null);
	if(GET_INVENTORY_WS.getResponseCode()==200)
	{
	org.json.JSONObject getRes = new
	org.json.JSONObject(GET_INVENTORY_WS.getRawResponse());
	Integer resultCount = getRes.get("result_count");
	int Qty=0;
	for(int i = 0; i < resultCount; i++)
	{
	Qty += resultCount.get(s).getInt("item_id__id");
	}
	flexi.setStatusMessage("Alloc Sum Value------>"+reserveQty);
	}
	*/

Field Name: XX_TOTL_LPN_PACK

Property Name	Property Value
_rendered	false
label	Total LPN Packed in Pallet

Field Name: GET_ALLOCATION_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}

_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation?order_dtl_id__order_id__order_nbr=${textOrderNbr}&values_list=id,order_dtl_id__order_id__order_nbr:orderNo,order_dtl_id__item_id__description:itemDesc,to_inventory_id__pack_qty:toInvPckQty,to_inventory_id__orig_qty:toInvOrgQty,to_inventory_id__curr_qty:toInvCurQty,from_inventory_id__pack_qty:fromInvPckQty,from_inventory_id__orig_qty:fromInvOrgQty,from_inventory_id__curr_qty:fromInvCurQty,to_inventory_id__id
_operationType	GET
_description	To get inventory id from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: textLoadNumber

Property Name	Property Value

_beforeExit	script:
	GET_OB_STOP_DTL_WS.callWebService(null);
	if(GET_OB_STOP_DTL_WS.getResponseCode()==200)
	{
	JSONObject ob_json =new JSONObject(GET_OB_STOP_DTL_WS.getRawResponse());
	JSONArray ob_arr = ob_json.getJSONArray("results");
	//NEW CODE
	int reserveQty=0;
	for(int s=0; s<ob_arr.length(); s++)
	{
	reserveQty += ob_arr.get(s).getInt("Qty");
	}
	//flexi.setStatusMessage("Current Qty Sum Value------>"+reserveQty);
	flexi.putObject("CURR_QTY_OBJ",reserveQty);
	String cntr=String.valueOf(flexi.getObject("CURR_QTY_OBJ"));
	XX_TOTL_QTY_PACK.setValue(cntr);
	}

Field Name: XX_ASSIGN_SKU_QTY

Property Name	Property Value
label	Assign SKU Qty

Field Name: XX_CAL_AREA

Property Name	Property Value
_rendered	false
label	Calculate Area

Field Name: XX_WEIGHT

Property Name	Property Value
_rendered	false
label	Weight

Field Name: XX_ASSIGN_PLT_COUNT

Property Name	Property Value
label	Assign PLT Count

Field Name: XX_TOTL_QTY_PACK

Property Name	Property Value
label	Total QTY Packed in Pallet
_readOnly	true

Field Name: GET_OB_STOP_DTL_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/ob_stop_dtl?values_list=ob_stop_id__load_id__load_nbr:load_nbr,container_id__container_nbr:container_nbr,container_id__cntr_inv__item_id__code:item_code,container_id__cntr_inv__to_from_inv__order_dtl_id__order_id__order_nbr:order_nbr2,container_id__cntr_inv__curr_qty:Qty&ob_stop_id__load_id__load_nbr=${textLoadNumber}
_operationType	GET
_description	To get LPN count and Current qty sum from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: GET_INVENTORY_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/inventory?id=${INV_ID}
_operationType	GET
_description	To get Item qty count
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Barcode Level Properties

<< End Personalization >>