FLEXI PERSONALIZATION REPORT

<< Start Personalization >>

Application Name: STD - Pick wave LPN / PLT

Page Name:

Personalization Level : Site

Personalization Value :

New Fields

Field Name	Type	Position
GET_ALLOCATION_ALLOC_WS	Web Service	after textInputable
GET_ALLOCATION_PICK_WS	Web Service	after textInputable
XX_DROP_FIELD	Text	before textInputable
GET_DROP_LOC_WS	Web Service	after textInputable
GET_TASK_WS	Web Service	after textInputable

Page Level Properties

Property Name	Property Value

_afterPageEntered	script:
	if(textInputable!=void)
	{
	if(textInputable.getLabel().contains("Task/Container")) {
	XX_DROP_FIELD.setHidden(true);
	}
	}
	if(textInputable!=void)
	{
	if(textInputable.getLabel().contains("Drop")) {
	textInputable.setHidden(true);
	XX_DROP_FIELD.setHidden(false);
	}
	}
	if(textTask!=void)
	{
	if(textTask.getLabel().contains("Task"))
	{
	XX_DROP_FIELD.setHidden(true);
	}
	}

Field Level Properties

Field Name: textInputable

Property Name	Property Value

_onKeyPress	script:
	if(textInputable.getLabel().contains("Task/Container"))
	{
	if(textInputable.getValue().length()>0)
	{
	flexi.putSessionObject("TASK_NUM",textInputable.getValue());
	}
	}else{
	
	}

_afterFocus	script: XX_DROP_FIELD.setHidden(true);
_lovSourceType	Web Service

_beforeExit	script:
	if(textInputable.getLabel().contains("Task/Container"))
	{
	if(textInputable.getValue().length()>0)
	{
	flexi.putSessionObject("TASK_NUM",textInputable.getValue());
	}
	}else{
	
	}

Field Name: GET_DROP_LOC_WS

Property Name	Property Value
_columnmap	results.barcode
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/location?type_id__description=Drop&values_list=barcode${LOC_STARTS}
_operationType	GET
_description	GET DROP LOCATION
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

_onCallingRequest	script:
	if(XX_DROP_FIELD.getValue().length()>0){
	
	flexi.putObject("LOC_STARTS","&barcode__startswith="+XX_DROP_FIELD.getValue());
	}else{
	flexi.putObject("LOC_STARTS","");
	}

Field Name: GET_TASK_WS

Property Name	Property Value
_columnmap	results.task_nbr
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/task?status_id=30&values_list=task_nbr&page_size=1250
_operationType	GET
_description	To get task number from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: XX_DROP_FIELD

Property Name	Property Value
_lovSourceType	Web Service
_webService	GET_DROP_LOC_WS

_beforeExit	script:
	if(XX_DROP_FIELD.getValue().length()>0)
	{
	textInputable.setHidden(false);
	textInputable.setValue(XX_DROP_FIELD.getValue());
	flexi.automate("enter");
	}

_lovPageTitle	Drop
_columnDisplay	true
_columnPrompt	Location
_lovValidation	true
lovEnabled	true
label	Drop

Field Name: GET_ALLOCATION_ALLOC_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation/?task_id__task_nbr=${TASK_NUM}&fields=alloc_qty,packed_qty
_operationType	GET
_description	To get Sum of alloc_qty from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Field Name: GET_ALLOCATION_PICK_WS

Property Name	Property Value
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation/?task_id__task_nbr=${TASK_NUM}&fields=alloc_qty,packed_qty
_operationType	GET
_description	To get Sum of picked qty from this web service
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Barcode Level Properties

<< End Personalization >>

<< Start Personalization >>

Application Name: STD - Pick wave LPN / PLT

Page Name: Pack NC Active

Personalization Level : Site

Personalization Value :

New Fields

Field Name	Type	Position
XX_TASK_QTY	Text	before textOBLPN
XX_TASK_PICK_QTY	Text	after XX_TASK_QTY
XX_TASK_BAL_QTY	Text	after XX_TASK_PICK_QTY

Page Level Properties

Property Name	Property Value

_afterPageEntered	script:
	GET_ALLOCATION_ALLOC_WS.callWebService(null);
	if(GET_ALLOCATION_ALLOC_WS.getResponseCode()==200)
	{
	JSONObject alloc_json =new
	JSONObject(GET_ALLOCATION_ALLOC_WS.getRawResponse());
	JSONArray alloc_arr = alloc_json.getJSONArray("results");
	//NEW CODE
	int reserveQty=0;
	for(int s=0; s<alloc_arr.length(); s++)
	{
	reserveQty += alloc_arr.get(s).getInt("alloc_qty");
	}
	//flexi.setStatusMessage("Alloc Sum Value------>"+reserveQty);
	flexi.putObject("ALLOC_QTY_OBJ",reserveQty);
	String cntr=String.valueOf(flexi.getObject("ALLOC_QTY_OBJ"));
	XX_TASK_QTY.setValue(cntr);
	}
	GET_ALLOCATION_PICK_WS.callWebService(null);
	if(GET_ALLOCATION_PICK_WS.getResponseCode()==200)
	{
	JSONObject pick_json =new
	JSONObject(GET_ALLOCATION_PICK_WS.getRawResponse());
	JSONArray pick_arr = pick_json.getJSONArray("results");
	//NEW CODE
	int pickedQty=0;
	for(int p=0; p<pick_arr.length(); p++)
	{
	pickedQty+= pick_arr.get(p).getInt("packed_qty");
	}
	flexi.setStatusMessage("Picked Qty Sum Value------>"+pickedQty);
	flexi.putObject("PICKED_QTY_OBJ",pickedQty);
	String pr=String.valueOf(flexi.getObject("PICKED_QTY_OBJ"));
	XX_TASK_PICK_QTY.setValue(pr);
	}
	double alloctn_qty = Double.parseDouble(XX_TASK_QTY.getValue());
	double pick_qty =
	Double.parseDouble(XX_TASK_PICK_QTY.getValue());
	double sum_qty = alloctn_qty + pick_qty;
	flexi.setStatusMessage("Sum Qty--->"+sum_qty);
	//flexi.gotoComponent("XX_TASK_BAL_QTY");
	String sum_str = String.valueOf(sum_qty);
	XX_TASK_BAL_QTY.setValue(sum_str);

Field Level Properties

Field Name: XX_TASK_QTY

Property Name	Property Value
label	Task qty
_readOnly	true

Field Name: XX_TASK_BAL_QTY

Property Name	Property Value
label	Task Balance qty
_readOnly	true

Field Name: XX_TASK_PICK_QTY

Property Name	Property Value
label	Task picked qty
_readOnly	true

Barcode Level Properties

<< End Personalization >>

<< Start Personalization >>

Application Name: STD - Pick wave LPN / PLT

Page Name: NSBP RF Move LPN

Personalization Level : Site

Personalization Value :

New Fields

Field Name	Type	Position
XX_TASK_QTY	Text	before textPlt6
XX_TASK_PICK_QTY	Text	after XX_TASK_QTY
XX_TASK_BAL_QTY	Text	after XX_TASK_PICK_QTY

Page Level Properties

Property Name	Property Value

_afterPageEntered	script:
	ArrayList List = new ArrayList();
	String orderDetailId = null;
	
	GET_ALLOCATION_ALLOC_WS.callWebService(null);
	if(GET_ALLOCATION_ALLOC_WS.getResponseCode()==200)
	{
	JSONObject alloc_json =new JSONObject(GET_ALLOCATION_ALLOC_WS.getRawResponse());
	JSONArray alloc_arr = alloc_json.getJSONArray("results");
	//NEW CODE
	int reserveQty=0;
	for(int s=0; s<alloc_arr.length(); s++)
	{
	reserveQty += alloc_arr.get(s).getInt("alloc_qty");
	
	}
	//flexi.setStatusMessage("Alloc Sum Value------>"+reserveQty);
	flexi.putObject("ALLOC_QTY_OBJ",reserveQty);
	String cntr=String.valueOf(flexi.getObject("ALLOC_QTY_OBJ"));
	XX_TASK_QTY.setValue(cntr);
	}
	
	GET_ALLOCATION_PICK_WS.callWebService(null);
	if(GET_ALLOCATION_PICK_WS.getResponseCode()==200)
	{
	JSONObject pick_json =new JSONObject(GET_ALLOCATION_PICK_WS.getRawResponse());
	JSONArray pick_arr = pick_json.getJSONArray("results");
	//NEW CODE
	int pickedQty=0;
	for(int p=0; p<pick_arr.length(); p++)
	{
	pickedQty+= pick_arr.get(p).getInt("packed_qty");
	
	}
	//flexi.setStatusMessage("Picked Qty Sum Value------>"+pickedQty);
	flexi.putObject("PICKED_QTY_OBJ",pickedQty);
	String pr=String.valueOf(flexi.getObject("PICKED_QTY_OBJ"));
	XX_TASK_PICK_QTY.setValue(pr);
	
	}
	
	double alloctn_qty = Double.parseDouble(XX_TASK_QTY.getValue());
	double pick_qty = Double.parseDouble(XX_TASK_PICK_QTY.getValue());
	double sum_qty = alloctn_qty + pick_qty;
	//flexi.setStatusMessage("Sum Qty--->"+sum_qty);
	//flexi.gotoComponent("XX_TASK_BAL_QTY");
	String sum_str = String.valueOf(sum_qty);
	XX_TASK_BAL_QTY.setValue(sum_str);

Field Level Properties

Field Name: XX_TASK_QTY

Property Name	Property Value
label	Task Qty
_readOnly	true

Field Name: XX_TASK_BAL_QTY

Property Name	Property Value
label	Task Balance Qty
_readOnly	true

Field Name: XX_TASK_PICK_QTY

Property Name	Property Value
label	Task Picked qty
_readOnly	true

Barcode Level Properties

<< End Personalization >>

<< Start Personalization >>

Application Name: STD - Pick wave LPN / PLT

Page Name: STD - Pick wave LPN / PLT

Personalization Level : Site

Personalization Value :

New Fields

Field Name	Type	Position
GET_TASK_NBR_WS	Web Service	after btnExitApp

Page Level Properties

Property Name	Property Value

Field Level Properties

Field Name: textInputTask

Property Name	Property Value
_lovSourceType	Web Service
_webService	GET_TASK_NBR_WS
_columnDisplay	true
_columnPrompt	Task No
_lovValidation	true
lovEnabled	true

Field Name: GET_TASK_NBR_WS

Property Name	Property Value
_columnmap	results.task_nbr
_passWS	${FLEXI_LOG_FIRE_PASSWORD}
_wsurl	${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/task?status_id_in=0&values_list=task_nbr
_operationType	GET
_userWS	${FLEXI_LOG_FIRE_USER}
_contentType	application/json

Barcode Level Properties

<< End Personalization >>