# FLEXI PERSONALIZATION REPORT

**<< Start Personalization >>**

**Application Name:** STD - Vehicle load

**Page Name:** STD - Vehicle load

**Personalization Level :** Site

**Personalization Value :**

## New Fields

| Field Name | Type | Position |
|---|---|---|
| XX_VEHICLE_NO | Text | before textLoadNumber |
| XX_LPN_PLT | Text | after textLoadNumber |
| XX_ASSIGN_SKU_QTY | Text | after textOrderNbr |
| XX_ASSIGN_LPN_CONT | Text | after XX_ASSIGN_SKU_QTY |
| XX_ASSIGN_PLT_CONT | Text | after XX_ASSIGN_LPN_CONT |
| XX_WEIGHT | Text | after XX_ASSIGN_PLT_CONT |
| XX_CAL_AREA | Text | after XX_WEIGHT |
| XX_CAL_CBM | Text | after XX_CAL_AREA |
| XX_TOTAL_LPN_PACK_PLT | Text | after XX_CAL_CBM |
| XX_TOTAL_QTY_PACK_PLT | Text | after XX_TOTAL_LPN_PACK_PLT |
| GET_ORDER_DTL_WS | Web Service | after btnPreviousscreen |
| GET_ALLOC_WS | Web Service | after btnPreviousscreen |
| GET_PALLET_WS_NEW | Web Service | after btnPreviousscreen |

## Page Level Properties

| Property Name | Property Value |
|---|---|

## Field Level Properties

**Field Name:** XX_CAL_CBM

| Property Name | Property Value |
|---|---|
| label | Calculate CBM |

**Field Name:** GET_PALLET_WS_NEW

| Property Name | Property Value |
|---|---|
| _columnmap | results.actual_weight,results.CAL_AREA,results.NET_WEIGHT |
| _passWS | ${FLEXI_LOG_FIRE_PASSWORD} |
| _wsurl | ${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/pallet?pallet_nbr=${LPN_PALLET_OBJ}&values_list=actual_weight,cust_field_4:CAL_AREA,cust_field_3:NET_WEIGHT |
| _operationType | GET |
| _description | To get the Weight, cal area and cal cbm from this web service |
| _userWS | ${FLEXI_LOG_FIRE_USER} |
| _contentType | application/json |

**Field Name:** XX_ASSIGN_PLT_CONT

| Property Name | Property Value |
|---|---|
| label | Assign PLT Count |

**Field Name:** XX_VEHICLE_NO

| Property Name | Property Value |
|---|---|
| label | Vehicle Number |

**Field Name:** textOrderNbr

| Property Name | Property Value |
|---|---|
| _onKeyPress | script:<br>flexi.putObject("ORDER_OBJ_NEW",textOrderNbr.getValue());<br>GET_ORDER_DTL_WS.callWebService(null);<br>if(GET_ORDER_DTL_WS.getResponseCode()==200){<br>JSONObject ordjson = new<br>JSONObject(GET_ORDER_DTL_WS.getRawResponse());<br>JSONArray ordarr = ordjson.getJSONArray("results");<br>flexi.putObject("ORDER_QTY_NEW",ordarr.get(0).get("ord_qty").toString<br>());<br>XX_ASSIGN_SKU_QTY.setValue(flexi.getObject("ORDER_QTY_NEW"))<br>;<br>}<br><br>//To get packed LPN result count from this web service<br>GET_ALLOC_WS.callWebService(null);<br>if(GET_ALLOC_WS.getResponseCode()==200)<br>{<br>org.json.JSONObject getRes = new<br>org.json.JSONObject(GET_ALLOC_WS.getRawResponse());<br>Integer resultCount = getRes.get("result_count");<br>flexi.putObject("LPN_COUNT1",String.valueOf(getRes.get("result_count")<br>));<br>XX_ASSIGN_LPN_CONT.setValue(flexi.getObject("LPN_COUNT1"));<br>//flexi.setStatusMessage("LPN count Object value-----<br>>"+flexi.getObject("LPN_COUNT1"));<br>} |

| | |
|---|---|
| _beforeExit | script:<br>flexi.putObject("ORDER_OBJ_NEW",textOrderNbr.getValue());<br>GET_ORDER_DTL_WS.callWebService(null);<br>if(GET_ORDER_DTL_WS.getResponseCode()==200){<br>JSONObject ordjson = new<br>JSONObject(GET_ORDER_DTL_WS.getRawResponse());<br>JSONArray ordarr = ordjson.getJSONArray("results");<br>flexi.putObject("ORDER_QTY_NEW",ordarr.get(0).get("ord_qty").toString<br>());<br>XX_ASSIGN_SKU_QTY.setValue(flexi.getObject("ORDER_QTY_NEW"))<br>;<br>}<br><br>//To get packed LPN result count from this web service<br>GET_ALLOC_WS.callWebService(null);<br>if(GET_ALLOC_WS.getResponseCode()==200)<br>{<br>org.json.JSONObject getRes = new<br>org.json.JSONObject(GET_ALLOC_WS.getRawResponse());<br>Integer resultCount = getRes.get("result_count");<br>flexi.putObject("LPN_COUNT1",String.valueOf(getRes.get("result_count")<br>));<br>XX_ASSIGN_LPN_CONT.setValue(flexi.getObject("LPN_COUNT1"));<br>//flexi.setStatusMessage("LPN count Object value-----<br>>"+flexi.getObject("LPN_COUNT1"));<br>} |

**Field Name:** XX_LPN_PLT

| Property Name | Property Value |
|---|---|
| _beforeExit | script:<br>if(XX_LPN_PLT.getValue().length()>0)<br>{<br>flexi.putSessionObject("LPN_PALLET_OBJ",XX_LPN_PLT.getValue());<br><br>GET_PALLET_WS_NEW.callWebService(null);<br>if(GET_PALLET_WS_NEW.getResponseCode()==200)<br>{<br>JSONObject plt_resp = new<br>JSONObject(GET_PALLET_WS_NEW.getRawResponse());<br>JSONArray plt_arr = plt_resp.getJSONArray("results");<br>flexi.putObject("ACTUAL_WGHT",plt_arr.get(0).get("actual_weight"));<br>flexi.putObject("CAL_AREA_OB",plt_arr.get(0).get("CAL_AREA"));<br>flexi.putObject("NET_WGHT",plt_arr.get(0).get("NET_WEIGHT"));<br>XX_WEIGHT.setValue(String.valueOf(flexi.getObject("ACTUAL_WGHT")<br>));<br>XX_CAL_AREA.setValue(String.valueOf(flexi.getObject("CAL_AREA_OB<br>")));<br>//XX_CAL_CBM.setValue(String.valueOf(flexi.getObject("NET_WGHT")))<br>;<br>}<br>} |
| label | LPN/PLT |

**Field Name:** XX_ASSIGN_SKU_QTY

| Property Name | Property Value |
|---|---|
| label | Assign SKU Qty |

**Field Name:** XX_CAL_AREA

| Property Name | Property Value |
|---|---|
| label | Calculate Area |

**Field Name:** XX_TOTAL_LPN_PACK_PLT

| Property Name | Property Value |
|---|---|
| label | TOTAL LPN PACKED in Pallet |

**Field Name:** XX_TOTAL_QTY_PACK_PLT

| Property Name | Property Value |
|---|---|
| label | TOTAL QTY PACKED in Pallet |

**Field Name:** XX_WEIGHT

| Property Name | Property Value |
|---|---|
| label | Weight |

**Field Name:** XX_ASSIGN_LPN_CONT

| Property Name | Property Value |
|---|---|
| label | Assign LPN Count |

**Field Name:** GET_ALLOC_WS

| Property Name | Property Value |
|---|---|
| _passWS | ${FLEXI_LOG_FIRE_PASSWORD} |
| _wsurl | ${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/allocation?order_dtl_id__order_id__order_nbr=${textOrderNbr}&to_inventory_id__container_id__status_id__description=Packed&values_list=id,order_dtl_id__order_id__order_nbr:orderNo,order_dtl_id__item_id__description:itemDesc,to_inventory_id__pack_qty:toInvPckQty,to_inventory_id__orig_qty:toInvOrgQty,to_inventory_id__curr_qty:toInvCurQty,from_inventory_id__pack_qty:fromInvPckQty,from_inventory_id__orig_qty:fromInvOrgQty,from_inventory_id__curr_qty:fromInvCurQty,to_inventory_id__id,order_dtl_id__order_id__id,to_inventory_id__container_id__status_id__description |
| _operationType | GET |
| _description | To get LPN Count from this web service |
| _userWS | ${FLEXI_LOG_FIRE_USER} |
| _contentType | application/json |

**Field Name:** GET_ORDER_DTL_WS

| Property Name | Property Value |
|---|---|
| _passWS | ${FLEXI_LOG_FIRE_PASSWORD} |
| _wsurl | ${LOGFIRE_WEBSERVICE_URL}/wms/lgfapi/v10/entity/order_dtl?order_id__order_nbr=${ORDER_OBJ_NEW} |
| _operationType | GET |
| _description | To get assign SKU qty from this web service |
| _userWS | ${FLEXI_LOG_FIRE_USER} |
| _contentType | application/json |

## Barcode Level Properties

## << End Personalization >>