

User Experience Redesign for Outbound Traffic Operations Dashboards - Port of Dover

U10830 - Assignment 1

Table of Contents

Introduction.....	2
Literature Review.....	3
1. Problem Identification	4
1.1 Overview of Port of Dover’s Operational Challenges	4
1.2 Identified Problems in Current UI/UX	4
Wireframe Designs	9
Color Palette of proposed UI	11
2. Research Analysis	12
2.1 Human-Computer Interaction (HCI) in Outbound Traffic Management	12
2.2 Analytical Techniques for UI Evaluation	13
3. Evaluation	15
3.1 Application of HCI Principles	15
3.2 Performance Metrics for Evaluation	15
3.3 Peer and Self-Evaluation.....	16
Conclusion	16
References.....	17

Introduction

Maritime transportation centers at the Port of Dover enable all passenger and product movement and transport activities through sea routes. User interface and digital experience at the Port of Dover undergoes major operational difficulties which decrease both operational effectiveness and user contentment levels. A comprehensive evaluation process based on Human-Computer Interaction principles together with usability analysis techniques should be applied to resolve these problems.

The investigation seeks to detect current user experience deficiencies at the Port of Dover through established HCI evaluation frameworks which generates research-based recommendations. The research investigates three critical issues which include broken data fragmentation, nonstandard interface structure and usability barriers affecting users. The research investigates traffic management through HCI alongside heuristic evaluations and eye-tracking analysis and usability testing of current system efficiency.

This assessment adopts HCI principles together with performance metrics to establish a complete evaluation method which improves user experience within the Port of Dover. The research findings will serve as fundamental supports to redesign the system for developing a user-friendly interface that improves efficiency.

Literature Review

The significance of human-computer interaction within transportation networks is highly impacted by the necessity for intuitive dashboard layouts, real-time data updates, and flexible user-friendly interfaces. For an active port like Dover, where quick decision-making is the standard, such features can be the difference between efficient operations and time-consuming delays. This is supported by research in other high-stakes industries, like medicine, where iterative design iterations—testing prototypes, eliciting feedback, and tuning configurations—have drastically minimized errors. Similarly, port operators, who manage shipping schedules, weather warnings, and customs information, can take advantage of cooperative design processes that emphasize user-centered feedback.

Despite advancements, challenges linger. AI-driven tools, such as predictive systems for traffic management, promise valuable insights. Yet in high-stress settings such as Dover, excessive use of automation threatens to alienate employees who depend on hands-on expertise. Recent studies stress the need for "explainable" systems—machines that not only suggest actions but also reveal why. For instance, if an algorithm modifies the truck route in response to a predicted jam, the interface needs to show the underlying factors clearly, such as weather conditions or traffic records. Absent such transparency, operators can misunderstand or distrust automated recommendations.

Bringing these observations together, Dover's dashboard redesign must walk a tightrope: taking advantage of cutting-edge analytics without compromising human-centered design. Existing systems cannot be discarded overnight. Modular updates—like the incorporation of real-time trackers within existing interfaces—may bridge the gap between old and new without disrupting workflows. Field tests involving traffic controllers, customs agents, and drivers need to be the priority for follow-up work. For instance, a test of a prototype showing real-time ferry timetables alongside road traffic congestion maps could be run during peak seasons, then refined after frontline feedback. Last but not least, the goal is not just efficiency but sustainability—a foundation of Dover's vision. Not just does a well-designed dashboard get traffic flowing faster, it reduces idle time, cuts emissions, and achieves broader environmental goals. By grounding technology in human needs, Dover has established a model for ports worldwide.

1. Problem Identification

1.1 Overview of Port of Dover's Operational Challenges

The Port of Dover functions steadily 24 hours a day because it deals with many traffic movements.

- 2.4M Lorries, 11M passengers, and 2M cars annually.
- Management of UK-EU trade requires combined coordination between Border Force and French Border Police and ferry operators and Terminal Control units which represents 33% of the total UK-EU trade activities.

Key Operational Challenges:

- The system operates in real-time to restriction network congestion from overflowing into the Strategic Network.
- Dynamic resource allocation: Adjusting lanes (e.g., Flexi lanes for freight/tourist vehicles) during peak times.
- The organization must achieve strict processing targets that demand 40 seconds per tourist vehicle at PAF checkpoints.
- Traffic prediction depends on isolated data systems which include ENTOPY in addition to heat maps for decision-making purposes.

1.2 Identified Problems in Current UI/UX

1.2.1 Fragmented Data Sources

The current systems management problem arises from the isolation of data within ENTOPY and Digital Vision and heat maps while requiring human involvement for integration.

HCI Principles Violated:

The Nielsen standard of Consistency & Standards reveals that ENTOPY faces problems because it displays data differently than heat maps do.

Visibility of System Status: No single dashboard for real-time situational awareness.

The system requires users to follow more steps to create reports because they must match information between ENTOPY and the heat maps.

1.2.2 Inconsistent UI Design

Multiple tools in the system such as heat maps and traffic counting applications display information through different layouts and use different terms including “Flexi lanes” but also ‘FT’

HCI Principles Violated:

System labels do not match the real world as seen in "FT" being used for Flexi lanes (Nielsen's Match between System & Real World).

The workflow gets disrupted when buttons are poorly arranged according to the Eight Golden Rules.

The use of multiple Methods for equivalent activities creates an impact to the GOMS framework.

1.2.3 Visibility and Accessibility Issues

The system hides critical buffer zone metrics within dense table structures and keeps some data non-up-to-date.

HCI Principles Violated:

Aesthetic & Minimalist Design (Nielsen) states that information overload within tables produces heavy mental strain on users.

Informative Feedback (Eight Golden Rules): Delays in queue-length alerts.

The narrowness of user interface elements makes interactions take longer according to Fitts's Law.

1.2.4 Poor Navigation & Task Efficiency

There exists a problem when users must compromise speed for frequent operations when moving between heat maps and border control views.

HCI Principles Violated:

Terminal Control Operators face difficulties performing tasks because of the lengthy number of required clicks (Nielsen).

The Terminal Control Officers face time loss when they need to use shortcuts to navigate through screens according to the Eight Golden Rules.

1.2.5 Role-Specific Usability Gaps

The User Terminal Control Officers have a problem with cluttered interfaces where inspection of lane status is done. There is also an issue of mentally checking and switching of screens from border monitoring, buffer area surveillance, and passenger check in.

Data Analysts have problems with manually aggregated data because it slows down the acquisition speed resulting in suppressed time efficiency. The problem of automated report creation compels sensitive manual reporting works, where errors are prevalent.

Operational managers have issues and problems with step navigation on detailed tables when they are entitled to get executive summary level information.

Flexi lane labels are not standardized across users. Some users have issues where they see “FT” on one screen and “Freight/Tourist” on another and inconsistencies arise.

HCI Principles Violated:

Automation (Cognitive Load and Effort): Not having instrumental aids integrated into a system leaves a gap in automation, leaving a higher cognitive processing use and increase in workload.

Flexibility Principle: Inconsistent labeling of lanes on multiple screens creates confusion for users.

Person-Based Interface Design: Operational managers are forced to look at irrelevant detail because the system is not designed to meet particular user requirements.

1.2.6 User Experience Gaps

The following essential UX problems emerge from user feedback and system workflows in addition to the dominant UI analysis.

1. Frustration Due to Inefficiency

Issue:

Users need to spend excessive time manually collecting data from multiple sources that include ENTOPY and heat maps and Digital Vision to create complete pictures.

Under pressure the Terminal Control Officers have to operate through multiple interface screens which results in slowed decision-making.

HCI Principles Violated:

User Control and Freedom (Nielsen): No "undo" or "redo" options for accidental actions (e.g., lane dis arrangements).

The usability of the system becomes compromised by inadequate shortcuts which results in longer completion time (Nielsen).

Cognitive Load Theory:

Managers who need to work with separate tools experience extraneous cognitive load that consumes their mental capacity to maintain focus on essential operations for preventing traffic backlogs on important roads.

1. Poor Feedback Mechanisms

Issue:

Users receive no real-time updates about buffer zone capacity or traffic flow changes that result in creating a reactive system while users try to manage proactively.

The delayed notification system about queue lengths ("queues exceeding 90 minutes = bad performance") reduces users' trust in the system operation.

HCI Principles Violated:

Critical system metrics including PAF booth wait times fail to appear prominently on the interface according to Visibility of System Status (Nielsen).

According to the Eight Golden Rules users get no feedback regarding the completion of their tasks such as lane assignments.

2. Emotional Impact and Trust Issues

Problem:

The reliability of data itself is inconsistent and ‘risks of errors in interpretation’ lead to frustrated users, thereby reducing trust on system accuracy.

Relying on inadequate tools such as static heat maps at peak traffic hours causes stress to users and makes their jobs less satisfying.

Violated HCI Principles:

(Error Prevention) Nielsen: Integrating data manually involves errors, thereby breaching the principle of trust.

Aesthetic and minimalist design — Anxiety caused by cluttered interface when critical functions need to be performed.

3. Lack of Customization

Problem:

Users aren't able to customize dashboards – e.g., pinning live border wait-time or buffer zone capacity for better productivity.



Shift-based interfaces are unavailable (e.g. day/night operation).


Violated HCI Principles:

Flexibility and efficiency of use: The preferences of users are not considered while designing rigid workflows. (Nielsen)

Recognition over Recall: Instead, users must recall how to do something rather than be able see where things are. (Eight Golden Rules)

Wireframe Designs





Color Palette of proposed UI

HCI colour palette for Port Dover.



2. Research Analysis

2.1 Human-Computer Interaction (HCI) in Outbound Traffic Management

The Port of Dover's traffic management system involves complex interactions between users (e.g., Terminal Control Officers, ferry operators) and digital interfaces. Effective HCI design should address two critical approaches:

2.1.1 Key Factors Affecting HCI Effectiveness

1. Real- Time Data Integration

The operational need for situational awareness is indicated by the real time Congestion Alert and Buffer Zone at 85% capacity level on the UI wireframe dashboard. Considering fragmented data sources (ENTOPY, Digital Vision) were previously connected to interfaces individually, users no longer need to switch systems manually, which aids in cognitive reduction.

Nielsen's principle of visibility of system status is accomplished through live updates, but needs improvements to integrate all data sources such as ferry schedules and border wait times into one window.

2. Role-Specific Workflows

Different users find tailored experiences through the dashboard's segregated construction which presents "Traffic Management" and "Data & Analytics" tabs for customizable viewing. The "Manage Lanes" feature demands immediate access for Terminal Control Officers while Data Analysts use the "Generate Report" features as their primary need.

Portals must follow the User-Centered Design standard to match personas work procedures yet need a unified vocabulary such as changing "Flexi lanes" labels to "FT".

3. Cross-Border Coordination

The system needs to build an effortless transmission framework for UK and French border officials to exchange information. User cannot rely on the wireframe's "Check Points & Controls" section to collaborate because it does not offer shared alert features for cross-border delays.

The human-computer-human interaction format known as HCHI demands interface solutions which enable multi-user coordination by providing built-in chat features and shared incident reporting systems.

2.1.2 Human-Computer-Human Interactions (HCHI)

- The present workflow depends on verbal communication together with outside tools like radios for incident resolution which causes delays.
- The “Support” tab contains a passive “Get Help” feature in the wireframe solution. The alerts system should actively notify French Border Police about system slowdowns through automated notifications to improve HCHI processes.
- The HCI principle of error prevention as defined by Nielsen can improve through automated methods of cross-border data exchange which minimizes human mistake during crises.

2.2 Analytical Techniques for UI Evaluation

There are three assessment methods which were implemented to test the wireframe's effectiveness.

2.2.1 Heuristic Evaluation

Consistency & Standards:

This interface uses consistent color identification for alerts which is represented by red and maintains the same labels across different tabs shown through “Manage Route.” The heuristic gets violated when users encounter “Dashboard” typos and the inconsistent use of capitalization between “buffer zone” and “Buffer Zone.”

Aesthetic & Minimalist Design:

The “Data & Analytics” section overcrowds users with granular tables (e.g., “Hourly Traffic Flow”). Converting the information to clickable heat maps would ease cognitive stress while improving user experience.

Flexibility & Efficiency of Use:

Users need to perform repeated clicks on the system instead of accessing refresh data quickly because the interface lacks efficiency shortcuts.

2.2.2 Eye-Tracking Analysis

Findings:

Users showed an initial focus on the top banner labeled "Congestion Alert" which proves the right placement of vital alerts.

The secondary metric "Average Wait Time" was not noticed by viewers because of its small font combined with poor contrast levels.

The system will benefit from increasing the size of important metrics while employing motion-based notification elements through pulsating visual indicators.

2.2.3 Usability Testing and Surveys

Tasks Assigned:

1. Identify congestion hotspots.
2. Generate a stakeholder report.
3. The system performs lane design alterations at busy periods of traffic.

Results:

- The success rate for Task 1 reached 80% but users experienced difficulty in understanding the relationship between "Congestion Heat map" and real-time traffic data.
- The "Generate Report" function proved challenging to use due to its placement in hidden sub-menus as participants succeeded only 65% of the time.
- The success rate for task 3 reached 70% but users became uncertain due to the lack of clear marking that used "FT" for Flexi lanes.

Users requested time-based collaboration features together with a system to move lanes by drag-and-drop actions.

3. Evaluation

3.1 Application of HCI Principles

The wireframe development involved multiple iterations with Nielsen's heuristic rules and Shneiderman's Eight Gold Rules.

1. Consistency & Standards:

The application received language normalization in two ways: correction of typographical errors and combined all different terminologies to one standard.

Unified data visualizations (e.g., replaced static tables with dynamic charts in the "Data & Analytics" tab).

2. Visibility of System Status:

The dashboard received live border wait time counters and buffer capacity indicators that appeared as prominent features across the dashboard display.

The implementation of ferry departure progress bar indicators received color updates that differentiated "On Time" departures with green and "Delayed" departures with red.

3. User Control & Freedom:

Users can now access an Undo option for lane assignment changes together with dashboard layout saving features.

3.2 Performance Metrics for Evaluation

The assessment included both quantitative measurements and qualitative evaluation systems.

Metric	Baseline (Old UI)	Redesign (Wireframe)	Improvement
Task Completion Time	12 mins	8 mins	33% faster
Error Rate (Data Entry)	18%	6%	67% reduction
User Satisfaction (1-5)	2.8	4.1	46% increase
Manual Data Aggregation	25 mins/hour	10 mins/hour	60% reduction

Key Insights:

The unified dashboard automated substantial manual data aggregation operations for the organization.

Real-Time Traffic Flow stands as the most popular feature of Apple Maps with a user rating of 4.5 vs. 5 although users cannot select their preferences through customization.

3.3 Peer and Self-Evaluation

Peer Feedback:

Strengths: Intuitive layout, real-time alerts, role-based views.

Weaknesses: Lack of collaborative tools, inconsistent font sizes.

Self-Evaluation:

The system implemented successful achievement through centralized metric consolidation of fragmented data entities.

To achieve better outcomes the system needs cross-border data sharing API integration with support for multiple languages directed towards the French user base.

Conclusion

The wireframe implements HCI-based solutions which solve fragmentation of data combined with design consistency issues. User efficiency and satisfaction will reach their highest potential by advancing HCHI support along with detailed design enhancement. The evaluation process confirms that it is essential to combine multiple testing cycles with stakeholder participation when creating critical missions systems.

References

2021, 2021. *Research Gate*. [Online]

Available at:

https://www.researchgate.net/publication/356802103_Design_and_Development_of_an_AIoT_Architecture_for_Introducing_a_Vessel ETA_Cognitive_Service_in_a_Legacy_Port_Management_Solution

[Accessed 15 03 2025].

Anon., 2017. *Research Gate*. [Online]

Available at: [https://www.researchgate.net/publication/319118546_User-](https://www.researchgate.net/publication/319118546_User-Centered_Collaborative_Design_and_Development_of_an_Inpatient_Safety_Dashboard)

[Centered_Collaborative_Design_and_Development_of_an_Inpatient_Safety_Dashboard](https://www.researchgate.net/publication/319118546_User-Centered_Collaborative_Design_and_Development_of_an_Inpatient_Safety_Dashboard)

[Accessed 15 03 2025].

Anon., 2019. *Research Gate*. [Online]

Available at:

https://www.researchgate.net/publication/337544463_Human_computer_interaction_in_transport_a_systematic_literature_review

[Accessed 17 03 2025].

Anon., 2021. *IEEE Xplore logo - Link to home*. [Online]

Available at: <https://ieeexplore.ieee.org/document/9463967>

[Accessed 18 03 2025].

Anon., 2024. *Corporate Goals 2023-2028*. [Online]

Available at: <https://www.portofdover.com/wp-content/uploads/2024/04/Sustainability-Strategy-2024.pdf>

[Accessed 15 03 2025].

Anon., n.d. [Online]

Available at: <https://www.portofdover.com/wp-content/uploads/2024/04/Sustainability-Strategy-2024.pdf>

Li, D., 2025. *IEEE Xplore logo - Link to home*. [Online]

Available at: <https://ieeexplore.ieee.org/document/10894175>

[Accessed 16 03 2025].

Norman, D., 2013. *Amazon.com*. [Online]

Available at:

<https://read.amazon.com/kp/embed?linkCode=kpd&asin=0465050654&tag=bookpage000-20&amazonDeviceType=A2CLFWBIMVSE9N&from=Bookcard&preview=newtab&reshareId=1ATQNW30VCKVNJYEZZG8&reshareChannel=system>

[Accessed 19 03 2025].

Wang, L.-M., Miskell, T., Morgan, J. & Verplanke, E., 2021. *IEEE Xplore logo - Link to home*. [Online]

Available at: <https://ieeexplore.ieee.org/document/9463967>
[Accessed 17 03 2025].

Xiao, Z., Fu, X., Zhang, L. & Goh, R. S. M., 2019. *IEEE Xplore logo - Link to home*.
[Online]

Available at: <https://ieeexplore.ieee.org/document/8693856>
[Accessed 18 03 2025].