

AMENDMENT NO. 4 SEPTEMBER 2014
TO
IS 302-1 : 2008 SAFETY OF HOUSEHOLD AND SIMILAR
ELECTRICAL APPLIANCES

PART 1 GENERAL REQUIREMENTS

(Sixth Revision)

(Page 2, clause 2) — Insert the following at the end of the clause:

<i>IS No.</i>	<i>Title</i>
14700 (Part 4/Sec5) : 2012	Electromagnetic compatibility (EMC): Part 4 Testing and measurement techniques, Section 5 Surge immunity test
14700 (Part 4/Sec 11) : 2008	Electromagnetic compatibility (EMC): Part 4 Testing and measurement techniques, Section 11 Voltage dips, short interruptions and voltage variations immunity tests
IEC 61000-4-6	Electromagnetic compatibility (EMC) — Part 4-6: Testing and measurement techniques — Immunity to conducted disturbances, induced by radio-frequency fields
IEC 61000-4-13	Electromagnetic compatibility (EMC) — Part 4-13: Testing and measurement techniques — Harmonics and interharmonics including mains signalling at a.c. power port, low frequency immunity tests

(Page 27, clause 19.11.4.4) — Substitute the following for the existing clause:

‘19.11.4.4 The power supply terminals of the appliance are subjected to voltage surges in accordance with IS 14700 (Part 4/Sec5), five positive impulses and five negative impulses being applied at the selected points.

Amendment No. 4 to IS 302-1 : 2008

Test level 3 is applicable for the line-to-line coupling mode, a generator having a source impedance of 2 Ω being used. Test level 4 is applicable for the line-to-earth coupling mode, a generator having a source impedance of 12 Ω being used.

Earthed heating elements in class I appliances are disconnected during this test.

For appliances having surge arresters incorporating spark gaps, the test is repeated at a level that is 95 percent of the flashover voltage.

NOTE — If a feedback system depends on inputs related to a disconnected heating element, an artificial network may be needed.

19.11.4.5 The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3 being applicable. During the test, all frequencies between 0.15 MHz to 80 MHz are covered.

NOTE — The dwell time for each frequency is to be sufficient to observe a possible malfunction of the protective electronic circuit.

19.11.4.6 The appliance is subjected to the Class 3 voltage dips and interruptions in accordance with IS 14700 (Part 4/Sec 11). The values specified in Table 1 and Table 2 of IS 14700 (Part 4/Sec 11) are applied at zero crossing of the supply voltage.

19.11.4.7 The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2 being applicable.'