Lab experiment 22 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc space.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
Enter text (up to 100 characters, use ~ to end):
void main()
{
int a;
int b;
a = b + c;
c = d * e;
}

^Z
Total number of words: 18
Total number of lines: 9
Total number of characters: 34
```

Lab experiment 23 :

```
      |  ^~~~~~~

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe

 Enter any operator:+

 Addition
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>
```

Lab experiment 24 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>g
comment.c: In function 'main':
comment.c:8:2: warning: call to 'gets' declared with
g gets() is always unsafe - use fgets() instead [-Wat
    8 |  gets(com);
      |  ^~~~~~~~~

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a

 Enter comment:hello

 It is not a comment
```

Lab experiment 25 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lexical.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
enter the string : a=b+c*10
 identifiers : a b c
 constants : 10
 operators :
```

Lab experiment 26 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex math.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
20+63
The answer is = 83.000000
20*89
The answer is = 1780.000000
```

\

Lab experiment 27 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex digit.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
10

Valid digit

e

Invalid digit
```

Lab experiment 28 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex dob.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
26/07/1995
```

Lab experiment 29 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex url.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe

Enter URL :  https:\\www.sse.in

URL Invalid

https://www.sse.in

URL Valid
```

Lab experiment 30 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex pn.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
10
positive number = 10

-89
negative number = -89
```

Lab experiment 31 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex vowel.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
Enter the string of vowels and consonants:my name is maheshbabu

^Z
Number of vowels are:  7
Number of consonants are:  11
```

Lab experiment 32 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex token.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe sample.c
define is a identifier
P is a identifier
314 is a number
include is a keyword
stdio.h is a standard library
include is a keyword
conio.h is a standard library
void is a keyword
main is a keyword
int is a keyword
a is a identifier
b is a identifier
c is a identifier
30 is a number
printf is a keyword
"hello" is a string literal
number of identifiers = 5
number of keywords = 6
```

Lab experiment 33 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex substrin.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
abcjyjkabc
ABCjyjkABC
```

Lab experiment 34 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex email.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
mike89@gmail.com

^Z
Accepted
```

Lab experiment 35 :

```
 Number of html tags: 8
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex lines.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
^Z
```

Lab experiment 36 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flrex html.l
'flrex' is not recognized as an internal or external command,
operable program or batch file.

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex html.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
Enter File Name : sample.html
<html>
<body>
<h1>
</h1>
<p>
</p>
</body>
</html>
```

Lab experiment 37 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex macros.l
flex: can't open macros.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex macros.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe sample.c
Number of macros defined = 1
Number of header files included = 2
```

Lab experiment 38 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex constants.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
Enter File Name : sample.c
314 is a constant
30 is a constant
Number of Constants : 2
```

Lab experiment 39 :

```
C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex lexics.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program File
s (x86)\CodeBlocks\MinGW\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe
#include <stdio.h>
int main()
{
int number1, number2, sum;
printf("Enter two integers: ");
scanf("%d %d", &number1, &number2);
sum = number1 + number2;
printf("%d + %d = %d", number1, number2, sum);
return 0;
}


^Z
Number of characters = 233
Number of words = 33
Number of lines = 12
```

Lab experiment 40 :

```
               10 File(s)        113,126 bytes
                2 Dir(s)  786,789,511,168 bytes free

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program Files (x86)\GnuWin32\bin

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>flex mobile.l

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>set path=C:\Program Files (x86)\CodeBlocks\MinGW\

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>gcc lex.yy.c

C:\Users\bmahe\OneDrive\Desktop\compiler design lab>a.exe

 enter the mobile number:9392753160

 mobile number valid
```