DATA MINING LAB 2

Name: Vaishhnavi Kadiyala

Roll No: 22cs3032


Branch: Cse

Query for Creating and Inserting values into to table


```
-- Create the table
CREATE TABLE products_sales (
  product_id INT PRIMARY KEY,
  product_name VARCHAR(255),
  sales_amount DECIMAL(10, 2),
  region VARCHAR(100),
  product_category VARCHAR(100),
  store_id INT,
  store_name VARCHAR(255)
-- Insert sample values
INSERT INTO products_sales (product_id, product_name, sales_amount, region, product_category, store_id, store_name)
(1, 'Smartphone', 15000.00, 'North', 'Electronics', 101, 'Tech Store'),
(2, 'Laptop', 30000.00, 'South', 'Electronics', 102, 'Gadget Hub'),
(3, 'Shoes', 5000.00, 'East', 'Fashion', 103, 'Style Mart'),
(4, 'T-shirt', 2000.00, 'West', 'Fashion', 104, 'Apparel Corner'),
(5, 'Refrigerator', 25000.00, 'North', 'Home Appliances', 105, 'Home Goods Store');
```

Iceberg Query


SELECT product_name, SUM(sales_amount) as total_sales FROM Products_sales GROUP BY product_name HAVING SUM(sales_amount) > 10000;



SELECT region, SUM(sales_amount) AS total_sales FROM products_sales WHERE product_category = 'Electronics' GROUP BY region HAVING SUM(sales_amount) > 5000;



SELECT store_name, SUM(sales_amount) AS total_sales FROM products_sales GROUP BY store_name HAVING SUM(sales_amount) > 20000;




Skyline Query

SELECT prod_id, prod_name, price, sales_amount


FROM salesData

GROUP BY prod_id, prod_name, price

HAVING not exists(SELECT 1 FROM salesData AS S2 WHERE S2.price < salesData.price AND S2.sales_amount > (SELECT SUM(sales_amount) FROM salesData AS S1 WHERE S1.prod_id = salesData.prod_id))



```
SELECT region, profit, cost
FROM region_finances AS R1
WHERE NOT EXISTS (
    SELECT 1
    FROM region_finances AS R2
    WHERE R2.region <> R1.region
    AND R2.profit > R1.profit
    AND R2.cost < R1.cost
```



```
-- Create the table for stores
CREATE TABLE store_performance (
   store_id INT PRIMARY KEY,
   store_name VARCHAR(255),
   customer_satisfaction DECIMAL(5, 2), -- Assuming it's on a scale of 0-100
   operational_cost DECIMAL(10, 2)
);
```

Insert sample values
 INSERT INTO store_performance (store_id, store_name, customer_satisfaction, operational_cost)
 VALUES
 (1, 'Tech Store', 85.00, 12000.00),

```
(2, 'Gadget Hub', 90.00, 15000.00),
(3, 'Style Mart', 80.00, 10000.00),
(4, 'Apparel Corner', 75.00, 8000.00),
(5, 'Home Goods Store', 95.00, 20000.00);

SELECT store_id, store_name, customer_satisfaction, operational_cost
FROM store_performance
WHERE NOT EXISTS (
    SELECT 1
    FROM store_performance AS S2
    WHERE S2.customer_satisfaction > store_performance.customer_satisfaction
    AND S2.operational_cost < store_performance.operational_cost
)
ORDER BY customer_satisfaction DESC, operational_cost ASC;
```

Result Grid					Export/Impo
	store_id	store_name	customer_satisfaction	operational_cost	
•	5	Home Goods Store	95.00	20000.00	
	2	Gadget Hub	90.00	15000.00	
	1	Tech Store	85.00	12000.00	
	3	Style Mart	80.00	10000.00	
	4	Apparel Corner	75.00	8000.00	
	NULL	NULL	NULL	NULL	