

```

set() ==> AL, LL, Stack
set() ==> HS, LHS, TS
Queue() ==> LL, PQ

Map()
==> If we want to store the data in the form of a key
value pairs
==> HashMap
==> LinkedHashMap
==> TreeMap

key value pairs

HashSet ==> HashTable
HashMap ==> HashTable

HashMap
==> Key Value pairs ==> Inside a HASH TABLE
==> Bucket Order is considered for HASH MAP

hm.add(45);

bucketIndex = hashCode(ele) && (bucketLength - 1)
bucketIndex = hashCode(45) && (bucketLength - 1)
bucketIndex = 45 && 15 ==> .....

hm.put(1, "Apple")

bucketIndex = hashCode(key) && (bucketLength - 1)
bucketIndex = 1 && 15 ==> ..... ==> 0001 && 1111 ==>
0001 ==> 1

```



LinkedHashMap  
 ==> the key value pairs and it maintains the insertion order  
 ==> Hash Table + Doubly Linked List

When we have same keys then always the latest key value pair will be considered for HM or LHM or TM, BUT value duplication is allowed

```

"Beju"

R: 1, a: 1, i: 2, u: 1

Find the first repeating character

i ==> R ==> If R is not available as a Key in my MAP
add that R with what as default value ==> 1
==> put(R, 1)
If R is already there, get that value + 1 ==> new value

get(i) ==> 1 ==> 2

```

words[] = {"flower", "flow", "flight"}  
 what is the largest common prefix for all  
 Answer ==> f

```

["flower", "flow", "flight"]
startingWord = "flower"
iterate the array from i = 1
nextWord = "flow"

(nextWord.startsWith(startingWord))

(flow.startsWith(flow))
{
  reduce last character of startingWord
  flow
}

"flight".startsWith("f")

f ==> Answer

```

## File Handling


File ==> store the data  
 1) Create a file  
 2) Write the data in to file  
 3) Read the data from a file

Create a file ==> File class  
 Write the data to a file ==> FileWriter class  
 Read the data from a file ==> FileReader class



Amount of times the Java visitinf the file in the HardDisk  
 ==> 3 times ==> more no of system calls

BufferedWriter ==> Buffer(Memory)



BufferedWriter ==> MemoryWriter ==> Used to write the data only to the MEMORY


BufferedWriter with FileWriter makes less no of system calls

BufferedWriter with FileWriter is also having a major problem, we can write only character data AND string data, but we cant write any boolean OR integer OR float

PrintWriter ==> Can write any type of data to a file using print()

Problems with FileReader  
 1) read() ==> read one character


BufferedReader  
 ==. It helps to read the entire line at a time instead of character by character



## Serialization and Deserialization




SERIALIZATION  
 Object(data) ==> File(Store)  
 Files(txt, pdf, ...) ==> Internally the data is kept in a binary format



Object Data will be converted in to a byte stream and then writing that byte data to a file is called as **SERIALIZATION**

To implement serialization we use 2 java classes:-  
 1) ObjectOutputStream  
 2) FileOutputStream



Java doesn't allow any object to be automatically converted to any other format(byte format), if we want to convert then that class should implement one interface(Serializable)

A class that implements serializable interface, only the objects of that class are eligible for **SERIALIZATION**

Serializable ==> Marker Interface(zero methods)

[10, 12, 11, 11] ==> 4

pitches = [10, 12, 11, 11]  
 Arrays.sort(pitches)  
 ==> [10, 11, 11, 12]

[10, 11, 11, 12]

```

if(pitches[right] - pitches[left] > 1)
{
  windowLeft++;
}

right - left + 1 ==> 0 - 0 + 1 ==> 1
right - left + 1 ==> 1 - 0 + 1 ==> 2

maxLength = 3

```

10, 11, 11, 12, 17, 18, 19, 55

571

display the min count to make the string beautiful

"ab~~d~~dde"

2 rules:

- 1) no 2 charcters should be same next to each other
- 2) no 2 character should be one after the other

"az"

"ab~~d~~dde"

ab ==> az

azdye

"ab~~d~~dde"

if(charAt(0) == charAt(1))

{ not beautiful }

if(charAt(1) == charAt(0) + 1)

{ not beautiful }

If it snot beatifula lways modify the 2nd character in that pair

ab ==> replace b

charAt(1) = charAt(0) + 2 && charAt(1) != charAt(2)