
Understanding the **when** Condition in Your Playbook

The **when** condition is used to control **whether a task should run or not** based on a certain rule.

In your playbook, the **when** condition checks the **operating system** of the target machine.

The variable Ansible uses to detect the OS is:

`ansible_distribution`

This fact is automatically gathered from each host.

How the **when** Condition Works in Your Playbook

Each task has a line like this:

`when: ansible_distribution == "Ubuntu"`

or

`when: ansible_distribution == "CentOS"`

This means:

- ✓ **Run this task only if the server is running that OS.**
 - ✓ **Skip this task if the OS is different.**
-

Detailed Explanation With Your Playbook

Below is a breakdown of each **when** condition exactly as used in your playbook.

1. Ubuntu-Specific Tasks

Example from your playbook:

when: ansible_distribution == "Ubuntu"

Description:

- Before the task runs, Ansible checks:
 - *"Is this server Ubuntu?"*
- If **YES**, task will run.
- If **NO**, task is skipped.

✓ These tasks run *only* on Ubuntu servers:

- Install apache2
- Start apache2
- Enable apache2

CentOS will ignore these tasks.

2. CentOS-Specific Tasks

Example from your playbook:

when: ansible_distribution == "CentOS"

Description:

- Before executing, Ansible checks:
 - *"Is this server CentOS?"*
- If **YES**, task runs.
- If **NO**, task is skipped.

✓ **These tasks run *only* on CentOS servers:**

- Install httpd
- Start httpd
- Enable httpd

Ubuntu will ignore these tasks.

Why the *when* Condition Is Critical

Without the *when* condition:

- Ubuntu would try to install **httpd** (does not exist → playbook fails)
- CentOS would try to install **apache2** (does not exist → playbook fails)
- Services would not match the OS
- Tasks would break on the wrong system

when protects each task and ensures:

- ✓ Correct package for each OS
 - ✓ Correct service for each OS
 - ✓ No errors on incompatible systems
-

In Plain English

The **when** condition is like saying:

*****If this server is Ubuntu, do these tasks.**

If this server is CentOS, do those tasks.***

It acts like an **if-statement** for each task.
