

## Day 21:

### Task 1: Establishing Database Connections

**Write a Java program that connects to a SQLite database and prints out the connection object to confirm successful connection.**

```
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.SQLException;

public class SQLiteConnectionExample {

    public static void main(String[] args) {
        Connection connection = null;

        try {
            Class.forName("org.sqlite.JDBC");
            String url = "jdbc:sqlite:/path/to/your/database.db"; // Replace this with the path to
            your SQLite database file
            connection = DriverManager.getConnection(url);

            if (connection != null) {
                System.out.println("Connected to the SQLite database.");
                System.out.println("Connection object: " + connection);
            } else {
                System.out.println("Failed to connect to the SQLite database.");
            }
        } catch (ClassNotFoundException e) {
            System.out.println("SQLite JDBC driver not found.");
            e.printStackTrace();
        } catch (SQLException e) {
```

```

        System.out.println("Failed to connect to the SQLite database.");
        e.printStackTrace();
    } finally {
        // Close the connection
        try {
            if (connection != null) {
                connection.close();
            }
        } catch (SQLException e) {
            e.printStackTrace();
        }
    }
}
}

```

## Task 2: SQL Queries using JDBC

**Create a table 'User' with a following schema 'User ID' and 'Password' stored as hash format (note you have research on how to generate hash from a string), accept "User ID" and "Password" as input and check in the table if they match to confirm whether user access is allowed or not.**

**let's create the SQLite table 'User':**

```

CREATE TABLE User (
    UserID TEXT PRIMARY KEY,
    PasswordHash TEXT
);

```

**let's write the Java code to perform the authentication:**

```

import java.sql.*;

public class UserAuthentication {

    public static void main(String[] args) {

        String url = "jdbc:sqlite:/path/to/your/database.db"; // Replace this with the path to
        your SQLite database file

        try (Connection connection = DriverManager.getConnection(url)) {
            String userId = "user123"; // Example user ID
            String password = "password123"; // Example password
            String hashedPassword = hashPassword(password);
            String sql = "SELECT * FROM User WHERE UserID = ? AND PasswordHash = ?";
            try (PreparedStatement statement = connection.prepareStatement(sql)) {
                statement.setString(1, userId);
                statement.setString(2, hashedPassword);

                ResultSet resultSet = statement.executeQuery();

                if (resultSet.next()) {
                    System.out.println("User authentication successful. Access granted.");
                } else {
                    System.out.println("Invalid credentials. Access denied.");
                }
            }
        } catch (SQLException e) {
            e.printStackTrace();
        }
    }
}

```

```
private static String hashPassword(String password) {  
    return "hashed_" + password; // Replace this with your actual hashing logic  
}  
}
```

### Task 3: PreparedStatement

**Modify the SELECT query program to use PreparedStatement to parameterize the query and prevent SQL injection.**

```
import java.sql.*;  
  
public class UserAuthentication {  
  
    public static void main(String[] args) {  
        String url = "jdbc:sqlite:/path/to/your/database.db"; // Replace this with the path to  
        your SQLite database file  
  
        try (Connection connection = DriverManager.getConnection(url)) {  
            String userId = "user123"; // Example user ID  
            String password = "password123"; // Example password  
            String hashedPassword = hashPassword(password);  
            String sql = "SELECT * FROM User WHERE UserID = ? AND PasswordHash = ?";  
            try (PreparedStatement statement = connection.prepareStatement(sql)) {  
                statement.setString(1, userId);  
                statement.setString(2, hashedPassword);  
  
                ResultSet resultSet = statement.executeQuery();  
  
                if (resultSet.next()) {  
                    System.out.println("User authentication successful. Access granted.");  
                }  
            }  
        }  
    }  
}
```

```
        } else {  
            System.out.println("Invalid credentials. Access denied.");  
        }  
    }  
} catch (SQLException e) {  
    e.printStackTrace();  
}  
}  
  
private static String hashPassword(String password) {  
  
    return "hashed_" + password; // Replace this with your actual hashing logic  
}  
}
```