

Day 19:

Task 1: Generics and Type Safety

Create a generic Pair class that holds two objects of different types, and write a method to return a reversed version of the pair.


```
public class Pair<T, U> {  
    private T first;  
    private U second;  
  
    public Pair(T first, U second) {  
        this.first = first;  
        this.second = second;  
    }  
  
    public T getFirst() {  
        return first;  
    }  
  
    public U getSecond() {  
        return second;  
    }  
  
    public Pair<U, T> reverse() {  
        return new Pair<>(second, first);  
    }  
  
    public static void main(String[] args) {  
        Pair<String, Integer> pair = new Pair<>("Hello", 123);  
        System.out.println("Original Pair: " + pair.getFirst() + ", " + pair.getSecond());  
  
        Pair<Integer, String> reversedPair = pair.reverse();
```

```

        System.out.println("Reversed Pair: " + reversedPair.getFirst() + ", " +
reversedPair.getSecond());
    }
}

```

OUTPUT:



```

<terminated> Salary (1) [Java Application] C:\Users\udhya\p2\pool\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64_17.0.11.v20240426-1830\jre\bin\javaw.exe (03-Jun-2024, 7:15:44 pm - 7:15:45 pm) [pid
Original Pair: Hello, 123
Reversed Pair: 123, Hello

```

Task 2: Generic Classes and Methods

Implement a generic method that swaps the positions of two elements in an array, regardless of their type, and demonstrate its usage with different object types.

```

public class ArrayUtils {

    public static <T> void swapElements(T[] array, int index1, int index2) {
        if (index1 < 0 || index1 >= array.length || index2 < 0 || index2 >= array.length) {
            throw new IllegalArgumentException("Invalid indices");
        }

        T temp = array[index1];
        array[index1] = array[index2];
        array[index2] = temp;
    }

    public static void main(String[] args) {
        Integer[] intArray = {1, 2, 3, 4, 5};
        System.out.println("Original Integer Array: " + java.util.Arrays.toString(intArray));
        swapElements(intArray, 1, 3);
        System.out.println("Array after swapping: " + java.util.Arrays.toString(intArray));
        String[] strArray = {"apple", "banana", "orange", "grape"};
    }
}

```


```

        System.out.println("\nOriginal String Array: " + java.util.Arrays.toString(strArray));
        swapElements(strArray, 0, 2);
        System.out.println("Array after swapping: " + java.util.Arrays.toString(strArray));

        Character[] charArray = {'a', 'b', 'c', 'd', 'e'};
        System.out.println("\nOriginal Character Array: " + java.util.Arrays.toString(charArray));
        swapElements(charArray, 2, 4);
        System.out.println("Array after swapping: " + java.util.Arrays.toString(charArray));
    }
}

```

OUTPUT:



```

<terminated> Salary (1) Java Application C:\Users\sudhya\p2\pool\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64.jre\bin\javaw.exe (03-Jun-2024, 7:17:38 pm - 7:17:39 pm) [p...
Original Integer Array: [1, 2, 3, 4, 5]
Array after swapping: [1, 4, 3, 2, 5]

Original String Array: [apple, banana, orange, grape]
Array after swapping: [orange, banana, apple, grape]

Original Character Array: [a, b, c, d, e]
Array after swapping: [a, b, e, d, c]

```

Task 3: Reflection API

Use reflection to inspect a class's methods, fields, and constructors, and modify the access level of a private field, setting its value during runtime

```

import java.lang.reflect.Field;
import java.lang.reflect.Method;
import java.lang.reflect.Constructor;

```

```

class MyClass {
    private int privateField;

    public MyClass(int privateField) {

```

```

        this.privateField = privateField;
    }

    private void privateMethod() {
        System.out.println("Private Method");
    }

    public void publicMethod() {
        System.out.println("Public Method");
    }
}

public class ReflectionExample {
    public static void main(String[] args) throws Exception {
        Class<?> myClass = MyClass.class;
        System.out.println("Methods:");
        Method[] methods = myClass.getDeclaredMethods();
        for (Method method : methods) {
            System.out.println(method.getName());
        }
        System.out.println("\nFields:");
        Field[] fields = myClass.getDeclaredFields();
        for (Field field : fields) {
            System.out.println(field.getName());
        }
        System.out.println("\nConstructors:");
        Constructor<?>[] constructors = myClass.getDeclaredConstructors();
        for (Constructor<?> constructor : constructors) {
            System.out.println(constructor);
        }
    }
}

```

```

    }

    System.out.println("\nModifying private field:");

    MyClass obj = new MyClass(10);

    Field privateField = myClass.getDeclaredField("privateField");

    privateField.setAccessible(true); // Set accessible to true to access private field

    int value = (int) privateField.get(obj); // Get the value of private field


    System.out.println("Original value of privateField: " + value);

    privateField.set(obj, 20); // Set new value to private field

    System.out.println("Modified value of privateField: " +
obj.getClass().getDeclaredField("privateField").get(obj));

    }
}

```



Task 4: Lambda Expressions

Implement a Comparator for a Person class using a lambda expression, and sort a list of Person objects by their age.

```

import java.util.ArrayList;

import java.util.Comparator;

import java.util.List;

```

```

class Person {

    private String name;

    private int age;

```

```
public Person(String name, int age) {  
    this.name = name;  
    this.age = age;  
}
```

```
public String getName() {  
    return name;  
}
```

```
public int getAge() {  
    return age;  
}
```

```
@Override
```

```
public String toString() {  
    return "Person{" +  
        "name='" + name + "\" +  
        ", age=" + age +  
        "'}";  
}  
}
```

```
public class PersonComparatorExample {  
    public static void main(String[] args) {  
        List<Person> people = new ArrayList<>();  
        people.add(new Person("Alice", 30));  
        people.add(new Person("Bob", 25));  
        people.add(new Person("Charlie", 35));  
    }  
}
```

```

        people.sort(Comparator.comparingInt(Person::getAge));

        System.out.println("Sorted list of Person objects by age:");

        for (Person person : people) {

            System.out.println(person);


        }

    }

}

```

OUTPUT:



```

<terminated> Salary (1) [Java Application] C:\Users\udhya\p2\pool\plugins\org.eclipse.justi.openjdk hotspot\jre.full.win32.x86_64-17.0.11.v20240426-1830\jre\bin\javaw.exe (03-Jun-2024, 7:22:28 pm - 7:22:29 pm) [pid
Sorted list of Person objects by age:
Person{name='Bob', age=25}
Person{name='Alice', age=30}
Person{name='Charlie', age=35}

```

Task 5: Functional Interfaces

Create a method that accepts functions as parameters using Predicate, Function, Consumer, and Supplier interfaces to operate on a Person object.

```

import java.util.function.Consumer;

import java.util.function.Function;

import java.util.function.Predicate;

import java.util.function.Supplier;

```

```

class Person {

    private String name;

    private int age;

```

```
public Person(String name, int age) {
```

```
    this.name = name;
```

```
    this.age = age;
```

```
}
```

```
public String getName() {
```

```
    return name;
```

```
}
```

```
public int getAge() {
```

```
    return age;
```

```
}
```

```
@Override
```

```
public String toString() {
```

```
    return "Person{" +
```

```
        "name='" + name + "'" +
```

```
        ", age=" + age +
```

```
        '}';
```

```
}
```

```
}
```

```
public class FunctionInterfaceExample {
```

```
    public static void processPerson(Person person,
```

```
        Predicate<Person> predicate,
```

```
        Function<Person, String> function,
```

```
        Consumer<String> consumer,
```

```
        Supplier<String> supplier) {
```

```
        if (predicate.test(person)) {
```

```
            String result = function.apply(person);
```



```

        consumer.accept(result);
    } else {
        String defaultResult = supplier.get();
        consumer.accept(defaultResult);
    }
}

public static void main(String[] args) {
    Person person = new Person("Alice", 30);
    Predicate<Person> isAdult = p -> p.getAge() >= 18;
    Function<Person, String> greetingFunction = p -> "Hello, " + p.getName();
    Consumer<String> printConsumer = System.out::println;
    Supplier<String> defaultGreetingSupplier = () -> "Sorry, you are not an adult.";

    System.out.println("Processing adult person:");
    processPerson(person, isAdult, greetingFunction, printConsumer,
defaultGreetingSupplier);

    person = new Person("Bob", 15);
    System.out.println("\nProcessing underage person:");
    processPerson(person, isAdult, greetingFunction, printConsumer,
defaultGreetingSupplier);
}
}

```

OUTPUT:

```

Processing adult person:
Hello, Alice

Processing underage person:
Sorry, you are not an adult.

```