
CS23333-Object Oriented Programming Using Java-2023





Question **1**Correct

Marked out of 1.00

☐
▼ Flag

question

Java HashSet class implements the Set interface, backed by a hash table which is actually a HashMap instance.

No guarantee is made as to the iteration order of the hash sets which means that the class does not guarantee the constant order of elements over time.

This class permits the null element.

The class also offers constant time performance for the basic operations like add, remove, contains, and size assuming the hash function disperses the elements properly among the buckets.

Java HashSet Features

A few important features of HashSet are mentioned below:

- Implements Set Interface.
- The underlying data structure for HashSet is Hashtable.
- As it implements the Set Interface, duplicate values are not allowed.
- Objects that you insert in HashSet are not guaranteed to be inserted in the same order. Objects are inserted based on their hash code.
- NULL elements are allowed in HashSet.
- HashSet also implements Serializable and Cloneable interfaces.

```
public class HashSet<E> extends AbstractSet<E> implements Set<E>, Cloneable, Serializable
Sample Input and Output:
5
90
56
45
78
25
78
Sample Output:
78 was found in the set.
Sample Input and output:
3
2
7
9
5
Sample Input and output:
5 was not found in the set.
```

Answer: (penalty regime: 0 %)

```
Reset answer
```

```
import java.util.HashSet;
import java.util.Scanner;
public class HashSetExample {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        HashSet<Integer> set = new HashSet<>();
        int n = sc.nextInt();
        for (int i = 0; i < n; i++) {
            set.add(sc.nextInt());
        }
        int num = sc.nextInt();
        if (set.contains(num)) {
            System.out.println(num + " was found in the set.");
        } else {
            System.out.println(num + " was not found in the set.");
        }
        sc.close();
    }
}</pre>
```

Test Input	Expected	Got	
1 5	78 was found in the set.	78 was found in the set.	

	Test	Input	Expected	Got	
		56			
		45			
		78			
		25			
		78			
	2	3	5 was not found in the set.	5 was not found in the set.	
		-1			
		2			
		4			
		5			
				l .	
Pas	sed all	tests!			

Question 2 Correct

Marked out of 1.00

question

```
Write a Java program to compare two sets and retain elements that are the same.
```

Sample Input and Output:

5

Football

Hockey

Cricket

Volleyball

Basketball

7 // HashSet 2:

Golf

Cricket

Badminton

Football

Hockey

Volleyball

Handball

SAMPLE OUTPUT:

Football

Hockey

Cricket

Volleyball

Basketball

Answer: (penalty regime: 0 %)

```
import java.util.HashSet;
import java.util.Scanner;
import java.util.Set;
public class SetIntersection {
  public static void main(String[] args) {
     Scanner sc = new Scanner(System.in);
     Set<String> set1 = new HashSet<>();
     Set<String> set2 = new HashSet<>();
     int n1 = sc.nextInt();
      sc.nextLine();
      for (int i = 0; i < n1; i++) {
        set1.add(sc.nextLine());
      int n2 = sc.nextInt();
      sc.nextLine();
      for (int i = 0; i < n2; i++) {
        set2.add(sc.nextLine());
      set1.retainAll(set2);
      for (String sport : set1) {
        System.out.println(sport);
      sc.close();
```

Test	Input	Expected	Got	
1	5 Football Hockey	Cricket Hockey Volleyball	Cricket Hockey Volleyball	

	Test	Input	Expected	Got	
		Cricket Volleyball Basketball 7 Golf Cricket Badminton Football Hockey Volleyball Throwball	Football	Football	
	2	4 Toy Bus Car Auto 3 Car Bus Lorry	Bus Car	Bus Car	

Passed all tests!

Question $\bf 3$

Correct

Marked out of 1.00

Java HashMap Methods

containsKey() Indicate if an entry with the specified key exists in the map

containsValue() Indicate if an entry with the specified value exists in the map

putlfAbsent() Write an entry into the map but only if an entry with the same key does not already exist

remove() Remove an entry from the map

replace() Write to an entry in the map only if it exists

size() Return the number of entries in the map

Your task is to fill the incomplete code to get desired output

Answer: (penalty regime: 0 %)

Reset answer

```
import java.util.HashMap;
import java.util.Map.Entry;
import java.util.Set;
import java.util.Scanner;
class prog {
  public static void main(String[] args) {
    HashMap<String, Integer> map = new HashMap<String, Integer>();
     String name;
      int num;
     Scanner sc = new Scanner(System.in);
      int n = sc.nextInt();
      for (int i = 0; i < n; i++) {
        name = sc.next();
        num = sc.nextInt();
        map.put(name, num);
     Set<Entry<String, Integer>> entrySet = map.entrySet();
     for (Entry<String, Integer> entry : entrySet) {
        System.out.println(entry.getKey() + ":" + entry.getValue());\\
      System.out.println("----");
    HashMap<String, Integer> anotherMap = new HashMap<String, Integer>();
     anotherMap.put("SIX", 6);
     anotherMap.put("SEVEN", 7);
     anotherMap.putAll(map);
     entrySet = anotherMap.entrySet();
     for (Entry<String, Integer> entry : entrySet) {
        System.out.println(entry.getKey() + ":" + entry.getValue());\\
     map.putIfAbsent("FIVE", \ 5);\\
     Integer value = map.get("TWO");
      if (value != null) {
        System.out.println(value);
      } else {
        System.out.println("Key 'TWO' not found in map.");
     System.out.println(map.containsKey("ONE"));
     System.out.println(map.containsValue(3));
     System.out.println(map.size());
```

Test	Input	Expected	Got
1	3	ONE : 1	ONE : 1
	ONE	TWO : 2	TWO : 2
	1	THREE : 3	THREE : 3
	TWO		
	2	SIX : 6	SIX : 6
	THREE	ONE : 1	ONE : 1
	3	TWO : 2	TWO : 2
		SEVEN: 7	SEVEN : 7
		THREE : 3	THREE : 3
		2	2
		true	true
		true	true
		4	4

Passed all tests!

Save the state of the flags

Finish review