

Lab Report: Lab3 - Association Analysis -2

Udaya Shanker Mohanan Nair(udamo524), Dhanush Kumar Reddy Narayana Reddy(dhana004)

2025-03-27

Introduction

In this experiment, we explored how different clustering algorithms identify structure within the **Monk1 dataset**, and why the clusters found may not align with the true class labels. We used both clustering and association rule analysis to examine the underlying logic of the data.

SimpleKMeans

SimpleKMeans in **Weka** is an implementation of the classic **K-Means** clustering algorithm. It partitions the data set into k clusters by minimizing the distance between data points and their assigned cluster centroids. It works best with numerical data and assumes that clusters are spherical and evenly sized.

SimpleKMeans with 2 Clusters

The **SimpleKMeans algorithm** was applied to the **Monk1 dataset** with $k = 2$ clusters using the Euclidean distance metric. The algorithm converged after just 3 iterations, producing a within-cluster sum of squared errors of *358.0*, indicating the compactness of clusters. The clustering process was efficient, taking only *0.01 seconds* to complete. The resulting clusters contained *77 instances (62%)* in **Cluster 0**, with *47 instances (38%)* in **Cluster 1**. Analyzing the cluster centroids, we observe that Cluster 0 typically has values like **attributes#1 = 1** and **attributes#2 = 2**, while Cluster 1 differs with features such as **attributes#1 = 3**, **attributes #3 = 2**, and **attributes#6 = 1**. These centroids reflect the average attribute values within each cluster, highlighting how the algorithm grouped instances based on numerical similarity.

```
=== Run information ===

Scheme:weka.clusterers.SimpleKMeans -N 2 -A "weka.core.EuclideanDistance -R first-last" -I 500 -S 10
Relation:      monk1-weka.filters.unsupervised.attribute.Remove-R7
Instances:     124
Attributes:    6
               attribute#1
               attribute#2
               attribute#3
               attribute#4
               attribute#5
               attribute#6
Test mode:evaluate on training data

=== Model and evaluation on training set ===
```

```

kMeans
=====

Number of iterations: 3
Within cluster sum of squared errors: 358.0
Missing values globally replaced with mean/mode

Cluster centroids:

Attribute      Full Data      Cluster#
                (124)      0          1
                (77)      (47)
=====
attribute#1      1          1          3
attribute#2      3          2          3
attribute#3      1          1          2
attribute#4      3          1          3
attribute#5      4          4          2
attribute#6      2          2          1

Time taken to build model (full training data) : 0.01 seconds

=== Model and evaluation on training set ===

Clustered Instances

0          77 ( 62%)
1          47 ( 38%)

```

SimpleKMeans with 3 Clusters

The **SimpleKmeans** algorithm was executed with **k = 3** on the **Monk1 dataset** using Euclidean distance. It converged in just 3 iterations and achieved a within-cluster sum of squared errors of *314.0*, which is slightly lower than the 2-cluster (358.0), indicating a tighter clustering. The instance were divided into **Cluster 0:59(48%)**, **Cluster 1:38(31%)**, and **Cluster 2:27(22%)**. From the cluster centroids, we observe that each cluster emphasizes different combinations of attribute values- for example, *attributes#1 = 1*, in **Cluster 0** vs *attributes #1 = 3* in **Cluster 1** - highlighting how the algorithm groups instances by numerical similarities. However, since clustering is unsupervised, these clusters don't necessarily align with the actual class labels of the data.

```

=== Run information ===

Scheme:weka.clusterers.SimpleKMeans -N 3 -A "weka.core.EuclideanDistance -R first-last" -I 500 -S 10
Relation:      monk1-weka.filters.unsupervised.attribute.Remove-R7
Instances:      124
Attributes:      6
                attribute#1
                attribute#2
                attribute#3
                attribute#4

```

```

        attribute#5
        attribute#6
Test mode:evaluate on training data

=== Model and evaluation on training set ===

kMeans
=====

Number of iterations: 3
Within cluster sum of squared errors: 314.0
Missing values globally replaced with mean/mode

Cluster centroids:

```

		Cluster#		
Attribute	Full Data	0	1	2
	(124)	(59)	(38)	(27)
attribute#1	1	1	3	2
attribute#2	3	2	1	3
attribute#3	1	1	2	1
attribute#4	3	1	3	2
attribute#5	4	3	2	1
attribute#6	2	2	1	1

```

=====

Time taken to build model (full training data) : 0 seconds

=== Model and evaluation on training set ===

Clustered Instances

0      59 ( 48%)
1      38 ( 31%)
2      27 ( 22%)

```

EM

EM with 2 Clusters

The **Expectation-Maximization(EM)** algorithm was applied to the **Monk1 dataset** with the number of clusters set to 2. The model was trained on *124 instances with 6 attributes*, using a probabilistic approach to assign instances based on likelihood. It completed in *0.04 seconds* with a final *log likelihood* of *-6.00606*, indicating a moderate fit. The instances were nearly evenly distributed between *Cluster 0 (48%)* and *Cluster 1 (52%)*. Cluster characteristics reveal notable differences in attribute distributions. For instance, **Cluster 0** had higher probabilities for *attributes#1 = 1* and *attributes#2 = 3*, while **Cluster 1** leaned more toward *attributes#1 = 2* and *attributes#2 = 1*. Similarly, *attribute#6 = 1* appeared more frequently in **Cluster 1**. Unlike KMeans, EM provides soft clustering, reflecting the underlying statistical patterns in the data rather than being rigid partitions.

=== Run information ===

Scheme: weka.clusterers.EM -I 100 -N 2 -M 1.0E-6 -S 100

Relation: monk1-weka.filters.unsupervised.attribute.Remove-R7

Instances: 124

Attributes: 6

attribute#1

attribute#2

attribute#3

attribute#4

attribute#5

attribute#6

Test mode: evaluate on training data

=== Model and evaluation on training set ===

EM

==

Number of clusters: 2

	Cluster	
Attribute	0	1
	(0.5)	(0.5)

=====

attribute#1

1	29.4776	17.5224
2	11.643	32.357
3	24.2423	14.7577
[total]	65.3629	64.6371

attribute#2

1	10.008	26.992
2	19.4842	24.5158
3	35.8707	13.1293
[total]	65.3629	64.6371

attribute#3

1	31.1592	35.8408
2	33.2037	27.7963
[total]	64.3629	63.6371

attribute#4

1	17.2532	26.7468
2	16.5682	24.4318
3	31.5415	13.4585
[total]	65.3629	64.6371

attribute#5

1	13.9353	17.0647
2	19.0736	13.9264
3	10.9633	21.0367
4	22.3906	13.6094
[total]	66.3629	65.6371

attribute#6

1	25.2844	32.7156
---	---------	---------

```

2          39.0785 30.9215
[total]    64.3629 63.6371

Time taken to build model (full training data) : 0.04 seconds

=== Model and evaluation on training set ===

Clustered Instances

0          59 ( 48%)
1          65 ( 52%)

Log likelihood: -6.00606

```

EM with 3 Clusters

The **EM algorithm** was executed on the **Monk1 dataset** using 3 clusters, completing the training in 0.02 seconds with a slightly improved *log likelihood* of -5.96262 compared to the 2-cluster model. The 124 instances were divided into *Cluster 0* (40%), *Cluster 1* (17%), and *Cluster 2* (43%). Cluster 1 is significantly smaller, capturing a more specific pattern in the data. Attribute distributions reveal distinct cluster behaviors: for example, *attributes#1 = 2* is more dominant in **Cluster 2**, while *attributes#1 = 3* show up strongly in **Cluster 0**. *Attributes#5 = 1* is highly concentrated in **Cluster 1**, hinting at a unique subgroup. Meanwhile, **Cluster 2** shows high values for *attributes#2 = 1* and *attributes#5 = 3*, suggesting different attribute combinations. Compared to the 2-cluster model, this setup captures more granular structures, possibly reflecting underlying class-like separations in the Monk1 dataset more effectively through soft clustering.

```

=== Run information ===

Scheme:weka.clusterers.EM -I 100 -N 3 -M 1.0E-6 -S 100
Relation:    monk1-weka.filters.unsupervised.attribute.Remove-R7
Instances:   124
Attributes:  6
              attribute#1
              attribute#2
              attribute#3
              attribute#4
              attribute#5
              attribute#6
Test mode:evaluate on training data

=== Model and evaluation on training set ===

EM
==

Number of clusters: 3

Attribute      Cluster
              0      1      2

```

```

              (0.4)   (0.2)   (0.39)
=====
attribute#1
  1          24.2508  3.6254 20.1238
  2           7.7929 10.2602 26.947
  3          20.8313 14.2613  4.9074
  [total]      52.875 28.1468 51.9782
attribute#2
  1           8.5876  8.3912 21.0211
  2          12.1224 10.3865 22.4911
  3          32.165  9.3691  8.4659
  [total]      52.875 28.1468 51.9782
attribute#3
  1          24.5556 15.7371 27.7073
  2          27.3194 11.4097 23.2709
  [total]      51.875 27.1468 50.9782
attribute#4
  1          11.8655 14.0256 19.1089
  2          14.2182  8.5015 19.2803
  3          26.7913  5.6197 13.5891
  [total]      52.875 28.1468 51.9782
attribute#5
  1           9.4906 17.4189  5.0905
  2          16.8562  4.5329 12.6109
  3           8.7413  3.5023 20.7564
  4          18.7869  3.6927 14.5204
  [total]      53.875 29.1468 52.9782
attribute#6
  1          17.9585 16.5912 24.4502
  2          33.9165 10.5555 26.528
  [total]      51.875 27.1468 50.9782

Time taken to build model (full training data) : 0.02 seconds

=== Model and evaluation on training set ===

Clustered Instances

0          50 ( 40%)
1          21 ( 17%)
2          53 ( 43%)

Log likelihood: -5.96262

```

Association Analysis

The **Association analysis** conducted using the **Apriori algorithm** on the **Monk1 dataset**, which consists of 124 instances and 6 attributes, aimed to identify strong relationships among attribute values. The algorithm was configured with a minimum support threshold of 5% and a minimum *confidence* of 0.9. Throughout **19 cycles**, the analysis identified a total of 17 frequent 1-itemsets, 118 frequent 2-itemsets, 214

frequent 3-itemsets, and 14 frequent 4-itemsets. Among the discovered rules, the most significant one states that if *attributes#2 equals 2*, *attribute#3 equal 1*, and *attributes#5 equal 4*, then *attributes#6 always 2*. This rule was found in 6 instance and exhibited a perfect *confidence of 1.0*, indicating a strong and consistent relationship within the dataset. Such a rule can be particularly useful for predicting attributes values or uncovering patterns in the data.

```

=== Run information ===

Scheme:      weka.associations.Apriori -N 19 -T 0 -C 0.9 -D 0.05 -U 1.0 -M 0.05 -S -1.0 -c -1
Relation:    monk1-weka.filters.unsupervised.attribute.Remove-R7
Instances:   124
Attributes:  6
              attribute#1
              attribute#2
              attribute#3
              attribute#4
              attribute#5
              attribute#6
=== Associator model (full training set) ===

Apriori
=====

Minimum support: 0.05 (6 instances)
Minimum metric <confidence>: 0.9
Number of cycles performed: 19

Generated sets of large itemsets:

Size of set of large itemsets L(1): 17

Size of set of large itemsets L(2): 118

Size of set of large itemsets L(3): 214

Size of set of large itemsets L(4): 14

Best rules found:

1. attribute#2=2 attribute#3=1 attribute#5=4 6 ==> attribute#6=2 6    conf:(1)

```