

CampusEats - Part D curl -v Transcript

```
=====
1. Successful Create -- 201 Created
=====
```

Note: Unnecessary use of -X or --request, POST is already inferred.

```
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> POST /restaurants HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Content-Type: application/json
> Accept: application/json
> Idempotency-Key: abc123
> Content-Length: 39
>
} [39 bytes data]
< HTTP/1.1 201 Created
< X-Powered-By: Express
< Location: /restaurants/1
< Content-Type: application/json; charset=utf-8
< ETag: "restaurant-1-v1"
< Content-Length: 46
< Date: Tue, 22 Sep 2026 17:09:11 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [46 bytes data]
* Connection #0 to host localhost left intact
{"id":1,"name":"Pizza Hub","category":"Pizza"}
```

```
=====
2. Repeat Create with Same Idempotency-Key -- No Duplicate
=====
```

Note: Unnecessary use of -X or --request, POST is already inferred.

```
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> POST /restaurants HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Content-Type: application/json
> Accept: application/json
> Idempotency-Key: abc123
> Content-Length: 39
>
} [39 bytes data]
```

```

< HTTP/1.1 201 Created
< X-Powered-By: Express
< Location: /restaurants/1
< Content-Type: application/json; charset=utf-8
< ETag: "restaurant-1-v1"
< Content-Length: 46
< Date: Tue, 22 Sep 2026 17:09:15 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [46 bytes data]
* Connection #0 to host localhost left intact
{"id":1,"name":"Pizza Hub","category":"Pizza"}

```

3. Conditional GET -- Step 1: Initial GET to obtain ETag

```

=====
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> GET /restaurants/1 HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Accept: */*
>
< HTTP/1.1 200 OK
< X-Powered-By: Express
< ETag: "restaurant-1-v1"
< Cache-Control: private, max-age=60
< Content-Type: application/json; charset=utf-8
< Content-Length: 46
< Date: Tue, 22 Sep 2026 17:09:20 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [46 bytes data]
* Connection #0 to host localhost left intact
{"id":1,"name":"Pizza Hub","category":"Pizza"}

```

3. Conditional GET -- Step 2: 304 Not Modified

```

=====
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> GET /restaurants/1 HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Accept: */*
> If-None-Match: "restaurant-1-v1"
>
< HTTP/1.1 304 Not Modified
< X-Powered-By: Express
< ETag: "restaurant-1-v1"
< Cache-Control: private, max-age=60
< Date: Tue, 22 Sep 2026 17:09:20 GMT

```

```

< Connection: keep-alive
< Keep-Alive: timeout=5
<
* Connection #0 to host localhost left intact

=====
4. Conditional Write -- 412 Precondition Failed
=====
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> PUT /restaurants/1 HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Accept: */*
> Content-Type: application/json
> If-Match: "old-etag"
> Content-Length: 19
>
} [19 bytes data]
< HTTP/1.1 412 Precondition Failed
< X-Powered-By: Express
< ETag: "restaurant-1-v1"
< Content-Type: application/json; charset=utf-8
< Content-Length: 90
< Date: Tue, 22 Sep 2026 17:09:25 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [90 bytes data]
* Connection #0 to host localhost left intact
{"error":"Precondition Failed","message":"Resource has changed; refresh before updating."}
=====
5. Bad Request -- 400 (Malformed JSON)
=====
Note: Unnecessary use of -X or --request, POST is already inferred.
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> POST /restaurants HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Accept: */*
> Content-Type: application/json
> Content-Length: 8
>
} [8 bytes data]
< HTTP/1.1 400 Bad Request
< X-Powered-By: Express
< Content-Type: application/json; charset=utf-8
< Content-Length: 67
< ETag: W/"43-Yh+YMb/tHxFl+ekIma07aRC04qY"
< Date: Tue, 22 Sep 2026 17:09:30 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5

```

```

<
{ [67 bytes data]
* Connection #0 to host localhost left intact
{"error":"Bad Request","message":"Malformed JSON in request body."}
=====
6. Missing Resource -- 404 Not Found
=====
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> GET /restaurants/999999 HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Accept: */*
>
< HTTP/1.1 404 Not Found
< X-Powered-By: Express
< Content-Type: application/json; charset=utf-8
< Content-Length: 59
< ETag: W/"3b-qTqpiScEb+16ktqIGr6islNbc8"
< Date: Tue, 22 Sep 2026 17:09:30 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [59 bytes data]
* Connection #0 to host localhost left intact
{"error":"Not Found","message":"Restaurant does not exist"}
=====
7. Missing Authorization -- 401 Unauthorized
=====
* Host localhost:5000 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
* Connected to localhost (127.0.0.1) port 5000
> GET /orders/1 HTTP/1.1
> Host: localhost:5000
> User-Agent: curl/8.5.0
> Accept: */*
>
< HTTP/1.1 401 Unauthorized
< X-Powered-By: Express
< Content-Type: application/json; charset=utf-8
< Content-Length: 76
< ETag: W/"4c-so3YkQgzZwjGH095Eraz1t00Vy4"
< Date: Tue, 22 Sep 2026 17:09:30 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [76 bytes data]
* Connection #0 to host localhost left intact
{"error":"Unauthorized","message":"Missing or invalid Authorization header"}

```