



Title

Complete Title	Toucan-Payments-Check Out-API Specifications
Brief Title	Check Out-API Specifications

Approval

Approver	Venkata Ponnappalli venkata.ponnappalli@toucanus.com
Approval Date	
Date to Initiate Next Version	

Reviewers

Review #	Start	End	Additional Review Required (Yes/No)	Reviewers
1				venkata.ponnappalli@toucanus.com
2				

Revision History

Date	Author	Comments	Version
09/24/2025	Siva Yanabotula SriDurga Devi		1.0

Table Of Contents

Checkout API	3
API Endpoint	3
Request Parameters	3
Headers	4
Request Body	4
Response	5
Possible error codes	6
Hash Amount Logic in Java	7

Checkout API

API Endpoint

- Method: POST
- Endpoint: <https://pay.testtoucanpay.in/api/auth/getpaymentsession>

Request Parameters

t	Terminal ID	String	Y	Any
o	Order id	String	Y	min 15 digits
ta	Transaction amount	String	Y	Any
c	Currency	String	Y	Any
mac	Merchant's designated token	String	Y	Any
murl	environment/region	String	Y	Any
name	Senders name	String	Y	Any
Phone number	senders' mobile number	String	Y	Any
Email id	senders Gmail	String	Y	Any
ha	Hash amount	String	Y	

Headers

Content-Type: application/x-www-form-urlencoded

Request Body

t:45789944

O:12022025173230443(invoice number unique for every transaction min 15 digits)

ta:23

c:INR

mac:eyJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJzZWxmc2VydmVAYmVycnlieXRlcylsImhhdCI6MTc2MDA5MTY0MiwiZXhwIjoxOTE3ODAxMDAwfQ.eLf0QEnXegASWurJYBi_T9j7uzxznzqdLFUSK-WlktzpmDXa3zeYwGaSqDqaULgjfH7z-

8wFAJQlhDQ2T6ibf99dap2pjjUKVryemvqzpXhNTj4YtoVDQ0Y97F8SF6OSpWea3cyYh1MqVI_Jg1Pw161c9n-0GhfDjv6hu_TwL4gXlc6rD-gVkEV_cNI5wN5cP-

heP3a2ZVdTj7RPNnsOLRIQmke4j1mnom1vdwq1PlnGcEj88-

0GHnLBfhJG0qeW_SwQvjTMqB2Fg5PVprtLnUT41TCSikaeEHYXuU7sqxQTMeSvGnhvfkg1qyJg4TvxouSql1PByvLCKNiKzWgaKQ

murl : <https://merchant.testtoucanpay.in/>

name:srikanth

phone:8745696254

email:asd@gmail.com

ha:6ff334e1051a09e90127ba4e309e026bb830163a2ce3a355af2ce2310ff6e7e9830d20196a3472bfc8632fd3b60cb56102a84fae70ab1a32942055eb40022225

Response

Note: This response is returned in the headers itself

Field name	Description	Data type	Mandatory	Length
Location	Location to be navigated	String		

- **Response:**

```
{  
  "Location": "https://pay-develop.acq.toucanint.com/#/auth/checkoutpage/NjdlNjgyYWVmNTY1YjMzZGJiNmNkM2Jm/ZXlKaGJHY2lPaUpJVXpJMU5pSjkuZXlKemRXSWlPaUpqYUdWamEyOTFkRUJrWl daaGRXeDBJaXdpYVdGMElqb3hOeIF6TVRVNU9UZ3lMQ0psZUhBaU9qRTNORE14TmpBNE9ESjkuTU81VF8zMzZ1cUJseGlEWS0tbWtnYV83YkVyWHVuLU8zRlBfYnpINjVYSQ",  
}
```
- **Behavior:** The app extracts the redirectUrl from the response and navigates it in a WebView, displaying the Payment Checkout screen. Subsequent navigation (e.g., to UPI or Card payment screens) happens within the WebView, managed by the Angular frontend.

Possible error codes

*** (All the validations for transaction amount, email Id, phone number are done in frontend itself) ***

Error Code	Description
302	Redirect url
200	The request was successful but the Redirect url was not sent from backend
404	Given Merchant token is not authorized to access the api
Failure url	this url will be sent in the field value "Location" which is in the headers

Field name	Field value	Status code	Displays failure url	Length
t	Empty/wrong terminal	302	Y	Any
o	Empty/wrong order id	302	N	Any
ta	Empty/0/-0. 2.. wrong format	302	N	Any
c	empty	200	N	Any
mac	empty	404	No url sent	Any
murl	Empty/wrong URL	302	N	Any

Hash Amount Logic in Java

```
private String computeSHA512(String data) throws Exception {  
    MessageDigest digest = MessageDigest.getInstance(SHA_512);  
    byte[] hash = digest.digest(data.getBytes(StandardCharsets.UTF_8)); // Use UTF-8  
    encoding  
    StringBuilder sb = new StringBuilder();  
    for (byte b : hash) {  
        sb.append(String.format(FORMAT, b));  
    }  
    return sb.toString();  
}
```