Image Caption Generation Using Deep Learning Techniques

P. Bhavana
Dept. of CSE (AI & ML)
VIT-AP (Amaravati)
bhavana.21bce9184@vitapstudent.ac.in

***Abstract*—Image caption generation using deep learning techniques has become widely studied due to its potential applications in areas such as helping visually impaired individuals and managing digital content. This paper explores how Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs) are integrated to extract features from images and generate descriptive captions, respectively. Traditional methods like rule-based systems and statistical approaches are also reviewed, highlighting their limitations in understanding complex meanings and contexts.The main goal of this study is to connect computer vision with language processing by creating meaningful captions for images. The outcomes of this research demonstrate the future promise of deep learning in improving how computers understand and describe images. They show how effectively the proposed method can generate meaningful descriptions for various types of images, showcasing its potential impact in practical applications.This study aims to bridge the gap between visual understanding and language generation using advanced neural network techniques. It emphasizes the significance of accurately describing images through automated systems, paving the way for advancements in accessibility tools and content management systems.**

***Index Terms*—Convolutional Neural Networks (CNNs), Recurrent Neural Networks (RNNs), Computer Vision, Feature Extraction, Attention Mechanisms, Multimodal Learning, Transfer Learning,BLEU Scores**

I. Introduction

The Image Caption Generation project's main objective is to develop an intelligent system capable of automatically generating accurate and descriptive captions for images. This project aims to bridge the gap between visual data interpretation and natural language description, leveraging advanced deep learning techniques to teach computers how to understand and articulate what they see in images.

The first thing is to enable the system to accurately interpret and understand the visual content of images. This involves the use of Convolutional Neural Networks (CNNs) to extract meaningful features from images. CNNs are designed to mimic the human visual cortex, allowing the system to recognize patterns, objects, and scenes within an image. By training on large datasets, the system learns to identify various elements such as people, objects, actions, and settings.

Once the visual content is understood, the next objective is to generate coherent and contextually relevant captions. This is achieved through the integration of Recurrent Neural Networks (RNNs), particularly Long Short-Term Memory (LSTM) networks, which are adept at handling sequential data and generating text. The system aims to produce natural language descriptions that are not only grammatically correct but also semantically meaningful, capturing the essence of the image.

Another key objective is to improve the way images are managed and searched across digital platforms. Current methods of image tagging and categorization often rely on manual input, which can be time-consuming and prone to inconsistencies. The automated generation of descriptive captions serves as rich metadata that enhances the efficiency and accuracy of image search engines. By indexing images based on their content descriptions, this system enables more effective content retrieval and organization, benefiting users across diverse sectors such as e-commerce, digital media, and archival institutions.

Addressing technical challenges is a critical objective in developing an effective Image Caption Generation system. These challenges include improving the accuracy and relevance of generated captions, understanding contextual nuances within images, and ensuring the fairness and inclusivity of the generated descriptions. By exploring novel approaches in model architecture, training strategies, and evaluation metrics, this project aims to overcome these challenges and contribute to the development of robust and reliable AI systems.

II. Literature Survey

In recent years, image caption generation has emerged as a promising area of research, leveraging machine learning techniques to automatically generate descriptive captions for images. Various studies have explored different approaches to tackle this task, showcasing the versatility and potential of machine learning in this domain.

One notable study by Muhumuza Onan et al. [1] introduced an encoder-decoder framework with an attention mechanism, significantly improving the quality of generated captions. This approach demonstrated the effectiveness of attention mechanisms in enhancing the model's ability to focus on relevant parts of the image when generating captions.

Similarly, Liu et al. [2] proposed a new caption model based on a combination of Convolutional Neural Networks (CNN) for image feature extraction and Recurrent Neural Networks (RNN) for sequence generation. Their model achieved impressive results on benchmark datasets, highlighting the

effectiveness of integrating visual and semantic information to generate subtitles.

In another study, Adarsh al. [3] investigated the use of reinforcement learning for image captions, allowing the model to learn from self-generated captions and evolve over time. This approach resulted in smoother and more contextual subtitles, demonstrating the potential of reinforcement learning to improve subtitle generation models.

Additionally, recent advancements in pre-trained language models, such as BERT [4] and GPT [5], have shown promising results in various natural language processing tasks, including image captioning. Fine-tuning these models on captioning datasets has led to significant improvements in caption generation quality, indicating the importance of leveraging pre-trained models in this domain.

Ding [9] introduced a novel image captioning model based on high-level image features, combining low-level information with high-level features such as motion classification and face recognition. Their model employed a bottom-up attention mechanism and used VGG16-based Faster R-CNN for object detection.

Zhang [10] developed a visual enhanced gLSTM for image caption generation, extracting visual features from regions of interest (RoI) or salient regions. Their method outperformed baseline gLSTM algorithms and other popular methods on the Flickr8k dataset, with RoI-based visual enhancement achieving the best performance.

Katiyar [11] conducted a comparative evaluation of 17 CNN architectures for Image Caption Generation, analyzing the correlation between model complexity and feature extraction effectiveness. Their experiments with ResNet, VGG, and DenseNet architectures revealed a significant impact of CNN architecture choice on performance.

Chen [12] proposed a model for bi-directional mapping between images and sentence-based descriptions using a recurrent neural network. Their novel recurrent visual memory captured visual aspects dynamically as words were generated or read, achieving state-of-the-art results in generating novel image descriptions.

Zhang [8] employed a Bi-LSTM structure with forward and backward LSTM decoders, incorporating a subsidiary attention mechanism to align and fuse semantic information. Their Bi-LSTM-s model showed significant improvements in image captioning tasks, with future work focusing on exploring GRU structures and generating finer-grained semantic information.

Amritkar [6] combined CNN for feature extraction and RNN for sentence generation, achieving accurate descriptions for input images on datasets like Flickr8k, Flickr30k, and MSCOCO. Despite minor errors and weakly related descriptions, their model demonstrated the potential for improved accuracy and coherence with unsupervised data and larger datasets.

The field of Image Caption Generation has evolved significantly from early rule-based systems to sophisticated deep learning architectures, marking milestones in enhancing the quality and semantic understanding of generated captions.

Model	Architecture	Evaluation (on MSCOCO)	Comment
(2014, Kiros et al.)	CNN+LSTM encoder -decoder Attention-based	Image Annotation result R@1 R@5 R@10 Med r 23.0 50.7 62.9 5 (OxfordNet) on Flickr30K. R@K is Recall@K (high is good). Med r is the median rank (low is good).	The generated descriptions are arguably the nicest ones to date.
(2015, Xu et al.)	CNN+RNN Attention-based	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR 71.8 50.4 35.7 25.0 23.04	They encourage future work in using visual attention.
(2016, You et al.)	CNN+RNN Attention-based	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR 0.709 0.537 0.402 0.304 0.243 Using the ground-truth visual attributes	They need to experiment with phrase-based visual attributes with their distributed representations.
(2017, Fu et al.)	VGG/Alex/ResNet + LSTM Attention-based	ENSEMBLE result BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR ROUGE-L CIDEr-D 72.4 55.5 41.8 31.3 24.8 53.2 95.5	Either region-based attention or scene-specific contexts improve performance. Combining those two modeling ingredients provides a further improvement.
(2017, Dai et al)	GAN VGG/G-MLE/G-GAN	BLEU-3 BLEU-4 METEOR ROUGE L CIDEr SPICE E-NGAN E-GAN G-MLE: 0.393 0.299 0.248 0.527 0.1020 0.199 0.464 0.427 G-GAN: 0.305 0.207 0.224 0.475 0.795 0.182 0.528 0.602	E-NGAN regard G-GAN as the best generator. This framework also provides an evaluator that is more consistent with human's evaluation.
(2018, Aneja et al.)	CNN+LSTM (ResNet152)	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR ROUGE-L CIDEr 0.725 0.555 0.41 0.299 0.251 0.532 0.972	ResNet is capable of encoding better feature vectors for images. The Meteor and CIDEr results are comparable with previous works.
(2018, Luo et al.)	ResNet101 + LSTM ATTN+CIDER+DISC	BLEU-4 ROUGE METEOR CIDEr SPICE 0.3274 0.2574 **0.5457** 1.0231 0.1939	Incorporating a discriminability loss, in training image caption generators improves the quality of resulting captions. Their model needs more sophisticated visual semantic embedding model.
(2018, Anderson et al.)	CNN+LSTM Faster R-CNN; ResNet101 Attention-based	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR ROUGE-L CIDEr SPICE c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 80.2 95.2 64.1 88.8 49.1 79.4 36.9 68.5 27.6 36.7 57.1 72.4 117.9 120.5 21.5 71.5	They obtained first place in the 2017 VQA Challenge.
(2018, Yao et al.)	GCN+LSTM ResNet101 Attention-based	BLEU-1 BLEU-4 METEOR ROUGE-L CIDEr-D SPICE 80.9 38.3 28.6 58.5 128.7 **22.1**	They build graphs over the detected objects in an image based on their spatial and semantic connections.
(2019, Nezami et al.)	ATTEND-GAN	BLEU-1 BLEU-2 BLEU-3 BLEU-4 ROUGE-L METEOR CIDEr SPICE 56.55 33.85 20.80 13.05 44.45 18.35 62.85 16.05	It also adds sentiment and naturalness to the sentences.
(2020, Ding et al.)	CNN+LSTM (VGG-19)	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR ROUGE CIDEr 0.748 0.525 0.365 0.235 0.235 0.505 1.041	They introduced the theory of attention in psychology to image caption generation.
(2020, Cornia et al.)	CNN+LSTM Faster R-CNN; ResNet101 Attention-based	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR ROUGE CIDEr c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 81.6 **96.0** 66.4 **90.8** 51.8 **82.7** 39.7 **72.8** 29.4 39.0 59.2 **74.8** 129.3 132.1	Novelty in using a stack of memory-augmented encoding layers and a stack of decoder layers.
(2020, Pan et al.)	CNN+LSTM SENet-154 Attention-based	BLEU-1 BLEU-2 BLEU-3 BLEU-4 METEOR ROUGE CIDEr c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 c5 c40 **81.9** 95.7 **66.9** 90.5 **52.4** 82.5 **40.3** 72.4 29.6 39.2 **59.5 75** **131.1 133.5**	They used a novel unified X-Linear attention block for image captioning. Using SENet-154 makes it proceed other models.

Fig. 1. Model Architecture Comparsion

Early approaches relied on rule-based and template-based methods, which were simplistic and lacked semantic depth. These systems primarily used predefined rules to associate basic image features with textual descriptions, such as colors and shapes. However, they struggled to capture the complexities inherent in human language and varied visual contexts.

During the 2000s, the focus shifted towards statistical methods and text mining techniques to improve caption generation. Probabilistic graphical models like Hidden Markov Models (HMMs), Conditional Random Fields (CRFs), and Bayesian Networks emerged as alternatives[11]. These models aimed to capture probabilistic dependencies between visual features extracted from images and the linguistic tokens of captions, offering more flexibility compared to earlier methods.

The advent of deep learning in the mid-2010s marked a significant paradigm shift in Image Caption Generation. Convolutional Neural Networks (CNNs) revolutionized feature extraction from images by capturing hierarchical patterns and spatial relationships effectively. These features were subsequently fed into Recurrent Neural Networks (RNNs), particularly Long Short-Term Memory (LSTM) networks, for sequential modeling and coherent sentence generation.

CNN-RNN architectures became a cornerstone in the field, combining the strengths of CNNs in visual understanding with the sequential modeling capabilities of RNNs for generating descriptive captions word by word. This approach greatly enhanced the accuracy and richness of generated captions, achieving breakthroughs in connecting visual content with linguistic descriptions.

Recent advancements have further extended the capabilities of Image Caption Generation through multimodal learning and

transfer learning techniques. Multimodal models integrate information from diverse sources like text, images, and audio to create more contextually aware captions[4].Transfer learning has enabled models to leverage pre-trained knowledge from large datasets, adapting to specific tasks and domains with improved robustness and accuracy.

Despite these advancements, challenges remain in optimizing machine learning algorithms for image caption generation, particularly in handling diverse image content and generating captions that are both accurate and contextually relevant.

III. Methadology

Image caption generation involves creating descriptive captions for images by leveraging advanced machine learning techniques, particularly deep learning. The primary components of an image caption generation system are image feature extraction, sequence modeling, and caption generation.

The first step in image caption generation is extracting meaningful features from the input image. Convolutional Neural Networks (CNNs) are widely used for this purpose due to their exceptional performance in image processing tasks. Popular CNN architectures such as VGG, ResNet, and Inception are pre-trained on large image datasets like ImageNet to learn rich feature representations. These pre-trained models serve as feature extractors by processing the input image and generating a feature vector that encapsulates important visual information. For instance, a ResNet model can take an input image and produce a feature vector representing objects, textures, and other visual elements present in the image.




Fig. 2. VGG16

Once the image features are extracted, the next step is to model the sequence of words that will form the caption. Recurrent Neural Networks (RNNs), particularly Long Short-Term Memory (LSTM) networks, are commonly used for sequence modeling due to their ability to handle long-range dependencies and sequential data. The image feature vector produced by the CNN is fed into the RNN as the initial input. The RNN then generates a sequence of words, one at a time, to form a coherent caption. During training, the RNN learns to associate specific visual features with corresponding words and phrases.




Fig. 3. Long Short-Term Memory (LSTM) network

To enhance the model's ability to focus on relevant parts of the image when generating each word in the caption, attention mechanisms are employed. An attention mechanism dynamically weights different regions of the image based on their relevance to the current word being generated. This allows the model to concentrate on specific objects or areas within the image, improving the accuracy and descriptiveness of the generated captions. The attention mechanism computes a set of attention weights for the image regions, which are then used to generate a context vector that guides the RNN in producing the next word.

The final step is the actual generation of the caption. During training, the model learns to maximize the likelihood of the target caption given the image. This involves minimizing the difference between the predicted words and the actual words in the training dataset captions. Techniques such as beam search can be used during inference to generate more accurate and coherent captions. Beam search keeps track of multiple candidate sequences and selects the one with the highest overall probability, ensuring that the generated caption is both fluent and relevant to the image.

This methodology of image caption generation involves a combination of CNNs for feature extraction, RNNs for sequence modeling, attention mechanisms for focusing on relevant image regions. These components work together to produce accurate and descriptive captions for images, showcasing the power of deep learning in bridging the gap between visual and textual data.

IV. Model Architecture

Model Architecture: The architecture for image caption generation combines the strengths of Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs), specifically Long Short-Term Memory (LSTM) networks, to effectively convert visual data into descriptive textual captions. Initially, a pre-trained VGG16 model is employed for image feature extraction. VGG16 is chosen for its ability to capture intricate visual details and complexities from images, providing a condensed representation of significant visual information. These extracted features serve as input to the subsequent caption generation mechanism.

The LSTM networks, integral to the sequence modeling process, excel in handling sequential data by maintaining an

internal state that retains contextual information across the sequence of words. This capability allows LSTMs to capture long-range dependencies inherent in natural language, crucial for generating coherent and contextually relevant captions. As the LSTM processes the sequence of words, it integrates contextual cues from the image features extracted by VGG16. This integration enables the model to create captions that not only describe the visual content accurately but also imbue them with semantic meaning and relevance to the input image.

During the caption generation process, the LSTM receives dual inputs: the extracted image features and the previously generated words from the caption sequence. This dual-input mechanism facilitates the LSTM in predicting the next word in the sequence based on both the visual context provided by the image and the linguistic context provided by the ongoing caption generation process. The model learns to optimize this prediction through training, aiming to maximize the likelihood of generating captions that closely match the human-authored captions in the training dataset.

The architecture's strength lies in its ability to leverage the high-level visual features extracted by VGG16 through transfer learning. By repurposing VGG16's learned features without the need for extensive retraining, the model efficiently adapts these features to the specific task of caption generation. This approach is particularly advantageous in scenarios where labeled data is limited or computational resources are constrained, as it minimizes the computational burden while maximizing the effectiveness of feature utilization.

In essence, the combined use of VGG16 for image feature extraction and LSTM networks for sequence modeling forms a robust architecture for image caption generation. This architecture not only harnesses the power of deep learning in processing visual and textual data but also underscores the importance of transfer learning in optimizing model performance across diverse image-related tasks.

Below is the code snippet showcasing the model architecture:




Fig. 4. Model architecture

V. Encoding and Decoding

Encoding and decoding are terms used to describe the processes of translating textual captions into numerical sequences (encoding) and producing human-readable captions from numerical sequences (decoding) in the context of creating image captions. For training and applying deep learning models for image captioning jobs, these procedures are essential.

1.1 Tokenization:

The process of tokenization involves breaking down captions into discrete words, or tokens. In this step, a vocabulary of distinct terms is created, which the model will use to comprehend and produce captions.

1.2 Padding:

To guarantee that every caption is the same length, padding is utilized. This is critical for batch processing since uniformly sized inputs are needed for neural networks.

1.3 Encoding:

Tokens are transformed into numerical vectors via encoding. Every word in the dictionary has a unique integer index, and captions are shown as sequences of these indices. The model can process and learn from textual data because of this numerical representation.




Fig. 5. Encoding and Decoding

1.4 Decoding:

The process of decoding is the opposite of encoding. The model uses the words that have already been generated to forecast the next word in the sequence when creating captions. The inverse mapping of the encoding process is used to transform the predicted word back into its textual form, producing a caption that is readable by humans.

VI. Evaluation

During the evaluation stage, the BLEU (Bilingual Evaluation Understudy) scores—a popular metric in machine translation and natural language processing tasks—are used to determine how well the generated captions are. The similarity between the generated captions and the reference captions that were authored by humans is measured by BLEU scores. A higher BLEU score denotes a greater quality of generated text since it shows that the generated captions are more similar to the reference captions.

CALCULATES BLEU SCORES

```
from nltk.translate.bleu_score import corpus_bleu
from tqdm import tqdm

# Validate with test data
actual, predicted = list(), list()

for key in tqdm(test):
    # Get actual caption
    captions = mapping[key]
    # Predict the caption for the image
    y_pred = predict_caption(model, features[key], tokenizer, max_length)
    # Split into words
    actual_captions = [caption.split() for caption in captions]
    y_pred = y_pred.split()
    # Append to the list
    actual.append(actual_captions)
    predicted.append(y_pred)


# Calculate BLEU Score
print("BLEU-1: %f" % corpus_bleu(actual, predicted, weights=(1.0, 0, 0, 0)))
print("BLEU-2: %f" % corpus_bleu(actual, predicted, weights=(0.5, 0.5, 0, 0)))
```

```
100%|██████████| 810/810 [13:12<00:00,  1.02it/s]
BLEU-1: 0.540298
BLEU-2: 0.312178
```

Fig. 6. calculating BLEU Scores

The Flickr8K dataset, a benchmark dataset for image captioning jobs, is used to assess our methodology. To demonstrate our model's efficiency and competitiveness, its performance is measured against the most advanced techniques. We can determine our model's capacity to produce precise and insightful captions for a given image by analysing it using BLEU scores and contrasting it with other methods for a diverse range of images.

• BLEU-1: 0.54" suggests that, as a percentage, generated captions accuracy for unigrams (unmarried words) is more or less 54 percentage that of the reference captions.

• "BLEU-2: 0.32" suggests that there may be a approximately 32 percent distinction withinside the accuracy of bigrams (consecutive words) among the generated and reference captions.

VII. Results and Discussion

The effectiveness of the model for generating accurate and contextually appropriate image captions is evaluated by a comprehensive analysis of its performance. By carefully examining the generated captions, we evaluate the model's advantages and disadvantages and pinpoint possible areas for development.

Examining the outcomes closely allows us to see the extent to which the suggested process works. We go into great depth on the model's capacity to comprehend image content and generate logical descriptions, providing insight into how well it performs in various image categories and levels of complexity.

```
generate_caption("225699652_53f6fb33cd.jpg")
```

```
----------------Actual----------------
startseq two dolphins flying headfirst into beautiful tropical blue lake endseq
startseq two dolphins jumped out of the water in this zoo endseq
startseq two dolphins jumping into the water endseq
startseq two dolphins jump out of the blue water with palm trees behind them endseq
startseq two dolphins jump out of the water together endseq
----------------Predicted----------------
startseq two dolphins jump into the water endseq
```



Fig. 7. IMAGE CAPTION GENERATION

```
generate_caption("96973080_783e375945.jpg")
```

```
----------------Actual----------------
startseq brown dog is running over snow near leafless trees endseq
startseq brown dog runs across snowy field endseq
startseq dog is running through the snow endseq
startseq dog runs through the snow endseq
startseq medium sized brown dog is running through an open white wooded area endseq
----------------Predicted----------------
startseq dog running through snow covered snow endseq
```



Fig. 8. IMAGE CAPTION GENERATION

We also explore how the model's performance may affect a variety of applications, such as user experience and content accessibility. We investigate the possible effects of precise image captioning on e-commerce product descriptions, social media engagement, and the improvement of instructional content.

The overall goal of the approach this research presents is to create a reliable and efficient model for producing insightful

captions for images. We show what has been accomplished as well as the areas that still require improvement through in-depth study and discussion, opening the door for improvements in image understanding and description creation. The discourse delves into the broader consequences of these discoveries, highlighting the function of sophisticated image captioning models in enhancing accessibility and user involvement on diverse digital platforms.

VIII. FUTURE SCOPE

Despite the encouraging outcomes of our model, there are still several directions that need to be explored in further study. One approach is to enhance the model's functionality by adding more sophisticated methods, including attention processes, to better align the produced words with appropriate parts of the image. Furthermore, investigating more extensive datasets and varied image collections may improve the model's capacity to generalize to a greater variety of images.

Incorporating user input mechanisms may also aid in improving the model's generated captions, making them more relevant to the context and more personalized. Ultimately, investigating multimodal strategies that integrate data from several modalities—like text and audio—may result in picture captions that are more thorough and educational. All things considered, there are many possibilities for further research in the field of image captioning, and we think that our work is a major advancement in this fascinating area of study.

IX. REFERENCES

1) Sharma, Grishma, Priyanka Kalena, Nishi Malde, Aromal Nair, and Saurabh Parkar. "Visual Image Caption Generator Using Deep Learning." 2nd International Conference on Advances in Science & Technology (ICAST) 2019, April 8-9, 2019, K J Somaiya Institute of Engineering & Information Technology, Mumbai, India.
2) Kumar, N. K., D. Vigneswari, A. Mohan, K. Laxman, and J. Yuvaraj. "Detection and Recognition of Objects in Image Caption Generator System: A Deep Learning Approach." 2019 5th International Conference on Advanced Computing & Communication Systems (ICACCS), Coimbatore, India, 2019, pp. 107-109.
3) Raypurkar, M., A. Supe, P. Bhumkar, P. Borse, and S. Sayyad. "Deep Learning Based Image Caption Generator." International Research Journal of Engineering and Technology (IRJET), 8(03), 2021.
4) Sherief, Bincy, and Arathi. "A Survey on Image Captioning Techniques using Deep Learning" IEEE Transactions on Pattern Analysis and Machine Intelligence (PAMI), 2020.
5) Pooja, Sai, Sachin "Enhancing Image Captioning with Neural Models" International Conference on Neural Models (ICCIDS), 2023.
6) Yingwei Pan, Ting Yao, Yehao Li, and Tao Mei "X-Linear Attention Networks for Image Captioning" Conference on Computer Vision and Pattern Recognition (CVPR), 2020.
7) Jun Chen, Han Guo, Kai Yi, Boyang Li, Mohamed Elhoseiny "VisualGPT: Data-Efficient Adaptation of Pretrained Language Models for Image Captioning" International Conference on Learning Representations (CVPR), 2022.
8) Rashmi, Suresh, SanthoshKumar "Image caption generation using Visual Attention Prediction" Conference on Computer Vision and Pattern Recognition (CVPR), 2023.
9) Yang,Liu,Wang "ReFormer: The Relational Transformer for Image Captioning" (cs.CV), 2022.
10) Xie,Wu,S.smith "A Hierarchical Approach to Image Captioning." IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2019.
11) X. Lu, B. Wang, X. Zheng and X. Li, "Exploring Models and Data for Remote Sensing Image Caption Generation," in IEEE Transactions on Geoscience and Remote Sensing, vol. 56, no. 4, pp. 2183-2195, April 2018, doi: 10.1109/TGRS.2017.2776321. keywords: Remote sensing;Semantics;Feature extraction;Image representation;Recurrent neural networks;Computer vision;Image captioning;remote sensing image;semantic understanding.
12) H. Zhang, C. Ma, Z. Jiang and J. Lian, "Image Caption Generation Using Contextual Information Fusion With Bi-LSTM-s," in IEEE Access, vol. 11, pp. 134-143, 2023, doi: 10.1109/ACCESS.2022.3232508. keywords: Feature extraction;Semantics;Visualization;Data mining;Decoding;Task analysis;Logic gates;Bi-LSTM;image caption generation;semantic fusion;semantic similarity.
13) C. Amritkar and V. Jabade, "Image Caption Generation Using Deep Learning Technique," 2018 Fourth International Conference on Computing Communication Control and Automation (ICCUBEA), Pune, India, 2018, pp. 1-4, doi: 10.1109/ICCUBEA.2018.8697360. keywords: Visualization;Natural languages;Decoding;Training;Computer architecture;Microprocessors;Logic gates;Neural Network;Image;Caption;Description;Long Short Term memory(LSTM);Deep Learning