

Use-Case Flow: Report Lost Baggage (UC-01)

Primary Actor: Passenger Includes: Validate Bag Tag Format (UC-02) - <<include>>

Preconditions

- Passenger has completed a flight and their baggage did not arrive at the claim belt.
- Passenger has their bag tag ID and flight number available.

Postconditions

- A new lost-baggage claim exists in the system with status 'Open' and a unique Claim ID.
- The claim is queued for cross-referencing against unrouted scan logs (FR-001).

Main Success Scenario

1. Passenger selects "Report Lost Baggage" in the portal.
2. System displays a claim form requesting bag tag ID, flight number, last-seen location, and bag description.
3. Passenger enters the requested details and submits the form.
4. System invokes Validate Bag Tag Format (<<include>>) to check the bag tag ID against the standard IATA tag format.
5. System confirms the format is valid.
6. System creates a claim record with a unique Claim ID and status 'Open'.
7. System automatically triggers cross-referencing against unrouted scan logs (FR-001).
8. System displays the Claim ID and confirmation message to the Passenger, along with a link to track status.
9. Use case ends successfully.

Alternate Flow

4a. Invalid Bag Tag Format

- 4a1. System displays an "Invalid bag tag format" error and highlights the field.
- 4a2. Passenger is prompted to re-enter the bag tag ID.
- 4a3. If the format fails validation three times, the system suggests the Passenger contact a Baggage Service Agent directly, and the claim is not created.