```
PROGRAM:
#include<stdio.h>
#include<string.h>
int trans_table[10][5][3];
char symbol[5],a;
int e_closure[10][10],ptr,state;
void find_e_closure(int x);
int main()
int i,j,k,n,num_states,num_symbols;
for(i=0;i<10;i++)
for(j=0;j<5;j++)
for(k=0;k<3;k++)
trans_table[i][j][k]=-1;
}
}
printf("How may states in the NFA with e-moves:");
scanf("%d",&num_states);
printf("How many symbols in the input alphabet including e:");
scanf("%d",&num_symbols);
printf("Enter the symbols without space. Give 'e' first:");
scanf("%s",symbol);
for(i=0;i<num_states;i++)</pre>
for(j=0;j<num_symbols;j++)</pre>
printf("How many transitions from state %d for the input
%c:",i,symbol[j]);
scanf("%d",&n);
for(k=0;k<n;k++)
printf("Enter the transitions %d from state %d for the input
%c:", k+1,i,symbol[j]);
scanf("%d",&trans_table[i][j][k]);
}
}
for(i=0;i<10;i++)
for(j=0;j<10;j++)
e_closure[i][j]=-1;
```

```
for(i=0;i<num_states;i++)</pre>
e_closure[i][0]=i;
for(i=0;i<num_states;i++)</pre>
if(trans_table[i][0][0]==-1)
continue;
else
{
state=i;
ptr=1;
find_e_closure(i);
}
for(i=0;i<num_states;i++)</pre>
printf("e-closure(%d)= {",i);
for(j=0;j<num_states;j++)</pre>
if(e_closure[i][j]!=-1)
printf("%d, ",e_closure[i][j]);
}
printf("}\n");
}
void find_e_closure(int x)
int i,j,y[10],num_trans;
i=0;
while(trans_table[x][0][i]!=-1)
y[i]=trans_table[x][0][i];
i=i+1;
}
num_trans=i;
for(j=0;j<num_trans;j++)</pre>
e_closure[state][ptr]=y[j];
ptr++;
find_e_closure(y[j]);
}
}
```

OUTPUT:

