

Ex.No.: 11
DATE:26/10/24

PL SQL PROGRAMS

PROGRAM 1

Write a PL/SQL block to calculate the incentive of an employee whose ID is 110.

```
declare
a employees.employee_id%type;
b employees.salary%type;
begin
Select salary into a from employees where employee_id = 110;
b:=0.05*a;
dbms_output.put_line('Salary after incentive : '||(a+b));
end;
```

Salary after incentive : 6300

Statement processed.

0.01 seconds

PROGRAM 2

Write a PL/SQL block to show an invalid case-insensitive reference to a quoted and without quoted user-defined identifier.

```
declare
non_quoted_variable varchar2(10) := 'Hi';
"quoted_variable" varchar2(10) := 'Hello';
begin
dbms_output.put_line(NON_QUOTED_VARIABLE);
dbms_output.put_line("quoted_variable");
dbms_output.put_line("QUOTED_VARIABLE");
end;
```

```
Hi
Hello
```

```
Statement processed.
```

```
ORA-06550: line 7, column 23:
PLS-00201: identifier 'QUOTED_VARIABLE' must be declared
ORA-06550: line 7, column 1:
PL/SQL: Statement ignored
```

Write a PL/SQL block to adjust the salary of the employee whose ID
122. Sample table: employees

```
declare
old_salary employees.salary%type;
new_salary employees.salary%type;
begin
new_salary:= :sal;
Select salary into old_salary from employees where employee_id = 122;
dbms_output.put_line('Before updation: '||old_salary);
Update employees set salary = salary + new_salary where employee_id = 122;
Select salary into new_salary from employees where employee_id = 122;
dbms_output.put_line('After updation: '||new_salary);
end;
```

Before updation: 8000

After updation: 9000

Statement processed.

0.00 seconds

Write a PL/SQL block to create a procedure using the "IS [NOT] NULL Operator" and show AND operator returns TRUE if and only if both operands are TRUE.

```
Create or replace procedure proc1( a boolean, b boolean) IS
BEGIN
if(a is not null) and (b is not null) then
  if(a = TRUE and b = TRUE) then
    dbms_output.put_line('TRUE');
  else
    dbms_output.put_line('FALSE');
  end if;
else
  dbms_output.put_line('NULL VALUES in arguments');
end if;
end proc1;

BEGIN
proc1(TRUE,TRUE);
proc1(TRUE,FALSE);
proc1(NULL,NULL);
end;
```

```
TRUE
FALSE
NULL VALUES in arguments
```

Statement processed.

0.00 seconds

Write a PL/SQL block to describe the usage of LIKE operator including wildcard characters and escape character.

```
Declare
name varchar2(20);
num number(3);
Begin num
:= :n;
Select first_name into name from employees where employee_id=num;
if name like 'D%' then
dbms_output.put_line('Name starts with
"D"); end if;
if name like 'Dan_e1%' then
dbms_output.put_line('Name contains "Dan" followed by one character');
end if;
name := 'Daniel_Andrea';
if name like 'Daniel\_Andrea' escape '\' then
dbms_output.put_line('Name contains "Daniel_Andrea"');
end if;
end;
```

```
Name starts with "D"
Name contains "Dan" followed by one character
Name contains "Daniel_Andrea"
```

```
Statement processed.
```

PROGRAM 6

Write a PL/SQL program to arrange the number of two variable in such a way that the small number will store in num_small variable and large number will store in num_large variable.

```
declare
a number(2);
b number(2);
num_small number(2);
num_large number(2);
begin
a := :s;
b := :l;
dbms_output.put_line('Value in a : '||a);
dbms_output.put_line('Value in b : '||b);
if a>b then
num_small := b;
num_large := a;
else
num_small :=a;
num_large :=b;
end if;
dbms_output.put_line('Smaller number is '||num_small);
dbms_output.put_line('Larger number is '||num_large);
end;
```

```
Value in a : 10
Value in b : 5
Smaller number is 5
Larger number is 10
```

```
Statement processed.
```

```
0.00 seconds
```

PROGRAM 7

Write a PL/SQL procedure to calculate the incentive on a target achieved and display the message either the record updated or not.

```
Create or replace procedure calc_incen(emp_id number,achievement number,target number)
AS
incentive number;
rowcount number;
Begin
if achievement > target then
incentive:= achievement*0.2;
else
incentive:=0;
end if;
Update employees set salary = salary + incentive where employee_id = emp_id;
rowcount:= SQL%ROWCOUNT;
if rowcount>0 then
dbms_output.put_line('Record(s) updated');
else
dbms_output.put_line('No Record(s) updated');
end if;
end;

Declare
id number; achievement
number; target
number;
Begin
id := :emp_id; achievement
:= :achieve; target :=
:target_;
calc_incen(id,achievement,target);
end;
```

Record(s) updated

Statement processed.

PROGRAM 8

Write a PL/SQL procedure to calculate incentive achieved according to the specific sale limit.

```
Create or replace procedure calc_incen(emp_id number,sales number) AS
  incentive number;
rowcount number;
Begin
if sales < 1000 then
  incentive:= 0;
elsif sales > 1000 and sales < 2000 then
incentive := sales * 0.2;
  else
incentive := sales * 0.5;
  end if;
Update employees set salary = salary + incentive where employee_id = emp_id;
  rowcount:= SQL%ROWCOUNT;
if rowcount>0 then
  dbms_output.put_line('Record(s) updated');
  else
dbms_output.put_line('No Record(s) updated');
  end if;
end;

Declare
id number; sales
  number; sal
  number;
Begin
id := :emp_id;
  sales := :sale;
select salary into sal from employees where employee_id = id;
  dbms_output.put_line('Before incentive calculation: '||sal);
  calc_incen(id,sales);
select salary into sal from employees where employee_id = id;
dbms_output.put_line('After incentive calculation: '||sal);
end;
```

Before incentive calculation: 21000

Record(s) updated

After incentive calculation: 23500

Statement processed.

Write a PL/SQL program to count number of employees in department 50 and check whether this department have any vacancies or not. There are 45 vacancies in this department.

```
declare
emp_count number;
vacancy number :=
20; begin
Select count(*) into emp_count from employees where department_id = 10;
dbms_output.put_line('Total seats : '||vacancy);
dbms_output.put_line('Number of employees in Department 50 : '||emp_count);
if emp_count>vacancy then
dbms_output.put_line('No vacancies available');
else
dbms_output.put_line('Available vacancies : '||(vacancy-emp_count));
end if;
end;
```

Total seats : 20

Number of employees in Department 50 : 3

Available vacancies : 17

Statement processed.

Write a PL/SQL program to count number of employees in a specific department and check whether this department have any vacancies or not. If any vacancies, how many vacancies are in that department.

```
declare
dept_id number;
emp_count number;
vacancy number :=
10; begin
dept_id := :id;
Select count(*) into emp_count from employees where department_id = dept_id;
dbms_output.put_line('Total seats : '||vacancy);
dbms_output.put_line('Number of employees in Department : '||emp_count);
if emp_count>vacancy then
dbms_output.put_line('No vacancies available');
else
dbms_output.put_line('Available vacancies : '||(vacancy-emp_count));
end if;
end;
```

```
Total seats : 10
Number of employees in Department : 2
Available vacancies : 8
```

Statement processed.

Write a PL/SQL program to display the employee IDs, names, job titles, hire dates, and salaries of all employees.

```
begin
for i in (select employee_id, first_name, job_id, hire_date, salary from employees)
loop
dbms_output.put_line('employee id: ' || i.employee_id);
dbms_output.put_line('name: ' || i.first_name);
dbms_output.put_line('job title: ' || i.job_id);
dbms_output.put_line('hire date: ' || to_char(i.hire_date, 'dd-mon-yyyy'));
dbms_output.put_line('salary: ' || i.salary);
dbms_output.put_line('-----');
end loop;
end;
```

```
employee id: 101
name: John
job title: IT_PROG
hire date: 01-jan-1994
salary: 6020
-----
```

```
employee id: 176
name: Jane
job title: HR_REP
hire date: 20-feb-2019
salary: 12500
-----
```

```
employee id: 103
name: Mike
job title: SA_MAN
hire date: 01-mar-1998
salary: 7200
-----
```

```
employee id: 104
name: Emily
job title: AC_ACCOUNT
hire date: 01-jan-1998
salary: 15000
-----
```

```
employee id: 105
name: Robert
job title: ST_CLERK
hire date: 25-jul-2018
salary: 6200
-----
```

Write a PL/SQL program to display the employee IDs, names, and department names of all employees.

```
begin
for i in (select e.employee_id, e.first_name, e.job_id from employees
e) loop
dbms_output.put_line('employee id: ' ||
i.employee_id); dbms_output.put_line('name: ' ||
i.first_name); dbms_output.put_line('department
name: ' || i.job_id); dbms_output.put_line(' ');
end loop;
end;
```

```
employee id: 101
name: John
department name: IT_PROG
-----
employee id: 176
name: Jane
department name: HR_REP
-----
employee id: 103
name: Mike
department name: SA_MAN
-----
employee id: 104
name: Emily
department name: AC_ACCOUNT
-----
employee id: 105
name: Robert
department name: ST_CLERK
-----
```

PROGRAM 13

Write a PL/SQL program to display the job IDs, titles, and minimum salaries of all jobs.

```
Begin
for i in (select job_id,job_title,min_salary from jobs)
loop
dbms_output.put_line('job id: ' || i.job_id);
dbms_output.put_line('job title: ' || i.job_title);
dbms_output.put_line('minimum salary: ' ||
i.min_salary); dbms_output.put_line('-----');--
end loop;
end;
```

```
job id: 101
job title: Software Engineer
minimum salary: 60000
-----
job id: 102
job title: Data Analyst
minimum salary: 50000
-----
job id: 103
job title: Project Manager
minimum salary: 70000
-----
job id: 104
job title: HR Manager
minimum salary: 55000
-----
job id: 105
job title: Marketing Specialist
minimum salary: 45000
-----
```

Write a PL/SQL program to display the employee IDs, names, and job history start dates of all employees.

```
Begin
for i in (select employee_id,employee_name,start_date from job_history)
loop
dbms_output.put_line('employee id: ' || i.employee_id);
dbms_output.put_line('name: ' || i.employee_name);
dbms_output.put_line('start date: ' || to_char(i.start_date,
'dd-mon-yyyy')); dbms_output.put_line('---');
end loop;
end;
```

```
employee id: 201
name: James
start date: 01-jan-2010
-----
employee id: 202
name: King
start date: 01-jan-2012
-----
employee id: 203
name: Smith
start date: 01-jan-2013
-----
employee id: 204
name: Steve
start date: 01-jan-2014
-----
employee id: 205
name: Robert
start date: 01-jan-2015
-----
```

Write a PL/SQL program to display the employee IDs, names, and job history end dates of all employees.

```
Begin
for i in (select employee_id,employee_name,end_date from job_history)
loop
dbms_output.put_line('employee id: ' || i.employee_id);
dbms_output.put_line('name: ' || i.employee_name);
dbms_output.put_line('end date: ' || to_char(i.end_date,
'dd-mon-yyyy')); dbms_output.put_line('---');
end loop;
end;
```

```
employee id: 201
name: James
end date: 10-oct-2015
```

```
-----
employee id: 202
name: King
end date: 15-sep-2016
```

```
-----
employee id: 203
name: Smith
end date: 20-mar-2017
```

```
-----
employee id: 204
name: Steve
end date: 05-apr-2018
```

```
-----
employee id: 205
name: Robert
end date: 12-may-2019
-----
```