

POM Enquiry

Tuesday, December 10, 2024 4:57 PM

It is used to search database, from ITK using APIs.

1. **POM_enquiry_create()**
2. **POM_enquiry_add_select_attrs()**

```
// set where exp
ITK_RETURN_ON_ERROR(POM_enquiry_create(query_id));
ITK_RETURN_ON_ERROR(POM_enquiry_add_select_attr(query_id, "V49_FPMTHD_IssueRevision", attrlist));
//ITK_RETURN_ON_ERROR(POM_enquiry_set_distinct(query_id, true));

//Add attribute expression
ITK_string_to_date("18-Nov-2022 00:00", &start_date);
ITK_RETURN_ON_ERROR(POM_enquiry_set_date_expr(query_id, "start_dateExpr", "V49_FPMTHD_IssueRevision", LAST_MOD_DATE_ATTR,
POM_enquiry_greater_than, start_date));
ITK_string_to_date("18-Nov-2023 00:00", &end_date);
ITK_RETURN_ON_ERROR(POM_enquiry_set_date_expr(query_id, "end_dateExpr", "V49_FPMTHD_IssueRevision", LAST_MOD_DATE_ATTR,
POM_enquiry_less_than_or_eq, end_date));
ITK_RETURN_ON_ERROR(POM_enquiry_set_expr(query_id, "dateExpr", "start_dateExpr", POM_enquiry_and, "end_dateExpr"));

//set where Exp
ITK_RETURN_ON_ERROR(POM_enquiry_set_where_expr(query_id, "dateExpr"));

//execute POM Query
ITK_RETURN_ON_ERROR(POM_enquiry_execute(query_id, &rows, &cols, &queryResult));
TC_write_printf("queryList02Rev: no of rev found : %d\n", rows);
cout<<"queryList02Rev: no of rev found : " << rows << "\n";
if(rows > 0)
{
    for(int i = 0; i < rows; i++)
    {
        tag_t obj = *(tag_t*)queryResult[i][0];
        vindex.push_back(obj);
    }
}
```