

Preferences

Wednesday, January 08, 2025 10:05 AM

PSEVariantsMode	Variants Mode
TC_config_rule_name	Sets the default revision rule Teamcenter uses when opening a new product structure window
PSM_set_default_rev_rule	Overrides the revision rule
PSEPreciseColorPref: PSEImpreciseColorPref:	Color
PSEShowSubstitutesPref	This is for showing local substitutes as separate bom line
TC_BOM_Precision_preference	Default imprecise
PSEAutoPackPref	Default packed structure

- **AE_dataset_default_keep_limit:**

Default number of versions of Teamcenter datasets to keep before deleting old versions. Changing the value will only affect datasets created after the value is changed.

- **TCDefaultKeepLimit:**

Determines the number of sequences the system maintains as an Item revision is checked in and out of the database. Sequences are subrevisions of item revisions that document the content of a revision during its evolution. Checking out an Item revision increments the sequence ID.

At logon, the system automatically removes the oldest sequence when the limit specified with this preference is reached.

Valid Values:

Accepts a single string as a value. Must be a single, positive integer.

- It is impossible to send this envelope to external recipients.

Either the "Mail_OSMail_activated" preference is not set to TRUE or the "Mail_server_name" preference is not set to a valid mail server. If you want to proceed, remove the external mail recipients.

PSudo folder??

- **TC_QRY_search_result_display_mode** preference specifies whether to display the total number of found objects for which the user has access privileges

- **ITEM_Group_order:**

Specifies the order by types of children components to be displayed when expanding the node of objects of type "Item" in the "My Teamcenter" perspective of the rich client.

Other children components whose types are not in the list will be displayed after the children components whose types are specified here.

The valid values are Business Object type name.

If this preference is not configured, then the children components will be displayed based on **Item_DefaultChildProperties** preference values.

- **PSEVariantsMode :**

Determines which mode of variants functionality is used: modular, legacy, or a hybrid of both modes. The legacy variants functionality does not provide all the encapsulation advantages that the modular variants functionality enforces, nor is it possible to create variant items within a structure containing legacy variants.

The hybrid mode allows legacy variants to be displayed, edited and configured using the modular variants dialog boxes. This is the recommended mode during migration from legacy to modular variants functionality. Once the migration is complete, this preference setting should be changed to modular.

Valid Values:

modular - Modular variant functionality is used. Legacy variant data cannot be viewed, edited, or configured.

hybrid - A hybrid of modular and legacy variant functionality is used, allowing variant modules to be defined in structures containing legacy variant data.

legacy - Legacy variant functionality is used.

- **TCDefaultKeepLimit** Limit no of sequences (Item revisions)
- **AE_dataset_default_keep_limit** Limit no of versions (dataset)
- **ItemRevision_default_relation** change default paste option
- **CR_allow_alterate_procedure**: Workflow template any / Assigned /none
- **WRKFLW_use_legacy_template_filter** true
- **WRKFLW_task_complete** adhoc checked
- **EPM_enable_apply_template_changes** active (optional/automatic)
- **Mail_internal_mail_activated** For epm-notify to work
- **Workspaceobject_default_workflow_template** Default WF