

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/319503839>

Machine Learning Techniques For Rainfall Prediction: A Review

Conference Paper · March 2017

CITATIONS

107

READS

38,730

3 authors:



Aakash Parmar

Uka Tarsadia University

1 PUBLICATION 107 CITATIONS

SEE PROFILE



Kinjal Mistree

Uka Tarsadia University

11 PUBLICATIONS 206 CITATIONS

SEE PROFILE



Mithila Sompura

chhotubhai gopalbhai patel institute of technology

3 PUBLICATIONS 117 CITATIONS

SEE PROFILE

Machine Learning Techniques For Rainfall Prediction: A Review

Aakash Parmar

Department of Computer
Engineering,
CGPIT, Uka Tarsadia University,
Bardoli, Surat, India
parmar.akash11@gmail.com

Kinjal Mistree

Department of Computer
Engineering,
CGPIT, Uka Tarsadia University,
Bardoli, Surat, India
kinjal.mistree@utu.ac.in

Mithila Sompura

Department of Computer
Engineering,
CGPIT, Uka Tarsadia University,
Bardoli, Surat, India
mithila.sompura@utu.ac.in

Abstract— Heavy rainfall prediction is a major problem for meteorological department as it is closely associated with the economy and life of human. It is a cause for natural disasters like flood and drought which are encountered by people across the globe every year. Accuracy of rainfall forecasting has great importance for countries like India whose economy is largely dependent on agriculture. Due to dynamic nature of atmosphere, Statistical techniques fail to provide good accuracy for rainfall forecasting. Nonlinearity of rainfall data makes Artificial Neural Network a better technique. Review work and comparison of different approaches and algorithms used by researchers for rainfall prediction is shown in a tabular form. Intention of this paper is to give non-experts easy access to the techniques and approaches used in the field of rainfall prediction.

I. INTRODUCTION

Rainfall prediction is helpful to avoid flood which save lives and properties of humans. Moreover, it helps in managing resources of water. Information of rainfall in prior helps farmers to manage their crops better which result in growth of country's economy. Fluctuation in rainfall timing and its quantity makes rainfall prediction a challenging task for meteorological scientists.

In all the services provided by meteorological department, Weather forecasting stands out on top for all the countries across the globe. The task is very complex as it requires numbers of specialized and also all calls are made without any certainty.

Section 2 discusses the different methods used for rainfall prediction for weather forecasting with their limitations. Various neural networks algorithm which are used for prediction are discussed with their steps in detail. Section 3 categorizes various approaches and algorithms used for rainfall prediction by various researchers in today's era. Finally, section 4 presents conclusion of paper.

II. BACKGROUND THEORY

Two widely used methods for rainfall forecasting are: Statistical methods and Numerical Weather Prediction (NWP) model [16]. Nature of rainfall data is non-linear. Frequency,

intensity and amount are main characteristics for time series rainfall. These values can be varied from one position on earth to other position of earth and from one time to other time. Every statistical model has some drawbacks. Combination of AR and MA together forms a general and useful class of the time series model known as ARMA model. ARMA model is only useful for stationary time-series data and forecasting of short term rainfall. The statistical approaches do not have the ability to identify nonlinear patterns and irregular trend in the time series [16].

A. ARIMA Model

Box and Jenkins [29] proposed a methodology that consists of four steps:

Step 1. In the identification stage, IDENTIFY statement is used to specify the response of series and identification of candidate. The IDENTIFY statement considers time series that will be used in later statements, possibly for differentiating them, and calculates autocorrelations, inverse autocorrelations, cross correlations and partial autocorrelations.

Step 2 and 3. In the estimation and diagnostic checking stage, ESTIMATE statement helps ARIMA model to fit to the variable taken in the previous IDENTIFY statement, and to estimate the parameters of that model.

Step 4. In the forecasting stage, FORECAST statement is used to forecast future values of the time series. Confidence intervals are generated for these forecasts from the ARIMA model.

Autocorrelation Function (ACF) and the Partial Autocorrelation Function (PACF) are important analytical tools used with the time series analysis and forecasting [30]. Main uses of these models are to measure the statistical relationships between observations in a single data series. ACF has big advantage of measuring the amount of linear dependence between results of a time series which will be separated by a lag k . In order to identify the model (step 1), ACF and PACF have to be estimated. They are used to guess the form of the model and to obtain approximate estimates of the parameters as well [30].




Fig. 1 Outline of Box-Jenkins Methodology [29]

B. Artificial Neural Network

ANN is a computational model that is inspired by the human brain [31]. ANN contains a big number of interconnected neurons, which mostly operate in parallel, and are well structured. Categories of neural networks are either single layer or multi-layer. Layer between input layer and output layer is called as hidden layer. A single-layer feed forward (SLFF) neural network consists of one input layer whose nodes have weights assigned and one output layer. A multi-layer feed-forward (MLFF) neural network architecture can be developed by adding hidden layers in SLFF neural network.

1) Back-Propagation Neural Network:

BPNN is made of MLFF neural network which contains one input layer, hidden layers and one output layer. BPNN architecture with one hidden layer is shown in figure 2. The ultimate goal of BPNN is to decrease the calculated error obtained from the difference between the calculated output and desired output of the neural network by adjusting the weights after each iteration. So in BPNN, each information is propagated in backward direction until the calculated error is very small or zero. There are three phases of BPNN training: (a) using FFNN for training process of input. Adjustment of weights and nodes are made in this phase, (b) to calculate the error, and (c) modification of weights.

ANN model has great ability to learn by doing proper adjustment of these parameters for achieving the desired output. During the training process, this output may fit to the data very well, but it may provide poor results during the testing process. This suggests that the neural network may not generalize well. This might be because of overfitting or overtraining of data [32], which can be controlled by analyzing the error during training process and stopping the process when the error reaches a minimum threshold with respect to the testing set [33]. Alternate option to make the neural network generalize enough is by doing small changes in the number of layers and neurons in the inputs, without changing the output components. However, best neural network architecture selection is a heuristic approach. Solution is to keep the architecture of neural network relatively simple and small [34], because complex architectures are much more prone to overfitting [35].




Fig. 2 A BPNN architecture with one hidden layer [39]

2) Cascade Forward Back Propagation Network:

The CFBP network shown in Figure 2.3 is one of the artificial neural network types, which is used for the prediction of new output data. All the layers in networks are not only connected with its previous layer but also connected with input. Inputs are provided to each layer in network.




Fig. 3 Cascade Forward Back Propagation Network [40]

3) Layer Recurrent Network:

In this type of neural network, connections between units create a directed cycle. Unlike other feedforward neural networks, RNNs can use their internal memory to process arbitrary sequences of inputs [36]. RNN are neural networks with a feedback loop. The previous processes of hidden layer and functional outputs are fed back into the network as part of the input to the next hidden layer processes.




Fig. 4 Layer Recurrent neural Network

C. Support Vector Machine (SVM)

Support Vector Machine is also one type of feed forward network. Support vector machines are applicable for tasks like pattern classification, nonlinear regression etc. Support Vector Machines were created by Vapnik and his co-workers which has been used for supervised learning due to – (i) Better generalization ability than other NN models (ii) SVM solution is identical, optimal and absent from local minima (iii) Applicable to non-vectorial data (Strings and Graphs) and (iv) Very few parameters are needed for tuning the learning m/c. Very few scientists have applied this technique for rainfall prediction and results were acceptable.

D. Self Organizing Map (SOM)

SOM is also a part of artificial neural network. It is based on competitive learning. Neurons in the network compete between themselves to get activated. One neuron only can get activated at one time. Only winning neuron's weight is updated. This scheme is called as "winner takes all" scheme. Base of SOM is unsupervised learning, in which human interpretation is not required during the learning process. Structure of neurons is in one or two dimensional lattice. Self Organizing Map is data visualization technique invented by Prof. Teuvo Kohonen which reduces the dimensions of data through self-organizing neural networks [37]. SOM reduces dimensions & display similarities ([37], [38]).

III. LITERATURE REVIEW

P. Goswami and Srividya [1] have combined RNN and TDNN features and conclusion of their work was that composite models gives better accuracy than the single model. C.Venkatesan et al. [2] used Multilayer Feed Forward Neural Networks (MLFNN) for predicting Indian summer monsoon rainfall. Error Back Propagation (EBP) algorithm is trained and applied to predict the rainfall. Three network models with two, three and ten input parameters have analyzed. They also compared the output result with the statistical models. A.Sahai et al. [3] used error back propagation algorithm for Summer Monsoon Rainfall prediction of India on monthly and seasonal time series. They used data of previous five years of monthly and seasonal mean rainfall values for rainfall prediction. N.Philip and K.Josheph [5] used ABF neural network for yearly rainfall forecasting Kerala region. Their work suggests that ABFNN performs better than the Fourier analysis.

V. Somvanshi et al. [7] predicted rainfall of Hyderabad, INDIA region using ANN model. They also compared ANN with ARIMA technique. They used past four months rainfall data as inputs to neural network model. S. Chattopadhyay and M. Chattopadhyay [9] have used two parameters minimum temperature and maximum temperature for rainfall forecasting. S. Chattopadhyaya and G. Chattopadhyaya [10] used Conjugate Gradient Decent (CGD) and Levenberg–Marquardt (LM) learning algorithm for training. Performances of both algorithms were same in prediction task. C. Wu et al. [12] predicted the rainfall of India and China. They applied Modular

Artificial Neural Network (MANN). MANN's performance was compared with LR, K-NN and ANN.

K. Htike and O. Khalifa [13] used yearly, biannually, quarterly and monthly rainfall data for rainfall prediction. They trained four different Focused Time Delay Neural Networks (FTDNN) for rainfall forecasting. Highest prediction accuracy was provided by the FTDNN model when yearly rainfall data is taken for training. S. Kannan and S. Ghosh [14] contributed towards developing K- mean clustering technique combined with decision tree algorithm, CART, is used for rainfall states generation from large scale atmospheric variables in a river basin. Rainfall state on daily basis is derived from the historical daily multi-site rainfall data using K-mean clustering. M. Kannan et al. [15] predicted short term rainfall. Empirical method technique is used for prediction task. Data of three specific months for five years is analyzed for particular region. Clustering is used for grouping the elements.

G. Geetha and R. Selvaraj [16] used ANN model for predicting monthly rainfall of Chennai region. M. Sharma and J. Singh [17] considered parameters such as rainfall, maximum and minimum temperature, and relative humidity. They predicted weekly rainfall over Pantnagar region. ANN obtained higher prediction accuracy than multiple linear regression model. J. Abbot and J. Marohasy [18] used Time Delay Recurrent Neural Network (TDRNN) for monthly rainfall prediction over Australia region. A. Kumar et al. [19] predicted average rainfall over Udipi district of Karnataka. They used ANN models for prediction task of rainfall. They concluded that Back Propagation Algorithm (BPA) was better than the layer recurrent and cascaded back propagation. Soo-Yeon Ji et al. [21] predicted the hourly rainfall. CART and C4.5 are used for prediction, which may provide hidden important patterns with their reasons. There were 18 variable used from weather station. 10 fold cross validation method is performed for validation purpose. CART performed better than C4.5.

S. Nanda et al. [24] predicted rainfall using a complex statistical model ARIMA and three ANNs models which are MLP, LPE (Legendre Polynomial Equation) and FLANN (Functional-Link Artificial Neural Network). In Comparision, FLANN gives better prediction accuracy compared to the ARIMA model. A. Naik and S. Pathan [25] used the ANN model for rainfall prediction. They modified back propagation algorithm which was more robust than the simple back propagation algorithm. Pinky Saikia Dutta and Hitesh Tahbilder [28] predicted monthly Rainfall of Assam by traditional statistical technique -Multiple Linear Regression. Parameters selected for the model are min-max temperature, mean sea level pressure, wind speed and rainfall. Acceptable accuracy is given by prediction model based on multiple linear regression.

Table presents categorization of different approaches of rainfall prediction. The categorization is based on following features: authors, region, dataset time period, techniques, accuracy measure and rainfall predicting variables.

TABLE I. CATEGORIZATION OF DIFFERENT APPROACHES OF RAINFALL PREDICTION

Authors	Region	Dataset Time Period	Techniques	Accuracy Measure	Rainfall Predicting Attribute
P. Goswami, Srividya (1996) [1]	Global (all over India)	Yearly (135 years)	Artificial Neural Network (EBP)	Relative percentage error	Mean rainfall
C. Venkatesan et al. (1997) [2]	Global (all over India)	Monthly (1939-1994)	Artificial Neural Network (EBP)	RMSE	Min-Max temperature
A. Sahai et al. (2000) [3]	Global (all over India)	Monthly (1876-1994)	Artificial Neural Network (EBP)	RMSE, correlation coefficient	Min-Max temperature
N. Philip et al. (2001) [4]	Local (Kerala)	Monthly (1893-1933)	ABFNN	RMSE	Wind, temperature, precipitation, latitude-longitude, sea surface pressure
N. Philip, K. Joseph (2002) [5]	Local (Kerala)	Yearly (1893-1933)	ABFNN	RMSE	Wind, temperature, precipitation, latitude-longitude, sea surface pressure
N. Chantasut et al. (2004) [6]	Local (Chao Pharya River)	Monthly (1941-1999)	Artificial Neural Network (EBP)	MSE	Temperature
V. Somvanshi et al. (2006) [7]	Local (Hyderabad)	Yearly (103 years)	ANN, ARIMA	RMSE, MAE	Humidity, Min-Max temperature
S. Chattopadhyay (2007) [8]	Global (all over India)	Monthly	Artificial Neural Network (EBP)	MSE	Temperature, Rainfall
S. Chattopadhyay, M. Chattopadhyay (2007) [9]	Global (all over India)	Monthly	Multilayer perceptron	MSE	Min-Max temperature
S. Chattopadhyay, G. Chattopadhyay (2008) [10]	Global (all over India)	Monthly	Artificial Neural Network (EBP)	MSE	Min-Max temperature
P. Guhathakurta (2008) [11]	Global (all over India)	Yearly (1941-2005)	Artificial Neural Network (EBP)	RMSE	Min-Max temperature
C. Wu et al. (2010) [12]	Global (India, China)	Daily, Monthly	Modular Artificial Neural Network	RMSE	Min-Max temperature
K. Htike, O. Khalifa (2010) [13]	Global (India)	Yearly, Monthly, Bi-annually, Quarterly	Focused Time Delay Neural Network	MAPE	Temperature, solar radiation, evaporation
S. Kannan, S. Ghosh (2010) [14]	Local (River)	Daily (50 years)	Decision tree, CART, K-mean	MSE	Temperature, pressure, wind speed, rainfall
M. Kannan et al. (2010) [15]	Global (India)	Quarterly (5 years)	Regression	MSE	Min-Max temperature, wind direction, humidity, rainfall
G. Geeta, R. Selvaraj (2011) [16]	Local (Chennai)	Monthly (1978-2009)	Multilayer Back Propagation Neural Network	RMSE	Wind speed, mean temperature, relative humidity, aerosol values
M. Sharma, J. Singh (2011) [17]	Local (Pantnagar, India)	Weakly (39 Years)	Multiple Regression Model, ANN(EBP)	Absolute mean difference	Min-Max temperature, relative humidity, pan evaporation
J. Abbot, J. Marohasy (2012) [18]	Local (Australia)	Monthly (1900-2009)	TDRNN	RMSE, Pearson correlation coefficient	Rainfall, climatic indices, atmospheric temperature, solar data
A. Kumar et al. (2012) [19]	Local (Udipi)	Monthly (1960-2010)	EBPNN, CBPNN, LRN	MSE	Average humidity, Average wind speed
R. Deshpande (2012) [20]	Local	Monthly	Elman neural network	MSE	Rainfall
S. Yeon et al. (2012) [21]	Local	Hourly (3 years)	Decision tree, CART	High prediction accuracy	Temperature, wind direction, gust, humidity, pressure
G. Shrivastava et al. (2013) [22]	Local (Ambikapur)	Yearly (1951-2011)	Artificial Neural Network (EBP)	MSE	Humidity, dew point, pressure
C. Wu, K. Chau (2013) [23]	Global (India, China)	Daily, Monthly	Moving Average, ANN	RMSE	Min-Max. temperature
S. Nanda et al. (2013) [24]	Global (India)	Yearly (1990-2012)	ARIMA model, ANN	MSE	Min-Max. temperature
A. Naik et al. (2013) [25]	Global (India)	Monthly	Artificial Neural Network (EBP)	RMSE	Wind speed, temperature, humidity

Priya et al. (2014) [26]	Global (India)	Monthly (1871-2010)	Artificial Neural Network (EBP)	RMSE	Min-Max. temperature
V. Dabhi, S. Chaudhary (2014) [27]	Local (Anand)	Daily (1991-2002)	Wavelet-postfix-GP model, Wavelet ANN	MAE, MSE, Adjusted fitness	Min-Max. temperature, evaporation, relative humidity, rainfall
P. Dutta, H. Tahbiller (2014) [28]	Global (India)	Monthly (6 years)	Regression	RMSE	Min-Max. temperature, wind direction, humidity, rainfall

IV. CONCLUSION

The estimation of rainfall is of great importance in terms of water resources management, human life and their environment. It can be met with the incorrect or incomplete estimation problems because rainfall estimation is affected from the geographical and regional changes and properties. This paper presented review of different methods used for rainfall prediction and problems one might encounter while applying different approaches for rainfall forecasting. Due to nonlinear relationships in rainfall data and ability of learning from the past makes Artificial Neural Network a preferable approach from all available approaches.

REFERENCES

- [1] P. Goswami and Srividya, "A novel Neural Network design for long range prediction of rainfall pattern," *Current Sci.(Bangalore)*, vol. 70, no. 6, pp. 447-457, 1996.
- [2] C. Venkatesanet, S. D. Raskar, S. S. Tambe, B. D. Kulkarni, and R. N. Keshavamurty, "Prediction of all India summer monsoon rainfall using Error-Back-Propagation Neural Networks," *Meteorology and Atmospheric Physics*, pp. 225-240, 1997.
- [3] A. K. Sahai, M. K. Soman, and V. Satyan, "All India summer monsoon rainfall prediction using an Artificial Neural Network," *Climate dynamics*, vol. 16, no. 4, pp. 291-302, 2000.
- [4] N. S. Philip and K. B. Joseph, "On the predictability of rainfall in Kerala-An application of ABF neural network," *Computational Science-ICCS*, Springer Berlin Heidelberg, pp. 1-12, 2001.
- [5] N. S. Philip and K. B. Joseph, "A Neural Network tool for analyzing trends in rainfall," *Comput. & Geosci.*, vol. 29, no. 2, pp. 215-223, 2003.
- [6] N. Chantasut, C. Charoenjit, and C. Tanprasert, "Predictive mining of rainfall predictions using artificial neural networks for Chao Phraya River," 4th Int Conf. of the Asian Federation of Inform. Technology in Agriculture and the 2nd World Congr. on Comput. in Agriculture and Natural Resources, Bangkok, Thailand, pp. 117-122, 2004.
- [7] V. K. Somvanshi, O. P. Pandey, P. K. Agrawal, N.V.Kalanker1, M.Ravi Prakash, and Ramesh Chand, "Modeling and prediction of rainfall using Artificial Neural Network and ARIMA techniques," *J. Ind. Geophys. Union*, vol. 10, no. 2, pp. 141-151, 2006.
- [8] S. Chattopadhyay, "Anticipation of summer monsoon rainfall over India by Artificial Neural Network with Conjugate Gradient Descent Learning," *arXiv preprint nlin/0611010*, pp. 2-14, 2006.
- [9] S. Chattopadhyay and M. Chattopadhyay, "A Soft Computing technique in rainfall forecasting," *Int. Conf. on IT, HIT*, pp. 19-21, 2007.
- [10] S. Chattopadhyay and G. Chattopadhyay, "Comparative study among different neural net learning algorithms applied to rainfall time series," *Meteorological applicat.*, vol. 15, no. 2, pp. 273-280, 2008.
- [11] P.Guhathakurta, "Long lead monsoon rainfall prediction using deterministic Artificial Neural Network model," *Meteorology and Atmospheric Physics* 101, pp. 93-108, 2008.
- [12] C. L. Wu, K. W. Chau, and C. Fan, "Prediction of rainfall time series using Modular Artificial Neural Networks coupled with datapreprocessing techniques," *J. of hydrology*, vol. 389, no. 1, pp. 146-167, 2010.
- [13] K. K. Htike and O. O. Khalifa, "Rainfall forecasting models using Focused Time-Delay Neural Networks," *Comput. and Commun. Eng. (ICCCE)*, Int. Conf. on IEEE, 2010.
- [14] S. Kannan, Subimal Ghosh, "Prediction of daily rainfall state in a river basin using statistical downscaling from GCM output", Springer-Verlag, July- 2010.
- [15] M.Kannan, S.Prabhakaran, P.Ramachandran, "Rainfall Forecasting Using Data Mining Technique", *International Journal of Engineering and Technology* Vol.2 (6), 397-401, 2010.
- [16] G. Geetha and R. S. Selvaraj, "Prediction of monthly rainfall in Chennai using Back Propagation Neural Network model," *Int. J. of Eng. Sci. and Technology*, vol. 3, no. 1, pp. 211 213, 2011.
- [17] M. A. Sharma and J. B. Singh, "Comparative Study of rainfall forecasting models," *New York Sci. J.*, pp. 115-120, 2011.
- [18] J. Abbot and J. Marohasy, "Application of Artificial Neural Networks to rainfall forecasting in Queensland, Australia," *Advances in Atmospheric Sci.*, vol. 29, no. 4, pp. 717-730, 2012.
- [19] A. Kumar, A. Kumar, R. Ranjan, and S. Kumar, "A rainfall prediction model using artificial neural network," *Control and Syst. Graduate Research Colloq. (ICSGRC)*, pp. 82-87, 2012.
- [20] R. R. Deshpande, "On the rainfall time series prediction using Multilayer Perceptron Artificial Neural Network," *Int. J. of Emerging Technology and Advanced Eng.*, vol. 2, no. 1, pp. 148-153, 2012.
- [21] Soo-Yeon Ji, Sharad Sharma, Byunggu Yu, Dong Hyun Jeong, "Designing a Rule-Based Hourly Rainfall Prediction Model", *IEEE IRI* 2012, August – 2012.
- [22] G. Shrivastava, S. Karmakar, and M. K. Kowar, "BPN model for long range forecast of monsoon rainfall over a very small geographical region and its verification for 2012," *Geofizika*, vol. 30, no. 2, pp. 155-172, 2013.
- [23] C. L. Wu and K. W. Chau, "Prediction of rainfall time series using modular soft computing methods," *Eng. Applicat. of Artificial Intell.*, vol. 26, no. 3, pp. 997-1007, 2013.
- [24] S. K. Nanda, D. P. Tripathy, S. K. Nayak, and S. Mohapatra, "Prediction of rainfall in India using Artificial Neural Network (ANN) models," *Int. J. of Intell. Syst. and Applicat.*, vol. 5, no. 12, pp. 1-22, 2013.
- [25] A. R. Naik and S. K. Pathan, "Indian monsoon rainfall Classification and Prediction using Robust Back Propagation Artificial Neural Network," *Int. J. of Emerging Technology and Advanced Eng.*, vol. 3, no. 11, pp. 99-101, 2013.
- [26] Priya, Shilpi, Vashistha and V. Singh, "Time Series Analysis of Forecasting Indian Rainfall," *Int. J. of Innovations & Advancement in Comput. Sci.*, vol. 3, no. 1, pp. 66-69, 2014.
- [27] V. K. Dabhi and S. Chaudhary, "Hybrid Wavelet-Postfix-GP model for rainfall prediction of Anand region of India," *Advances in Artificial Intell.*, pp. 1-11, 2014.
- [28] Pinky Saikia Dutta, Hitesh Tahbiller, "Prediction Of Rainfall Using Data mining Technique Over Assam", *Indian Journal of Computer Science and Engineering (IJCSE)*, Vol. 5 No.2 Apr May 2014.
- [29] Pankratz, A., *Forecasting With Univariate Box-Jenkins Models Concepts and Cases*. John Wiley Sons, Inc. New York, pp: 414.
- [30] M. T.Hagan, H.B.Demuth and M.Beale, *Neural Network Design Thomson Asia Pte. Ltd*, Singapore, 2002.
- [31] Bose NK, Liang P (1998) *Neural network fundamentals with graphs, algorithms, and applications*. Tata McGraw-Hill, New Delhi.
- [32] Weigend A (1994) *An overfitting and the effective number of hidden units*. Lawrence Erlbaum Associates, Hillsdale, p 335342.
- [33] Sivanandam SN, Deepa SN (2007) *Principles of soft computing*. Wiley India (P) Ltd., New Delhi.
- [34] Beale MH, Hagan MT, Demuth HB (2010) *Neural network toolbox 7. The Math- Works, Inc., Natick*.

- [35] Haykin S (1999) Neural networks, a comprehensive foundation. Macmillan College Publishing Co., New York.
- [36] <https://en.wikipedia.org/wiki/Recurrent-neural-network>
- [37] S. Haykin, 1999: Neural Networks- A Comprehensive Foundation. Addison Wesley Longman.
- [38] T. Kohonen, (1990), The self organizing map. Proceedings of IEEE, 78(9), 1464-1478.
- [39] Singh, P. and Borah, B., 2013. Indian summer monsoon rainfall prediction using artificial neural network. 27(7), pp.1585-1599.
- [40] <http://www.mdpi.com/2073-4433/5/2/454/htm>
- [41] <https://en.wikibooks.org/wiki/Artificial-Neural-Networks/Recurrent-Network>