NYselections BDD Automation - Test Cases Summary

Document of all automation work completed so far for the Playwright + Cucumber BDD framework.

Framework Overview

Item	Detail
Stack	Playwright + Cucumber (BDD-only)
Pattern	Feature → Step Definitions → Page Objects
App under test	NYselections Lightning (Salesforce)
Reporting	Allure + console / JSON side reports for some flows
Auth	Salesforce login via env credentials + optional saved session (`npm run auth:save`)

Architecture

```
features/*.feature          → WHAT (business scenarios)
features/step-definitions/  → GLUE (Cucumber steps)
pages/*.ts                  → HOW (locators & UI actions)
```

How to Run

Command	Purpose
`npm run bdd`	Run all scenarios
`npm run bdd:tags "@TagName"`	Run by tag (e.g. `@DuplicateTransaction`)
`npm run bdd:headed`	Run headed (visible browser)
`npm run report`	Generate & open Allure report

Test Inventory

Total: **10 features**, **11 scenario examples** (Empty Error Message has 2 Examples rows).

#	Feature	Tag(s)	Case #	Status
1	Framework smoke check	`@Sanity` `@Smoke`	N/A (example.com)	Done
2	NYselections Auditor1	`@Auditor1` `@End_to_End`	00120464	Done
3	Duplicate Transaction	`@DuplicateTransaction`	00120877	Done
4	Repeat Contributor Code	`@RepeatContributorCode`	00120859	Done
5	Clear Shared Contributor Code	`@ClearSharedContributorCode`	00120859	Done

6	Is District (No)	`@IsDistrict`	00120857	Done
7	Is District Yes	`@IsDistrictYes`	00120877	Done
8	Verification Agree	`@VerificationAgree`	00120861	Done
9	Verification Disagree	`@VerificationDisagree`	00120861	Done
10	Empty Error Message	`@EmptyErrorMessage`	00120861	Done

All NYselections features also carry `@Regression` `@NYselections` `@End_to_End`.

Feature Details

1. Framework smoke check

File: `features/smoke.feature`

Verifies the BDD framework can launch a browser and open a page (example.com). Not an app business test.

Scenario

- Open application home page
- Assert title, heading, and URL

---

2. NYselections Auditor1

File: `features/auditor1.feature`
Page Object: `pages/Auditor1Page.ts`
Steps: `features/step-definitions/auditor1.steps.ts`

Log into Lightning, open a case, select party, set Primary Auditor, and complete the Eligibility Dashboard questionnaire (all Yes).

Scenario Outline data

CaseNumber	Party	PrimaryAuditor
00120464	Republican	Udith Racha

Flow

- Login to NYselections Lightning
- Open case
- Select party (if present) → Next (if present)
- Details tab → set Primary Auditor
- Eligibility Dashboard → party again if needed
- Complete eligibility questionnaire answering Yes
- Assert case is visible

---

3. Duplicate Transaction

File: `features/duplicate-transaction.feature`
Page Object: `pages/DuplicateTransactionPage.ts`
Steps: `features/step-definitions/duplicate-transaction.steps.ts`

Search a case, open the duplicate transaction report, clear flags on all flagged rows across pages, Finish so removals persist, refresh, and assert no Flagged rows remain.

Scenario Outline data

CaseNumber
00120877

Flow

- Login → search & open case
- Open duplicate transaction report
- Clear duplicate flags on all flagged transactions (all pages)
- Next → close dialog
- Assert case visible, report affected transaction numbers
- Assert no flagged transactions remain

---

4. Repeat Contributor Code

File: `features/repeat-contributor-code.feature`
Page Object: `pages/RepeatContributorCodePage.ts`
Steps: `features/step-definitions/repeat-contributor-code.steps.ts`

Rows that share the same Contributor Full Name must share the same Repeat Contributor Code. Mixed codes are aligned via the edit icon and save.

Scenario Outline data

CaseNumber
00120859

Side report

- Console output
- `reports/repeat-contributor-code-changes.json` (Contributor Full Name, Old Code, New Code)

Flow

- Login → search & open case
- Open Repeat Contributor Report
- Align codes for duplicate contributor names
- Assert change report & all duplicate names share the same code

---

5. Clear Shared Repeat Contributor Code

File: `features/clear-shared-contributor-code.feature`
Page Object: `pages/RepeatContributorCodePage.ts` (shared)

Steps: `features/step-definitions/clear-shared-contributor-code.steps.ts`

A Repeat Contributor Code that appears on different Contributor Full Name groups must be cleared from minority name group(s). Majority name keeps the code. Scans every report page.

Scenario Outline data

CaseNumber
00120859

Side report

- Console output
- `reports/clear-shared-contributor-code-changes.json`

Flow

- Login → search & open case
- Open Repeat Contributor Report
- Clear codes shared across different names
- Assert change report & no code shared across different names

---

6. Is District (set to No)

File: `features/isdistrict.feature`
Page Object: `pages/IsDistrictPage.ts`
Steps: `features/step-definitions/isdistrict.steps.ts`

Open Audit Matching Claim Data, set empty In District Confirmed values to **No** on every report page, Save, and report transaction numbers marked No.

Scenario Outline data

CaseNumber
00120857

Flow

- Login → search & open case
- Open Audit Matching Claim Data
- Set empty In District Confirmed → No (all pages)
- Save → assert success
- Report transaction numbers marked No

---

7. Is District Yes

File: `features/isdistrict-yes.feature`
Page Object: `pages/IsDistrictPage.ts` (shared)
Steps: `features/step-definitions/isdistrict.steps.ts` (shared)

Same flow as Is District, but empty values are set to **Yes**.

Scenario Outline data

CaseNumber
00120877

---

8. Verification Agree

File: `features/verification-agree.feature`
Page Object: `pages/VerificationAgreePage.ts`
Steps: `features/step-definitions/verification-agree.steps.ts`

Open Random Sampling Records, set every empty Verifier Status to **Agree** on all pages, Save, confirm success, and report transaction numbers.

Scenario Outline data

CaseNumber
00120861

---

9. Verification Disagree

File: `features/verification-disagree.feature`
Page Object: `pages/VerificationAgreePage.ts` (shared)
Steps: `features/step-definitions/verification-agree.steps.ts` (shared Agree/Disagree)

Same flow as Verification Agree, but empty Verifier Status is set to **Disagree**.

Scenario Outline data

CaseNumber
00120861

---

10. Empty Error Message

File: `features/empty-error-message.feature`
Page Objects: `pages/EmptyErrorMessagePage.ts` + `pages/VerificationAgreePage.ts`
Steps: `features/step-definitions/empty-error-message.steps.ts`

When Random Sampling Records still has empty Verifier Status fields, Accept or Reject from Approval History must show the incomplete review error. Covers both approval actions via Examples.

Scenario Outline data

CaseNumber	ApprovalAction	Comments
00120861	Reject	test
00120861	Accept	test

Flow

- Login → search & open case
- Open Random Sampling Records
- Verify empty Verifier Status fields exist (precondition)
- Close Random Sampling Records
- Choose Accept or Reject from Approval History with comments
- Assert incomplete review error message
- Cancel & close approval dialog
- Report all empty Verifier Status transaction numbers

Page Object Map

Page Object	Used by features
`BasePage.ts`	Shared base (goto, waits)
`HomePage.ts`	Smoke
`SalesforceLoginPage.ts`	All NYselections login
`Auditor1Page.ts`	Auditor1
`DuplicateTransactionPage.ts`	Duplicate Transaction (also provides shared case search helpers)
`RepeatContributorCodePage.ts`	Repeat Contributor Code, Clear Shared Contributor Code
`IsDistrictPage.ts`	Is District, Is District Yes
`VerificationAgreePage.ts`	Verification Agree, Verification Disagree, Empty Error Message (empty-status scan)
`EmptyErrorMessagePage.ts`	Empty Error Message (Approval History actions)

Supporting Files

Path	Role
`features/step-definitions/world.ts`	Cucumber World (browser, page, testData)
`features/step-definitions/hooks.ts`	Before/After hooks
`features/step-definitions/common.steps.ts`	Shared steps (e.g. login)
`cucumber.js`	Cucumber config
`scripts/save-sf-session.ts`	Persist Salesforce session

Conventions Followed

- BDD-only — no Playwright `.spec.ts` for coverage
- Steps call Page Object methods only (no raw selectors in steps)
- Prefer `getByRole` / `getByLabel` / `getByText` ; XPath with `normalize-space()` when needed

- Fluent waits; avoid hard `waitForTimeout()`
- Scenario Outline + Examples for case-driven data
- Shared Page Objects reused across related Agree/Disagree and Yes/No variants

---

Suggested Tag Runs

Goal	Command
Smoke only	`npm run bdd:tags "@Smoke"`
All regression	`npm run bdd:tags "@Regression"`
One flow	`npm run bdd:tags "@VerificationAgree"`
All district flows	`npm run bdd:tags "@IsDistrict"`
Verification family	`npm run bdd:tags "@VerificationAgree or @VerificationDisagree or @EmptyErrorMessage"`

Notes

- Case numbers in Examples are environment-specific and may need updating if data is refreshed.
- Empty Error Message depends on case **00120861** still having at least one empty Verifier Status.
- Verification Agree / Disagree mutate the same Random Sampling Records area on the same case — run order / data state matters.
- Contributor-code scenarios write JSON change reports under `reports/`.