MySQL 8.0 Command Line Cli

```
mysql> -- Q1: Write a query to list the number of jobs available in the employees table.
mysql> select count(distinct job_id) as no_of_jobs from employees;
+-------------+
| no_of_jobs |
+-------------+
|         14 |
+-------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:38 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q2: Write a query to get the total salaries payable to employees.
mysql> select sum(salary) as total_salary from employees;
+--------------+
| total_salary |
+--------------+
|    286316.00 |
+--------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:38 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q3: Write a query to get the minimum salary from employees table.
mysql> select min(salary) as minimum_salary from employees;
+----------------+
| minimum_salary |
+----------------+
|        2200.00 |
+----------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:38 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q4: Write a query to get the maximum salary of an employee working as a Programmer.
mysql> select max(salary) as maximum_salary from employees where job_id = 'IT_PROG';
+----------------+
| maximum_salary |
+----------------+
|        9000.00 |
+----------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:38 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q5: Write a query to get the average salary and number of employees working the department 90.
mysql> select avg(salary) as average_salary, count(*) as no_of_employees from employees where department_id = 90;
+----------------+-----------------+
| average_salary | no_of_employees |
+----------------+-----------------+
|   19333.333333 |               3 |
+----------------+-----------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:38 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q6: Write a query to get the highest, lowest, sum, and average salary of all employees.
mysql> select max(salary) as highest_salary, min(salary) as lowest_salary, sum(salary) as total_salary, avg(salary) as average_salary from employees;
+----------------+---------------+--------------+----------------+
| highest_salary | lowest_salary | total_salary | average_salary |
+----------------+---------------+--------------+----------------+
|       24000.00 |       2200.00 |    286316.00 |    9236.000000 |
+----------------+---------------+--------------+----------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q7: Write a query to get the number of employees with the same job.
mysql> select job_id, count(*) as no_of_employees from employees group by job_id;
+------------+-----------------+
| job_id     | no_of_employees |
+------------+-----------------+
| AC_ACCOUNT |               1 |
| AC_MGR     |               1 |
| AD_ASST    |               1 |
| AD_PRES    |               1 |
| AD_VP      |               2 |
| FI_ACCOUNT |               4 |
| FI_MGR     |               1 |
| IT_PROG    |               3 |
| MK_MAN     |               1 |
| MK_REP     |               1 |
| SA_MAN     |               3 |
| SA_REP     |               6 |
| ST_CLERK   |               4 |
| ST_MAN     |               2 |
+------------+-----------------+
14 rows in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q8: Write a query to get the difference between the highest and lowest salaries.
mysql> select max(salary) - min(salary) as salary_difference from employees;
+-------------------+
| salary_difference |
+-------------------+
|          21800.00 |
+-------------------+
1 row in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q9: Write a query to find the manager ID and the salary of the lowest-paid employee for that manager.
mysql> select manager_id, min(salary) as lowest_salary from employees where manager_id is not null group by manager_id;
+------------+---------------+
| manager_id | lowest_salary |
+------------+---------------+
|        100 |       8000.00 |
|        101 |       4400.00 |
|        102 |       9000.00 |
|        103 |       4800.00 |
|        108 |       7700.00 |
|        120 |       2700.00 |
|        121 |       2200.00 |
|        145 |      10000.00 |
|        146 |       9000.00 |
|        147 |       6400.00 |
|        201 |       6000.00 |
|        205 |       8300.00 |
+------------+---------------+
12 rows in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q10: Write a query to get the department ID and the total salary payable in each department.
mysql> select department_id, sum(salary) as total_salary from employees group by department_id;
+---------------+--------------+
| department_id | total_salary |
+---------------+--------------+
|          NULL |      7000.00 |
|            10 |      4400.00 |
|            20 |     19000.00 |
|            50 |     26700.00 |
|            60 |     19800.00 |
|            80 |     86400.00 |
|            90 |     58000.00 |
|           100 |     44708.00 |
|           110 |     20308.00 |
+---------------+--------------+
9 rows in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q11: Write a query to get the average salary for each job ID excluding programmer.
mysql> select job_id, avg(salary) as average_salary from employees where job_id <> 'IT_PROG' group by job_id;
+------------+----------------+
| job_id     | average_salary |
+------------+----------------+
| AC_ACCOUNT |    8300.000000 |
| AC_MGR     |   12008.000000 |
| AD_ASST    |    4400.000000 |
| AD_PRES    |   24000.000000 |
| AD_VP      |   17000.000000 |
| FI_ACCOUNT |    8175.000000 |
| FI_MGR     |   12008.000000 |
| MK_MAN     |   13000.000000 |
| MK_REP     |    6000.000000 |
| SA_MAN     |   13166.666667 |
| SA_REP     |    8983.333333 |
| ST_CLERK   |    2625.000000 |
| ST_MAN     |    8100.000000 |
+------------+----------------+
13 rows in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q12: Write a query to get the total salary, maximum, minimum, average salary of employees (job ID wise), for department ID 90 only.
mysql> select job_id, sum(salary) as total_salary, max(salary) as maximum_salary, min(salary) as minimum_salary, avg(salary) as average_salary from employee
s where department_id = 90 group by job_id;
+---------+--------------+----------------+----------------+----------------+
| job_id  | total_salary | maximum_salary | minimum_salary | average_salary |
+---------+--------------+----------------+----------------+----------------+
| AD_PRES |     24000.00 |       24000.00 |       24000.00 |   24000.000000 |
| AD_VP   |     34000.00 |       17000.00 |       17000.00 |   17000.000000 |
+---------+--------------+----------------+----------------+----------------+
2 rows in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q13: Write a query to get the job ID and maximum salary of the employees where maximum salary is greater than or equal to $4000.
mysql> select job_id, max(salary) as maximum_salary from employees group by job_id having max(salary) >= 4000;
+------------+----------------+
| job_id     | maximum_salary |
+------------+----------------+
| AC_ACCOUNT |        8300.00 |
| AC_MGR     |       12008.00 |
| AD_ASST    |        4400.00 |
| AD_PRES    |       24000.00 |
| AD_VP      |       17000.00 |
| FI_ACCOUNT |        9000.00 |
| FI_MGR     |       12008.00 |
| IT_PROG    |        9000.00 |
| MK_MAN     |       13000.00 |
| MK_REP     |        6000.00 |
| SA_MAN     |       14000.00 |
| SA_REP     |       11000.00 |
| ST_MAN     |        8200.00 |
+------------+----------------+
13 rows in set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026

MySQL 8.0 Command Line Cli

```
mysql> -- Q14: Write a query to get the average salary for all departments employing more than 10 employees.
mysql> select department_id, avg(salary) as average_salary from employees group by department_id having count(*) > 10;
Empty set (0.00 sec)

mysql>
```

Search
ENG
IN
10:39 PM
31-10-2026