

238 Webster Street #3 · Worcester, MA 01603
(774) 578-7186 / (508) 579-0762 · greenideainsulation@gmail.com

GreenFiber SANCTUARY

CELLULOSE INSULATION

R-3.7
PER INCH
(SETTLED)

85%
RECYCLED
CONTENT

25 lb
BAG
SIZE

60%
SOUND POWER
REDUCTION

PRODUCT DESCRIPTION

SANCTUARY by GreenFiber is an all-in-one cellulose insulation that can be blow-in, spray-applied, or dense-packed. It installs easily over existing insulation and, unlike batt or roll alternatives, is engineered to fill gaps, voids, and hard-to-reach spaces — forming a dense barrier that reduces air infiltration to boost thermal performance and reduce sound. Made with 85% recycled materials and free from harmful additives.

INSTALLATION METHODS

Blow-In (Loose Fill)
Open attic floors and accessible horizontal cavities. Fast, even coverage to a target settled depth.

Dense-Pack
Enclosed wall cavities, floors, and slopes. Blown at higher density to resist settling and seal air paths.

Spray-Applied
Open wall cavities in new construction. Adheres in place before drywall is installed.

THERMAL PERFORMANCE & COVERAGE

TARGET R-VALUE	APPROX. SETTLED DEPTH	TYPICAL USE
R-30	~8.1 in	Attic (milder zones)
R-38	~10.3 in	Attic (common code minimum)
R-49	~13.3 in	Attic (DOE zones 5–7, incl. Massachusetts)
R-60	~16.3 in	Attic (high-performance / deep energy retrofit)

Manufacturer coverage: 27.4 sq. ft. per 25 lb bag at R-30. Depths shown are settled thickness for estimating purposes. Cellulose settles roughly 7% from the initial blown depth; coverage charts already account for this, so blow slightly deeper than the settled target.

KEY PERFORMANCE ATTRIBUTES

- **Air sealing.** Dense fiber structure fills gaps and voids, slowing air movement far better than loose batts.
- **Sound control.** In field testing on identical 2x4 exterior walls, GreenFiber R-13 stabilized spray-applied insulation outperformed R-15 unfaced fiberglass batts by 4 NIC rating points — equal to a 60% reduction in sound power.
- **Fire resistance.** Borate-treated for flame resistance; cellulose is a Class 1 / Class A fire-rated material when tested per ASTM E84.
- **Recycled content.** 85% recycled material — one of the lowest environmental footprints of any insulation.
- **Pest and mold resistance.** Borate treatment also resists mold growth and discourages pests.

STANDARDS & COMPLIANCE

STANDARD	WHAT IT COVERS
ASTM C739	Specification for cellulosic fiber loose-fill thermal insulation (manufacturing requirements and settled density)
ASTM C518	Heat flow meter test used to determine R-value per inch for labeling
ASTM E84	Surface burning characteristics (flame spread and smoke developed)
FTC R-Value Rule (16 CFR Part 460)	Requires coverage charts to state settled thickness, and both settled and initial depths on the bag label

INSTALLATION REQUIREMENTS

- The installer must meet **both** the minimum number of bags per 1,000 sq. ft. and the minimum installed thickness to achieve the stated R-value.
- Coverage charts are based on settled thickness and are for estimating only; job conditions, technique, equipment, and settings influence actual coverage.
- Do not exceed the maximum square footage per bag.
- Attics with active roof leaks, fans venting into the attic, or chronic ice damming should have the moisture source corrected before insulating.

WHY GREEN IDEA SPECIFIES CELLULOSE

Cellulose delivers more R-value per inch than blown fiberglass at the same depth, fills irregular framing completely, and adds meaningful sound control — which matters in bedrooms, home offices, and shared walls. For attic retrofits it can often be added over existing insulation without demolition, keeping upgrade costs down.

Note on product line. GreenFiber's current cellulose line includes SANCTUARY and SANCTUARY DEFENSE. Both share the same coverage chart and R-value per inch; DEFENSE adds enhanced pest protection. The specifications in this sheet apply to either product. This sheet summarizes published manufacturer data — always confirm against the coverage chart printed on the bag supplied for your project, and refer to the manufacturer's technical data sheet for complete specifications.