

MHG - GIATA Multilingual Hotel Guide

GIATA GmbH

Andreas Funderich

<andreas.fuenderich@giata.de>

\$Id: ghgml.en.xml 505 2016-11-23 14:10:57Z afue \$

Copyright © 2006 - 2016 GIATA GmbH

Table of Contents

[1. Authentication](#)

[2. Resources](#)

[3. Conversion](#)

[A. Tables](#)

[1. Views](#)

Abstract

This web service is provided as a REST application (REST = REpresentational State Transfer).

The web service and its associated documentation are currently being extended;

1. Authentication

Access to the resources of this web service is password-protected.

Password protection supports HTTP Basic authentication.

The username for authentication consists of the username (usually the first part of the email address before "@") + | (Pipe) + the company name.

Thus access for testing purposes is given using:

Username

testUser|testCompany

Password

testPw

2. Resources

[2.1. List of properties](#)

[2.2. Views to individual properties](#)

[2.3. Helpers](#)

2.1. List of properties

2.1.1. List of individual properties

<http://ghgml.giatamedia.com/webservice/rest/1.0/items/>

The following modifiers can be used and may be added to this URI as a QueryString:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Displays properties last modified after the given date (format: YYYY-MM-DD)

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/items/?country=ES>

<http://ghgml.giatamedia.com/webservice/rest/1.0/items/?changedSince=2006-09-01>

<http://ghgml.giatamedia.com/webservice/rest/1.0/items/?country=ES&changedSince=2006-09-01>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xlink="http://www.w3.org/1999/xlink">
```

```
  <items changedSince="2006-09-01" country="ES">
```

```
    <item giataId="2272" lastUpdate="2006-09-04T17:13:46+02:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/items/2272" />
```

```
    <item giataId="2275" lastUpdate="2006-09-04T17:13:46+02:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/items/2275" />
```

<!-- ... -->

</items>

</result>

The node <items> in <result> may contain the following attributes depending on the modifiers used in the request:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Indicates that properties were last modified after the given date (format: YYYY-MM-DD)

Each node <item> in <result><items> has the following attributes:

giataId

GIATA-ID

lastUpdate

Time of the last modification according to ISO 8601

xlink:href

URI representing the individual view of this property

2.1.2. List of all properties, which have texts in a given language

http://ghgml.giatamedia.com/webservice/rest/1.0/texts/*language*/

language

The language as a 2-letter-code according to ISO 639-1

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/>

The following modifiers can be used and may be added to this URI as a QueryString:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Displays properties last modified after the given date (format: YYYY-MM-DD)

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/?country=ES>

<http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/?changedSince=2006-09-01>

<http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/?country=ES&changedSince=2006-09-01>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xlink="http://www.w3.org/1999/xlink">
```

```
  <items lang="en" changedSince="2006-09-01" country="ES">
```

```
    <item giataId="2687" lastUpdate="2006-09-04T17:13:46+02:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/2687" />
```

```
    <item giataId="3159" lastUpdate="2006-09-04T17:13:21+02:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/3159" />
```

```
  <!-- ... -->
```

```
</items>
```

```
</result>
```

The node <items> in <result> has the following attribute:

lang

The language as a 2-letter-code according to ISO 639-1

The node <items> in <result> may contain the following attributes depending on the modifiers used in the request:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Indicates that properties were last modified after the given date (format: YYYY-MM-DD)

Each Node <item> in <result><items> has the following attributes:

giataId

GIATA-ID

lastUpdate

The time of the last modification according to ISO 8601

xlink:href

URI representing the texts in the given language for this property.

2.1.3. List of all properties with images

<http://ghgml.giatamedia.com/webservice/rest/1.0/images/>

The following modifiers can be used and may be added to this URI as a QueryString:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Displays properties last modified after the given date (format: YYYY-MM-DD)

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/images/?country=ES>

<http://ghgml.giatamedia.com/webservice/rest/1.0/images/?changedSince=2006-09-01>

<http://ghgml.giatamedia.com/webservice/rest/1.0/images/?country=ES&changedSince=2006-09-01>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xlink="http://www.w3.org/1999/xlink">
```

```
  <items changedSince="2006-09-01" country="ES">
```

```
    <item giataId="2275" lastUpdate="2006-08-18T17:06:38+02:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275" />
```

```
    <item giataId="2284" lastUpdate="2006-08-18T17:06:38+02:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2284" />
```

```
  <!-- ... -->
```

```
</items>
```

```
</result>
```

The node <items> in <result> may contain the following attributes depending on the modifiers used in the request:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Indicates that properties were last modified after the given date (format: YYYY-MM-DD)

Each node <item> in <result><items> has the following attributes:

giataId

GIATA-ID

lastUpdate

Date of the last modification to a picture of this property according to ISO 8601

xlink:href

URI, representing the List of all images of this property

2.1.4. List of all properties with fact sheets

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/>

The following modifiers can be used and may be added to this URI as a QueryString:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Displays properties last modified after the given date (format: YYYY-MM-DD)

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/?country=ES>

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/?changedSince=2006-09-01>

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/?country=ES&changedSince=2006-09-01>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xlink="http://www.w3.org/1999/xlink">
```

```
  <items changedSince="2006-09-01" country="ES">
```

```
    <item giataId="2275" lastUpdate="2006-12-30T11:41:34+01:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/2275" />
```

```
    <item giataId="2284" lastUpdate="2006-12-30T11:41:34+01:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/2284" />
```

```
  <!-- ... -->
```

```
</items>
```

```
</result>
```

The node <items> in <result> may contain the following attributes depending on the modifiers used in the request:

country

The country as a 2-letter-code according to ISO 3166-1

destination

The ID of the destination in GIATA's database

city

The ID of the city in GIATA's database

changedSince

Indicates that properties were last modified after the given date (format: YYYY-MM-DD)

Each node <item> in <result><items> has the following attributes:

giataId

GIATA-ID

lastUpdate

Date of the last modification to a fact for this property according to ISO 8601

xlink:href

URI, representing the fact sheet for this property

2.1.5. List of several properties with details

When retrieving details (name, address, texts, images) within a list of several properties, you must know the GIATA-IDs for these properties.

Modifiers (such as country or changedSince) are not available.

GIATA-IDs must be sent in a HTTP-POST request.

It depends on the URI to which the request is sent what details are delivered in the response.

Name, address, images

<http://ghgml.giatamedia.com/webService/rest/1.0/items>

([Section 2.1.1, "List of individual properties"](#))

Texts

http://ghgml.giatamedia.com/webService/rest/1.0/texts/*language*

([Section 2.1.2, "List of all properties, which have texts in a given language"](#))

E.g.: <http://ghgml.giatamedia.com/webService/rest/1.0/texts/en>

Images

<http://ghgml.giatamedia.com/webservice/rest/1.0/images>

([Section 2.1.3, "List of all properties with images"](#))

Name, address, texts, images

http://ghgml.giatamedia.com/webservice/rest/1.0/items/*language*

E.g.: <http://ghgml.giatamedia.com/webservice/rest/1.0/items/en>

There are 2 ways to send the HTTP-Post request:

1.

As an URL encoded HTTP-POST, having GIATA-IDs as an array in a variable giataIds.

E.g.:

```
curl -s --basic -u "*user*|*company*:*password*"
      -d "giataIds[]=2275&giataIds[]=2272"
      "*url*"
```

2.

As a HTTP-POST, having the request wrapped in an XML document.

Example for the XML document:

```
<?xml version="1.0" encoding="UTF-8"?>
<giataIds>
  <giataId>2275</giataId>
  <giataId>2272</giataId>
</giataIds>
```

Example for the request:

```
curl -s --basic -u "*user*|*company*:*password*"
      -d "<?xml version=\"1.0\" encoding=\"UTF-
8\"?><giataIds><giataId>2275</giataId><giataId>2272</giataId></giataIds>"
      "*url*"
```

E.g.:

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xlink="http://www.w3.org/1999/xlink"
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/listOfItems.xsd">
  <items>
    <item giataId="2275">
      <!--
      BEGIN name, city, country
      http://ghgml.giatamedia.com/webservice/rest/1.0/items/
      http://ghgml.giatamedia.com/webservice/rest/1.0/items/en
      -->
      <name>Melia Alicante</name>
      <city>San Juan</city>
      <country>ES</country>
      <!--
      END name, city, country
      -->
      <!--
      BEGIN texts
      http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en
      http://ghgml.giatamedia.com/webservice/rest/1.0/items/en
      -->
      <texts>
        <text lastUpdate="2007-04-05T00:10:08+02:00"
          lang="en">
          <sections>
            <section type="100">
              <title>Location</title>
              <para>
```

This attractive beach hotel can be found
just 100 metres from the centre of San
Juans...

</para>

</section>

<section type="101">

<title>Facilities</title>

<para>

Built in 1973, the hotel offers a total
of 1150 rooms, of which 5 are suites 54
are singles and 486 are doubles...

</para>

</section>

<!-- ... -->

</sections>

</text>

</texts>

<!--

END texts

-->

<!--

BEGIN images

<http://ghgml.giatamedia.com/webservice/rest/1.0/images>

<http://ghgml.giatamedia.com/webservice/rest/1.0/items>

<http://ghgml.giatamedia.com/webservice/rest/1.0/items/en>

-->

<images>

<image type="a"

```

lastUpdate="2007-06-05T01:56:10+02:00">
  <sizes>
    <size maxwidth="74" width="74" height="59"
      filesize="4729"
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14662" />
    <size maxwidth="320" width="320" height="256"
      filesize="33044"
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14663" />
    <size maxwidth="800" width="749" height="600"
      filesize="110853"
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14664" />
  </sizes>
</image>
<!-- ... -->
</images>
<!--
END images
-->
</item>
<item giataId="2272">
  <!-- ... -->
</item>
<!-- ... -->
</items>
</result>

```

XML Schema: <http://ghgml.giatamedia.com/xsd/1.0/listOfItems.xsd>

The node <result><items> contains one or more nodes <item>.

You can find the documentation for subsequent nodes within the description of the according resources to single properties:

[Section 2.2.1, "List of resources for an property"](#)

[Section 2.2.2, "Texts for an property in a given language"](#)

[Section 2.2.3, "List of all images for an property"](#)

2.2. Views to individual properties

2.2.1. List of resources for an property

http://ghgml.giatamedia.com/webservice/rest/1.0/items/*GIATA-ID*

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/items/2275>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xmlns:xlink="http://www.w3.org/1999/xlink"
```

```
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/item.xsd">
```

```
  <item giataId="2275">
```

```
    <name>Melia Alicante</name>
```

```
    <street/>
```

```
    <city>San Juan</city>
```

```
    <country>ES</country>
```

```
    <factsheet lastUpdate="2006-12-30T11:41:34+01:00"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/2275" />
```

```
  <texts>
```

```
    <text lastUpdate="2005-10-06T11:55:33+02:00" lang="de"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/texts/de/2275" />
```

```
    <text lastUpdate="2005-12-16T20:40:16+01:00" lang="en"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/2275" />
```

```
<!-- ... -->
```

```

</texts>

<images>

  <image type="a" lastUpdate="2006-08-18T17:06:38+02:00">

    <sizes>

      <size maxwidth="74" width="74" height="59" filesize="4729"

xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14662" />

      <size maxwidth="320" width="320" height="256" filesize="33044"

xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14663" />

      <size maxwidth="800" width="749" height="600" filesize="110853"

xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14664" />

    </sizes>

  </image>

  <image type="l" lastUpdate="2006-08-18T17:06:38+02:00">

    <sizes>

      <size maxwidth="74" width="74" height="42" filesize="3617"

xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14665" />

      <!-- ... -->

    </sizes>

  </image>

  <!-- ... -->

</images>

</item>

</result>

```

XML Schema: <http://ghgml.giatamedia.com/xsd/1.0/item.xsd>

The node <result><item> has the following nodes:

name

Offer name

street

empty

city

City

country

The country as a 2-letter-code according to ISO 3166-1

factsheet

The attribute `xlink:href` contains the URI representing the fact sheet for this property.

Texts

Contains one or more nodes `<text>` with attributes `lang` representing the language and `xlink:href` representing the URI of texts for this property in this language.

images

Contains one or more node of type `<image>` with attributes `type` representing the aspect and `lastUpdate` indicating the time of the last modification.

Each node `<image><sizes>` contains one or more nodes `<size>` with attributes `maxwidth` for the maximum width (currently 74, 320, 800), `width` and `height` for the actual measures of the picture, furthermore an attribute `xlink:href` representing the URI of the image file.

2.2.2. Texts for an property in a given language

http://ghgml.giatamedia.com/webservice/rest/1.0/texts/*language*/*GIATA-ID*

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/texts/en/2275>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/itemText.xsd">
```

```
  <item giataId="2275">
```

```
    <text>
```

```

<text lastUpdate="2005-12-16T20:40:16+01:00" lang="en">
  <sections>
    <section type="100">
      <title>Location</title>
      <para>
        This attractive beach hotel...
      </para>
    </section>
    <section type="101">
      <title>Facilities</title>
      <para>
        Built in 1973, the hotel offers a total of
        1150 rooms...
      </para>
    </section>
    <!-- ... -->
  </sections>
</text>
</texts>
</item>
</result>

```

XML Schema: <http://ghgml.giatamedia.com/xsd/1.0/itemText.xsd>

Each <result><item><text><text><section> contains one or more nodes <section>:

Each node <section> represents a piece of information and contains two nodes:

Title

Title

para

Body of text

The value of the attribute type represents the kind of information and can be used to determine the use of customised titles.

2.2.3. List of all images for an property

http://ghgml.giatamedia.com/webservice/rest/1.0/images/*GIATA-ID*

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xmlns:xlink="http://www.w3.org/1999/xlink"
```

```
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/itemImage.xsd">
```

```
  <item giataId="2275">
```

```
    <images>
```

```
      <image type="a" lastUpdate="2006-08-18T17:06:38+02:00">
```

```
        <sizes>
```

```
          <size maxWidth="74" width="74" height="59" filesize="4729"
```

```
            xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14662" />
```

```
          <size maxWidth="320" width="320" height="256" filesize="33044"
```

```
            xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14663" />
```

```
          <size maxWidth="800" width="749" height="600" filesize="110853"
```

```
            xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/images/2275/14664" />
```

```
        </sizes>
```

```
      </image>
```

```
    <!-- ... -->
```

```
  </images>
```

```
</item>
```

```
</result>
```

XML Schema: <http://ghgml.giatamedia.com/xsd/1.0/itemImage.xsd>

The node `<result><item><images>` contains one or more nodes `<image>`:

Each node `<image>` has the attributes `type` representing the aspect and `lastUpdate` indicating the time of the last modification.

Each node `<image>` contains one or more nodes `<sizes><size>` with attributes `maxwidth` for the maximum width (currently 74, 320, 800), `width` and `height` for the actual measures of the picture, furthermore an attribute `xlink:href` representing the URI of the image file.

2.2.4. Fact sheet for an property

http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/*GIATA-ID*

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheets/3183>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/itemFactSheet.xsd">
```

```
  <item giataId="2817">
```

```
    <name>Orquidea Bahia Feliz</name>
```

```
    <street/>
```

```
    <city>Bahia Feliz</city>
```

```
    <country>ES</country>
```

```
    <factsheet lastUpdate="2006-12-30T11:41:34+01:00">
```

```
      <sections>
```

```
        <section type="1001" name="object_information">
```

```
          <facts>
```

```
            <fact id="3" name="hotel_chain"
```

```
              typeHint="string">
```

```
                <value>HOTET</value>
```

```
            </fact>
```

```
            <fact id="6" name="postcode"
```

```
        typeHint="string">
        <value>35107</value>
    </fact>
    <fact id="8" name="phone_reservation"
        typeHint="string">
        <value>928157240</value>
    </fact>
    <!-- ... -->
</facts>
</section>
<!-- ... -->
<section type="1006" name="beach">
    <facts>
        <fact id="59" name="beach_sandy"
            typeHint="bool">
            <value>true</value>
        </fact>
        <fact id="62" name="beach_sunloungers"
            typeHint="bool">
            <value fee="true">true</value>
        </fact>
        <!-- ... -->
    </facts>
</section>
<!-- ... -->
<section type="1011" name="distances">
    <facts>
        <fact id="1001" name="dist_city_centre"
```

```

        typeHint="int">
        <value name="distance" unit="m">700</value>
    </fact>
    <fact id="1002" name="dist_tourist_centre"
        typeHint="int">
        <value name="distance" unit="m">4000</value>
    </fact>
    <!-- ... -->
</facts>
</section>

```

```

    </sections>
</factsheet>
</item>
</result>

```

XML Schema: <http://ghgml.giatamedia.com/xsd/1.0/itemFactSheet.xsd>

The node <result><item> has the following nodes:

name

Offer name

street

empty

city

City

country

The country as a 2-letter-code according to ISO 3166-1

factsheet

The fact sheet for this property with an attribute lastUpdate indicating the time of the last modification.

Contains one node of type <sections> with one or more nodes of type <section>.

Each node of type <section> represents a group of facts and contains the following attributes:

type

A constant integer value to identify the group of facts, see fact definitions

name

The name of the group of facts, see fact definitions

Each node of type <section> contains one node of type <facts> with several nodes of type <fact>

Each node of type <fact> represents one fact and contains the following attributes:

id

A constant integer value to identify the fact, see fact definitions

name

The name of the fact, see fact definitions

typeHint

Indicates the type of the values of the fact

Possible values:

bool

int

float

string

Each node of type <fact> contains one or more nodes of type <value> representing the values of the fact.

Possible attributes:

fee

Indicates if a fee is applicable

dummy

Indicates the value as a test value which may differ from the actual value

name

Used to identify the value when a fact has more than one value

unit

Indicates the unit in which the value is given when not deduced from the fact

Possible values:

m: meters

min: minutes

2.3. Helpers

2.3.1. Fact Definitions

2.3.1.1. Listing of languages in which translations of fact definitions are available

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xlink="http://www.w3.org/1999/xlink">
```

```
  <languages>
```

```
    <!-- ... -->
```

```
    <factdefinitions lang="de"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/de"
    />
```

```
    <factdefinitions lang="en"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/en"
    />
```

```
    <factdefinitions lang="en-US"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/en-
      US" />
```

```
    <factdefinitions lang="es"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/es"
    />
```

```
<factdefinitions lang="es-419"
```

```
xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/es-419" />
```

```
<!-- ... -->
```

```
<factdefinitions lang="zh-cmn-Hans"
```

```
xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/zh-cmn-Hans" />
```

```
<!-- ... -->
```

```
</languages>
```

```
</result>
```

The node <result><languages> contains several nodes of type <factdefinitions> with the following attributes:

lang

Language according to ISO 639-1 or RFC 4646 if the language is a variant

xlink:href

URI of the translation of fact definitions in this language

2.3.1.2. Fact definitions and translations in a given language

http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/*language*/

language

Language according to ISO 639-1 or RFC 4646 if the language is a variant

E.g. English:

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/en>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result>
```

```
<factdefinitions lang="en">
```

```
<sections>
```

```
<section type="1001" name="object_information">
```

```
<title>Object Information</title>

<facts>

  <fact id="3" name="hotel_chain" typeHint="string">

    <title>Hotel Chain</title>

  </fact>

  <fact id="6" name="postcode" typeHint="string">

    <title>Postcode</title>

  </fact>

  <fact id="8" name="phone_reservation"

    typeHint="string">

    <title>Telephone Reservation</title>

  </fact>

  <!-- ... -->

</facts>

</section>

<!-- ... -->

<section type="1006" name="beach">

  <title>Beach</title>

  <facts>

    <fact id="59" name="beach_sandy" typeHint="bool">

      <title>Sandy Beach</title>

    </fact>

    <!-- ... -->

    <fact id="62" name="beach_sunloungers"

      typeHint="bool">

      <title>Sun loungers</title>

    </fact>

    <!-- ... -->
```



```

    </facts>
</section>
<!-- ... -->
<section type="1011" name="distances">
  <title>Distances</title>
  <facts>
    <fact id="1001" name="dist_city_centre" typeHint="int">
      <title>City Centre</title>
    </fact>
    <fact id="1002" name="dist_tourist_centre" typeHint="int">
      <title>Tourist Centre</title>
    </fact>
  <!-- ... -->
</facts>
</section>
</sections>
</factdefinitions>
</result>

```

E.g. German:

<http://ghgml.giatamedia.com/webservice/rest/1.0/factsheetdefinitions/de>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```

<result>
  <factdefinitions lang="de">
    <sections>
      <section type="1001" name="object_information">
        <title>Objekt-Informationen</title>
        <facts>
          <fact id="3" name="hotel_chain" typeHint="string">

```

```
        <title>Hotelkette</title>

    </fact>

    <fact id="6" name="postcode" typeHint="string">

        <title>Post-Code</title>

    </fact>

    <fact id="8" name="phone_reservation"

        typeHint="string">

        <title>Telefon Empfang</title>

    </fact>

    <!-- ... -->

</facts>

</section>

<!-- ... -->

<section type="1006" name="beach">

    <title>Strand</title>

    <facts>

        <fact id="59" name="beach_sandy" typeHint="bool">

            <title>Sandstrand</title>

        </fact>

        <!-- ... -->

        <fact id="62" name="beach_sunloungers"

            typeHint="bool">

            <title>Liegestühle</title>

        </fact>

        <!-- ... -->

    </facts>

</section>

<!-- ... -->
```

```

<section type="1011" name="distances">
  <title>Entfernungen</title>
  <facts>
    <fact id="1001" name="dist_city_centre" typeHint="int">
      <title>Stadtzentrum</title>
    </fact>
    <fact id="1002" name="dist_tourist_centre" typeHint="int">
      <title>Touristenzentrum</title>
    </fact>
    <!-- ... -->
  </facts>
</section>
</sections>
</factdefinitions>
</result>

```

Each node `<result><factsheetdefinitions>` has an attribute `lang` indicating the language and contains one node `<sections>` with several nodes `<section>`.

Each node `<section>` represents a group of facts and contains the following attributes:

type

A constant integer value to identify the group of facts

name

The name of the group of facts

Each node `<section>` contains one node of type `<title>` with the translation of the name of the group of facts.

Each node `<section>` contains one node of type `<facts>` with several nodes of type `<fact>`

Each node `<fact>` represents one fact and contains the following attributes:

id

A constant integer value to identify the fact

name

The name of the fact

typeHint

Indicates the type of the values of the fact

Possible values:

bool

int

float

string

Each node <fact> contains one node of type <title> with the translation of the name of the fact.

2.3.2. Mappings

A special agreement is required. Please contact <service@giata.de>.

2.3.2.1. List of suppliers

<http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xlink="http://www.w3.org/1999/xlink">
```

```
  <mappings>
```

```
    <mapping supplier="hotelbeds"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/hotelbeds" />
```

```
    <mapping supplier="tourico"
```

```
      xlink:href="http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/tourico"
```

```
  />
```

```
  <!-- ... -->
```

```
</mappings>
```

```
</result>
```

The node <result><mappings> contains several nodes <mapping> with the attributes:

supplier

Name of the supplier, whose properties have been matched to GIATA-IDs in MHG

xlink:href

URI of the mapping of GIATA-IDs to codes of the supplier

2.3.2.2. Mapping

http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/*name of supplier*

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/tourico>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/mapping.xsd">
```

```
  <items supplier="tourico">
```

```
    <!-- ... -->
```

```
    <item giataId="1399">
```

```
      <code>
```

```
        <value>1038976</value>
```

```
      </code>
```

```
    </item>
```

```
    <item giataId="1410">
```

```
      <code>
```

```
        <value>13806</value>
```

```
      </code>
```

```
    </item>
```

```
    <item giataId="1411">
```

```
      <code>
```

```
        <value>1035278</value>
```

```
      </code>
```

```
    <code>
```

```
      <value>13797</value>
```

```

        </code>

    </item>

    <!-- ... -->

</items>

</result>

```

XML-Schema: <http://ghgml.giatamedia.com/xsd/1.0/mapping.xsd>

The node <result><items> has an attribute supplier with the name of the supplier and contains several nodes <item>.

Each node <item> has the attribute giataId (GIATA-ID) and contains one or more nodes <code>.

Each node <code> contains one or more nodes <value>. <value> will occur more than once when the code provided by the supplier is split, e.g. into Hotel chain and Hotel ID.

Each node <value> may contain the attribute name, e.g. into Hotel chain or Hotel ID.

2.3.2.3. Mapping for an property

You can retrieve the mapping for an property using the name of the supplier and the code of the property. All known codes of several suppliers ([Section 2.3.2.1, "List of suppliers"](#)) are returned.

http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/*name of supplier*/*code of property*

E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/tourico/1038976>

```

<?xml version="1.0" encoding="UTF-8"?>

<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/mappings.xsd">

  <items supplier="tourico" id="1038976">

    <item giataId="1399">

      <name>Holiday Inn Golden Mile</name>

      <city>Kowloon - Hongkong</city>

      <country>CN</country>

      <code supplier="hotelbeds">

```

```

        <value>69601</value>
    </code>
    <code supplier="tourico">
        <value>1038976</value>
    </code>
    <code supplier="pegs">
        <value name="Chain Code">HI</value>
        <value name="Property Code">HKGKL</value>
    </code>
</item>
</items>
</result>

```

XML-Schema: <http://ghgml.giatamedia.com/xsd/1.0/mappings.xsd>

The node <result><items> has two attributes: supplier with the name of the supplier and id containing the code of the property assigned by this supplier. Furthermore it contains one or more nodes of type <item>.

Each node <item> has the attribute giataId (GIATA-ID) and may contain the nodes <name>, <city>, <street> and <country> identifying the property.

Each node <item> contains one or more nodes <code>.

Each node <code> contains one or more nodes <value>. <value> will occur more than once when the code provided by the supplier is split, e.g. into Hotel chain and Hotel ID.

Each node <value> may contain the attribute name, e.g. into Hotel chain or Hotel ID.

Mapping can also be retrieved using the GIATA-ID, e.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/giata/1399>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/mappings.xsd">
```

```
  <items supplier="giata" id="1399">
```

```
    <item giataId="1399">
```

```

<name>Holiday Inn Golden Mile</name>
<city>Kowloon - Hongkong</city>
<country>CN</country>
<code supplier="hotelbeds">
  <value>69601</value>
</code>
<code supplier="tourico">
  <value>1038976</value>
</code>
<code supplier="pegs">
  <value name="Chain Code">HI</value>
  <value name="Property Code">HKGKL</value>
</code>
</item>
</items>
</result>

```

In some cases a request will not produce a result.

This could be because your request was made up of a compound code.

In this case you should concatenate the various components (e.g. hotel chain and hotel code or country code, destination code and hotel code) without spaces, hyphens or other separators. E.g.:

<http://ghgml.giatamedia.com/webservice/rest/1.0/mappings/pegs/HIHKGKL>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```

<result xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://ghgml.giatamedia.com/xsd/1.0/mappings.xsd">
  <items supplier="pegs" id="HIHKGKL">
    <item giataId="1399">
      <name>Holiday Inn Golden Mile</name>
      <city>Kowloon - Hongkong</city>

```



```

<country>CN</country>

<code supplier="hotelbeds">
  <value>69601</value>
</code>

<code supplier="tourico">
  <value>1038976</value>
</code>

<code supplier="pegs">
  <value name="Chain Code">HI</value>
  <value name="Property Code">HKGKL</value>
</code>
</item>
</items>
</result>

```

3. Conversion

For the integration a gif file to inform GIATA about bookings made on the customer's site (§7.a of the Licensing Agreement) sample code is provided by GIATA.

A. Tables

1. Views

Type	Views
a	View of exterior
ba	Bar
f	Sport/ leisure
k	Conference facilities
l	Lobby
p	Pool
r	Restaurant

s	Beach
t	Terrace
w	Accommodation

Gesellschaft zur Entwicklung und Vermarktung interaktiver Tourismusanwendungen
mbH

www.giata.de