


# **REGULARIZED SPATIOTEMPORAL DECONVOLUTION OF fMRI DATA USING GRAY-MATTER CONSTRAINED TOTAL VARIATION**

Younes Farouj, F. Işık Karahanoğlu and Dimitri Van De Ville

**IEEE International Symposium on Biomedical Imaging  
Melbourne, April 20, 2017**

# In just one slide




The observed signal  $\mathbf{y}$  ( $3D+t$ ) is a noisy version of the BOLD response  $\mathbf{x}(t)$  (activity related signal):

$$\mathbf{y} = \mathbf{x} + \varepsilon.$$

Random noise and nuisance components (fluctuations, signal drift, residual errors from motion correction, etc  $\dots$ )  $\Rightarrow$  Very low signal-to-noise ratio.

# In just one slide




The observed signal  $\mathbf{y}$  ( $3D+t$ ) is a noisy version of the BOLD response  $\mathbf{x}(t)$  (activity related signal):

$$\mathbf{y} = \mathbf{x} + \varepsilon.$$

Random noise and nuisance components (fluctuations, signal drift, residual errors from motion correction, etc  $\dots$ )  $\Rightarrow$  Very low signal-to-noise ratio.

**Aim:** Uncover the underlying activity from corrupted observations (preprocessing).

# In just one slide



The observed signal  $\mathbf{y}$  ( $3D+t$ ) is a noisy version of the BOLD response  $\mathbf{x}(t)$  (activity related signal):

$$\mathbf{y} = \mathbf{x} + \varepsilon.$$


Random noise and nuisance components (fluctuations, signal drift, residual errors from motion correction, etc  $\dots$ )  $\Rightarrow$  Very low signal-to-noise ratio.

**Aim:** Uncover the underlying activity from corrupted observations (preprocessing).

$\rightarrow$  Without knowledge about timing, duration or position of neuronal events (spontaneous and resting-state activity).

# BOLD modeling


- Temporal modeling:



$\mathcal{H}$ : Linear Translation Invariant system describing the response of the neuronal system (hemodynamic response function).


# BOLD modeling

- Temporal modeling:




$\mathcal{H}$ : Linear Translation Invariant system describing the response of the neuronal system (hemodynamic response function).

- Spatial modeling: Neurons are not activated individually; clustered localized regions are evoked




# BOLD modeling

- Temporal modeling:



$\mathcal{H}$ : Linear Translation Invariant system describing the response of the neuronal system (hemodynamic response function).

- Spatial modeling: Neurons are not activated individually; clustered localized regions are evoked



→ Use of an adapted total variation.

- Generalized Linear Models (most commonly used) .



# fMRI Analysis

- Generalized Linear Models (most commonly used) .
- Deconvolution techniques (for exploring spontaneous activity / resting-state networks) [Gaudes-Caballero et al. 2011].

# fMRI Analysis

- Generalized Linear Models (most commonly used) .
- Deconvolution techniques (for exploring spontaneous activity / resting-state networks) [Gaudes-Caballero et al. 2011].
- Spatio-temporal deconvolution (More robust: Takes into account spatial and temporal properties)  $\longrightarrow$  **total activation (TA)** of [Karahanoğlu et al. 2013].

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \mathcal{R}_T(\mathbf{x}) + \mathcal{R}_S(\mathbf{x}) \right\}.$$

$\mathcal{R}_T$ : Generalized total variation.

$\mathcal{R}_S$ :  $\ell_2$ -smoothness within regions predefined by an atlas.

- Generalized Linear Models (most commonly used) .
- Deconvolution techniques (for exploring spontaneous activity / resting-state networks) [Gaudes-Caballero et al. 2011].
- Spatio-temporal deconvolution (More robust: Takes into account spatial and temporal properties)  $\rightarrow$  **total activation (TA)** of [Karahanoğlu et al. 2013].

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \mathcal{R}_T(\mathbf{x}) + \mathcal{R}_S(\mathbf{x}) \right\}.$$


$\mathcal{R}_T$ : Generalized total variation.

$\mathcal{R}_S$ :  $\ell_2$ -smoothness within regions predefined by an atlas.

**Our proposal:** Construct a method that is not biased by atlas-based partitioning of the brain (extension of TA).

# Proposed framework

- Temporal regularization  $\mathcal{R}_T$ :




$\Delta_t$ : Temporal finite difference operator.

The activity-inducing signal  $\mathbf{s}$  is block-type  $\implies \Delta_t\{\mathbf{s}\}$  is a sparse (innovation) signal.

This suggests using  $TV\{\mathbf{s}\} = \|\Delta_t\{\mathbf{s}\}\|_1$  as a regularizer.

# Proposed framework

- Temporal regularization  $\mathcal{R}_T$ :



$\Delta_t$ : Temporal finite difference operator.

The activity-inducing signal  $\mathbf{s}$  is block-type  $\Rightarrow \Delta_t\{\mathbf{s}\}$  is a sparse (innovation) signal.


This suggests using  $TV\{\mathbf{s}\} = \|\Delta_t\{\mathbf{s}\}\|_1$  as a regularizer.

The BOLD signal  $\mathbf{x}$  is given as  $\mathbf{s}$  under the action of  $\mathcal{H}$

$\Rightarrow$  Sparsify  $\mathbf{x}$ :  $\Delta_L\{\mathbf{x}\}$ , with  $\Delta_L = \Delta_t\mathcal{H}^{-1}$ .

# Proposed framework

- Temporal regularization  $\mathcal{R}_T$ :



$\Delta_t$ : Temporal finite difference operator.

The activity-inducing signal  $\mathbf{s}$  is block-type  $\implies \Delta_t\{\mathbf{s}\}$  is a sparse (innovation) signal.

This suggests using  $TV\{\mathbf{s}\} = \|\Delta_t\{\mathbf{s}\}\|_1$  as a regularizer.

The BOLD signal  $\mathbf{x}$  is given as  $\mathbf{s}$  under the action of  $\mathcal{H}$

$\implies$  Sparsify  $\mathbf{x}$ :  $\Delta_L\{\mathbf{x}\}$ , with  $\Delta_L = \Delta_t\mathcal{H}^{-1}$ .

$\implies$  Generalized TV (GTV) of [Karahanoğlu et al. 2011]

$\mathcal{H}$  can be elegantly described as a differential operator [Khalidov et al. 2011]:

$$\mathcal{H} = \frac{D - \gamma I}{\prod_{i=1}^4 (D - \alpha_i I)}, \quad D : \text{Temporal derivative.}$$

$\mathcal{H}$  can be elegantly described as a differential operator [Khalidov et al. 2011]:

$$\mathcal{H} = \frac{D - \gamma I}{\prod_{i=1}^4 (D - \alpha_i I)}, \quad D : \text{Temporal derivative.}$$

$\Rightarrow$  Impulse response  $h$  characterized by 4 poles and 1 zeros:

$$\hat{h} = \frac{j\omega - \gamma}{\prod_{i=1}^4 (j\omega - \alpha_i)}$$



$\mathcal{H}$  can be elegantly described as a differential operator [Khalidov et al. 2011]:

$$\mathcal{H} = \frac{D - \gamma I}{\prod_{i=1}^4 (D - \alpha_i I)}, \quad D : \text{Temporal derivative.}$$

$\Rightarrow$  Impulse response  $h$  characterized by 4 poles and 1 zeros:

$$\hat{h} = \frac{j\omega - \gamma}{\prod_{i=1}^4 (j\omega - \alpha_i)}$$

$\rightarrow$  To compute  $\Delta_L = \Delta_t \mathcal{H}^{-1}$ , add a zero at the origin.

$$\Delta_L = \frac{D \prod_{i=1}^4 (D - \alpha_i I)}{D - \gamma I}$$

$\mathcal{H}$  can be elegantly described as a differential operator [Khalidov et al. 2011]:

$$\mathcal{H} = \frac{D - \gamma I}{\prod_{i=1}^4 (D - \alpha_i I)}, \quad D : \text{Temporal derivative.}$$

$\Rightarrow$  Impulse response  $h$  characterized by 4 poles and 1 zeros:

$$\hat{h} = \frac{j\omega - \gamma}{\prod_{i=1}^4 (j\omega - \alpha_i)}$$

$\rightarrow$  To compute  $\Delta_L = \Delta_t \mathcal{H}^{-1}$ , add a zero at the origin.

$$\Delta_L = \frac{D \prod_{i=1}^4 (D - \alpha_i I)}{D - \gamma I}$$

- Remember this regularization should be applied for all voxel:


$$\mathcal{R}_T(\mathbf{x}) = \sum_{v=1}^{N_x} \lambda_T(v) \|\Delta_L\{\mathbf{x}\}[v]\|_1,$$

$N_x$ : number of voxels and  $\lambda_T(v)$  temporal regularization parameter for voxel  $v$ .

- Spatial regularization  $\mathcal{R}_S$ :

We expect that the activation takes place in localized clusters of the brain (gray-matter) with possibly sharp variations between them.

⇒ We restrict a 3D conventional TV-regularization on the gray-matter.




Conceptual 2D-view on gray-matter grid that is derived from the anatomical segmentation.

- Spatial regularization  $\mathcal{R}_S$ :

We expect that the activation takes place in localized clusters of the brain (gray-matter) with possibly sharp variations between them.

⇒ We restrict a 3D conventional TV-regularization on the gray-matter.



Conceptual 2D-view on gray-matter grid that is derived from the anatomical segmentation.


- At a time-point  $t$ : 
$$TV^{GM}\{\mathbf{x}\}[t] = \sum_{v=1}^{N_x} \left( \sum_{u \in \mathcal{N}_v} \left( \mathbf{x}[v, t] - \mathbf{x}[u, t] \right)^2 \right)^{1/2},$$

where  $\mathcal{N}_v$  denotes the set of neighbor voxels around  $v$ .

- Spatial regularization  $\mathcal{R}_S$ :

We expect that the activation takes place in localized clusters of the brain (gray-matter) with possibly sharp variations between them.

⇒ We restrict a 3D conventional TV-regularization on the gray-matter.



Conceptual 2D-view on gray-matter grid that is derived from the anatomical segmentation.

- At a time-point  $t$ : 
$$TV^{GM}\{\mathbf{x}\}[t] = \sum_{v=1}^{N_x} \left( \sum_{u \in \mathcal{N}_v} \left( \mathbf{x}[v, t] - \mathbf{x}[u, t] \right)^2 \right)^{1/2},$$

where  $\mathcal{N}_v$  denotes the set of neighbor voxels around  $v$ .

- Here again, the regularization should be applied for all time-points:

$$\mathcal{R}_S(\mathbf{x}) = \sum_{t=1}^{N_t} \lambda_S(t) TV^{GM}\{\mathbf{x}\}[t], \quad N_t : \text{number of time-points}$$

We have, now, the variational formulation:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \overbrace{\sum_{t=1}^{N_t} \lambda_S(t) \, TV^{GM}\{\mathbf{x}\}[t]}^{\mathcal{R}_S} + \overbrace{\sum_{v=1}^{N_x} \lambda_T(v) \, \|\Delta_L\{\mathbf{x}\}[v]\|_1}^{\mathcal{R}_T} \right\}.$$

We have, now, the variational formulation:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \underbrace{\sum_{t=1}^{N_t} \lambda_S(t) \overbrace{TV^{GM}\{\mathbf{x}\}[t]}^{\mathcal{R}_S}} + \underbrace{\sum_{v=1}^{N_x} \lambda_T(v) \|\Delta_L\{\mathbf{x}\}[v]\|_1}_{\mathcal{R}_T} \right\}.$$

4D Structured TV

We have, now, the variational formulation:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \underbrace{\sum_{t=1}^{N_t} \lambda_S(t) \, TV^{GM}\{\mathbf{x}\}[t]}_{\mathcal{R}_S} + \underbrace{\sum_{v=1}^{N_x} \lambda_T(v) \, \|\Delta_L\{\mathbf{x}\}[v]\|_1}_{\mathcal{R}_T} \right\}.$$

4D Structured TV

Different operators on  $\mathcal{R}_S$  and  $\mathcal{R}_T$



We have, now, the variational formulation:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \underbrace{\sum_{t=1}^{N_t} \lambda_S(t) \overbrace{TV^{GM}\{\mathbf{x}\}[t]}^{\mathcal{R}_S}} + \underbrace{\sum_{v=1}^{N_x} \lambda_T(v) \|\Delta_L\{\mathbf{x}\}[v]\|_1}_{\mathcal{R}_T} \right\}.$$

4D Structured TV

Different operators on  $\mathcal{R}_S$  and  $\mathcal{R}_T \implies$  Generalized forward-backward [Raguet et al. 2013]

We have, now, the variational formulation:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \underbrace{\sum_{t=1}^{N_t} \lambda_S(t) TV^{GM}\{\mathbf{x}\}[t]}_{\mathcal{R}_S} + \underbrace{\sum_{v=1}^{N_x} \lambda_T(v) \|\Delta_L\{\mathbf{x}\}[v]\|_1}_{\mathcal{R}_T} \right\}.$$

4D Structured TV

Different operators on  $\mathcal{R}_S$  and  $\mathcal{R}_T \implies$  Generalized forward-backward [Raguet et al. 2013]

**Algorithm:**

**Input:** Corrupted data  $\mathbf{y}$ ,  $(\omega_t, \omega_s) \in [0, 1]^2$  with  $\omega_s + \omega_t = 1$

**Output:** Estimate  $\tilde{\mathbf{x}}$

**for**  $k = 1 : k_{max}$  **do**

1:  $\mathbf{x}_t^k = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \mathcal{R}_T(\mathbf{x}) \right\},$

2:  $\mathbf{x}_s^k = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \mathcal{R}_S(\mathbf{x}) \right\},$

3:  $\mathbf{x}^k = \omega_t \mathbf{x}_t^k + \omega_s \mathbf{x}_s^k$

**end for**

$\tilde{\mathbf{x}} = \mathbf{x}^{k_{max}}$

We have, now, the variational formulation:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \underbrace{\sum_{t=1}^{N_t} \lambda_S(t) TV^{GM}\{\mathbf{x}\}[t]}_{\mathcal{R}_S} + \underbrace{\sum_{v=1}^{N_x} \lambda_T(v) \|\Delta_L\{\mathbf{x}\}[v]\|_1}_{\mathcal{R}_T} \right\}.$$

4D Structured TV

Different operators on  $\mathcal{R}_S$  and  $\mathcal{R}_T \implies$  Generalized forward-backward [Raguet et al. 2013]

**Algorithm:**

**Input:** Corrupted data  $\mathbf{y}$ ,  $(\omega_t, \omega_s) \in [0, 1]^2$  with  $\omega_s + \omega_t = 1$

**Output:** Estimate  $\tilde{\mathbf{x}}$

**for**  $k = 1 : k_{max}$  **do**

1:  $\mathbf{x}_t^k = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \mathcal{R}_T(\mathbf{x}) \right\},$

2:  $\mathbf{x}_s^k = \arg \min_{\mathbf{x}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{x}\|_2^2 + \mathcal{R}_S(\mathbf{x}) \right\},$

3:  $\mathbf{x}^k = \omega_t \mathbf{x}_t^k + \omega_s \mathbf{x}_s^k$

**end for**


$\tilde{\mathbf{x}} = \mathbf{x}^{k_{max}}$

Solve steps 1 and 2 with a forward-backward algorithm (Fast Iterative Soft-Thresholding).

$\lambda_t$ : Estimated from wavelet coefficients.


# Test on simulated data

- FSL's simulation tool POSSUM



# Test on simulated data


- FSL's simulation tool POSSUM




$\Rightarrow \varepsilon \sim \mathcal{N}(0, 1)$ , PSNR=8.49 dB.

# Test on simulated data

## • FSL's simulation tool POSSUM




$\Rightarrow \varepsilon \sim \mathcal{N}(0, 1)$ , PSNR=8.49 dB.



Reconstructed activity-related signal  $\mathbf{x}$


# Test on simulated data

- FSL's simulation tool POSSUM



$\Rightarrow \varepsilon \sim \mathcal{N}(0, 1)$ , PSNR=8.49 dB.


- Less artifacts outside the activation regions  $\Rightarrow$  Better PSNR.




Reconstructed activity-related signal  $\mathbf{x}$

# Test on simulated data

## • FSL's simulation tool POSSUM



$\Rightarrow \varepsilon \sim \mathcal{N}(0, 1)$ , PSNR=8.49 dB.




Reconstructed activity-related signal  $\mathbf{x}$

- Less artifacts outside the activation regions  $\Rightarrow$  Better PSNR.
- Considerable gain in running time (5h53min vs 4h30min)



# Test on real data


- Visual stimuli:




Flickering checkerboard.

# Test on real data

- Visual stimuli:




Flickering checkerboard.




Visual cortex.

# Test on real data

- Visual stimuli:



Flickering checkerboard.




Visual cortex.


→ Rest periods disturbed by 9 visual stimuli of 1s at random time points.

# Test on real data

- Visual stimuli:





Flickering checkerboard.



Visual cortex.


→ Rest periods disturbed by 9 visual stimuli of 1s at random time points.




Recovered activity: (left) at a time point during the 2<sup>nd</sup> activation, (right) within an activated area.

# Test on real data

- Visual stimuli:




Flickering checkerboard.



Visual cortex.

→ Rest periods disturbed by 9 visual stimuli of 1s at random time points.



→ Richness of the activity during rest (networks).

# Concluding remarks

→ What I didn't talk about:

- Evoked regions have high activity in the center that is vanishing towards white matter  $\implies$  drive the process by a probability map.



# Concluding remarks

→ What I didn't talk about:

- Evoked regions have high activity in the center that is vanishing towards white matter  $\Rightarrow$  drive the process by a probability map.

→ Main perspectives:

- Applying the method to large datasets of resting-state fMRI to obtain innovation-driven co-activation patterns [Karahanoğlu & Van de Ville 2015].





# Concluding remarks

→ What I didn't talk about:

- Evoked regions have high activity in the center that is vanishing towards white matter  $\Rightarrow$  drive the process by a probability map.

→ Main perspectives:

- Applying the method to large datasets of resting-state fMRI to obtain innovation-driven co-activation patterns [Karahanoğlu & Van de Ville 2015].



- Semi-blind deconvolution: Estimating the time-to-peak and dispersion of the hemodynamic function from data.



Thanks for your attention !

Any Questions ?