

File [ET
detector
devices]

To: [REDACTED]
CC: [REDACTED]
CC: [REDACTED]
CC: [REDACTED]
CC: [REDACTED]
CC: [REDACTED]
CC: [REDACTED]
CC: "Dr. Steven Greer", Dr_ET
From: INTERNET [REDACTED] INTERNET [REDACTED]
Date: 5/17/98, 4:00 PM
Re: Re: UFO DETECTION DEVICE STATUS

[REDACTED]

From: [REDACTED]
Reply-To: [REDACTED]
Organization: Psi APPLICATIONS
X-Mailer: Mozilla 4.02 [en]C-DIAL (Win95; U)
MIME-Version: 1.0
To: Dave <[REDACTED]>
CC: Dan Smith <[REDACTED]>

"Dr. Steven Greer" <[REDACTED]>

[REDACTED]
[REDACTED]
[REDACTED]
[REDACTED]

Subject: Re: UFO DETECTION DEVICE STATUS

Content-Type: multipart/alternative; boundary="-----952C0084B520844E680368A8

Dave wrote:

> Recent developments around the Mk4 head and signal analysis.
> Up to and including May 1998.
>
> The Mk4 head is the most functional model to date. We started 2
> years ago with a sandwich disc constructed by sheathing an aluminium
> plate in hard plastic. The original idea was sparked by previous
> experiments in seismology where we had discovered a few things about
> damping eddy currents. Principles from our sailing days, where we
> grounded the rigging (usually stainless steel or wire) by connecting
> chains and dumping them over the side into salt to reduce the mast head to
> sea level electrically, were injected into the thinking, and we began to
> consider having some form of grounding element to reduce the actual
> head to ground potential. We experimented by both grounding and not
> grounding the plate, and grounding the plate by driving a copper pipe 2
> meters into ground seemed to provide the most exciting results.
>
> Grounding the head does give raise to a few interesting
> problems. No doubt there will always be some sort of potential in the
> head, and the magnetically sensitive element, even when constructed with
> aluminium alloy, may be difficult to calibrate in an environment that is
> changing ALL the time. In order to gain some insight into these
> problems, in April this year we sunk a sensor 2 meters into the earth and

> began to log some data while simultaneously logging sky fields. This is
> still going on, and it seems that there is little similarity between the two
>
> signals.

>
> We observed that the sky sensor reacts strongly to sunset, and
> background noise levels can change on the order of KHz per hour.
> We considered a PLL system but have edged more to microprocessor
> control, and this is what is currently being worked on. A beta version of
> the
> PC software should be available by late June. After testing and
> evaluation, operational documentation will be put together. We are also
> working on a stand alone model using the same sensor head and its own
> display requiring a 12V DC source. This is intended as a cheaper model
> with relay possibilities for outside equipment, lamps, cameras etc. We are
> very happy with the stand alone model's design and construction. It is
> made with simple parts, has strong housing, and is totally waterproof.
> However, it will have less features than the PC model.

>
> The PC model will provide state of the art filtering, analysis, and
> calibration control which brings us to the matter that has held us up for so
>
> long: aircraft type identification. This matter has given us not only a
> dilemma, but it opens up some interesting areas. It appears that as an
> aircraft passes through the 2 lobes of the detection field, it creates a
> signature in the magnetosphere for a short time. We are currently
> studying the phenomenon intensely. Apparently, any powered aircraft
> gives off a signature. Prop planes deliver different data from jets, and I
> am almost certain that all different types of aircraft will give off
> different
> signatures; therefore, the general type of aircraft should be identifiable,
> even if not seen visually. Questions arise when there are several aircraft
> in the air at the same time. Also in highly populated areas, there will be
> strong noise levels from various other sources. Adjusting to these noise
> levels is the primary reason we have adopted a sensing element which can
> be grounded or not. With a number of detectors working in different
> areas, we will eventually find out how it performs in all sorts of
> environments and make adjustments accordingly. The aircraft type
> analysis will take a while to evaluate. In the mean time, we opted for the
> staggered alarm system based on elimination with limited noise filtering
> control.

> Finally, we are still as convinced as ever that UFOs use magnetism,
> in
> whatever form or method, in large quantities to achieve navigation, flight,
> or both inside and outside our atmosphere. It seems that from a simple
> idea some 25 years ago, today presents 'n' times the possibilities.

> [REDACTED] wrote:

> > [REDACTED]
> >
> > What ever became of the status of this? Never received any further post
> > on this.

> > To Truth & Advancement

> > [REDACTED]
> > Founder & Managing Director
> > Psi APPLICATIONS
> > Humanity's Right To Know !!
> > <http://psi-app.com>

>

>
> --
> ***** ((())) *****
> THE Home of the A4 Locomotive Society
> UFO Detection
> D&K Hard Balls Design
> -----
> Dave at > [REDACTED]
> HTTP://www.euronet.nl/users/do42/index.htm
> =====

[REDACTED]

Thanks for the update. Please keep me informed of further progress as it occurs. If it is possible for us to obtain a prototype at a reasonable cost, given proper testing and results Psi APPLICATIONS would be happy to market this device for you through it array of connections within the field as a whole. The CC's are to a few substantial individuals whom may also have an interest in your work. Keep up the good work!

--

To Truth & Advancement

[REDACTED]
Founder & Managing Director
Psi APPLICATIONS
Humanity's Right To Know !!
<http://psi-app.com>