

BLM2041 Signals and Systems

The Instructors:

Prof. Dr. Nizamettin Aydın

naydin@yildiz.edu.tr

Asist. Prof. Dr. Ferkan Yilmaz


ferkan@yildiz.edu.tr

BLM2041 Signals and Systems

Spectrum Representation

Problem Solving Skills

- Math Formula
 - Sum of Cosines
 - Amp, Freq, Phase
- Recorded Signals
 - Speech
 - Music
 - No simple formula
- Plot & Sketches
 - $S(t)$ versus t
 - Spectrum
- MATLAB
 - Numerical
 - Computation
 - Plotting list of numbers



LECTURE OBJECTIVES

- Sinusoids with DIFFERENT Frequencies
 - SYNTHESIZE by Adding Sinusoids

$$x(t) = \sum_{k=1}^N A_k \cos(2\pi f_k t + \varphi_k)$$


- SPECTRUM Representation
 - Graphical Form shows DIFFERENT Freqs

LECTURE OBJECTIVES

- Signals with HARMONIC Frequencies
 - Add Sinusoids with $f_k = kf_0$

$$x(t) = A_0 + \sum_{k=1}^N A_k \cos(2\pi kf_0 t + \varphi_k)$$

FREQUENCY can change **vs. TIME**

Chirps:

$$x(t) = \cos(\alpha t^2)$$

Introduce Spectrogram Visualization (**specgram.m**)
(plotspec.m)

LECTURE OBJECTIVES


- Work with the Fourier Series Integral

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi k/T_0)t} dt$$

- ANALYSIS via Fourier Series
 - For PERIODIC signals: $x(t+T_0) = x(t)$
- SPECTRUM from Fourier Series
 - a_k is Complex Amplitude for k -th Harmonic

FREQUENCY DIAGRAM

- Plot Complex Amplitude vs. Freq



Another FREQ. Diagram

Frequency is the vertical axis





Figure 3.18 Sheet-music notation is a time–frequency diagram.

Time is the horizontal axis

MOTIVATION


- Synthesize Complicated Signals

- Musical Notes



- Piano uses 3 strings for many notes
 - Chords: play several notes simultaneously

- Human Speech




- Vowels have dominant frequencies
 - Application: computer generated speech


- Can all signals be generated this way?

- Sum of sinusoids?

Fur Elise WAVEFORM




Fur Elise




**Beat
Notes**

Speech Signal: BAT



- Nearly Periodic in Vowel Region
 - Period is (Approximately) $T = 0.0065$ sec



Euler's Formula Reversed

- Solve for cosine (or sine)

$$e^{j\omega t} = \cos(\omega t) + j \sin(\omega t)$$

$$e^{-j\omega t} = \cos(-\omega t) + j \sin(-\omega t)$$

$$e^{-j\omega t} = \cos(\omega t) - j \sin(\omega t)$$

$$e^{j\omega t} + e^{-j\omega t} = 2 \cos(\omega t)$$

$$\boxed{\cos(\omega t) = \frac{1}{2}(e^{j\omega t} + e^{-j\omega t})}$$

INVERSE Euler's Formula

- Solve for cosine (or sine)

$$\cos(\omega t) = \frac{1}{2}(e^{j\omega t} + e^{-j\omega t})$$

$$\sin(\omega t) = \frac{1}{2j}(e^{j\omega t} - e^{-j\omega t})$$

SPECTRUM Interpretation

- Cosine = sum of 2 complex exponentials:

$$A \cos(7t) = \frac{A}{2} e^{j7t} + \frac{A}{2} e^{-j7t}$$

The diagram illustrates the decomposition of a cosine wave into two complex exponentials. A blue arrow points from the term $\frac{A}{2} e^{j7t}$ to a point on a circle in the upper half-plane. Another blue arrow points from the term $\frac{A}{2} e^{-j7t}$ to a point on a circle in the lower half-plane. This visualizes the complex plane representation where the positive frequency component is in the upper half-plane and the negative frequency component is in the lower half-plane.

One has a positive frequency

The other has **negative** freq.

Amplitude of each is half as big

NEGATIVE FREQUENCY

- Is negative frequency real?
- Doppler Radar provides an example
 - Police radar measures speed by using the Doppler shift principle
 - Let's assume 400Hz \leftrightarrow 60 mph
 - +400Hz means towards the radar
 - -400Hz means away (opposite direction)
 - Think of a train whistle

SPECTRUM of SINE

- Sine = sum of 2 complex exponentials:

$$A \sin(7t) = \frac{A}{2j} e^{j7t} - \frac{A}{2j} e^{-j7t}$$

$$= \frac{1}{2} A e^{-j0.5\pi} e^{j7t} + \frac{1}{2} A e^{j0.5\pi} e^{-j7t}$$


$$\frac{-1}{j} = j = e^{j0.5\pi}$$

- Positive freq. has phase = -0.5π
- Negative freq. has phase = $+0.5\pi$

GRAPHICAL SPECTRUM

EXAMPLE of SINE


$$A \sin(7t) = \frac{1}{2} A e^{-j0.5\pi} e^{j7t} + \frac{1}{2} A e^{j0.5\pi} e^{-j7t}$$



AMPLITUDE, PHASE & FREQUENCY are shown

SPECTRUM ---> SINUSOID

- Add the spectrum components:



What is the formula for the signal $x(t)$?

Gather (A, ω, ϕ) information

- Frequencies:
 - -250 Hz
 - -100 Hz
 - **0 Hz**
 - 100 Hz
 - 250 Hz
- Amplitude & Phase
 - 4 $-\pi/2$
 - 7 $+\pi/3$
 - 10 **0**
 - 7 $-\pi/3$
 - 4 $+\pi/2$




Note the **conjugate phase**


DC is another name for zero-freq component

DC component always has $\phi=0$ or π (for real $x(t)$)

Add Spectrum Components-1



Add Spectrum Components-2



$$x(t) = 10 +$$

$7e^{-j\pi/3} e^{j2\pi(100)t} + 7e^{j\pi/3} e^{-j2\pi(100)t}$

$$4e^{j\pi/2} e^{j2\pi(250)t} + 4e^{-j\pi/2} e^{-j2\pi(250)t}$$

Simplify Components

$$x(t) = 10 +$$
$$7e^{-j\pi/3}e^{j2\pi(100)t} + 7e^{j\pi/3}e^{-j2\pi(100)t}$$
$$4e^{j\pi/2}e^{j2\pi(250)t} + 4e^{-j\pi/2}e^{-j2\pi(250)t}$$

Use Euler's Formula to get **REAL** sinusoids:

$$A\cos(\omega t + \varphi) = \frac{1}{2} Ae^{-j\varphi} e^{j\omega t} + \frac{1}{2} Ae^{-j\varphi} e^{-j\omega t}$$

FINAL ANSWER

$$x(t) = 10 + 14\cos(2\pi(100)t - \pi/3) \\ + 8\cos(2\pi(250)t + \pi/2)$$

So, we get the general form:

$$x(t) = A_0 + \sum_{k=1}^N A_k \cos(2\pi f_k t + \varphi_k)$$



Summary: GENERAL FORM

$$x(t) = A_0 + \sum_{k=1}^N A_k \cos(2\pi f_k t + \varphi_k)$$

$$x(t) = X_0 + \sum_{k=1}^N \Re e \left\{ X_k e^{j2\pi f_k t} \right\}$$

$$X_k = A_k e^{j\varphi_k}$$

Frequency = f_k

$$\Re e \{ z \} = \frac{1}{2} z + \frac{1}{2} z^*$$


$$x(t) = X_0 + \sum_{k=1}^N \left\{ \frac{1}{2} X_k e^{j2\pi f_k t} + \frac{1}{2} X_k^* e^{-j2\pi f_k t} \right\}$$

Example: Synthetic Vowel

- Sum of 5 Frequency Components
 - Complex amplitudes for harmonic signal that approximates the vowel sound «ah»

f_k (Hz)	X_k	Mag	Phase (rad)
200	$(771 + j12202)$	12,226	1.508
400	$(-8865 + j28048)$	29,416	1.876
500	$(48001 - j8995)$	48,836	-0.185
1600	$(1657 - j13520)$	13,621	-1.449
1700	$4723 + j0$	4723	0


SPECTRUM of VOWEL




- Note: Spectrum has $0.5X_k$ (except X_{DC})
- Conjugates in negative frequency

SPECTRUM of VOWEL (Polar Format)

Vowel: Magnitude Spectrum




Vowel: Phase Angle Spectrum



Vowel Waveform (sum of all 5 components)

- Sum of all of the signals in the previous slides




- Note that the period is 10 ms, which equals $1/f_0$

BLM2041 Signals and Systems

Periodic Signals, Harmonics & Time-Varying Sinusoids

SPECTRUM DIAGRAM



- Recall Complex Amplitude vs. Freq



$$x(t) = 10 + 14\cos(2\pi(100)t - \pi/3) + 8\cos(2\pi(250)t + \pi/2)$$

SPECTRUM for PERIODIC ?

- Nearly Periodic in the Vowel Region
 - Period is (Approximately) $T = 0.0065$ sec



PERIODIC SIGNALS

- Repeat every T secs

- Definition

$$x(t) = x(t + T)$$

- Example:

$$x(t) = \cos^2(3t)$$

$$T = ?$$

- Speech can be “quasi-periodic”

$$T = \frac{2\pi}{3}$$

$$T = \frac{\pi}{3}$$

Period of Complex Exponential

$$x(t) = e^{j\omega t}$$

$$x(t + T) = x(t) ?$$

Definition: Period is T

$$\begin{aligned} \cancel{e^{j\omega(t+T)}} &= \cancel{e^{j\omega t}} \\ \Rightarrow e^{j\omega T} &= 1 \end{aligned} \Rightarrow \omega T = 2\pi k$$

$$e^{j2\pi k} = 1$$

$$\omega = \frac{2\pi k}{T} = \left(\frac{2\pi}{T} \right) k = \omega_0 k$$

$k = \text{integer}$

Harmonic Signal Spectrum

Periodic signal can only have : $f_k = k f_0$

$$x(t) = A_0 + \sum_{k=1}^N A_k \cos(2\pi k f_0 t + \varphi_k)$$

$$f_0 = \frac{1}{T}$$

$$X_k = A_k e^{j\varphi_k}$$



$$x(t) = X_0 + \sum_{k=1}^N \left\{ \frac{1}{2} X_k e^{j2\pi k f_0 t} + \frac{1}{2} X_k^* e^{-j2\pi k f_0 t} \right\}$$

Define FUNDAMENTAL FREQ

$$x(t) = A_0 + \sum_{k=1}^N A_k \cos(2\pi k f_0 t + \varphi_k)$$


$$f_k = k f_0 \quad (\omega_0 = 2\pi f_0)$$

$$f_0 = \frac{1}{T_0}$$

f_0 = fundamental Frequency (largest)

T_0 = fundamental Period (shortest)

Harmonic Signal (3 Freqs)




What is the fundamental frequency?

10 Hz

POP QUIZ: FUNDAMENTAL

- Here's another spectrum:




What is the fundamental frequency?

100 Hz ?

50 Hz ?


IRRATIONAL SPECTRUM



Harmonic Signal (3 Freqs)


T=0.1

Sum of Cosine Waves with Harmonic Frequencies



NON-Harmonic Signal


Sum of Cosine Waves with Nonharmonic Frequencies



**NOT
PERIODIC**

FREQUENCY ANALYSIS

- Now, a much HARDER problem
- Given a recording of a song, have the computer write the music



- Can a machine extract frequencies?
 - Yes, if we COMPUTE the spectrum for $x(t)$
 - During short intervals

Time-Varying FREQUENCIES Diagram

Frequency is the vertical axis





Figure 3.18 Sheet-music notation is a time–frequency diagram.

Time is the horizontal axis

SIMPLE TEST SIGNAL

- C-major SCALE: stepped frequencies






– Frequency is constant for each note

SPECTROGRAM

- SPECTROGRAM Tool
 - MATLAB function is `specgram.m`
 - SP-First has `plotspec.m` & `spectgr.m`
- ANALYSIS program
 - Takes $x(t)$ as input &
 - Produces spectrum values X_k
 - Breaks $x(t)$ into SHORT TIME SEGMENTS
 - Then uses the FFT (Fast Fourier Transform)

SPECTROGRAM EXAMPLE


- Two Constant Frequencies: Beats



$$\cos(2\pi(660)t) \sin(2\pi(12)t)$$

AM Radio Signal

- Same as BEAT Notes



$$\cos(2\pi(660)t) \sin(2\pi(12)t)$$


$$\frac{1}{2} \left(e^{j2\pi(660)t} + e^{-j2\pi(660)t} \right) \frac{1}{2j} \left(e^{j2\pi(12)t} - e^{-j2\pi(12)t} \right)$$

$$\frac{1}{4j} \left(e^{j2\pi(672)t} - e^{-j2\pi(672)t} - e^{j2\pi(648)t} + e^{-j2\pi(648)t} \right)$$

$$\frac{1}{2} \cos(2\pi(672)t - \frac{\pi}{2}) + \frac{1}{2} \cos(2\pi(648)t + \frac{\pi}{2})$$

SPECTRUM of AM (Beat)

- 4 complex exponentials in AM:





What is the fundamental frequency?

648 Hz ?

24 Hz ?


STEPPED FREQUENCIES

- C-major SCALE: stepped frequencies




– Frequency is constant for each note


SPECTROGRAM of C-Scale



Spectrogram of LAB SONG



Beethovens FIFTH (Robby GRIFFIN)




Time-Varying Frequency

- Frequency can change **vs.** time
 - Continuously, not stepped
- **FREQUENCY MODULATION (FM)**

$$x(t) = \cos(2\pi f_c t + v(t))$$

VOICE

- CHIRP SIGNALS 
 - Linear Frequency Modulation (LFM)

New Signal: Linear FM

- Called Chirp Signals (LFM)

- Quadratic phase

QUADRATIC

$$x(t) = A \cos(\alpha t^2 + 2\pi f_0 t + \varphi)$$

- Freq will change LINEARLY vs. time
 - Example of Frequency Modulation (FM)
 - Define “instantaneous frequency”

INSTANTANEOUS FREQ

- Definition

$$\begin{aligned}x(t) &= A \cos(\psi(t)) \\ \Rightarrow \omega_i(t) &= \frac{d}{dt} \psi(t)\end{aligned}$$

*Derivative
of the “Angle”*

- For Sinusoid:

$$x(t) = A \cos(2\pi f_0 t + \varphi)$$

$$\psi(t) = 2\pi f_0 t + \varphi$$

Makes sense

$$\Rightarrow \omega_i(t) = \frac{d}{dt} \psi(t) = 2\pi f_0$$

INSTANTANEOUS FREQ of the Chirp



- Chirp Signals have Quadratic phase
- Freq will change LINEARLY vs. time

$$x(t) = A \cos(\alpha t^2 + \beta t + \varphi)$$



$$\Rightarrow \psi(t) = \alpha t^2 + \beta t + \varphi$$

$$\Rightarrow \omega_i(t) = \frac{d}{dt} \psi(t) = 2\alpha t + \beta$$

CHIRP SPECTROGRAM



CHIRP WAVEFORM



OTHER CHIRPS

$\psi(t)$ can be anything:



$$x(t) = A \cos(\alpha \cos(\beta t) + \varphi)$$

$$\Rightarrow \omega_i(t) = \frac{d}{dt} \psi(t) = -\alpha \beta \sin(\beta t)$$

$\psi(t)$ could be speech or music:

- FM radio broadcast

SINE-WAVE FREQUENCY MODULATION (FM)



BLM2041 Signals and Systems

Fourier Series Coefficients

HISTORY

- Jean Baptiste Joseph Fourier (1768-1830)




- Napoleonic era
- Studied the mathematical theory of heat conduction
- Established the partial differential equation governing heat diffusion and solved it by using infinite series of trigonometric functions.

- <http://www-groups.dcs.st-and.ac.uk/~history/Mathematicians/Fourier.html>

SPECTRUM DIAGRAM

- Recall Complex Amplitude vs. Freq



$$x(t) = \boxed{a_0} + \sum_{k=1}^N \left\{ \boxed{a_k} e^{j2\pi f_k t} + \boxed{a_k^*} e^{-j2\pi f_k t} \right\}$$

Harmonic Signal

$$x(t) = \sum_{k=-\infty}^{\infty} a_k e^{j2\pi k f_0 t}$$

PERIOD/FREQUENCY of COMPLEX EXPONENTIAL:

$$2\pi(f_0) = \omega_0 = \frac{2\pi}{T_0} \quad \text{or} \quad T_0 = \frac{1}{f_0}$$

Fourier Series Synthesis

$$x(t) = \sum_{k=-\infty}^{\infty} a_k e^{j2\pi k f_0 t}$$


$$a_k = \frac{1}{2} X_k = \frac{1}{2} A_k e^{j\varphi_k}$$

$$x(t) = A_0 + \sum_{k=1}^N A_k \cos(2\pi k f_0 t + \varphi_k)$$

$$X_k = A_k e^{j\varphi_k}$$


COMPLEX
AMPLITUDE

Harmonic Signal (3 Freqs)



Sum of Cosine Waves with Harmonic Frequencies

$T = 0.1$



SYNTHESIS vs. ANALYSIS

- SYNTHESIS
 - Easy
 - Given (ω_k, A_k, ϕ_k) create $x(t)$
- Synthesis can be HARD
 - Synthesize Speech so that it sounds good
- ANALYSIS
 - Hard
 - Given $x(t)$, extract (ω_k, A_k, ϕ_k)
 - How many?
 - Need algorithm for computer

STRATEGY: $x(t) \rightarrow a_k$

- **ANALYSIS**
 - Get representation from the signal
 - Works for **PERIODIC** Signals
- Fourier Series
 - Answer is: an INTEGRAL over one period

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j\omega_0 k t} dt$$

INTEGRAL Property of $\exp(j)$

- INTEGRATE over ONE PERIOD

$$\int_0^{T_0} e^{-j(2\pi/T_0)mt} dt = \frac{T_0}{-j2\pi m} e^{-j(2\pi/T_0)mt} \Big|_0^{T_0}$$
$$= \frac{T_0}{-j2\pi m} (e^{-j2\pi m} - 1)$$

$$\int_0^{T_0} e^{-j(2\pi/T_0)mt} dt = 0$$

$$m \neq 0$$

$$\omega_0 = \frac{2\pi}{T_0}$$

ORTHOGONALITY of $\exp(j)$

- PRODUCT of $\exp(+j)$ and $\exp(-j)$

$$\frac{1}{T_0} \int_0^{T_0} e^{j(2\pi/T_0)\ell t} e^{-j(2\pi/T_0)kt} dt = \begin{cases} 0 & k \neq \ell \\ 1 & k = \ell \end{cases}$$

$$\frac{1}{T_0} \int_0^{T_0} e^{j(2\pi/T_0)(\ell-k)t} dt$$

Isolate One FS Coefficient

$$x(t) = \sum_{k=-\infty}^{\infty} a_k e^{j(2\pi/T_0)kt}$$

$$\frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)\ell t} dt = \frac{1}{T_0} \int_0^{T_0} \left(\sum_{k=-\infty}^{\infty} a_k e^{j(2\pi/T_0)kt} \right) e^{-j(2\pi/T_0)\ell t} dt$$

$$\frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)\ell t} dt = \sum_{k=-\infty}^{\infty} a_k \left(\frac{1}{T_0} \int_0^{T_0} e^{j(2\pi/T_0)kt} e^{-j(2\pi/T_0)\ell t} dt \right) = a_\ell$$


$$\Rightarrow a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)kt} dt$$

Integral is zero
except for $k = \ell$

SQUARE WAVE EXAMPLE

$$x(t) = \begin{cases} 1 & 0 \leq t < \frac{1}{2} T_0 \\ 0 & \frac{1}{2} T_0 \leq t < T_0 \end{cases}$$

for $T_0 = 0.04$ sec.



FS for a SQUARE WAVE $\{a_k\}$

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)kt} dt \quad (k \neq 0)$$

$$a_k = \frac{1}{.04} \int_0^{.02} 1 e^{-j(2\pi/.04)kt} dt = \frac{1}{.04(-j2\pi k/.04)} e^{-j(2\pi/.04)kt} \Big|_0^{.02}$$

$$= \frac{1}{(-j2\pi k)} (e^{-j(\pi)k} - 1) = \frac{1 - (-1)^k}{j2\pi k}$$

DC Coefficient: a_0

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)kt} dt \quad (k = 0)$$

$$a_0 = \frac{1}{T_0} \int_0^{T_0} x(t) dt = \frac{1}{T_0} (\text{Area})$$

$$a_0 = \frac{1}{.04} \int_0^{.02} 1 dt = \frac{1}{.04} (.02 - 0) = \frac{1}{2}$$

Fourier Coefficients a_k


- a_k is a function of k
 - Complex Amplitude for k -th Harmonic
 - This one doesn't depend on the period, T_0

$$a_k = \frac{1 - (-1)^k}{j2\pi k} = \begin{cases} \frac{1}{j\pi k} & k = \pm 1, \pm 3, \dots \\ 0 & k = \pm 2, \pm 4, \dots \\ \frac{1}{2} & k = 0 \end{cases}$$

Spectrum from Fourier Series

$$\omega_0 = 2\pi / (0.04) = 2\pi(25)$$

$$a_k = \begin{cases} \frac{-j}{\pi k} & k = \pm 1, \pm 3, \dots \\ 0 & k = \pm 2, \pm 4, \dots \\ \frac{1}{2} & k = 0 \end{cases}$$



Fourier Series Integral

- HOW do you determine a_k from $x(t)$?

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)kt} dt$$

Fundamental Frequency $f_0 = 1/T_0$


$$a_{-k} = a_k^* \quad \text{when } x(t) \text{ is real}$$

$$a_0 = \frac{1}{T_0} \int_0^{T_0} x(t) dt \quad (\text{DC component})$$

Fourier Series & Spectrum

SPECTRUM DIAGRAM

- Recall Complex Amplitude vs. Freq



$$x(t) = a_0 + \sum_{k=1}^N \left\{ a_k e^{j2\pi f_k t} + a_k^* e^{-j2\pi f_k t} \right\}$$

Harmonic Signal


$$x(t) = \sum_{k=-\infty}^{\infty} a_k e^{j2\pi k f_0 t}$$

PERIOD/FREQUENCY of COMPLEX EXPONENTIAL:

$$2\pi(f_0) = \omega_0 = \frac{2\pi}{T_0} \quad \text{or} \quad T_0 = \frac{1}{f_0}$$

Example

$$x(t) = \sin^3(3\pi t)$$




$$x(t) = \left(\frac{j}{8}\right)e^{j9\pi t} + \left(\frac{-3j}{8}\right)e^{j3\pi t} + \left(\frac{3j}{8}\right)e^{-j3\pi t} + \left(\frac{-j}{8}\right)e^{-j9\pi t}$$

Example

$$x(t) = \sin^3(3\pi t)$$

$$x(t) = \left(\frac{j}{8}\right)e^{j9\pi t} + \left(\frac{-3j}{8}\right)e^{j3\pi t} + \left(\frac{3j}{8}\right)e^{-j3\pi t} + \left(\frac{-j}{8}\right)e^{-j9\pi t}$$

In this case, analysis just requires picking off the coefficients.



STRATEGY: $x(t) \rightarrow a_k$

- **ANALYSIS**
 - Get representation from the signal
 - Works for **PERIODIC** Signals
- Fourier Series
 - Answer is: an INTEGRAL over one period

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j\omega_0 k t} dt$$

FS: Rectified Sine Wave $\{a_k\}$

$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)kt} dt \quad (k \neq \pm 1)$$


$$a_k = \frac{1}{T_0} \int_0^{T_0/2} \sin\left(\frac{2\pi}{T_0}t\right) e^{-j(2\pi/T_0)kt} dt$$

$$= \frac{1}{T_0} \int_0^{T_0/2} \frac{e^{j(2\pi/T_0)t} - e^{-j(2\pi/T_0)t}}{2j} e^{-j(2\pi/T_0)kt} dt$$

$$= \frac{1}{j2T_0} \int_0^{T_0/2} e^{-j(2\pi/T_0)(k-1)t} dt - \frac{1}{j2T_0} \int_0^{T_0/2} e^{-j(2\pi/T_0)(k+1)t} dt$$

$$= \frac{e^{-j(2\pi/T_0)(k-1)t}}{j2T_0(-j(2\pi/T_0)(k-1))} \Big|_0^{T_0/2} - \frac{e^{-j(2\pi/T_0)(k+1)t}}{j2T_0(-j(2\pi/T_0)(k+1))} \Big|_0^{T_0/2}$$

Half-Wave Rectified Sine




FS: Rectified Sine Wave {a_k}

$$\begin{aligned}
 a_k &= \frac{e^{-j(2\pi/T_0)(k-1)t}}{j2T_0(-j(2\pi/T_0)(k-1))} \Big|_0^{T_0/2} - \frac{e^{-j(2\pi/T_0)(k+1)t}}{j2T_0(-j(2\pi/T_0)(k+1))} \Big|_0^{T_0/2} \\
 &= \frac{1}{4\pi(k-1)} \left(e^{-j(2\pi/T_0)(k-1)T_0/2} - 1 \right) - \frac{1}{4\pi(k+1)} \left(e^{-j(2\pi/T_0)(k+1)T_0/2} - 1 \right) \\
 &= \frac{1}{4\pi(k-1)} \left(e^{-j\pi(k-1)} - 1 \right) - \frac{1}{4\pi(k+1)} \left(e^{-j\pi(k+1)} - 1 \right) \\
 &= \left(\frac{k+1-(k-1)}{4\pi(k^2-1)} \right) \left(-(-1)^k - 1 \right) = \begin{cases} 0 & k \text{ odd} \\ \pm \frac{1}{j4} & k = \pm 1 \\ \frac{-1}{\pi(k^2-1)} & k \text{ even} \end{cases}
 \end{aligned}$$

SQUARE WAVE EXAMPLE

$$x(t) = \begin{cases} 1 & 0 \leq t < \frac{1}{2} T_0 \\ 0 & \frac{1}{2} T_0 \leq t < T_0 \end{cases}$$

for $T_0 = 0.04$ sec.



Fourier Coefficients a_k


- a_k is a function of k
 - Complex Amplitude for k -th Harmonic
 - This one doesn't depend on the period, T_0

$$a_k = \frac{1 - (-1)^k}{j2\pi k} = \begin{cases} \frac{1}{j\pi k} & k = \pm 1, \pm 3, \dots \\ 0 & k = \pm 2, \pm 4, \dots \\ \frac{1}{2} & k = 0 \end{cases}$$

Spectrum from Fourier Series

$$\omega_0 = 2\pi / (0.04) = 2\pi(25)$$

$$a_k = \begin{cases} \frac{-j}{\pi k} & k = \pm 1, \pm 3, \dots \\ 0 & k = \pm 2, \pm 4, \dots \\ \frac{1}{2} & k = 0 \end{cases}$$



Fourier Series Synthesis

- HOW do you APPROXIMATE $x(t)$?



$$a_k = \frac{1}{T_0} \int_0^{T_0} x(t) e^{-j(2\pi/T_0)kt} dt$$

- Use FINITE number of coefficients

$$x(t) = \sum_{k=-N}^N a_k e^{j2\pi k f_0 t}$$



$$a_{-k} = a_k^* \quad \text{when } x(t) \text{ is real}$$

Fourier Series Synthesis





Synthesis: 1st & 3rd Harmonics

$$y(t) = \frac{1}{2} + \frac{2}{\pi} \cos(2\pi(25)t - \frac{\pi}{2}) + \frac{2}{3\pi} \cos(2\pi(75)t - \frac{\pi}{2})$$




Synthesis: up to 7th Harmonic

$$y(t) = \frac{1}{2} + \frac{2}{\pi} \cos(50\pi t - \frac{\pi}{2}) + \frac{2}{3\pi} \sin(150\pi t) + \frac{2}{5\pi} \sin(250\pi t) + \frac{2}{7\pi} \sin(350\pi t)$$



Fourier Synthesis

$$x_N(t) = \frac{1}{2} + \frac{2}{\pi} \sin(\omega_0 t) + \frac{2}{3\pi} \sin(3\omega_0 t) + \dots$$



Gibbs' Phenomenon

- Convergence at **DISCONTINUITY** of $x(t)$
 - There is always an **overshoot**
 - 9% for the Square Wave case

