MO601 - Projeto 3

Wormhole: Wisely Predicting Multidimensional Branches

Jorge Albericio, Joshua San Miguel, Natalie Enright Jerger, and Andreas Moshovos
Edward S. Rogers Sr. Department of Electrical and Computer Engineering
University of Toronto
Toronto, ON, Canada

Uglaybe Piell Fernandes
UNICAMP

Campinas – 31 de outubro de 2016

Situação que queremos melhorar

Program 1

```
// X is a vector with the position of objects
//    randomly placed in a 3D space
// p is a point in the 3D space
while(true)                          // Loop 1
  for( j=0; j<NumObjects; j++)       // Loop 2
    if( distance(X[j], p) < threshold )    // Branch 1
     { /* do something */ }
```

Program 2: Jacobi1 algorithm

```
// A is the matrix
// B is the right hand side
// X is the current solution estimate
// X0 is the partial solution
 for ( i = 0; i < N; i++ ) {   // Loop 3
   X0[i] = B[i];
   for ( j = 0; j < N; j++ )        // Loop 4
     if ( j != i )                   // Branch 2
       X0[i] = X0[i] - A[i + j*n] * X[j];
   X0[i] = X0[i] /A[i + i*n];
 }
```

Como fazemos isso?

Exemplo para o programa 2.

E os outros Branchs?

ISL-TAGE – “A 64 Kbytes ISL-TAGE branch predictor”, André Seznec INRIA/IRISA

- TAGE predictor.
- Loop predictor
- Statistical Corrector predictor (SC)
- The Immediate Update Mimicker

TAGE predictor



O que reproduzir?



Figure 6: MPKI reductions with respect to ISL-TAGE for the 40 traces, for 4KB and 32KB base predictors.

Referências

- **Wormhole: Wisely Predicting Multidimensional Branches**:

Jorge Albericio, Joshua San Miguel, Natalie Enright Jerger, and Andreas Moshovos

Edward S. Rogers Sr., Department of Electrical and Computer Engineering, University of Toronto

- **A 64 Kbytes ISL-TAGE branch predictor:**

André Seznec, INRIA/IRISA

- **A case for (partially) TAgged GEometric history length branch prediction:**

André Seznec, Pierre Michaud, IRISA/INRIA/HIPEAC

- **Analysis of the O-GEometric History Length branch predictor**:

André Seznec, IRISA/INRIA/HIPEAC

Obrigado