GREAT POWER

World-Class Manufacturer: Safe | Durable | Dependable

MAGNA-UTL ENERGY STORAGE CABINET

Energy Storage for Commercial, Industrial, and Utility-Scale Applications

The Great Power Energy Storage Cabinet is a modular system with a nominal energy range from 52 to 418 kWh, compatible with 150 to 1500 Volt inverters. The Cabinet is shipped as a complete product, significantly reducing on-site installation time and costs. The integrated liquid cooling and heating system ensures consistent cell operation across a wide operating temperature range.

FEATURES AND BENEFITS

MODULAR
- 52 kWh to 418 kWh Preassembled Battery Cabinets.

SCALABLE
- Parallel Up to Sixteen Battery Cabinets 6.7 MWh.

COMPATIBLE
- Inverters with 150 Vdc to 1500 Vdc Battery Input. 220V, 480V, 690Vac, 800V output

OUTDOOR
- NEMA 3R (IP55).

EFFICIENT
- Liquid Cooling / Heating of LFP Battery Module Cells).

OPTIMIZED
- Multi-tiered Battery Management System.

SAFE
- Fire Suppression, Heat and Smoke Detection, Deflagration Panel.

CERTIFIED
- UL9540 Certified/NFPA855/IEC

ELECTRICAL SPECIFICATIONS

Model	UTL-52	UTL-104	UTL-157	UTL-209	UTL-261	UTL-313	UTL-366	UTL-418
Cell Configuration	1P52S	1P104S	1P156S	1P208S	1P260S	1P312S	1P364S	1P416S
Chemistry	$LiFePO_4$							
Capacity (Ah)	320							
Energy (kWh)	52	104	157	209	261	313	366	418
Nominal Voltage (V)	166	333	499	666	832	998	1165	1331
High/Low Voltage Range (V)	187 / 135	374 / 270	561 / 405	749 / 540	936 / 676	1,123 / 811	1,310 / 946	1,498 / 1,082
Max Charge/Discharge Current (A)	173							
Nominal Charge/Discharge Current (A)	157							
Communications	ModbusTCP (Ethernet) and Modbus RTU							
Warranty	Up to 20 years or up to 10,000 Cycles							
Efficiency	Up to 96%							

MECHANICAL SPECIFICATIONS

Length (A)	51.18 in (1,300 mm)							
Width (B)	51.18 in (1,300 mm)							
Height (C)	92.71 in (2,355 mm)							
Weight (lb/kg)	3,075 / 1,395	3,836 / 1,740	4,594 / 2,084	5,355 / 2,429	6,115 / 2,774	6,876 / 3,119	7,636 / 3,464	8,395 / 3,808

ENVIRONMENTAL SPECIFICATIONS

Charge Temperature	35.6°F to 132.8°F (2°C to 56°C)
Discharge Temperature	-0.4°F to 132.8°F (-18°C to 56°C)
Operating Temperature	-31°F to 131°F (-35°C to 55°C)
Noise	≤75 dB
Altitude	≤6562 ft (≤2000 m)
IP Rating	NEMA 3R / IP55
Thermal Management	Integrated Liquid Cooling and Heating System
Cabinet Scalability	Up to 15 cabinets / 6.4 MWh
Fire Suppression	Fire Suppression, Heat and Smoke Detection, Deflagration Panel

CERTIFICATION STANDARDS

Certification Standards	UL1973, UL9540A, UL9540, UL60730, IEC/EN 62619, IEC/EN 61000, IEC/EN 62477, UL61000, NFPA855, NFPA68
Shipping Classification	UN 38.3, UN3536, UN3480, Class 9 (Lithium batteries)

Greatpower.net/en 300438/SZ 3146B Sports Arena Blvd, San Diego, Ca 92110 + 1.619.681.4609 Evan.Bierman@greatpower.net