GREAT POWER

World-Class Manufacturer - Safe | Durable | Dependable

ULTRA MAX 5000 ENERGY STORAGE CONTAINER

Energy Storage for Commercial, Industrial, and Utility-Scale Applications

The Great Power Energy Storage Container is a modular system with a nominal energy range from 2508 to 5,016 kWh, compatible with 150 to 1500 Volt inverters. The container is shipped as a complete product, significantly reducing on-site installation time and costs. The integrated liquid cooling and heating system ensures consistent cell operation across a wide operating temperature range.

FEATURES & BENEFITS

MODULAR
- 2,508 kWh to 5016 kWh Preassembled Battery Containers.

COMPATIBLE
- Inverters with 1000 Vdc to 1500 Vdc Battery Input. 220Vac to 800Vac output

OUTDOOR
- NEMA 3R (IP55).

EFFICIENT
- Liquid Cooling / Heating of LFP Battery Module Cells).

OPTIMIZED
- Multi-tiered Battery Management System.

SAFE
- Fire Suppression, Heat and Smoke Detection, Deflagration Panel.

CERTIFIED
- UL9540Certified/NFPA855/IEC

FLEXIBLE
- Up to 6 independent DC busses and connections

ELECTRICAL SPECIFICATIONS

Model	MAX-2508-LV	MAX-2508	MAX-3344	MAX-3762	MAX-4180	MAX-4598	MAX-5016
Cell Configuration	1P208S*12	1P416S*6	1P416S*8	1P416S*9	1P416S*10	1P416S*11	1P416S*12
Chemistry	LFP/LiFePO4						
Capacity (Ah)	314						
Energy (kWh)	2508	2508	3344	3762	4180	4598	5016
Nominal Voltage (V)	665.6	1331.2	1331.2	1331.2	1331.2	1331.2	1331.2
High/Low Voltage Range (V)	540.8~749	1081.6 ~ 1497.6	1081.6 ~ 1497.6	1081.6 ~ 1497.6	1081.6 ~ 1497.6	1081.6 ~ 1497.6	1081.6 ~ 1497.6
Max Charge/Discharge Current (A)	1158						
Nominal Charge/Discharge Current (A)	942						
Communications	ModbusTCP (Ethernet) and Modbus RTU						
Warranty	Up to 20 years or up to 10,000 Cycles						
Efficiency	Up to 93.5%						

MECHANICAL SPECIFICATIONS

Length (A)	238.50 in (6,058 mm)						
Width (B)	95.98 in (2,438 mm)						
Height (C)	114.02 in (2,896 mm)						
Weight (lb/t)	59,436/26.96	59,436/26.96	71,959/32.64	78,485/35.6	84,481/38.32	90,830/41.2	97,003/44

ENVIRONMENTAL SPECIFICATIONS

Charge Temperature	32°F to 132.8°F (0°C to 55°C)
Discharge Temperature	-22°F to 132.8°F (-30°C to 55°C)
Operating Temperature	-22°F to 132.8°F (-30°C to 55°C)
Noise	⩽ 80 dB
Altitude	⩽13,123 ft (⩽ 4000 m)
IP Rating	IP55
Thermal Management	Integrated Liquid Cooling and Heating System
Corrosion Resistance	C4, (C5 optional)
Fire Suppression	Fire Suppression, Heat and Smoke Detection, Deflagration Panel

CERTIFICATION STANDARDS

Certification Standards	UL9540, NFPA69/68/70E/855, IEC61000, IEC62477, IEC62933
Shipping Classification	UN 3536 , UN3480, Class 9 (Lithium batteries)

Greatpower.net/en 300438/SZ 3146B Sports Arena Blvd, San Diego, Ca 92110 + 1.619.681.4609 Evan.Bierman@greatpower.net