

BIL576 PROJECT REPORT

Uğur Güdelek
m.gudelek@etu.edu.tr
Computer Engineering Department
TOBB ETU, Ankara

Simla Burcu Harna
s.harna@etu.edu.tr
Computer Engineering Department
TOBB ETU, Ankara

INTRODUCTION

In today's world, internet has an undeniable part in human life. With the increasing amount of data, reaching the information one needs has become a major research problem. The recommendation systems are useful to reach the desirable data and to increase user's experience, so research has been going on this topic for several decades now.

Recommender systems play a big role in the economy of the major companies making use of it, such as Netflix, Amazon.com, Google News, Amazon, Choicestream, etc. Table 1 shows the profit of some websites from the recommendation system [8].

Netflix	2/3rd of the movies watched are recommended
Google News	recommendations generate 38% more click-throughs
Amazon	35% sales from recommendations
Choicestream	28% of the people would buy more music if they found what they liked

Table 1: Companies and their benefit from recommender systems [8].

Movie Recommendation Systems have become popular with the increase in the popularity of movie streaming services like Netflix. Rather than checking the highest rated movies for a genre, users desire to find movies for their special taste.

Recommendation systems are mainly categorized into collaborative filtering, content-based filtering and hybrid recommender systems according to the types of the input. Collaborative filtering systems learn from user-item interactions in the past based on the user ratings or users' browsing history by looking at similar contents in common, the new content recommendation will easily be predicted for each user. This approach has many advantages: it is content-dependent (relies only on connections), as a result of explicit ratings we receive real quality assessment of items, and it provides serendipitous recommendations because it is based on user's similarity [8]. However, as described above, content rates are essential however, not all movies are evaluated by every user in the system so that this causes a problem. Another issue is that diversity between users will be downgraded and within a certain subgroup of users, similar movies are recommended. Collaborative filtering based systems face the cold start problem due to lack of primary information since the user-item matrix can be huge, so sparse. Content-based filtering is based on the user's preference in the past and the item's description. Same aforementioned issues arise when content-based filtering is applied, for instance, if the user's liking is diverse than recommendation will also be diverse. Hybrid approach is another technique combining these two methods.

When applying either methods liking or disliking must be defined in a definitive way. The methods are based on the similarity between users and movies, and this makes the choice of similarity measure important. The

vectorized liking and dislikings will be used as inputs to the similarity functions. Several approaches can be found in the literature however more general and widely used similarity metric is the cosine similarity. Thus we will use cosine similarity on our work.

In this project, we work on the question that how can we predict the movies that a person could love, whose favourite movies are known and we will focus on implementing a personalized collaborative filtering movie recommender system. In order to overcome the problems of the approach; we choose our data carefully and as we face other problems on the way, we will adapt and optimize our system. For the experiments, we will use the popular Netflix and MovieLens datasets. For the evaluation of our work, we will use traditional metrics: Mean Absolute Error (MAE) and Root Square Mean Error (RSME) to measure the error in the predicted ratings and Recall, Precision, Mean Average Precision (MAP) and Normalized Discounted Cumulative Gain (NDCG) to measure the quality of the top-n ranked list of items. In order to implement the movie recommendation system, Python 3 is selected because of the dominance in the area of data processing and machine learning. Python Data Analysis Library (pandas) and Numpy will be examined for data analysis and numerical computation respectively.

We determine Jian Wei et. al.'s timeSVD++ [11] and Rahul Katarya and Om Prakash Verma's movie recommender [6] as our baseline methods since they are recent work and achieve competitive results.

RELATED WORK

Current Recommender Systems in the literature can be classified in three main categories based on the methodology they use: Collaborative Filtering, Content-Based, and Hybrid approaches. Collaborative Filtering approach evaluates similar likes and dislikes on the same content by these two users, and by looking at similar contents in common, the new content recommendation will be predicted for each user. In Content-Based Filtering, a method initially proposed for recommendation of text documents, recommendations are provided for each user just by looking at their previous likes and dislikes. This method has several drawbacks such as the diversity of user's liking will result on diverse recommendations. Hybrid approach, on the other hand, makes use of both techniques and takes their advantageous parts [3, 4].

There has been a significant amount of work on Collaborative Filtering approaches in Recommendation Systems. D.K. Yadav et. al. presented a collaborative-filtering based movie recommendation system: MOVREC, which makes use of the information provided by users [8]. They sorted movies with previous users' ratings by using K-means clustering. They used their own dataset by taking the information from IMDB. To evaluate the success of the algorithm they proposed and their system, they tested their system over a small group of people.

Another work on movie recommenders using traditional user-based Collaborative Filtering uses the pre-filled sparse user project scoring matrix [12]. In order to deal with complex relations in database system they used graph database in their recommender. They used MovieLens100K data sets, including 100,000 ratings from 1000 users on 1700 movies. However they did not mention any experiments.

Since content-based approaches on collaborative filtering suffer from poor accuracy, scalability, data sparsity and big-error prediction [9]; researchers use item-based collaborative filtering approach. They used Netflix user item ratings dataset which was available on Movie Lens web site. The dataset consist of one million ratings of 6040 users over for 3952 movies. In evaluation of their work they used Mean Absolute Error (MAE) and experimented for various neighbor sizes. The lowest MAE is 0.938 when the number of neighbors is 20. Mukesh Kumar Kharita[7] et. al. also used item-based collaborative filtering with the same motivation and the difference of their research was being in real time, making the system dynamic and trainable from positive use feedback. They used MovieLens dataset with ratings given by 943 users for more than 1682 movies. They state that the accuracy of the system is low compared to the other recommendation systems in the literature, however being in real-time makes their research standout from the rest.

In order to improve the accuracy, KNN is another popular approach on movie recommenders using collaborative filtering. V. Subramaniaswamy and R. Logesh developed a movie recommender using their proposed Adaptive KNN algorithm for collaborative filtering [10]. They experimented on MovieLens dataset, and evaluated the results with precision, recall, F-measure and accuracy. They overperformed the baseline methods on their research. Bei-Bei CUI also designed a movie recommendation system using KNN algorithm [2].

While collaborative filtering is one of the most popular techniques for recommendation systems, it suffers from cold-start problem. When there is a small number of rating records or no rating records, the cold-start problem arises. Jian Wei et. al. proposed two recommendation models to solve this problem [11]. They used a specific deep neural network SADE to extract the features of the items, and they modified the state of the art model timeSVD++ to take the content features into prediction of ratings for cold start items. They experimented on Netflix rating dataset and outperformed the baseline models. They used Root Mean Squared Error (RMSE) as a metric and obtained 1.048 on 300 movies.

In order to improve the quality of predictions and to overcome cold-start problem, various clustering techniques have been used. K-means algorithm is one of the most popular ones and for collaborative filtering researchers use this algorithm with genetic algorithms. Rahul Katarya and Om Prakash Verma [6] proposed a collaborative recommender system making use of k-means clustering by adopting cuckoo search optimization algorithm. They performed their experiments on MovieLens dataset and used MAE as an evaluation metric. Their system has 0.68 MAE which outperforms previous approaches. Another movie recommender system [5] developed by Rahul Katarya uses k-means clustering algorithm with bio-inspired artificial bee colony (ABD) optimization technique. In this research, for the experiments, again, the MovieLens dataset is used. Precision, MAE, recall and accuracy were used as evaluation metrics for this work. 0.764 MAE is obtained for k=15. Meng-Hui Chen et. al. also used a bio-inspired technique [1]. In their work, they applied artificial immune network to collaborative filtering for movie recommendation. For their experiments they used MovieLens and EachMovie datasets; and for evaluation, they used MAE, precision and recall. They obtained around 0.72 MAE with optimized parameters.

CURRENT STATUS

We created a shared Google Sheet and each of us added at least 5 papers related to our research. After that we select the most relevant ones together, and shared the work. We have read and summarized the papers. After that we shared the information we had and combined our summaries together. We wrote the introduction part together as well.

Simla: Currently, I have been doing research for the ways to implement our work, checking the current implementations on the literature, and learning the essentials of collaborative filtering.

Uğur: Nowadays, I have been looking into state-of-the-art papers and their methodology. In addition to that, I have been focusing on theoretical knowledge on collaborative and content-based filtering approaches.

REFERENCES

- [1] Chen, Meng-Hui, Chin-Hung Teng, and Pei-Chann Chang. "Applying artificial immune systems to collaborative filtering for movie recommendation." *Advanced Engineering Informatics* 29.4 (2015): 830-839.
- [2] Cui, Bei-Bei. "Design and Implementation of Movie Recommendation System Based on Knn Collaborative Filtering Algorithm." *ITM Web of Conferences*. Vol. 12. EDP Sciences, 2017.
- [3] Geetha, G., et al. "A hybrid approach using collaborative filtering and content based filtering for recommender system." *Journal of Physics: Conference Series*. Vol. 1000. No. 1. IOP Publishing, 2018.
- [4] Jung, Kyung-Yong, Dong-Hyun Park, and Jung-Hyun Lee. "Hybrid collaborative filtering and content-based filtering for improved recommender system." *International Conference on Computational Science*. Springer, Berlin, Heidelberg, 2004.
- [5] Katarya, Rahul. "Movie recommender system with metaheuristic artificial bee." *Neural Computing and Applications* 30.6 (2018): 1983-1990.

- [6] Katarya, Rahul, and Om Prakash Verma. "An effective collaborative movie recommender system with cuckoo search." *Egyptian Informatics Journal* 18.2 (2017): 105-112.
- [7] Kharita, Mukesh Kumar, Atul Kumar, and Pardeep Singh. "Item-Based Collaborative Filtering in Movie Recommendation in Real time." *2018 First International Conference on Secure Cyber Computing and Communication (ICSCCC)*. IEEE, 2019.
- [8] Kumar, Manoj, et al. "A movie recommender system: Movrec." *International Journal of Computer Applications* 124.3 (2015).
- [9] Ponnamm, Lakshmi Tharun, et al. "Movie recommender system using item based collaborative filtering technique." *2016 International Conference on Emerging Trends in Engineering, Technology and Science (ICETETS)*. IEEE, 2016.
- [10] Subramaniaswamy, V., and R. Logesh. "Adaptive KNN based recommender system through mining of user preferences." *Wireless Personal Communications* 97.2 (2017): 2229-2247.
- [11] Wei, Jian, et al. "Collaborative filtering and deep learning based recommendation system for cold start items." *Expert Systems with Applications* 69 (2017): 29-39.
- [12] Yi, Ningning, et al. "Design and implementation of movie recommender system based on graph database." *2017 14th Web Information Systems and Applications Conference (WISA)*. IEEE, 2017.