



NEW from APAC »

Kabızalı Elektrikli Tornavida





NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



E7T-U



E9T-U

Model	Screw Size		Free Speed	Torque Range		Weight	Length	Available Drive Bit
	Machine Screw	Tapping Screw		Hard Joint	Soft Joint			
	mm			RPM	Nm			
BSD-E7T2-14-U	2.3-3.5	2.3-3.0	1400	0.3-2	0.3-1.6	0.9	196.7	1/4" Hex
BSD-E7T3-33-U	2.0-4.0	2.0-3.5	3300	1-3	1-2.4	0.9	196.7	1/4" Hex
BSD-E7T3-16-U	2.6-4.0	2.6-3.5	1600	1.2-3.5	1.2-2.8	0.9	196.7	1/4" Hex
BSD-E7T5-12-U	4.0-5.0	≤ 4	1200	2-5	2-4	0.9	196.7	1/4" Hex
BSD-E7T7-09-U	5.0-6.0	≤ 5	950	2.5-7	2.5-5.6	0.9	196.7	1/4" Hex

Model	Screw Size		Free Speed	Torque Range		Weight	Length	Available Drive Bit
	Machine Screw	Tapping Screw		Hard Joint	Soft Joint			
	mm			RPM	Nm			
P15-E9T6-10-U	4.0-5.0	≤ 4	1000	2-6	2-4.8	1.4	249.2	1/4"Hex, 3/8 Sq
P15-E9T9-07-U	5.0-6.0	≤ 4.5	770	3-9	3-7.2	1.4	249.2	1/4"Hex, 3/8 Sq
P15-E9T12-05-U	≤ 8	≤ 6	550	4-12	4-9.6	1.4	249.2	1/4"Hex, 3/8 Sq
P15-E9T18-03-U	≤ 10	≤ 8	350	6-18	6-14.4	1.4	249.2	1/4"Hex, 3/8 Sq



NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



E7T-D



E9T-D

Model	Screw Size		Free Speed	Torque Range		Weight	Length	Available Drive Bit
	Machine Screw	Tapping Screw		Hard Joint	Soft Joint			
	mm			RPM	Nm			
P15-E7T2-14-D	2.3-3.5	2.3-3.0	1400	0.3-2	0.3-1.6	0.9	196.7	1/4" Hex
P15-E7T3-33-D	2.0-4.0	2.0-3.5	3300	1-3	1-2.4	0.9	196.7	1/4" Hex
P15-E7T3-16-D	2.6-4.0	2.6-3.5	1600	1.2-3.5	1.2-2.8	0.9	196.7	1/4" Hex
BSD-E7T5-12-D	4.0-5.0	≤ 4	1200	2-5	2-4	0.9	196.7	1/4" Hex
BSD-E7T7-09-D	5.0-6.0	≤ 5	950	2.5-7	2.5-5.6	0.9	196.7	1/4" Hex

Model	Screw Size		Free Speed	Torque Range		Weight	Length	Available Drive Bit
	Machine Screw	Tapping Screw		Hard Joint	Soft Joint			
	mm			RPM	Nm			
P15-E9T6-10-D	4.0-5.0	≤ 4	1000	2-6	2-4.8	1.4	249.2	1/4”Hex, 3/8 Sq
P15-E9T9-07-D	5.0-6.0	≤ 4.5	770	3-9	3-7.2	1.4	249.2	1/4”Hex, 3/8 Sq
P15-E9T12-05-D	≤ 8	≤ 6	550	4-12	4-9.6	1.4	249.2	1/4”Hex, 3/8 Sq
P15-E9T18-03-D	≤ 10	≤ 8	350	6-18	6-14.4	1.4	249.2	1/4”Hex, 3/8 Sq



Model	PA9T-8301	PA9L-8301
Input Voltage	AC 100-240V 50/60Hz 6.3A	AC 100-240V 50/60Hz 6.3A
Output Voltage	DC 40V	DC 40V
Output Current	6A, 240W Max	9A, 360W Max
Dimension	172 x 147 x 70 (mm)	172 x 147 x 70 (mm)
Weight	1.66 Kg	1.66 kg
AC Cord Length	1.8M with ground	1.8M with ground
Applicable Model	P15-E7T P15-E9T	P15-E9L P15-E9A



NEW from APAC »

Elektrikli Tornavida Düz Tip





NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



Start Option	Model	Screw Size \varnothing		Free Speed		Torque Range		Weight	Length	Available Drive Bit
		Machine Screw	Tapping Screw	HI	LO					
		mm		RPM		Kg-cm	Nm	g	mm	mm
Lever Start	P15-E1L01-10	1.0-1.7	1.0-1.5	1000	700	0.35-1.8	0.03-0.17	320	222.9	$\varnothing 4$
	P15-E1L03-10	1.0-2.3	1.0-2.0	1000	700	0.5-3.5	0.05-0.34	320	222.9	$\varnothing 4$
	P15-E1L01-02	1.0-1.7	1.0-1.5	270	200	0.35-1.8	0.03-0.17	320	222.9	$\varnothing 4$
	P15-E1L03-02	1.0-2.3	1.0-2.0	270	200	0.5-3.5	0.05-0.34	320	222.9	$\varnothing 4$



NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



E3L (Lever Star)



E3P (Push Star)

Start Option	Model	Screw Size Ø		Free Speed		Torque Range		Weight	Length	Available Drive Bit
		Machine Screw	Tapping Screw	HI	LO					
		mm		RPM		Kg-cm	Nm	g	mm	mm / inch
Lever Start	P15-E3L04-16	1.6-2.6	1.6-2.3	1600	1200	1.2-4	0.11-0.39	430	238.9	Ø4、Ø5、1/4" Hex
	P15-E3L07-10	1.6-2.6	1.6-2.3	1000	700	1.5-7.5	0.12-0.73	430	238.9	Ø4、Ø5、1/4" Hex
	P15-E3L11-10	1.6-3.0	1.6-2.6	1000	700	2-11	0.2-1.07	430	238.9	Ø4、Ø5、1/4" Hex
	P15-E3L04-04	1.6-2.6	1.6-2.3	470	350	1.2-4	0.11-0.39	430	238.9	Ø4、Ø5、1/4" Hex
	P15-E3L11-04	1.6-3.0	1.6-2.6	470	350	2-11	0.2-1.07	430	238.9	Ø4、Ø5、1/4" Hex
	P15-E3L14-04	2.3-3.5	2.3-3.0	470	350	3-14	0.29-1.37	430	238.9	Ø4、Ø5、1/4" Hex
Push start	P15-E3P11-10	1.6-3.0	1.6-2.6	1000	700	2-11	0.2-1.07	450	262.7	Ø4、Ø5、1/4" Hex



NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



E5L (Lever Star)




E5P (Push Star)

Start Option	Model	Screw Size ø		Free Speed		Torque Range		Weight	Length	Available Drive Bit
		Machine Screw	Tapping Screw	HI	LO					
		mm		RPM		Kg-cm	Nm	g	mm	mm / inch
Lever Start	P15-E5L10-20	1.6-3.0	1.6-2.6	2000	1500	3-10	0.29-0.98	670	283.2	ø5、 1/4" Hex
	P15-E5L11-11	1.6-3.0	1.6-2.6	1100	800	3-11	0.29-1.08	670	283.2	ø5、 1/4" Hex
	P15-E5L20-11	2.3-3.5	2.3-3.0	1100	800	5-20	0.49-1.96	670	283.2	ø5、 1/4" Hex
	P15-E5L11-03	1.6-3.0	1.6-2.6	330	240	3-11	0.29-1.08	670	283.2	ø5、 1/4" Hex
	P15-E5L20-03	2.3-3.5	2.3-3.0	330	240	5-20	0.49-1.96	670	283.2	ø5、 1/4" Hex
Push start	P15-E5P10-20	1.6-3.0	1.6-2.6	2000	1500	3-10	0.29-0.98	700	299	ø5、 1/4" Hex
	P15-E5P11-11	1.6-3.0	1.6-2.6	1100	800	3-11	0.29-1.08	700	299	ø5、 1/4" Hex
	P15-E5P20-11	2.3-3.5	2.3-3.0	1100	800	5-20	0.49-1.96	700	299	ø5、 1/4" Hex
	P15-E5P11-03	1.6-3.0	1.6-2.6	330	240	3-11	0.29-1.08	700	299	ø5、 1/4" Hex
	P15-E5P20-03	2.3-3.5	2.3-3.0	330	240	5-20	0.49-1.96	700	299	ø5、 1/4" Hex



NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



E7L (Lever Star)



E7P (Push Star)

Start Option	Model	Screw Size ϕ		Free Speed		Torque Range		Weight	Length	Available Drive Bit
		Machine Screw	Tapping Screw	HI	LO					
		mm		RPM		Kg-cm	Nm	g	mm	mm / inch
Lever Start	P15-E7L30-19	2.6-4.0	2.6-3.5	1900	—	15-30	1.47-2.94	850	306.9	1/4" Hex
	P15-E7L30-10	2.6-4.0	2.6-3.5	1000	—	15-30	1.47-2.94	850	306.9	1/4" Hex
	P15-E7L40-10	4.0-5.0	≤ 4	1000	—	17-40	1.67-3.92	850	306.9	1/4" Hex
	P15-E7L50-06	4.0-5.0	≤ 4	650	—	20-50	1.96-4.9	850	306.9	1/4" Hex
	P15-E7L30-02	2.64-4.0	2.6-3.5	260	—	15-30	1.47-2.94	850	306.9	1/4" Hex
	P15-E7L50-02	4.0-5.0	≤ 4	260	—	20-50	1.96-4.9	850	306.9	1/4" Hex
Push start	P15-E7P30-19	2.6-4.0	2.6-3.5	1900	—	15-30	1.47-2.94	880	324.1	1/4" Hex
	P15-E7P30-10	2.6-4.0	2.6-3.5	1000	—	15-30	1.47-2.94	880	324.1	1/4" Hex
	P15-E7P40-10	4.0-5.0	≤ 4	1000	—	17-40	1.67-3.92	880	324.1	1/4" Hex
	P15-E7P50-06	4.0-5.0	≤ 4	650	—	20-50	1.96-4.9	880	324.1	1/4" Hex
	P15-E7P30-02	2.6-4.0	2.6-3.5	260	—	15-30	1.47-2.94	880	324.1	1/4" Hex
	P15-E7P50-02	4.0-5.0	≤ 4	260	—	20-50	1.96-4.9	880	324.1	1/4" Hex



NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



Start Option	Model	Screw Size		Free Speed	Torque Range		Weight	Length	Available Drive Bit
		Machine Screw	Tapping Screw		Hard Joint	Soft Joint			
		mm			RPM	Nm			
Lever Start	P15-E9L6-21	4.0-5.0	≦ 4	2100	2-6	2-4.8	1.15	339	1/4" Hex
	P15-E9L9-10	≦ 6	≦ 5	1000	3-9	3-7.2	1.15	339	1/4" Hex
	P15-E9L12-08	≦ 8	≦ 6	880	5-12	5-9.6	1.15	339	1/4" Hex



NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)





NEW from APAC » DC ELECTRIC SCREWDRIVER WITH BRUSHLESS MOTOR (CLUTCH TYPE)



Start Option	Model	Drive Size	Screw Size		Free Speed	Torque Range		Weight	Length
			Machine Screw	Tapping Screw		Hard Joint	Soft Joint		
		inch	mm		RPM	Nm		kg	mm
Lever Start	P15-E9A9Q-13	1/4" Hex.	≤ 6	≤ 4.5	1350	3-9	3-7.2	1.48	384.2
	P15-E9A9W-13	1/4" Sq.	≤ 6	≤ 4.5	1350	3-9	3-7.2	1.48	384.2
	P15-E9A9X-13	3/8" Sq.	≤ 6	≤ 4.5	1350	3-9	3-7.2	1.48	384.2
	P15-E9A13Q-06	1/4" Hex.	≤ 8	≤ 6	650	5-13	5-10.4	1.48	384.2
	P15-E9A13W-06	1/4" Sq.	≤ 8	≤ 6	650	5-13	5-10.4	1.48	384.2
	P15-E9A13X-06	3/8" Sq.	≤ 8	≤ 6	650	5-13	5-10.4	1.48	384.2
	P15-E9A18Q-05	1/4" Hex.	≤ 10	≤ 8	550	7-18	7-14.4	1.48	384.2
	P15-E9A18W-05	1/4" Sq.	≤ 10	≤ 8	550	7-18	7-14.4	1.48	384.2
	P15-E9A18X-05	3/8" Sq.	≤ 10	≤ 8	550	7-18	7-14.4	1.48	384.2



NEW from APAC » Power Controllers(Standard Version)





Model	PA1L-8301	PA3L-8301	PA5L-8301	PA7L-8301
Input Voltage	AC 100-240V 50/60Hz 0.6A	AC 100-240V 50/60Hz 1.5A	AC 100-240V 50/60Hz 2.2A	AC 100-240V 50/60Hz 2.2A
Output Voltage	LO DC 9V HI DC 12V	LO DC 24V HI DC 32V	LO DC 24V HI DC 32V	DC 36V
Output Current	2.0A, 24W Max	2.0A, 64W Max	2.0A, 64W Max	2.0A, 72W Max
Dimension	170 x 71 x 52 (mm)	170 x 71 x 52 (mm)	170 x 71 x 52 (mm)	170 x 71 x 52 (mm)
Weight	228g	303g	316g	316g
AC Cord Length	1.8M	1.8M	1.8M	1.8M
Applicable Model	P15-E1L	P15-E3L P15-E3P	P15-E5L P15-P5P	P15-E7L P15-E7P



Model	PA3L-8301B	PA5L-8301B	PA7L-8301B
Input Voltage	AC 100-240V 50/60Hz 1.5A	AC 100-240V 50/60Hz 2.2A	AC 100-240V 50/60Hz 2.2A
Output Voltage	LO DC 24V HI DC 32V	LO DC 24V HI DC 32V	DC 36V
Output Current	2.0A, 64W Max	2.0A, 64W Max	2.0A, 72W Max
Dimension	170 x 71 x 52 (mm)	170 x 71 x 52 (mm)	170 x 71 x 52 (mm)
Weight	305g	318g	318g
AC Cord Length	1.8M	1.8M	1.8M
Applicable Model	P15-E3L P15-E3P	P15-E5L P15-E5P	P15-E7L P15-E7P