Table 1: Component ablation on LIBERO-OBJECT and LIBERO-GOAL (mean ± sample standard deviation over three seeds). Rows cumulatively add ALIGN, execution supervision, support-weighted retention, and candidate gating to RA-Coreset; Ours includes all components. Higher FWT and AUC and lower NBT are better. The best mean in each column is shown in bold.

Configuration	LIBERO-OBJECT			LIBERO-GOAL		
	FWT↑	NBT↓	AUC↑	FWT↑	NBT↓	AUC↑
RA-Coreset	73.3±2.9	−0.1±3.8	73.2±1.8	83.8±1.2	**2.6±5.1**	82.0±3.0
RA-Coreset + ALIGN	77.5±5.4	−4.9±4.3	80.2±3.7	85.8±5.1	10.8±5.2	81.1±3.4
+ Execution Supervision	**81.2±2.5**	−8.1±2.4	85.0±3.1	85.0±8.2	5.6±2.2	82.5±7.1
+ Support-Weighted Retention	78.8±3.3	−10.9±4.5	84.6±2.5	85.8±2.6	4.4±1.9	83.5±1.5
Ours	80.4±8.5	**−11.0±11.6**	**86.5±2.2**	**89.6±1.9**	5.3±5.2	**87.3±2.6**