

Stylesheet for Menota in Corpuscle

according to v. 3.0 of *The Menota Handbook*, 8 August 2019, revised 10 August 2019

Encoding	Display	Unicode codepoints
<code><add></code> <i>except when</i> <code><add place="margin"></code>	<code>\ ... /</code> <code>/ ... \</code>	2E0C + 2E0D 2E1D + 2E1C
<i>also note when</i> <code><add rendition="first middle last"></code>	do not show sign at the end of ‘first’, not at all in ‘middle’, and not at the start of ‘last’	
<code></code> <i>also note when</i> <code><del rendition="first middle last"></code>	<code>‖ ... ‖</code> do not show sign at the end of ‘first’, not at all in ‘middle’, and not at the start of ‘last’	2E20 + 2E21
<code><orig></code> and <code><reg></code> <i>in a single-level edition</i>	display <code><reg></code> in the running text, and <code><orig></code> in a note linked by an asterisk in the running text	
<code><orig></code> and <code><reg></code> <i>in a multi-level edition</i>	<code><orig></code> is used on the facsimile level and should be displayed in the running text <code><reg></code> is used on the diplomatic and normalised levels and should be displayed in the running text on each level	

Note: In a multi-level encoding, the `<orig>` reading will be on the facsimile level and it need not be highlighted in any way. The reading is simply what the manuscript offers. The `<reg>` reading will be found on the normalised level, and preferably also on the normalised level. On these levels, the reading in the `<reg>` element should be given, but with a note (linked by an asterisk) about the `<orig>` reading, and possibly a comment as to why it has been corrected.

<sic> and <corr>
in a single-level edition

display <corr> in the running text,
and <sic> in a note linked by an asterisk in the running text

<sic> and <corr>
in a multi-level edition

<sic> is used on the facsimile level and should be displayed in the running text
<corr> is used on the diplomatic and normalised levels and should be displayed
in the running text on each level

Note: In a multi-level encoding, the <sic> reading will be on the facsimile level and it need not be highlighted in any way. The reading is simply what the manuscript offers. The <corr> reading will be found on the normalised level, and preferably also on the normalised level. On these levels, the reading in the <corr> element should be given, but with a note (linked by an asterisk) about the <sic> reading, and possibly a comment as to why it has been corrected.

<supplied>
except when <supplied reason="emendation">

[...]
⟨ ... ⟩

005B + 005D
27E8 + 27E9

also note when

<supplied rendition="first|middle|last">

do not show sign at the end of 'first', not at all in 'middle', and not at the start of 'last'

<surplus> and <me:suppressed>

{ ... }

007B + 007D

also note when

<surplus rendition="first|middle|last">

do not show sign at the end of 'first', not at all in 'middle', and not at the start of 'last'

<me:suppressed rendition="first|middle|last">

do not show sign at the end of 'first', not at all in 'middle', and not at the start of 'last'

<unclear>

in grey colour in the running text,
also grey colour on the dotted circle
and the small zero

25CC
F1BD

<code><note></code> <i>except when</i>	in a separate text box, linked by an asterisk in the running text
<code><note type="explanatory"></code>	in grey colour in the running text, blank line above and below
<code><note type="codicological"></code>	in grey colour in the running text, blank line above and below
<code><gap unit="chars" quantity="1"/></code>	display by dotted circles, ○ (25CC), one for each number of characters given
<code><gap unit="line" quantity="1"/></code>	display by ○○○ one line gap ○○○, one for each number of lines given
<i>Note that the dotted circles as well as “one line gap” should be displayed in the same gray colour as for <unclear> text.</i>	
<code><space unit="chars" quantity="1"/></code>	display by empty character-wide spaces (invisible chars.), one for each number given
<code><space unit="line" quantity="1"/></code>	display by empty lines, one for each number given

Hyphenation	Display	Unicode codepoints
<code><c type="hyphen">-</c></code>	-	002D ordinary
This is how <code><w>hyphen<c type="hyphen">-</c><lb ed="ms" n="2"/>ation</w></code> will be encoded when there actually is a hyphen in the manuscript. The hyphen will be displayed where the <code><c></code> element is located.		
<i>no hyphen in the source</i>	.	00B7 middot
This how <code><w>hyphen<lb ed="ms" n="2"/>ation</w></code> will be encoded when there is no hyphen in the manuscript. The middot will then be displayed where the <code><lb/></code> element is located.		