

Relationship Between Track Geometry and Components Health Conditions

This manuscript ([permalink](#)) was automatically generated from [uiceds/cee-492-term-project-fall-2022-shans@668b22b](#) on October 29, 2022.

Authors

- **Arthur Bilheri**

 [XXXX-XXXX-XXXX-XXXX](#) ·  [artbil94](#) ·  [I dont like birds](#)

Hogwarts school of witchcraft

- **Negin Shafie**

 [XXXX-XXXX-XXXX-XXXX](#) ·  [negins2](#) ·  [NA](#)

Department of Civil and Environmental Engineering, University of Illinois at Urbana-Champaign · Funded by none

- **Shirin Qiam**

 [XXXX-XXXX-XXXX-XXXX](#) ·  [Shirin-qiam](#) ·  [NA](#)

Department of Civil and Environmental Engineering, University of Illinois at Urbana-Champaign · Funded by none

- **Sadaf Shafie**

 [XXXX-XXXX-XXXX-XXXX](#) ·  [sadafs2](#) ·  [NA](#)

Department of Civil and Environmental Engineering, University of Illinois at Urbana-Champaign · Funded by none

Introduction

Railroad tracks have four main components: rail, ties, fastening systems, and ballast. The rail is the main component that supports the loads transmitted by the trains. The fastening system is responsible for fastening the rail to the ties and keeping the rail in a proper position. Fastening systems are made of spikes, tie plates, anchors, and sometimes clips. The ties are the interface between the rails and ballast. The two main materials used for ties in the United States are timber and concrete. The last layer on the railroad superstructure is the ballast. Its main functions are to spread the loads on the ground and to provide proper drainage for the track system.

These components are inspected using the LRAIL technology that combines 2D imagery and laser triangulation to assess the health and condition of each component. The collected data is processed through a DNN (Deep Convolutional Neural Network) model that identifies and classifies the components. This technology has been used under the scope of research led by the RailTEC group at UIUC, funded by the FRA-DOT with two Class I railroads in the US. The output of this technology, which will be used in this project, is described in an Excel file (filename: Datasets) attached to this proposal.

Track geometry can be defined as the relative position of the rails. The common measurements are related to horizontal and vertical irregularities, gage, and superelevation. CFR 213 establishes safety limits that must be kept in order to provide the trains with a safe ride. Railroads use laser-based contactless systems to measure track geometry. Recently these systems have been installed in boxcars and locomotives to provide autonomous measurements, reduce inspection costs, and collect more data. Geometry cars, as they are called, collect measurements of each foot of the track to calculate the deviations.

The purpose of this project is to look for relationships between components' health and geometry data collected over the same tracks in a short period and to identify possible correlations. The approaches of this project consist of but are not limited to EDA methods, regressions, and correlation models. The data can be found in [Project](#), "LRAIL" contains the component health conditions, "Geometry 1" and "Geometry 2" include the geometry data for that same track, and "Datasets" describes each of the above.

Column name	Type	Range	Unit	Observation
SectionID	int	0-inf		The ID number of section containing the tie. Each section is 2m wide.
Distance_m	float	0-inf	meters	The position of the tie. The distance is computed from the beginning of the survey. The unit is meter
Material	string	Wooden, Concrete		The material of the tie
Rating	int	0-3 (Wooden) 0-2 (Concrete)		The rating of tie based on condition of crack on surface of tie. 0: good. 3 or 2 is bad.

Column name	Type	Range	Unit	Observation
Askew_Angle	float	-inf to inf	degrees	Askew angle of the tie. This is angle between the horizontal line and the center line of the tie (passing through middle of tie) positive if we need to rotate the tie clockwise to make the center line fit the horizontal line and it is negative if we need to rotate the tie counter-clockwise. The unit is degrees.
FastenerConditionROI_1	int	1, 2, 3, 20		The condition of fastener in ROI 1 to 4. 1: Good, 2: Covered, 3: Missing and 20: Defective
SpikeTotalROI_1 to 4	int	0-inf		Number of spike in each ROI on tie
SpikeMean_Height_ROI1_mm	float	0-inf	milimeters	The mean height of all tie in each ROI on tie. The unit is millimeter
SpikeNearRailROI_1	int	0-inf		Number of spike is near the rail boundary in each ROI on tie
AnchorROI_1	int	0-inf		Number of anchor in each ROI (relating to the tie)
Tieplate_Right	int	0-inf		Number of tieplate on left/right side of tie
TieplateCondition_Right	int	1-5		Condition of tieplate. 1: Good, 2: Sunken, 4: Covered, 5: Twisted
Latitude	float	-90 to +90	degrees	GPS coordinates of the center of the tie
Longitude	float	-90 to +90	degrees	GPS coordinates of the center of the tie

Exploratory Data Analysis

Negin's part

References
